

Produkte
 Products

RF Exposure Statement: 12022407 002

Page 1 of 1

Client: Topcon Corporation
 75-1, Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan

Test item: Wireless Terminal

Identification: WT-100

FCC Requirement

According to FCC 2.1091, mobile equipment must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:

| Equipment Use | Frequency Range | Power Density [mW/cm ²] | Average Time [min] |
|--|-----------------|-------------------------------------|--------------------|
| General Population / Uncontrolled Exposure | 1.5 – 100GHz | 1 | 6 |

IC Requirement

According to RSS-102 (Issue 4), clause 2.5.2, no routine RF exposure evaluation is required if the transmitter has a minimum separation distance to the user greater than 20cm and has an output power (e.i.r.p.) below the following threshold:

| Frequency Range | RF Exp. Evaluation Threshold [W] |
|-----------------|----------------------------------|
| Above 1.5GHz | 5 |

Measurement Result

The maximum measured transmitter power is given in the following table:

| Conducted Output Power P _{out} [mW] | Maximum Antenna Gain [dBi] | EIRP Output Power [mW] | Power Density at 20cm [mW/cm ²] |
|--|----------------------------|------------------------|---|
| 188.52 | 2 | 298.54 | 0.06 |

Note:

The power density S in mW/cm² is calculated according to the Friis formula: $S = (P_{out} \cdot G) / (4\pi \cdot D^2)$, where
 P_{out} = antenna conducted output power in mW,
 G = antenna gain in linear scale (here: 2dBi = 1.58 linear),
 D = distance between observation point and radiating structure in cm (here: 20cm).

Conclusion

The device complies with the FCC and IC RF exposure requirements since the maximum transmitter power density is below the FCC limit and the e.i.r.p. output power is below the IC RF exposure evaluation exemption threshold.

Refer to test report 12022407 001 for more details.