



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR 352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

FCC
VHF PORTABLE PART 90
TEST REPORT

APPLICANT	KP ELECTRONIC SYSTEMS LTD.
	P.O. BOX 42 TEFEN INDUSTRIAL PARK 24959 ISRAEL
FCC ID	H78KPMTPIT
MODEL NUMBER	MTPIT25
PRODUCT DESCRIPTION	TRANSMITTER FOR WATER METER
STANDARD APPLIED	CFR 47 Part 90
DATE SAMPLE RECEIVED	2/10/2015
DATE TESTED	23 February 2015
REPORT ISSUE DATE	24 February 2015
TESTED BY	Sid Sanders
APPROVED BY	Cory Leverett
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

Report Number	Version Number	Description	Issue Date
335AUT15TestReport	Rev.1	Initial Issue	2/25/15

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.

TABLE OF CONTENTS

GENERAL REMARKS.....	3
GENERAL INFORMATION.....	4
TEST REPORT SUMMARY.....	5
TEST PROCEDURE.....	6
RF POWER OUTPUT.....	7
MODULATION CHARACTERISTICS.....	8
OCCUPIED BANDWIDTH.....	8
OCCUPIED BANDWIDTH PLOTS: ANALOG 5K2F3E.....	9
SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED).....	10
SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED).....	11
FIELD STRENGTH OF SPURIOUS EMISSIONS.....	12
FIELD STRENGTH OF SPURIOUS EMISSIONS (Cont.).....	13
FREQUENCY STABILITY.....	14
TRANSIENT FREQUENCY BEHAVIOR.....	15
TRANSIENT FREQUENCY BEHAVIOR.....	16
TRANSIENT FREQUENCY BEHAVIOR.....	17
TRANSIENT FREQUENCY BEHAVIOR.....	18
EQUIPMENT LIST.....	19

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
 not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:



Engineering Project Manager

Date: 23 February 2015

[Table of Contents](#)

Applicant: KP ELECTRONIC SYSTEMS LTD.
FCC ID: H78KPMTPIT
Report: K\KP H78\335AUT15\335AUT15TestReport.docx

GENERAL INFORMATION

EUT Specification

EUT Description	TRANSMITTER FOR WATER METER
FCC ID	H78KPMPIT
Model Number	MTPIT25
Operating Frequency Range	172.5 – 173.5 MHz
Test Frequencies	173.000MHz,
Type of Emission	1K90F1D
Modulation	FM
EUT Power Source	<input type="checkbox"/> 110–120Vac/50– 60Hz
	<input checked="" type="checkbox"/> DC Power 6.0V
	<input type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed
	<input type="checkbox"/> Mobile
	<input type="checkbox"/> Portable
Test Conditions	The temperature was 24-26°C with a relative humidity of 50-65%.
Revision History to the EUT	None
Test Exercise	The EUT was placed in continuous transmit mode.
Applicable Standards	ANSI/TIA 603-D:2010, FCC CFR 47 Part 90
Test Facility	Timco Engineering Inc. 849 NW State Road 45 Newberry, FL 32669 USA.

[Table of Contents](#)

TEST REPORT SUMMARY

Rule Part No.	Scope of Work	Status Pass/Fail/NA
Part 2.1033(c)(8) , Part 2.1046(a) , Part 90	RF Power Output	PASS
Part 2.1033(c)(4) Part 2.1047(a)(6)	Modulation Characteristics	NA
2.1049(c) , 90.210(b) , 90.210(c) 90.210(d) , 90.210(e)	Emission Mask and Occupied Bandwidths	PASS
2.1051(a)	Antenna Conducted Emissions	PASS
2.1053 , Part 90	Field Strength Spurious Emissions	PASS
Part 2.1055 , Part 90.213	Frequency Stability	PASS
Part 90.214	Transient Frequency Behavior	PASS

[Table of Contents](#)

TEST PROCEDURE

Power Line Conducted Interference: The procedure used was ANSI/TIA 603-D:2010, using a 50uH LISN. Both lines were observed with the EUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was ANSI/TIA 603-D:2010, using an Rohde & Schwarz – EMI test receiver. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

[Table of Contents](#)

RF POWER OUTPUT


Rule Part No.: Part 2.1046(a), Part 90

Test Requirements: Manufacturer's Specification

Method of Measurement: RF power is measured by using a 50-ohm, resistive wattmeter to the RF output connector. With a nominal battery voltage (if battery operated), or a properly adjusted power supply (if not battery operated), and the transmitter properly adjusted the RF output measures:

For the device with a fixed or integral antenna, the RF power is measured as ERP. The substitution method was used. The RF output measures:

Test Setup Diagram:



Test Data: RF power of the EUT can be set at 0.0W to 0.0W.

OUTPUT POWER:

Tuned Frequency (MHz)	RF POWER	
	dBm	Watts
173.000	33	2.0

Part 2.1033 (C) (8) DC Input into the final amplifier

FOR POWER SETTING INPUT POWER: $(6.0V)(0.5A) = 3.0 \text{ Watts}$

[Table of Contents](#)

MODULATION CHARACTERISTICS

Rule Part No.: Part 2.1047(a)(b)

Test Requirements: Not Applicable No Analog modulation.

OCCUPIED BANDWIDTH

Part 2.1049(c) EMISSION BANDWIDTH:
Part 90.210(b) 25kHz Channel Spacing


Data in the plots show that on any frequency removed from the assigned frequency by more than 50%, but not more than 100%: At least 25dB. On any frequency removed from the assigned frequency by more than 100%, but not more than 250%: At least 35 dB. On any frequency removed from the assigned frequency by more than 250%, of the authorized bandwidth: At least $43 + 10\log(P)$ dB.

Part 90.210(e) Emission Mask E – 6.25 kHz channel BW equipment.

For transmitters designed to operate with a 6.25 kHz bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 3.0 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least $30 + 16.67(f_d - 3.0 \text{ kHz})$ or $55 + 10 \log(P)$ or 65, whichever us the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6kHz: At least $55 + 10\log(P)$ dB or 65 dB, whichever is the lesser attenuation.

Method of Measurement: ANSI/TIA 603-D:
Test Setup Diagram:



Test Data: See the plots below


Applicant: KP ELECTRONIC SYSTEMS LTD.

FCC ID: H78KPMTPIT

Report: K\KP H78\335AUT15\335AUT15TestReport.docx

OCCUPIED BANDWIDTH PLOTS: ANALOG 5k2F3E

Part 90.210(e) Emission Mask D – 6.25 kHz Channel Bandwidth - ANALOG



[Table of Contents](#)

Applicant: KP ELECTRONIC SYSTEMS LTD.
FCC ID: H78KPMTPIT
Report: K\KP H78\335AUT15\335AUT15TestReport.docx

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)

Rule Part No.: Part 2.1051(a)


Requirements:

6.25kHz Channel Spacing = On any frequency removed from the center of the authorized bandwidth by more than 4.6kHz: At least 55 + 10log(P) dB or 65 dB, whichever is the lesser attenuation.

$$6.25 \text{ kHz Channel Spacing} = 55 + 10 \log (2.0) = 58.0 \text{ dBc (high power)}$$

Method of Measurement: The carrier was modulated 100% using a 2500 Hz tone. The spectrum was scanned from the lowest frequency generated to at least the 10th harmonic of the fundamental. The measurements were made in accordance with standard ANSI/TIA 603-D: 2010.

Method of Measuring Conducted Spurious Emissions



SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)

Test Data: High Power

	dBm	Watts	Margin
Power Output	33	2	
LIMIT	58		
	Frequency	dBc	dB
	173	0	
	346	66.4	8.4
	519	74.7	16.7
	692	75.2	17.2
	865	76.4	18.4
	1038	77.1	19.1
	1211	70.6	12.6
	1384	78.2	20.2
	1557	78.3	20.3
	1730	76.5	18.5

Results: Meets requirements

[Table of Contents](#)

FIELD STRENGTH OF SPURIOUS EMISSIONS


Rule Parts. No.: Part 2.1053

- (4) **Requirements:** 6.25kHz Channel Spacing On any frequency removed from the center of the authorized bandwidth by more than 4.6kHz: At least $55 + 10\log(P)$ dB or 65 dB, whichever is the lesser attenuation.

$$6.25\text{kHz Channel Spacing} = 55 + 10 \log(2) = 58.0\text{dBc}$$

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per ANSI/TIA 603-D: 2010 using the substitution method. Measurements were made at the test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

Test Setup Diagram:



FIELD STRENGTH OF SPURIOUS EMISSIONS (Cont.)

Test Data:

Emission Frequency (MHz)	Power Mode	ERP Power Output (dBm)	ERP Power Output (Watts)	FCC Requirement dB	Bandwidth - BW - kHz
173.00	Hi	33.00	2.00	58.00	6.25
Emission Frequency (MHz)	Ant. Polarity	Below Carrier (dBc)	Margin		
346.00	V	71.23	13.23		
519.00	H	73.58	15.58		
692.00	H	78.84	20.84		
865.00	V	69.92	11.92		
1,038.00	V	79.68	21.68		
1,211.00	V	82.11	24.11		
1,384.00	H	83.79	25.79		
1,557.00	V	79.28	21.28		
1,730.00	V	80.13	22.13		

Results: Meets requirements

FREQUENCY STABILITY

Rule Parts. No.: Part 2.1055, Part 90.213

Requirements: Temperature range requirements: -30 to +50° C.
Voltage Variation +, -15%
±2.5 PPM

Method of Measurements: ANSI/TIA 603-D: 2010.

Test Data:

Temperature	Frequency MHz	Cycles	PPM
25°C (reference)	172.999800		
-30°C	172.999850	50	0.289
-20°C	172.999790	-10	-0.058
-10°C	172.999810	10	0.058
0°C	172.999800	0	0.000
10°C	172.999800	0	0.000
20°C	172.999800	0	0.000
30°C	172.999800	0	0.000
40°C	172.999720	-80	-0.462
50°C	172.999740	-60	-0.347
Battery Voltage	Frequency	Cycles	PPM
-15%	172.999830	30	0.173
15%(6.9)	172.999820	20	0.116

Results: Meets requirements

[Table of Contents](#)

TRANSIENT FREQUENCY BEHAVIOR

Part 90.214 Transient Frequency Behavior

REQUIREMENTS: Transmitters designed to operate in the 150-174 MHz and 421-512 MHz frequency bands must maintain transient frequencies within the maximum transient frequencies within the maximum frequency difference limits during the time intervals indicated:

Time Intervals	Maximum frequency difference	All Equipment	
		150-174 MHz	421-512 MHz

Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels

Time Interval	Maximum frequency difference	150-174 MHz	421-512 MHz
t_1^4	± 25.0 kHz	5.0 ms	10.0 ms
t_2	± 12.5 kHz	20.0 ms	25.0 ms
t_3^4	± 25.0 kHz	5.0 ms	10.0 ms


Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels

Time Interval	Maximum frequency difference	150-174 MHz	421-512 MHz
t_1^4	± 12.5 kHz	5.0 ms	10.0 ms
t_2	± 6.25 kHz	20.0 ms	25.0 ms
t_3^4	± 12.5 kHz	5.0 ms	10.0 ms

Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels

Time Interval	Maximum frequency difference	150-174 MHz	421-512 MHz
t_1^4	± 6.25 kHz	5.0 ms	10.0 ms
t_2	± 3.125 kHz	20.0 ms	25.0 ms
t_3^4	± 6.25 kHz	5.0 ms	10.0 ms

a) Method of Measurement




TRANSIENT FREQUENCY BEHAVIOR

TEST PROCEEDURE: ANSI/TIA 603-D, the levels were set as follows:

1. Using the variable attenuator set the transmitter level was set to 40 dB below the test receivers maximum input level, then the transmitter was turned off.
2. With the transmitter off the signal generator was set 20dB below the level of the transmitter in the above step, this level will be maintained with the signal generator through-out the test.
3. Reduce the attenuation between the transmitter and the RF detector by 30 dB.
4. With the levels set as above, the transient frequency behavior was observed and recorded.


Test Results:

TRANSIENT FREQUENCY BEHAVIOR
Test Data: Turn ON



[Table of Contents](#)

TRANSIENT FREQUENCY BEHAVIOR
Test Data: Turn Off



Results: Meets requirements

[Table of Contents](#)

EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
DC Power Supply	HP	6286A	1744A03842	12/12/99	12/12/99
Antenna: Biconnical Chamber	Eaton Chamber	94455-1	1057	06/14/13	06/14/15
Antenna: Log-Periodic Chamber	Eaton	96005	1243	05/31/13	05/31/15
Temperature Chamber LARGE	Tenney Engineering	TTRC	11717-7	08/19/14	08/19/16
AC Voltmeter	HP	400FL	2213A14728	06/26/13	06/26/15
Digital Multimeter	Fluke	77	35053830	08/22/13	08/22/15
Frequency Counter Large Chamber	HP	5352B	2632A00165	06/26/13	06/26/15
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/13	12/31/15
Ant: Double-Ridged Horn/ETS Horn 1 Ch	ETS-Lindgren Chamber	3117	00035923	06/13/14	06/13/16
EMI Test Receiver R & S ESIB 40 Screen Room	Rohde & Schwarz	ESIB 40	100274	08/12/14	08/12/16
Software: Field Strength Program	Timco	N/A	Version 4.0	12/12/14	12/12/17
Hygro-Thermometer	Extech	445703	0602	06/20/13	06/20/15
30 dB Attenuator	Narda	769-30	10267	03/15/13	03/15/15
EMI Test Receiver R & S ESU 40 Chamber	Rohde & Schwarz	ESU 40	100320	03/11/14	03/11/16
Signal Generator HP 8648C	HP	8648C	3623A02898	08/29/13	08/29/15
Attenuator 30dB 500W	Bird	8325	1761	02/25/13	02/25/15

*EMI RECEIVER SOFTWARE VERSION

The receiver firmware used was version 4.43 Service Pack 3

[Table of Contents](#)

Applicant: KP ELECTRONIC SYSTEMS LTD.

FCC ID: H78KPMTPIT

Report: K\KP H78\335AUT15\335AUT15TestReport.docx