



MPE ESTIMATION

FCC ID: H79-NCX700

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

BT

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
GFSK	6.571	6±1(7)	5.01	1	1.2589	0.00126
π/4DQPSK	6.252	6±1(7)	5.01	1	1.2589	0.00126
8DPSK	6.522	6±1(7)	5.01	1	1.2589	0.00126

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-1E, antenna port 1 gain=1dBi



For antenna 1:

2.4G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	14.74	14±1(15)	31.62	1	1.2589	0.00792
11g	13.16	13±1(14)	25.12	1	1.2589	0.00629
11n/HT20	10.45	10±1(11)	12.59	1	1.2589	0.00315
11n/HT40	9.74	10±1(11)	12.59	1	1.2589	0.00315

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-2E, antenna port 1 gain=1dBi, antenna port 2 gain=1dBi, MIMO gain=4.01dBi

5.2G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11a	10.48	10±1(11)	12.59	1	1.2589	0.00315
11n(HT20)	10.42	10±1(11)	12.59	1	1.2589	0.00315
11n(HT40)	9.77	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT20)	10.36	10±1(11)	12.59	1	1.2589	0.00315
11ac(HT40)	9.22	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT80)	9.37	9±1(10)	10.00	1	1.2589	0.00251

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-3E, antenna port 1 gain=1dBi, antenna port 2 gain=1dBi, MIMO gain=4.01dBi



5.8G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11a	9.48	9±1(10)	10.00	1	1.2589	0.00251
11n(HT20)	9.88	9±1(10)	10.00	1	1.2589	0.00251
11n(HT40)	9.45	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT20)	8.86	8±1(9)	7.94	1	1.2589	0.00199
11ac(HT40)	8.86	8±1(9)	7.94	1	1.2589	0.00199
11ac(HT80)	8.17	8±1(9)	7.94	1	1.2589	0.00199

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-4E, antenna port 1 gain=1dBi, antenna port 2 gain=1dBi, MIMO gain=4.01dBi

For antenna 2:

2.4G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	14.63	14±1(15)	31.62	1	1.2589	0.00792
11g	12.66	12±1(13)	19.95	1	1.2589	0.00500
11n/HT20	10.48	10±1(11)	12.59	1	1.2589	0.00315
11n/HT40	10.12	10±1(11)	12.59	1	1.2589	0.00315

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-2E, antenna port 1 gain=1dBi, antenna port 2 gain=1dBi, MIMO gain=4.01dBi



5.2G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11a	10.66	10±1(11)	12.59	1	1.2589	0.00315
11n(HT20)	9.58	9±1(10)	10.00	1	1.2589	0.00251
11n(HT40)	9.47	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT20)	9.24	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT40)	8.65	8±1(9)	7.94	1	1.2589	0.00199
11ac(HT80)	9.76	9±1(10)	10.00	1	1.2589	0.00251

$$Pd = \frac{Pout * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-3E, antenna port 1 gain=1dBi, antenna port 2 gain=1dBi, MIMO gain=4.01dBi

5.8G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11a	9.56	9±1(10)	10.00	1	1.2589	0.00251
11n(HT20)	9.66	9±1(10)	10.00	1	1.2589	0.00251
11n(HT40)	9.35	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT20)	8.67	8±1(9)	7.94	1	1.2589	0.00199
11ac(HT40)	8.89	8±1(9)	7.94	1	1.2589	0.00199
11ac(HT80)	8.65	8±1(9)	7.94	1	1.2589	0.00199

$$Pd = \frac{Pout * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-4E, antenna port 1 gain=1dBi, antenna port 2 gain=1dBi, MIMO gain=4.01dBi



For MIMO: 2.4G WIFI

Mode	MPE (mW/cm ²)
11n/HT20	0.0063
11n/HT40	0.0063
Note: The estimation distance is 20cm	
Note: PK Output power= conducted power. Conducted power see the test report HK1910232645-2E, The MIMO mode power is max, so only calculate max power mode and antenna port 1 gain=1dBi, antenna port 2 gain=1dBi.	

5.2G WIFI

Mode	MPE (mW/cm ²)
11n(HT20)	0.00566
11n(HT40)	0.00502
11ac(HT20)	0.00566
11ac(HT40)	0.0045
11ac(HT80)	0.00502
Note: The estimation distance is 20cm	
Note: PK Output power= conducted power. Conducted power see the test report HK1910232645-3E, The MIMO mode power is max, so only calculate max power mode and antenna port 1 gain=1dBi, antenna port 2 gain=1dBi.	



5.8G WIFI

Mode	MPE (mW/cm ²)
11n(HT20)	0.00502
11n(HT40)	0.00502
11ac(HT20)	0.00398
11ac(HT40)	0.00398
11ac(HT80)	0.00398

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1910232645-4E, The MIMO mode power is max, so only calculate max power mode and antenna port 1 gain=1dBi, antenna port 2 gain=1dBi.

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine SAR test exclusion. The test exclusion threshold is 0.00792mW/cm² which is < 1.0mW/cm², SAR testing is not required.

-----The End-----