

## RF Exposure Evaluation declaration

|              |  |
|--------------|--|
| Product Name | DLP Projector                                |
| Model No.    | D85yyyyyy ( y can be any character or blank) |
| FCC ID       | H79D85YYYYYY                                 |

|           |  |
|-----------|--|
| Applicant | DELTA ELECTRONICS, INC.  |
| Address   | 3 Tungyuan Road Chungli Industrial Zone Taoyuan<br>County 32063, Taiwan. |

|                     |                    |
|---------------------|--------------------|
| Date of Receipt     | Apr. 23, 2012      |
| Date of Declaration | May. 23, 2012      |
| Report No.          | 124463R-RFUSP42V01 |

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz)                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures            |                               |                               |                                     |                        |
| 300-1500  | --                            | --                            | F/300                               | 6                      |
| 1500-100,000  | --                            | --                            | 5                                   | 6                      |
| (B) Limits for General Population/ Uncontrolled Exposures |                               |                               |                                     |                        |
| 300-1500  | --                            | --                            | F/1500                              | 6                      |
| 1500-100,000  | --                            | --                            | 1                                   | 30                     |

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : DLP Projector  
 Test Item : RF Exposure Evaluation  
 Test Site : No.3 OATS

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.85 dBi in logarithm scale.

#### Output Power Into Antenna & RF Exposure Evaluation Distance (2.85 dBi):

| Channel | Frequency (MHz) | Output Power to Antenna<br>(mW) | Power Density at R = 20 cm<br>(mW/cm <sup>2</sup> ) |
|---------|-----------------|---------------------------------|---|
| 01      | 2401.00         | 0.3148                          | 0.000121  |
| 16      | 2448.00         | 0.3319                          | 0.000127  |
| 29      | 2481.00         | 0.3954                          | 0.000152  |

Power density in column 4 is much lower than the limit (1 mW/cm<sup>2</sup>).