

Modular Approval Request FCC (per DA 00-1407) FCC ID: H79DFWM-GIN01

| | | D: H/9DFWM-GINUI |
|----|--|-----------------------------------|
| | as to be covered | Answer from applicant |
| 1. | The modular transmitter must have its own RF shielding. | The EUT has its own power |
| | | supply regulation. Please see |
| _ | | the schematic diagram. |
| 2. | The modular transmitter must have buffered modulation/data inputs (if such inputs | The EUT meets the FCC |
| | are provided) to ensure that the module will comply with Part 15 requirements | antenna requirement; unique |
| | under conditions of excessive data rates or over-modulation. | antenna connector and phone |
| | | of antenna are shown in the |
| | | test report. |
| 3. | The modular transmitter must have its own power supply regulation. | The EUT was tested in a |
| | | standalone configuration via a |
| | | test kit. Please see section |
| | | photographs of test |
| | | configuration in the test report. |
| 4. | The modular transmitter must comply with the antenna requirements of Section | Please see exhibition label |
| | 15.203 and 15.204(c). The antenna must either be permanently attached or employ | sample for FCC ID of this |
| | a "unique" antenna coupler (at all connections between the module and the antenna, | module. And also in the |
| | including the cable) | exhibition. Users manual. |
| 5. | The modular transmitter must be tested in a stand-alone configuration, i.e., the | The EUT is compliant with all |
| | module must not be inside another device during testing. This is intended to | applicable FCC rules. Details |
| | demonstrate that the module is capable of complying with Part 15 emission limits | instructions for maintaining |
| | regardless of the device into which it is eventually installed. | compliance are give in the |
| | , and the second | User Manual. |
| 6. | The modular transmitter must be labeled with its own FCC ID number, and, if the | The EUT comply with RF |
| | FCC ID is not visible when the module is installed inside another device, then the | exposure requirement. RF |
| | outside of the device into which the module is installed must also display a label | exposure is addressed in the |
| | referring to the enclosed module. This exterior label can use wording such as the | RF exposure exhibition. |
| | following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains | 1 |
| | FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning | |
| | may be used. The Grantee may either provide such a label, an example of which | |
| | must be included in the application for equipment authorization, or, must provide | |
| | adequate instructions along with the module which explain this requirement. In the | |
| | latter case, a copy of these instructions must be included in the application for | |
| | equipment authorization. | |
| 7. | The modular transmitter must comply with any specific rule or operating | The EUT has its own power |
| | requirements applicable to the transmitter and the manufacturer must provide | supply regulation. Please see |
| | adequate instructions along with the module to explain any such requirements. A | the schematic diagram. |
| | copy of these instructions must be included in the application for equipment | are seriemane diagram. |
| | authorization. For example, there are very strict operational and timing | |
| | requirements that must be met before a transmitter is authorized for operation under | |
| | Section 15.231. For instance, data transmission is prohibited, except for operation | |
| | under Section 15.231(e), in which case there are separate field strength level and | |
| | timing requirements. Compliance with these requirements must be assured. | |
| | Control of the case of the second and the control of The case of t | |
| 8. | The modular transmitter must comply with any applicable RF exposure | The EUT meets the FCC |
| | requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific | antenna requirement; unique |
| | Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), | antenna connector and phone |
| | require that Unlicensed PCS, UNII and millimeter wave devices perform routine | of antenna are shown in the |
| | environmental evaluation for RF Exposure to demonstrate compliance. In | test report. |
| | addition, spread spectrum transmitters operating under Section 15.247 are | test report. |
| | required to address RF Exposure compliance in accordance with Section | |
| | | |
| | 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, | |
| | when necessary, may also need to address certain RF Exposure concerns, | |
| | typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. | |
| | DISTANCES AND OTHER INTERESTED DATHES TO ENSURE COMBINANCE | |

Note: If compliance with one or more of the numbered requirements, listed above, cannot be demonstrated, it may be possible to obtain a "Limited Modular Approval" (LMA).

Name and surname of applicant (or authorized representative): Ray Chen

Date: Aug. 11, 2014 Signature: Pay Chen