



Neutron Engineering Inc.

Radio Test Report

FCC ID: H8GGL100

This report concerns (check one) : ☒ Original Grant ☐ Class I Change

Issued Date : Jul. 16, 2009
Project No. : R0905002
Equipment : 2.4G RF Keyboard
Model Name : GL-100; GLS-100

Applicant : A-FOUR TECH CO., LTD.
Address : 6F, No.108, Min-Chuan Rd., Hsin-Tien,
Taipei, Taiwan, R.O.C.

Tested by:
Neutron Engineering Inc. EMC Laboratory
Date of Test:
Jul. 06, 2009 ~ Jul. 10, 2009

Testing Engineer : Rush Kao
(Rush Kao)

Technical Manager : Jeff Yang
(Jeff Yang)

Authorized Signatory : Andy Chiu
(Andy Chiu)

Neutron Engineering Inc.

B1, No. 37, Lane 365, YangGuang St.,
NeiHu District 114, Taipei, Taiwan.

TEL: +886-2-2657-3299

FAX: +886-2-2657-3331





Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents	Page
1 . CERTIFICATION	5
2 . SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3 . GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
3.4 DESCRIPTION OF SUPPORT UNITS	12
4 . EMC EMISSION TEST	13
4.1 RADIATED EMISSION MEASUREMENT	13
4.1.1 RADIATED EMISSION LIMITS	13
4.1.2 MEASUREMENT INSTRUMENTS LIST	14
4.1.3 TEST PROCEDURE	14
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS-BETWEEN 30MHz – 1000MHz	16
4.1.8 TEST RESULTS-ABOVE 1000MHz	18
4.1.9 TEST RESULTS-RESTRICTED BANDS REQUIREMENTS	30
5 . BANDWIDTH TEST	34
5.1 APPLIED PROCEDURES / LIMIT	34
5.1.1 MEASUREMENT INSTRUMENTS LIST	34
5.1.2 TEST PROCEDURE	34
5.1.3 DEVIATION FROM STANDARD	34
5.1.4 TEST SETUP	34
5.1.5 EUT OPERATION CONDITIONS	34
5.1.6 TEST RESULTS	35
6 . PEAK OUTPUT POWER TEST	37
6.1 APPLIED PROCEDURES / LIMIT	37
6.1.1 MEASUREMENT INSTRUMENTS LIST	37
6.1.2 TEST PROCEDURE	37
6.1.3 DEVIATION FROM STANDARD	37
6.1.4 TEST SETUP	37
6.1.5 EUT OPERATION CONDITIONS	37
6.1.6 TEST RESULTS	38



Table of Contents	Page
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	39
7.1 APPLIED PROCEDURES / LIMIT	39
7.1.1 MEASUREMENT INSTRUMENTS LIST	39
7.1.2 TEST PROCEDURE	39
7.1.3 DEVIATION FROM STANDARD	39
7.1.4 TEST SETUP	39
7.1.5 EUT OPERATION CONDITIONS	39
7.1.6 TEST RESULTS	40
8 . POWER SPECTRAL DENSITY TEST	42
8.1 APPLIED PROCEDURES / LIMIT	42
8.1.1 MEASUREMENT INSTRUMENTS LIST	42
8.1.2 TEST PROCEDURE	42
8.1.3 DEVIATION FROM STANDARD	42
8.1.4 TEST SETUP	42
8.1.5 EUT OPERATION CONDITIONS	42
8.1.6 TEST RESULTS	43
9 . RF EXPOSURE TEST	45
9.1 APPLIED PROCEDURES / LIMIT	45
9.1.1 MEASUREMENT INSTRUMENTS LIST	45
9.1.2 MPE CALCULATION METHOD	45
9.1.3 DEVIATION FROM STANDARD	46
9.1.4 TEST SETUP	46
9.1.5 EUT OPERATION CONDITIONS	46
9.1.6 TEST RESULTS	46
10 . EUT TEST PHOTO	47



1. CERTIFICATION

Equipment : 2.4G RF Keyboard
Brand Name : A4TECH
Model No. : GL-100; GLS-100
Applicant : A-FOUR TECH CO., LTD.
Date of Test : Jul. 06, 2009 ~ Jul. 10, 2009
Test Item : ENGINEERING SAMPLE
Standards : FCC Part15, Subpart C(15.247) / ANCI C63.4 : 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-R0905002) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

**2. SUMMARY OF TEST RESULTS**

Test procedures according to the technical standards:

FCC Part15, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.247 (c)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	
1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

**2.1 TEST FACILITY**

The test facilities used to collect the test data in this report is **CB08(FCC R.N.: 614388)** at the location of 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Neutron's test firm number is 614388

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %** ◦

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
OS-01	ANSI	30MHz ~ 200MHz	V	2.86	
		30MHz ~ 200MHz	H	2.56	
		200MHz ~ 1,000MHz	V	2.88	
		200MHz ~ 1,000MHz	H	2.98	
OS-02	ANSI	30MHz ~ 200MHz	V	2.48	
		30MHz ~ 200MHz	H	2.16	
		200MHz ~ 1,000MHz	V	2.50	
		200MHz ~ 1,000MHz	H	2.66	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	2.4G RF Keyboard	
Brand Name	A4TECH	
Model No.	GL-100; GLS-100	
OEM Brand/Model No.	N/A	
Model Difference	Models' differences between each other only the changes of model name which do not affect the EMI performance. Model GL-100 was used for final testing and collecting test data included in this report.	
Product Description	The EUT is a 2.4G RF Keyboard.	
	Operation Frequency:	2407~2473MHz
	Modulation Type:	GFSK
	Number Of Channel	29CH
	Antenna Designation:	Please refer to the Note 3.
	Antenna Gain(Peak)	Please refer to the Note 3.
	Output Power:	0.43dBm (Max.)
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Power Source	Battery supplied	
Power Rating	DC 3V	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2407	08	2424	16	2443	24	2462
01	2409	09	2426	17	2445	25	2465
02	2411	10	2428	18	2447	26	2468
03	2413	11	2430	19	2451	27	2471
04	2415	12	2434	20	2454	28	2473
05	2417	13	2437	21	2456		
06	2420	14	2439	22	2458		
07	2422	15	2441	23	2460		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printer Antenna	N/A	0.37



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Test Mode	Description
Mode 1	CH00
Mode 2	CH14
Mode 3	CH28

For Radiated Test (30 -1000MHz)	
Final Test Mode	Description
Mode 2	CH14

For Radiated Test (Above 1000MHz)	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH14
Mode 3	CH28



3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



**3.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	2.4G RF Keyboard	A4TECH	GL-100	H8GGL100	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
	N/A	N/A	N/A	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



4. EMC EMISSION TEST

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



4.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Log-Bicon Antenna	Schwarzbeck	VULB 9160	3176	Jul. 24, 2009
2	Test Cable	N/A	LMR-400	N/A	Jan. 05, 2010
3	Test Cable	N/A	OS01-1/-2	N/A	Oct. 08, 2009
4	Pre-Amplifier	Anritsu	MH648A	M09961	Dec. 29, 2009
5	Spectrum Analyzer	HP	8591EM	3536A00687	Mar. 13, 2010
6	EMI Measuring Receiver	SHCAFFNER	SCR 3501	408	Nov. 24, 2009
7	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010
8	Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-546	May 19, 2010
9	Microwave Pre-amplifier	Agilent	8449B	3008A02331	Jan. 19, 2010
10	Microflex Cable	NA	NA	1m	Sep. 15, 2009
11	Microflex Cable	NA	NA	10M	Feb. 19, 2010

Remark: " N/A" denotes No Model No. / Serial No. and No Calibration specified.

4.1.3 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation

4.1.5 TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operation condition was tested and used to collect the included data.




4.1.7 TEST RESULTS-BETWEEN 30MHz – 1000MHz

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23 °C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH14		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
119.24	V	38.17	-21.93	16.24	43.50	- 27.26	
224.00	V	38.62	-22.81	15.81	46.00	- 30.19	
255.04	V	39.91	-21.87	18.04	46.00	- 27.96	
288.02	V	43.19	-20.87	22.32	46.00	- 23.68	
319.06	V	39.37	-20.09	19.28	46.00	- 26.72	
412.18	V	35.71	-18.00	17.71	46.00	- 28.29	

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz ◦
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz ◦
- (4) If the peak scan value is under the limit for more than 20dB, the signal will not show in table ◦






EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH14		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
224.00	H	48.60	-22.81	25.79	46.00	- 20.21	
255.04	H	51.26	-21.87	29.39	46.00	- 16.61	
288.02	H	50.56	-20.87	29.69	46.00	- 16.31	
319.06	H	49.75	-20.09	29.66	46.00	- 16.34	
352.04	H	43.95	-19.38	24.57	46.00	- 21.43	
383.08	H	39.16	-18.72	20.44	46.00	- 25.56	

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz ◦
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz ◦
- (4) If the peak scan value is under the limit for more than 20dB, the signal will not show in table ◦





4.1.8 TEST RESULTS-ABOVE 1000MHz

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH00		



Freq. (MHz)	Ant. Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	18.39	11.25	32.38	50.77	43.63	74.00	54.00	X/E
2407.20	V	58.26	13.34	32.45	90.71	45.79			X/F
4814.16	V	52.12	29.13	4.42	56.54	33.55	74.00	54.00	X/H
7220.88	V	44.96	30.79	10.72	55.68	41.51	74.00	54.00	X/H

Remark :

- (1) Spectrum Setting :
 QP: 30MHz – 1000MHz: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
 Peak: 1GHz- 25GHz: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
 AV: 1GHz- 25GHz: RBW= 1MHz, VBW= 10Hz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ “F” denotes fundamental frequency; “H” denotes spurious frequency. “E” denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown “ * ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes :
 “X” - denotes Laid on Table ; “Y” - denotes Vertical Stand ; “Z” - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Orthogonal Axes : X
CH00 (Above 1000 MHz, Vertical)





EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH00		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	28.89	11.38	32.38	61.27	43.76	74.00	54.00	X/E
2407.12	H	68.77	13.97	32.45	101.22	46.42			X/F
4813.40	H	46.39	30.34	4.41	50.80	34.75	74.00	54.00	X/H
7221.00	H	47.80	30.84	10.72	58.52	41.56	74.00	54.00	X/H

Remark :

- (1) Spectrum Setting :
 QP: 30MHz – 1000MHz: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
 Peak: 1GHz- 25GHz: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
 AV: 1GHz- 25GHz: RBW= 1MHz, VBW= 10Hz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Orthogonal Axes : X
CH00 (Above 1000 MHz, Horizontal)





EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH14		



Freq. (MHz)	Ant. Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2438.80	V	59.33	12.76	32.57	91.90	45.33			X/F
4878.00	V	50.27	28.24	4.58	54.85	32.82	74.00	54.00	X/H

Remark :

- (1) Spectrum Setting :
 QP: 30MHz – 1000MHz: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
 Peak: 1GHz- 25GHz: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
 AV: 1GHz- 25GHz: RBW= 1MHz, VBW= 10Hz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Orthogonal Axes : X
CH14(Above 1000 MHz, Vertical)





EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH14		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2439.00	H	71.23	13.40	32.57	103.80	45.97			X/F
4878.00	H	45.95	29.67	4.58	50.53	34.25	74.00	54.00	X/H

Remark :

- (1) Spectrum Setting :
 QP: 30MHz – 1000MHz: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
 Peak: 1GHz- 25GHz: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
 AV: 1GHz- 25GHz: RBW= 1MHz, VBW= 10Hz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Orthogonal Axes : X
CH14(Above 1000 MHz, Horizontal)





EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH28		



Freq. (MHz)	Ant. Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2473.20	V	59.06	13.43	32.70	91.76	46.13			X/F
2483.50	V	27.57	11.32	32.74	60.31	44.06	74.00	54.00	X/E
4946.00	V	50.00	30.63	4.76	54.76	35.39	74.00	54.00	X/H

Remark :

- (1) Spectrum Setting :
 QP: 30MHz – 1000MHz: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
 Peak: 1GHz- 25GHz: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
 AV: 1GHz- 25GHz: RBW= 1MHz, VBW= 10Hz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Orthogonal Axes : X
CH28 (Above 1000 MHz, Vertical)





EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	CH28		



Freq. (MHz)	Ant. Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2473.10	H	67.94	14.08	32.70	100.64	46.78			X/F
2483.50	H	32.42	11.42	32.74	65.16	44.16	74.00	54.00	X/E
4946.00	H	43.22	30.21	4.76	47.98	34.97	74.00	54.00	X/H

Remark :

- (1) Spectrum Setting :
 QP: 30MHz – 1000MHz: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
 Peak: 1GHz- 25GHz: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
 AV: 1GHz- 25GHz: RBW= 1MHz, VBW= 10Hz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Orthogonal Axes : X
CH28 (Above 1000 MHz, Horizontal)





4.1.9 TEST RESULTS-RESTRICTED BANDS REQUIREMENTS

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	TX CH 2407MHz/2473MHz(Vertical)		
Note :	The emission of the carrier radiated field strength is measured for (Peak and AV) as following: 1. The transmitter was then configured with the worst case antenna and setup to transmit at the lowest channel (CH00). Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was configured with the worst case antenna and setup to transmit at the highest channel (CH28). Then the field strength was measured at 2483.5-2500 MHz.		


Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	18.39	11.25	32.38	50.77	43.63	74.00	54.00	CH00
2483.50	V	27.57	11.32	32.74	60.31	44.06	74.00	54.00	CH28

Remark :


- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (2) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand



TX CH00 (Restricted Bands Requirements, Vertical)



TX CH28 (Restricted Bands Requirements, Vertical)





EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	23°C	Relative Humidity :	42%
Test Power :	DC 3V		
Test Mode :	TX CH 2407MHz/2473MHz (Horizontal)		
Note :	The emission of the carrier radiated field strength is measured for (Peak and AV) as following: 1. The transmitter was then configured with the worst case antenna and setup to transmit at the lowest channel (CH00). Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was configured with the worst case antenna and setup to transmit at the highest channel (CH28). Then the field strength was measured at 2483.5-2500 MHz.		


Freq. (MHz)	Ant. Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	28.89	11.38	32.38	61.27	43.76	74.00	54.00	CH00
2483.50	H	32.42	11.42	32.74	65.16	44.16	74.00	54.00	CH28

Remark :


- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (2) EUT Orthogonal Axes :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand



TX CH00 (Restricted Bands Requirements, Horizontal)



TX CH28 (Restricted Bands Requirements, Horizontal)





5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C			
Test Item	Limit	Frequency Range (MHz)	Result
Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010

Remark: " N/A" denotes No Model No. , Serial No. or No Calibration specified.

5.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP



5.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





5.1.6 TEST RESULTS

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	29 °C	Relative Humidity :	76%
Test Power :	DC 3V		
Test Mode :	CH00/CH14/CH28		

Test Channel	Frequency (MHz)	Bandwidth (MHz)	99% Occupied BW (MHz)	LIMIT (MHz)
CH00	2407	0.57	1.40	>=500KHz
CH14	2439	0.56	1.42	>=500KHz
CH28	2473	0.57	1.42	>=500KHz







6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C			
Test Item	Limit	Frequency Range (MHz)	Result
Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487A	6K00004714	Feb. 10, 2010
2	Power Meter Sensor	Anritsu	MA2491A	34138	Feb. 10, 2010

Remark: " N/A" denotes No Model No. , Serial No. or No Calibration specified.

6.1.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,

6.1.3 DEVIATION FROM STANDARD

No deviation.

6.1.4 TEST SETUP



6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.6 TEST RESULTS

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	29 ° C	Relative Humidity :	76%
Test Power :	DC 3V		
Test Mode :	CH00/CH14/CH28		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH00	2407	0.43	30	1
CH14	2439	0.13	30	1
CH28	2473	0.29	30	1



7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C			
Test Item	Limit	Frequency Range (MHz)	Result
Antenna conducted Spurious Emission	20dB less than the peak value of fundamental frequency	30-25000	PASS

7.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010

Remark: " N/A" denotes No Model No. , Serial No. or No Calibration specified.


7.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP



7.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.




7.1.6 TEST RESULTS

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	29 °C	Relative Humidity :	76%
Test Power :	DC 3V		
Test Mode :	CH00/CH28		

Channel of Worst Data: CH00,CH28			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2310.8	-54.61	2488.9	-48.26
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			







8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C			
Test Item	Limit	Frequency Range (MHz)	Result
Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

8.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010

Remark: " N/A" denotes No Model No. , Serial No. or No Calibration specified.


8.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW=3KHz, VBW=30KHz, Sweep time = 500s.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP



8.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





8.1.6 TEST RESULTS

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	29 °C	Relative Humidity :	76%
Test Power :	DC 3V		
Test Mode :	CH00/CH14/CH28		

Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH00	2407	-8.46	8
CH14	2439	-8.29	8
CH28	2473	-7.90	8







9. RF EXPOSURE TEST

9.1 APPLIED PROCEDURES / LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

9.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487A	6K00004714	Feb. 10, 2010
2	Power Meter Sensor	Anritsu	MA2491A	34138	Feb. 10, 2010

Remark: " N/A" denotes No Model Name , Serial No. or No Calibration specified.

9.1.2 MPE CALCULATION METHOD

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



9.1.3 DEVIATION FROM STANDARD

No deviation.

9.1.4 TEST SETUP



9.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

9.1.6 TEST RESULTS

EUT :	2.4G RF Keyboard	Model No. :	GL-100
Temperature :	29° C	Relative Humidity :	76%
Test Power :	DC 3V		
Test Mode :	CH00/CH14/CH28		

CH00/2407MHz						
Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0.37	1.0889	0.4300	1.1041	0.000239	1	Complies



CH14/2439MHz						
Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0.37	1.0889	0.1300	1.0304	0.000223	1	Complies

CH28/2473MHz						
Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0.37	1.0889	0.2900	1.0691	0.000232	1	Complies



10. EUT TEST PHOTO

Radiated Measurement Photos



Radiated Measurement Photos

