

FCC Radio Test Report

FCC ID: H8GGN30

This report concerns (check one): ☒ Original Grant ☐ Class II Change

Project No. : 1601183
Equipment : 2.4G RF Dongle
Model Name : GN-30
Applicant : A-FOUR TECH CO., LTD.
Address : 6F., No.108, Min-Chuan Rd., Xindian Dist., New Taipei City, Taiwan R.O.C.

Date of Receipt : Jan. 27, 2016
Date of Test : Jan. 27, 2016 ~ Mar. 17, 2016
Issued Date : Mar. 22, 2016
Tested by : BTL Inc.

Testing Engineer : Rush Kao
(Rush Kao)

Technical Manager : Jeff Yang
(Jeff Yang)

Authorized Signatory : Andy Chiu
(Andy Chiu)

B T L I N C .

B1, No.37, Lane 365, Yang Guang St.,
Nei-Hu District, Taipei City 114, Taiwan.
TEL:+886-2-2657-3299 FAX: +886-2- 2657-3331

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	10
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
3.5 DESCRIPTION OF SUPPORT UNITS	11
4 . EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 EUT TEST CONDITIONS	13
4.1.7 TEST RESULTS	13
4.2 RADIATED EMISSION MEASUREMENT	14
4.2.1 RADIATED EMISSION LIMITS	14
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	15
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS	17
4.2.6 EUT TEST CONDITIONS	17
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	17
4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)	17
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	18
5 . BANDWIDTH TEST	19
5.1 TEST PROCEDURE	19
5.2 DEVIATION FROM STANDARD	19
5.3 TEST SETUP	19
5.4 EUT OPERATION CONDITIONS	19
5.5 EUT TEST CONDITIONS	19
5.6 TEST RESULTS	19
6 . MEASUREMENT INSTRUMENTS LIST	20
7 . EUT TEST PHOTO	21

Table of Contents	Page
ATTACHMENT A - CONDUCTED EMISSION	25
ATTACHMENT B -RADIATED EMISSION (9KHZ TO 30MHZ)	28
ATTACHMENT C -RADIATED EMISSION (30MHZ TO 1000MHZ)	33
ATTACHMENT D -RADIATED EMISSION (ABOVE 1000MHZ)	36
ATTACHMENT E - BANDWIDTH	49

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1601183	Original Issue.	Mar. 22, 2016

1. CERTIFICATION

Equipment : 2.4G RF Dongle

 Brand Name : bloodyY, A4Tech
 Model Name : GN-30
 Applicant : A-FOUR TECH CO., LTD.
 Date of Test : Jan. 27, 2016 ~ Mar. 17, 2016
 Standard(s) : FCC Part15, Subpart C (15.249) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1601183) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.249)			
Standard(s) Section	Test Item	Judgment	Remark
15.207(a)	Conducted Emission	PASS	
15.205	Restricted Band of Operation	PASS	
15.209 15.249(a)	Radiated Emissions	PASS	
15.215(c)	20dB Bandwidth Test	PASS	

NOTE:

(1) "N/A" denotes test is not applicable to this device.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

Conducted emission Test:

C05: (VCCI RN: C-4742; FCC RN:949005; FCC DN:TW1082)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Radiated emission Test (Below 1 GHz):

CB11: (VCCI RN: R-4260; FCC RN:949005; FCC DN:TW1082; IC Assigned Code:20088)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Radiated emission Test (Above 1 GHz):

CB11: (VCCI RN: G-868; FCC RN:949005; FCC DN:TW1082; IC Assigned Code:20088)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty is not specified by FCC rules and Canada Industry for reference only.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U,(dB)
C05	CISPR	150 kHz ~ 30MHz	2.04

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U,(dB)
CB11 (3m)	CISPR	9kHz ~ 150kHz	4.00
		150kHz ~ 30MHz	4.00

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
CB11 (3m)	CISPR	30MHz ~ 200MHz	V	3.06
		30MHz ~ 200MHz	H	2.58
		200MHz ~ 1,000MHz	V	3.50
		200MHz ~ 1,000MHz	H	3.10

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
CB11 (3m)	CISPR	1GHz ~ 6GHz	V	4.14
		1GHz ~ 6GHz	H	4.14
		6GHz ~ 18GHz	V	5.34
		6GHz ~ 18GHz	H	5.34

Note: unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz : 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz : 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	2.4G RF Dongle	
Brand Name	bloodY,  ,A4Tech	
Model Name	GN-30	
Model Difference	N/A	
Product Description	Operation Frequency	2404.5~2477.5 MHz
	Modulation Technology	GFSK
	Bit Rate of Transmitter	2 Mbps
	Field Strength	61.38dBuV/m (AVG Max) 93.64dBuV/m (Peak Max)
Power Source	Supplied from USB Port.	
Power Rating	I/P: DC 5V 30mA	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. Channel List:

Channel	Frequency (MHz)		Channel	Frequency (MHz)	
	TX	RX		TX	RX
01	2404.5	2402.5	13	2440	2438
02	2406.5	2404.5	14	2442.5	2440.5
03	2409	2407	15	2444.5	2442.5
04	2411	2409	16	2450.5	2448.5
05	2413	2411	17	2453	2451
06	2419	2417	18	2455	2453
07	2421.5	2419.5	19	2457.5	2455.5
08	2423.5	2421.5	20	2467.5	2465.5
09	2426	2424	21	2472.5	2470.5
10	2428	2426	22	2475.5	2473.5
11	2436	2434	23	2477.5	2475.5
12	2438	2436			

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	PSA	N/A	Chip	N/A	2.00

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:


For Conducted Test	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX Mode NOTE (1)

Note:

(1) The measurements are performed at the high, middle, low available channels.

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	Notebook PC	ASUS	X450J	DOC	E8N0WU31377235F

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.22m	USB Cable

Note:

(1) The support equipment was authorized by Declaration of Conformity (DOC).

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 54%
Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』 . If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform.In this case, a “ * ” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) “ N/A” denotes test is not applicable to this device.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.209)

FREQUENCY (MHz)	(dBuV/m) (at 3m)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC Part 15.249)

FCC Part15 (15.249) , Subpart C	
Limit	Frequency Range(MHz)
Field strength of fundamental 50000 μ V/m (94 dB μ V/m) @ 3 m	2400-2483.5
Field strength of harmonics 500 μ V/m (54 dB μ V/m) @ 3 m	Above 2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 **unless** otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 45%

Test Voltage: DC 3.7V

4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Attachment C.

Remark:

- (1) Measuring frequency range from 30MHz to 1000MHz.
- (2) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

4.2.9TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (2) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (3) EUT Orthogonal Axis:
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (4) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (5) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH TEST

5.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.2 DEVIATION FROM STANDARD

No deviation.

5.3 TEST SETUP



5.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC 3.7V

5.6 TEST RESULTS

Please refer to the Attachment E.

6. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TWO-LINE V-NETWORK	R&S	ENV216	101050	Jan. 26, 2017
2	Test Cable	TIMES	CFD300-NL	C02	Jun. 14, 2016
3	EMI Test Receiver	R&S	ESR7	101433	Dec. 09, 2016
4	Power Dividers	HP	11636A	8103	May 04, 2016
5	Measurement Software	EZ	EZ EMC (Version NB-03A)	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jul. 30, 2016
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 20, 2016
3	Horn Antenna	Schwarzbeck	BBHA 9120	9120D-1333	May 20, 2016
4	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 16, 2016
5	Pre-Amplifier	Agilent	8449B	3008A01714	Apr. 14, 2016
6	Test Cable	LMR	LMR-400	01(10M)	May 12, 2016
7	Test Cable	LMR	LMR-400	01(3M)	May 12, 2016
8	Test Cable	Harbour industries	27478LL142	1M	May 13, 2016
9	Test Cable	Harbour industries	27478LL142	3M	May 13, 2016
10	Test Cable	AISI	S104-SMAP-1	8M	May 13, 2016
11	Spectrum Analyzer	Agilent	N9020A	MY51160196	Aug. 02, 2016
12	EMI Test Receiver	R&S	ESCI	100080	May 13, 2016
13	Measurement Software	Farad	EZ EMC (Version NB-03A)	N/A	N/A
14	Loop Ant	EMCO	6502	42960	Nov.15.2016


Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 07, 2016

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.



7. EUT TEST PHOTO

Conducted Measurement Photos





Radiated Measurement Photos

9K-30MHz



Radiated Measurement Photos

30MHz-1G



Radiated Measurement Photos


Above 1G



ATTACHMENT A - CONDUCTED EMISSION

Test Mode	TX Mode
-----------	---------


Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	30.80	9.67	40.47	65.99	-25.52	QP	
2		0.1500	20.50	9.67	30.17	55.99	-25.82	AVG	
3		0.2291	35.20	9.66	44.86	62.48	-17.62	QP	
4		0.2291	24.50	9.66	34.16	52.48	-18.32	AVG	
5	*	0.6350	34.00	9.68	43.68	56.00	-12.32	QP	
6		0.6350	18.20	9.68	27.88	46.00	-18.12	AVG	
7		1.0760	26.70	9.70	36.40	56.00	-19.60	QP	
8		1.0760	14.60	9.70	24.30	46.00	-21.70	AVG	
9		2.0570	25.10	9.76	34.86	56.00	-21.14	QP	
10		2.0570	19.70	9.76	29.46	46.00	-16.54	AVG	
11		14.6000	26.50	9.85	36.35	60.00	-23.65	QP	
12		14.6000	20.40	9.85	30.25	50.00	-19.75	AVG	

Test Mode	TX Mode
-----------	---------

Neutral




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1514	33.10	9.66	42.76	65.92	-23.16	QP	
2		0.1514	22.50	9.66	32.16	55.92	-23.76	AVG	
3		0.3845	27.20	9.67	36.87	58.18	-21.31	QP	
4		0.3845	24.10	9.67	33.77	48.18	-14.41	AVG	
5	*	0.6530	33.40	9.69	43.09	56.00	-12.91	QP	
6		0.6530	18.50	9.69	28.19	46.00	-17.81	AVG	
7		1.0850	27.20	9.70	36.90	56.00	-19.10	QP	
8		1.0850	15.50	9.70	25.20	46.00	-20.80	AVG	
9		2.0570	28.20	9.75	37.95	56.00	-18.05	QP	
10		2.0570	20.60	9.75	30.35	46.00	-15.65	AVG	
11		13.9000	24.80	9.88	34.68	60.00	-25.32	QP	
12		13.9000	18.80	9.88	28.68	50.00	-21.32	AVG	

ATTACHMENT B -RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode	TX Mode
-----------	---------


Open



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.0140	47.15	19.40	66.55	128.16	-61.61	peak	

Test Mode	TX Mode
-----------	---------


Open



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.5082	36.55	11.80	48.35	73.64	-25.29	peak	
2		1.0754	30.36	11.97	42.33	68.58	-26.25	peak	
3		1.7022	25.41	11.68	37.09	62.99	-25.90	peak	
4		2.1201	23.06	11.50	34.56	69.54	-34.98	peak	
5		3.2244	19.31	11.13	30.44	69.54	-39.10	peak	
6		4.3290	18.38	11.30	29.68	69.54	-39.86	peak	

Test Mode	TX Mode
-----------	---------


Close



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0100	45.72	20.50	66.22	128.45	-62.23	peak	

Test Mode	TX Mode
-----------	---------

Close




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.5680	35.78	11.83	47.61	73.10	-25.49	peak	
2		0.9261	31.48	11.97	43.45	69.91	-26.46	peak	
3		1.4336	27.49	11.80	39.29	65.39	-26.10	peak	
4		1.8216	24.07	11.63	35.70	69.54	-33.84	peak	
5		2.2395	24.62	11.44	36.06	69.54	-33.48	peak	
6		3.5530	18.85	11.18	30.03	69.54	-39.51	peak	

ATTACHMENT C -RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode	TX Mode
-----------	---------


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		146.4000	37.03	-8.71	28.32	43.50	-15.18	peak	
2		167.7400	37.18	-8.79	28.39	43.50	-15.11	peak	
3		232.7300	38.20	-9.95	28.25	46.00	-17.75	peak	
4		445.1600	34.80	-3.65	31.15	46.00	-14.85	peak	
5		599.3900	32.10	-0.23	31.87	46.00	-14.13	peak	
6	*	760.4100	31.30	2.45	33.75	46.00	-12.25	peak	

Test Mode	TX Mode
-----------	---------


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		137.6700	33.03	-8.86	24.17	43.50	-19.33	peak	
2		206.5400	42.00	-10.87	31.13	43.50	-12.37	peak	
3		277.3500	41.26	-8.06	33.20	46.00	-12.80	peak	
4		501.4200	36.10	-2.62	33.48	46.00	-12.52	peak	
5		573.2000	29.72	-0.92	28.80	46.00	-17.20	peak	
6	*	760.4100	32.32	2.45	34.77	46.00	-11.23	peak	

ATTACHMENT D -RADIATED EMISSION (ABOVE 1000MHZ)


Test Mode	TX Low Channel
-----------	----------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2385.000	26.13	32.12	58.25	74.00	-15.75	peak	
2	*	2385.000	12.28	32.12	44.40	54.00	-9.60	AVG	
3		2404.500	58.75	32.21	90.96	114.00	-23.04	peak	
4		2404.500	27.87	32.21	60.08	94.00	-33.92	AVG	


Test Mode	TX Low Channel
-----------	----------------

Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4809.000	65.21	-9.69	55.52	74.00	-18.48	peak	
2		4809.000	49.33	-9.69	39.64	54.00	-14.36	AVG	
3		7213.500	61.94	-3.72	58.22	74.00	-15.78	peak	
4		7213.500	46.78	-3.72	43.06	54.00	-10.94	AVG	
5		9618.000	59.67	-1.06	58.61	74.00	-15.39	peak	
6	*	9618.000	45.12	-1.06	44.06	54.00	-9.94	AVG	


Test Mode	TX Low Channel
-----------	----------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	25.78	32.14	57.92	74.00	-16.08	peak	
2	*	2390.000	12.35	32.14	44.49	54.00	-9.51	AVG	
3		2404.500	60.70	32.21	92.91	114.00	-21.09	peak	
4		2404.500	28.61	32.21	60.82	94.00	-33.18	AVG	

Test Mode	TX Low Channel
-----------	----------------


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4809.000	62.53	-9.69	52.84	74.00	-21.16	peak	
2		4809.000	47.63	-9.69	37.94	54.00	-16.06	AVG	
3		7213.500	63.90	-3.72	60.18	74.00	-13.82	peak	
4		7213.500	47.33	-3.72	43.61	54.00	-10.39	AVG	
5		9618.000	57.80	-1.06	56.74	74.00	-17.26	peak	
6	*	9618.000	46.57	-1.06	45.51	54.00	-8.49	AVG	

Test Mode	TX Middle Channel
-----------	-------------------


Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment				
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2438.000	59.42	32.35	91.77	114.00	-22.23	peak	
2		2438.000	28.16	32.35	60.51	94.00	-33.49	AVG	

Test Mode	TX Middle Channel
-----------	-------------------


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4876.000	62.60	-9.43	53.17	74.00	-20.83	peak	
2		4876.000	47.23	-9.43	37.80	54.00	-16.20	AVG	
3		7314.000	60.35	-3.49	56.86	74.00	-17.14	peak	
4		7314.000	45.56	-3.49	42.07	54.00	-11.93	AVG	
5		9752.000	61.06	-0.41	60.65	74.00	-13.35	peak	
6	*	9752.000	45.78	-0.41	45.37	54.00	-8.63	AVG	

Test Mode	TX Middle Channel
-----------	-------------------


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2438.000	59.53	32.35	91.88	114.00	-22.12	peak	
2		2438.000	28.21	32.35	60.56	94.00	-33.44	AVG	


Test Mode	TX Middle Channel
-----------	-------------------

Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4876.000	62.61	-9.43	53.18	74.00	-20.82	peak	
2		4876.000	47.21	-9.43	37.78	54.00	-16.22	AVG	
3		7314.000	60.58	-3.49	57.09	74.00	-16.91	peak	
4		7314.000	45.46	-3.49	41.97	54.00	-12.03	AVG	
5		9752.000	58.61	-0.41	58.20	74.00	-15.80	peak	
6	*	9752.000	45.18	-0.41	44.77	54.00	-9.23	AVG	


Test Mode	TX High Channel
-----------	-----------------



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	2477.500	59.49	32.53	92.02	114.00	-21.98	peak	
2	2477.500	28.27	32.53	60.80	94.00	-33.20	AVG	
3	2483.500	26.10	32.55	58.65	74.00	-15.35	peak	
4 *	2483.500	12.90	32.55	45.45	54.00	-8.55	AVG	


Test Mode	TX High Channel
-----------	-----------------

Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4955.000	70.31	-9.13	61.18	74.00	-12.82	peak	
2		4955.000	51.62	-9.13	42.49	54.00	-11.51	AVG	
3		7432.500	45.83	-3.22	42.61	54.00	-11.39	AVG	
4		7432.500	59.43	-3.21	56.22	74.00	-17.78	peak	
5		9910.000	58.87	0.36	59.23	74.00	-14.77	peak	
6	*	9910.000	44.71	0.36	45.07	54.00	-8.93	AVG	


Test Mode	TX High Channel
-----------	-----------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2477.500	61.11	32.53	93.64	114.00	-20.36	peak	
2		2477.500	28.85	32.53	61.38	94.00	-32.62	AVG	
3		2483.500	26.25	32.55	58.80	74.00	-15.20	peak	
4	*	2483.500	12.99	32.55	45.54	54.00	-8.46	AVG	

Test Mode	TX High Channel
-----------	-----------------

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4955.000	67.80	-9.13	58.67	74.00	-15.33	peak	
2		4955.000	50.93	-9.13	41.80	54.00	-12.20	AVG	
3		7432.500	58.92	-3.21	55.71	74.00	-18.29	peak	
4		7432.500	46.08	-3.21	42.87	54.00	-11.13	AVG	
5		9910.000	58.70	0.36	59.06	74.00	-14.94	peak	
6	*	9910.000	44.66	0.36	45.02	54.00	-8.98	AVG	

ATTACHMENT E - BANDWIDTH

Test Mode:	TX Mode
------------	---------

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)
Low Channel	2.39	2.18
Middle Channel	2.39	2.15
High Channel	2.34	2.16

TX Low Channel



Date: 14.MAR.2016 21:13:12

TX Middle Channel



Date: 15.MAR.2016 11:49:41

TX High Channel



Date: 14.MAR.2016 21:20:31