

Date: July 1, 2021

Askey Computer Corporation

10F, No. 119, Jiankang Rd., Zhonghe Dist., New Taipei City, Taiwan

Request for Modular/Limited Modular Approval

Sub	ject: Manufacturer's Declaration for	☑ - Modular Approval☐ - Limited Modular Approval	-	Modular Approval ed Split Modular Approval		
Cor	fidentiality Request for: <u>H8N-AP62</u>	<u>75S</u>				
		sic Requirements – FCC Part 15.212(Limited Module Description Must be		llowing Page	2	
		pproval Requirement	i meu out on the ro	Requirement Met		
1.	The modular transmitter must have its own does not have to rely upon the shielding pro modular transmitter emissions to comply wibetween the RF circuitry of the module and installed. Such coupling may result in non-capacitors may be located external to the sh	RF shielding. This is intended to ensure vided by the device into which it is instath FCC limits. It is also intended to prevany wires or circuits in the device into vompliant operation. The physical crysta	alled in order for all vent coupling which the module is	⊠ - YES	□ - NO(*)	
	The radio portion of this module has been s	hielded, please see exhibition External l	Photo.			
2.	The modular transmitter must have buffered ensure that the module will comply with FC over-modulation. 15.212(a)(1)(ii)			⊠ - YES	□ - NO(*)	
	Data to the modulation circuit is buffered a.	s described in the operational description	on provided with the a	application.		
3.	The modular transmitter must have its own ensure that the module will comply with FC supplying circuitry in the device into which	C requirements regardless of the design	of the power	⊠ - YES	□ - NO(*)	
	The module contains its own power supply i	regulation. Please refer to schematic fil	ed with this application	on.		
4.	The modular transmitter must comply with \$\\$ 15.203, 15.204(b), 15.204(c), 15.212(a), attached or employ a "unique" antenna cou antenna, including the cable). The "professi to modules but can apply to limited modular	and 2.929(b). The antenna must either bupler (at all connections between the motional installation' provision of § 15.203	be permanently dule and the B is not applicable	⊠ - YES	□ - NO(*)	
	The EUT meets the FCC antenna requireme in the test report.	nts. The spurious emission, unique ante	nna connector and pl	hoto of antenn	as are shown	
5.	The modular transmitter must be tested in a inside another device during testing. This is complying with Part 15 emission limits regardless the transmitter module will be batter requirements found in Section 15.207. AC of the module must not contain ferrites, unless 15.27(a)). The length of these lines shall be least 10 centimeters to insure that there is no equipment. Any accessories, peripherals, or shall be unmodified or commercially available.	intended to demonstrate that the module ardless of the device into which it is every powered, it must comply with the AC or DC power lines and data input/output they will be marketed with the module length typical of actual use or, if that less coupling between the case of the modus support equipment connected to the module length typical or actual use or, if the less coupling between the case of the module support equipment connected to the module.	e is capable of ntually installed. line conducted lines connected to (see Section ngth is unknown, at alle and supporting dule during testing	⊠ - YES	□ - NO(*)	
	The EUT was tested in a stand-alone config		n Photographs of Tes	t Configuratio	on in the test	



Askey Computer Corporation

10F, No. 119, Jiankang Rd., Zhonghe Dist., New Taipei City, Taiwan

	Modular Approval Requirement		Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	⊠ - YES	□ - NO(*)	
	If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)			
	There is a label on the module as shown in the labeling exhibit filed with this application. Host specific l shown in the installation manual filed with this application.	abeling instru	ctions are	
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)	
	The EUT is compliant with all applicable FCC rules. Detail instructions for maintaining compliance are	given in the U	Iser Manual.	
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)	
	The module meets Portable exclusion levels as shown in the RF exposure information filed with this appl	application.		

Sincerely,

Name: John Chiou Position: Manager Date: 2021-07-01