

# RF EXPOSURE EVALUATION REPORT

FCC ID : H8N-ASK-NCQ1338  
Equipment : Verizon Internet Gateway  
Brand Name : Verizon Internet Gateway  
Model Name : ASK-NCQ1338  
Applicant : Askey Computer Corporation  
10F, NO.119, JIANKANG RD.,  
ZHONGHE DIST., NEW TAIPEI CITY 23585,  
TAIWAN, R.O.C.  
Manufacturer : Askey Computer Corporation  
10F, NO.119, JIANKANG RD.,  
ZHONGHE DIST., NEW TAIPEI CITY 23585,  
TAIWAN, R.O.C.  
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full



Approved by: Cona Huang / Deputy Manager



**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## **Table of Contents**

<b>1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>4</b>
<b>2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS .....</b>	<b>5</b>
<b>3. RF EXPOSURE LIMIT INTRODUCTION .....</b>	<b>6</b>
<b>4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION .....</b>	<b>7</b>
4.1. Standalone Power Density Calculation .....	7
4.2. Collocated Power Density Calculation.....	7





1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Verizon Internet Gateway
Brand Name	Verizon Internet Gateway
Model Name	ASK-NCQ1338
FCC ID	H8N-ASK-NCQ1338
Wireless Technology and Frequency Range	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 1710 MHz ~ 1780 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n77 : 3700 MHz ~ 3980 MHz WLAN 2.4GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8GHz Band: 5725 MHz ~ 5825 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	LTE: QPSK, 16QAM, 64QAM, 256QAM 5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/HE20/HE40/HE80 Bluetooth LE
HW Version	REV 1.0
EUT Stage	Identical Prototype
<b>Remark:</b>	
1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	
2. Variant report to enable WLAN 5.3GHz & 5.6GHz.	

Reviewed by: Jason Wang

Report Producer: Daisy Peng



**2. Maximum RF average output power among production units**

<WLAN Non-Beamforming>

Mode		4Tx Maximum Average Power (dBm)
5GHz WLAN	802.11a	21.92
	802.11n-HT20	22.05
	802.11n-HT40	23.87
	802.11ac-VHT20	21.95
	802.11ac-VHT40	23.77
	802.11ac-VHT80	23.87
	802.11ax-HE20	22.15
	802.11ax-HE40	23.97
	802.11ax-HE80	23.97

<WLAN Beamforming>

Mode		Maximum Average Power (dBm)
5GHz WLAN	802.11ac-VHT20	19.17
	802.11ac-VHT40	19.25
	802.11ac-VHT80	19.24
	802.11ax-HE20	19.27
	802.11ax-HE40	19.35
	802.11ax-HE80	19.34



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Table with 5 columns: Frequency range (MHz), Electric field strength (V/m), Magnetic field strength (A/m), Power density (mW/cm²), Averaging time (minutes). It is divided into two sections: (A) Limits for Occupational/Controlled Exposures and (B) Limits for General Population/Uncontrolled Exposure.

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

S = PG / (4πR²)

Where:

- S = Power Density
P = Output Power at Antenna Terminals
G = Gain of Transmit Antenna (linear gain)
R = Distance from Transmitting Antenna



4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

<WLAN Non-Beamforming>

Table with 9 columns: Band, Antenna Gain (dBi), Maximum Power (dBm), Maximum EIRP (dBm), Maximum EIRP (W), Average EIRP (mW), Power Density at 20cm (mW/cm^2), Limit (mW/cm^2), Power Density / Limit. Row 1: WLAN5GHz Band, 3.50, 23.97, 27.5, 0.56, 558.47, 0.111, 1.000, 0.111

<WLAN Beamforming>

Table with 9 columns: Band, Antenna Gain (dBi), Maximum Power (dBm), Maximum EIRP (dBm), Maximum EIRP (W), Average EIRP (mW), Power Density at 20cm (mW/cm^2), Limit (mW/cm^2), Power Density / Limit. Row 1: WLAN5GHz Band, 9.40, 19.35, 28.8, 0.75, 749.89, 0.149, 1.000, 0.149

Note:

- 1. For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.
2. This device supports Beamforming for WLAN 5GHz VHT20/VHT40/VHT80/HE20/HE40/HE80 only; therefore, in the table above which consider maximum directional Gain 9.4dBi for WLAN 5GHz Beamforming mode.

4.2. Collocated Power Density Calculation

Table with 5 columns: Maximum WLAN Power Density / Limit, Maximum Bluetooth Power Density / Limit, Maximum WWAN(LTE) Power Density / Limit, Maximum WWAN(5G NR) Power Density / Limit, Σ(Power Density / Limit) of WWAN(LTE) + WWAN(5G NR) + WLAN + Bluetooth. Row 1: 0.564, 0.001, 0.177, 0.195, 0.937

Note:

- 1. For 2.4GHz WLAN / 5.2GHz WLAN / 5.8GHz WLAN, Bluetooth and WWAN standalone power density calculation can refer to Sporton RF Exposure Evaluation Original Report No: FA110616
2. Σ(Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for LTE + 5G NR + WLAN + Bluetooth.
3. Considering the WWAN collocation with the WLAN and Bluetooth transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 4 collocated transmitters is compliant

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.