

FCC RF Exposure Report

Report No.: MFBCUN-WTW-P23110664

FCC ID: H8N60156A

Model No.: NR xCell 60156A

Received Date: 2023/11/24

Issued Date: 2024/4/24

Applicant: ASKEY COMPUTER CORP.

Address: 10F, NO. 119, JIANKANG RD., ZHONGHE DIST., NEW TAIPEI CITY
23585, TAIWAN, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 General Information	5
2.1 General Description of EUT	5
3 RF Exposure	6
3.1 Limits for Maximum Permissible Exposure (MPE).....	6
3.2 MPE Calculation Formula	6
3.3 Classification	6
4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
MFBCUN-WTW-P23110664	Original release	2024/4/24

1 Certificate of Conformity

Product: 5G small cell

Brand: ASKEY

Test Model: NR xCell 60156A

Sample Status: Engineering sample

Applicant: ASKEY COMPUTER CORP.

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

We, **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, declare that the equipment above has been found compliance with the requirement limits of applicable standards. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate under the standards herein specified.

Prepared by : Pettie Chen , **Date:** 2024/4/24
Pettie Chen / Senior Specialist

Approved by : Jeremy Lin , **Date:** 2024/4/24
Jeremy Lin / Project Engineer

2 General Information

2.1 General Description of EUT

Product	5G small cell	
Brand	ASKEY	
Test Model	NR xCell 60156A	
Status of EUT	Engineering sample	
Power Supply Rating	100-240 Vac	
Modulation Type	5G NR	QPSK, 64QAM, 256QAM
Operating Frequency	5G NR n48	3560.01MHz ~ 3690.00MHz
	5G NR n77	3720.00MHz ~ 3960.00MHz
Antenna Type	Refer to note	

Note:

1. The EUT contains following accessory devices.

AC Adapter	Brand	MEAN WELL
	Model	LRS-100-12
	AC Input	85~264V 12V/8.5A
	DC Output	36V 2.8A 100.8W
	DC Output Cable	2.75m non-shielded cable without core

2. The EUT device does not support 16QAM modulation and only supports Full RB mode.

3. The antenna information is listed as below.

Antenna Type	Antenna Gain(dBi)			Connector Type
	Frequency (MHz)	Ant 1	Ant 2	
PCB	3300	3.38	5.20	SMA
	3800	3.89	4.63	
	4300	4.18	5.55	
	4400	5.66	5.50	
	4700	3.87	5.57	
	5000	4.66	4.39	

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

4 Calculation Result of Maximum Conducted Power

Mode	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5G NR n48	34.53	20	0.565	1.000
5G NR n77 (Part 270)	33.47	20	0.442	1.000

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

---END---