



# RF Exposure Evaluation Report

**Equipment** : DBDC ROUTER  
**Brand Name** : Charter  
**Model No.** : RAC2V1K  
**FCC ID** : H8NRAC2V1K  
**Standard** : 47 CFR Part 2.1091  
**Applicant** : Askey Computer Corp.  
10F, NO.119, JIANKANG RD., ZHONGHE DIST., NEW  
TAIPEI CITY 23585, TAIWAN  
**Manufacturer** : Askey Computer Corp.  
10F, NO.119, JIANKANG RD., ZHONGHE DIST., NEW  
TAIPEI CITY 23585, TAIWAN

The product sample received on Feb. 15, 2017 and completely tested on May 11, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Cliff Chang  
SPORTON INTERNATIONAL INC.





## **TABLE OF CONTENTS**

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	EUT General Information .....	4
1.2	Table for Class II Change.....	4
1.3	Testing Location .....	4
<b>2</b>	<b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>5</b>
2.1	Limit of Maximum Permissible Exposure .....	5
2.2	MPE Calculation Method.....	5
2.3	Calculated Result and Limit.....	6
<b>PHOTOGRAPHS OF EUT V01</b>		





# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

## 1.2 Table for Class II Change

This product is an extension of original one reported under Sporton project number: FA711935-02

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Revising the Ant. Gain of 2.4GHz to 1dBi. 2. Revising the Ant. Gain of 5GHz band 1/band 4 to 1.2dBi. 3. Removing Capacitor*3:(1000 pF: C1170 (bottom), C1173, C1176 (Top).	After evaluating, it is verified for 2.4G and 5G B1 / B4 maximum permissible exposure.

Note: RF Exposure Evaluation of 5GHz Band 2, 3 are based on original test report

## 1.3 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 25 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
5.2G;D1D	7.22	25.73	32.95	1.97242	25	0.25126	1.00000	0.25126
5.3G;D1D	10.84	18.84	29.68	0.92897	25	0.11828	1.00000	0.11828
5.6G;D1D	10.84	19.12	29.96	0.99083	25	0.12616	1.00000	0.12616
2.4G;G1D	1.00	29.52	30.52	1.12720	25	0.14359	1.00000	0.14359
							Sum Ratio	0.63929
							Ratio Limit	1