



## ELECTROMAGNETIC COMPATIBILITY TEST REPORT

Company : ASKEY COMPUTER CORP.  
Address : 10F, NO.119, CHIENKANG RD., CHUNG-HO, TAIPEI,  
TAIWAN, R.O.C.  
Product name : Wireless ADSL Router  
Model name : RTA 300W  
Date Received : JUL. 26, 2002  
Date Tested : JUL. 26-31, 2002

### MEASUREMENT REQUIREMENT USED :

47 CFR Part 15, Subpart B and Subpart C (Section 15.247),  
ANSI C63.4-1992

WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.

	Name	Signature	Date
Testing Engineer	M. C. Huang	M. C. Huang	Aug. 16, 2002
Approving Manager	C. F. Wu	C. F. Wu	Aug. 16, 2002

### Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to test, and is invalid as separately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.
5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.



## TABLE OF CONTENTS

TITLE	PAGE NO.
1. GENERAL INFORMATION .....	4
1.1 GENERAL DESCRIPTION OF EUT & POWER .....	4
1.2 DESCRIPTION OF PERIPHERALS .....	5-6
1.3 EUT & PERIPHERALS SETUP DIAGRAM .....	7
1.4 EUT OPERATING CONDITION .....	7
1.5 DESCRIPTION OF TEST SITE .....	8
1.6 SUMMARY OF TEST RESULTS .....	8
2. CONDUCTED POWERLINE TEST .....	9
2.1 TEST EQUIPMENTS .....	9
2.2 TEST SETUP .....	9
2.3 CONDUCTED POWER LINE EMISSION LIMIT .....	10
2.4 TEST PROCEDURE .....	10
2.5 UNCERTAINTY OF CONDUCTED EMISSION .....	10
2.6 CONDUCTED RF VOLTAGE MEASUREMENT .....	11-12
2.7 PHOTOS OF CONDUCTION TEST .....	13
3. RADIATED EMISSION TEST .....	14
3.1 TEST EQUIPMENTS .....	14
3.2 TEST SETUP .....	14
3.3 RADIATION LIMIT .....	15
3.4 TEST PROCEDURES .....	16
3.5 UNCERTAINTY OF RADIATED EMISSION .....	16
3.6 RADIATED RF NOISE MEASUREMENT .....	17-24
3.7 PHOTOS OF OPEN SITE .....	25-26
4. 6dB BANDWIDTH MEASUREMENT .....	27
4.1 TEST EQUIPMENTS .....	27
4.2 TEST SETUP .....	27
4.3 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	27
4.4 TEST PROCEDURE .....	27
4.5 UNCERTAINTY OF CONDUCTED EMISSION .....	27
4.6 TEST RESULTS .....	28
4.7 PHOTO OF 6DB BANDWIDTH MEASUREMENT .....	29
5. MAXIMUM PEAK OUTPUT POWER .....	30
5.1 TEST EQUIPMENTS .....	30
5.2 TEST SETUP .....	30
5.3 LIMITS OF MAXIMUM PEAK OUTPUT POWER .....	30
5.4 TEST PROCEDURE .....	31
5.5 UNCERTAINTY OF CONDUCTED EMISSION .....	31
5.6 TEST RESULTS .....	31



## **TABLE OF CONTENTS**

<b>TITLE</b>	<b>PAGE NO.</b>
6. POWER SPECTRAL DENSITY MEASUREMENT .....	32
6.1 TEST EQUIPMENTS .....	32
6.2 TEST SETUP .....	32
6.3 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	32
6.4 TEST PROCEDURE .....	33
6.5 UNCERTAINTY OF CONDUCTED EMISSION .....	33
6.6 TEST RESULTS .....	33
6.7 PHOTO OF POWER SPECTRAL DENSITY MEASUREMENT .....	34
7. OUT OF BAND MEASUREMENT .....	35
7.1 TEST EQUIPMENTS .....	35
7.2 TEST SETUP .....	35
7.3 LIMITS OF OUT OF BAND EMISSIONS MEASUREMENT .....	35
7.4 TEST PROCEDURE .....	36
7.5 UNCERTAINTY OF CONDUCTED EMISSION .....	36
7.6 TEST RESULTS .....	36
7.7 PHOTO OF OUT OF BAND MEASUREMENT .....	37
8. ANTENNA REQUIREMENT .....	38
8.1 STANDARD APPLICABLE .....	38
8.2 ANTENNA CONNECTED CONSTRUCTION .....	38
9. RF EXPOSURE EVALUATION .....	39
9.1 FRIIS FORMULA .....	39
9.2 EUT OPERATING CONDITION .....	39
9.3 TEST RESULT OF RF EXPOSURE EVALUATION .....	40
9.3.1 ANTENNA GAIN .....	40
9.3.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE EVALUATION DISTANCE .....	40
10. PROCESSING GAIN .....	41
10.1 TEST CONDITION .....	41
10.2 MINIMUM STANDARD .....	41
10.3 METHOD OF MEASUREMENT .....	41
10.4 CALCULATION OF PROCESSING GAIN .....	42
10.5 TEST RESULT OF PROCESSING GAIN .....	43



## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF EUT & POWER

MANUFACTURER : ASKEY COMPUTER CORP.  
SAMPLE NAME : Wireless ADSL Router  
MODEL NO : RTA 300W  
FREQUENCY RANGE : 2412 MHz TO 2462MHz  
CHANNEL NUMBER : 11  
AIR DATA RATE : 11Mbps (Highest Mode)  
TYPE OF MODULATION : DIRECT SEQUENCE SPREAD SPECTRUM  
FREQUENCY SELECTION : BY SOFTWARE  
EUT Description : 2.4GHz Direct Sequence Spread Spectrum Data Transceiver  
for 11Mbps Wireless ADSL Router with 10/100M LAN  
switch  
ANTENNA TYPE : PCB ANTENNA

#### Power Adapter (1)

Manufacturer : DELTA ELECTRONICS, INC.  
Model Number : ADP-12SB Rev.B  
Input Power : 100-240VAC / 50~60Hz  
Output Power : 12VDC

#### Power Adapter (2)

Manufacturer : P TRANS  
Model Number : UP01241120  
Input Power : 100-240VAC / 50~60Hz  
Output Power : 12VDC, 1A

☒ Engineering Sample , ☐ Product Sample , ☐ Mass Product Sample



## 1.2 DESCRIPTION OF PERIPHERALS

### (1) Notebook PC

MANUFACTURER : DELL CORP.  
MODEL NUMBER : PP01L  
SERIAL NUMBER : CN-09C748-48155-1AP-6081  
F.C.C. : DOC  
POWER CORD : Unshielded, Detachable, 1.8m

### (2) MODEM

MANUFACTURER : ZyXEL CORP.  
MODEL NUMBER : omni 56K  
SERIAL NUMBER : S1Z4107729  
F.C.C. ID : I880MNI56K  
POWER CORD : UnShielded , Detachable , 1.8m ( 9VAC from Power Adapter )

### (3) PRINTER

MANUFACTURER : HP CORP.  
MODEL NUMBER : C6431D  
SERIAL NUMBER : CN19T6S011  
F.C.C. : DOC  
POWER CORD : Unshielded , Detachable , 1.8m  
DATA CABLE : Shielded , Detachable , 1.2m

### (4) MONITOR

MANUFACTURER : HP CORP.  
MODEL NUMBER : D8894A  
SERIAL NUMBER : CN00905269  
F.C.C. ID : ARSCM569N  
POWER CORD : UnShielded , Detachable , 1.8m  
SIGNAL CABLE : Shielded , Undetachable , 1.8m

### (5) KEYBOARD

MANUFACTURER : HP CORP.  
MODEL NUMBER : SK-2502C  
SERIAL NUMBER : M000303429  
F.C.C. ID : -----  
POWER SOURCE : 5VDC (from Notebook PC)  
SIGNAL CABLE : Shielded , Undetachable , 1.8m



**(6) MOUSE**

MODEL NUMBER : M-S34  
SERIAL NUMBER : LZE95050431  
MANUFACTURER : HP CORP.  
FCC ID : DZL211029  
SIGNAL CABLE : Shielded , Undetachable , 1.8m  
POWER SOURCE : 5VDC (from PC)

**(7) PC**


MANUFACTURER : HP CORP.  
MODEL NUMBER : 8894  
SERIAL NUMBER : P3129-WOYO  
F.C.C. : DOC  
POWER CORD : Unshielded, Detachable, 1.8m

**(8) CABLE**

	Type	Connector	shielded	Length
(A)	Cross-over Cat5 twisted-pair	RJ-45, Plasoc	NO	15m
(B)	Telephone Line	RJ-45, Plasoc	NO	15m



### 1.3 EUT & PERIPHERALS SETUP DIAGRAM



The indicated numbers (1) (2)...., Please refer to item  
1.3

### 1.4 EUT OPERATING CONDITION

1. Set up all computer like the setup diagram.
2. PC2 ping 10.0.0.1-t-1 1024.
3. PC1 ping 10.0.0.1-t-1 1024.
4. Notebook PC ping 192.168.1.1-t-1 1024.
5. All of the function are under run.
6. Start test.



## 1.5 DESCRIPTION OF TEST SITE

SITE DESCRIPTION : FCC certificate NO. : 31040/PRV  
TUV certificate NO. : I9664582-9911  
BSMI certificate NO. : SL2-IN-E-0002  
NVLAP Lab code : 200118-0  
CNLA certificate NO. : CNLA-ZL97018  
VCCI certificate NO. : R-1229, C-1250

NAME OF SITE : Electronics Research & Service Organization  
Industrial Technology Research Institute

SITE LOCATION : R1500, 195-4, sec. 4, Chung Hsing Rd.,  
Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

## 1.6 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications :

APPLIED STANDARD : 47 CFR Part 15, Subpart B and Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.107 15.207	AC Power Conducted Emission Limit : 48dBuV	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : 6dB bandwidth > 500KHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit : max. 30dBm	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(d)	Power Spectral Density Limit : max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band Limit: Table 15.209	PASS	Meet the requirement of limit






## 2. CONDUCTED POWERLINE TEST

### 2.1 TEST EQUIPMENTS

The following test equipments are used during the conducted powerline tests :

MANUFACTURER OR TYPE	MODEL No	SERIAL NO.	DATE OF CALIBRATION	CALIBRATION PERIOD	REMARK
SPECTRUM ANALYZER & DISPLAY	HP 8568A	2235A02320	APR. 01, 2002	1 Year	PRETEST
QUASI-PEAK ADAPTER	HP 85650 A	2341A00672	APR. 01, 2002	1 Year	PRETEST
ISOLATION TRANSFORMER	SOLAR 7032-1	N/A	N/A	N/A	FINAL
L.I.S.N.	EMCO 3850/2	9311-1025 9401-1028	JAN. 08, 2002 For Characteristic impedance MAY 18, 2002 For Insertion loss	1 Year	FINAL
TEST RECEIVER	R/S ESHS30	838550/003	JUN. 07, 2002	1 Year	FINAL
SHIELDED ROOM	KEENE 5983	NO.1	N/A	N/A	FINAL
PULSE LIMIT	R/S EHS3Z2	357.8810.52	JUL. 10, 2002	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	JUL. 10, 2002	1 Year	FINAL
50 TERMINATOR	-----	-----	JUL. 10, 2002	1 Year	FINAL

### 2.2 TEST SETUP





## 2.3 CONDUCTED POWER LINE EMISSION LIMIT

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Emissions ( $\mu$ V)	Emissions (dB $\mu$ V)
0.45 – 30.0	250	48.0

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

## 2.4 TEST PROCEDURE

The test procedure is performed in a 12ft $\times$  12ft $\times$  8ft(L $\times$  W $\times$  H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W) $\times$  1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

## 2.5 UNCERTAINTY OF CONDUCTED EMISSION

The uncertainty of conducted emission is  $\pm 1.36$ dB.



## 2.6 CONDUCTED RF VOLTAGE MEASUREMENT

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 26

Humidity : 65 % RH

FREQUENCY (MHz)	READING(dB $\mu$ V)		LIMITS (dB $\mu$ V)
	ONE END & GRD'D	THE OTHER END & GRD'D	
	Q.P.	Q.P.	
0.699	*	35.60	48.00
1.007	38.50	*	48.00
1.180	39.00	*	48.00
1.570	*	40.30	48.00
3.061	39.00	36.90	48.00
7.565	38.20	40.30	48.00
9.440	37.10	*	48.00
10.228	*	36.20	48.00
16.208	*	26.40	48.00
18.113	29.20	*	48.00
30.000	*	*	48.00

REMARKS : 1. \* Undetectable  
2. For Power adapter (1).



## 2.6 CONDUCTED RF VOLTAGE MEASUREMENT

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 26

Humidity : 65 % RH

FREQUENCY (MHz)	READING(dB $\mu$ V)		LIMITS (dB $\mu$ V)
	ONE END & GRD'D	THE OTHER END & GRD'D	
	Q.P.	Q.P.	
0.509	31.40	28.90	48.00
0.616	28.70	*	48.00
0.819	*	32.40	48.00
1.784	33.60	33.10	48.00
2.124	*	25.30	48.00
2.264	33.30	*	48.00
6.550	*	29.10	48.00
7.564	36.20	*	48.00
8.190	38.90	*	48.00
9.008	*	37.50	48.00
16.980	*	41.30	48.00
21.913	34.50	*	48.00
30.000	*	*	48.00

REMARKS : 1. \* Undetectable  
2. For Power adapter (2).



## 2.7 PHOTOS OF CONDUCTION TEST





### 3. RADIATED EMISSION TEST


#### 3.1 TEST EQUIPMENTS

The following test equipments are utilized in making the measurements contained in this report.

MANUFACTURER OR TYPE	MODEL NO	SERIAL NO	DATE OF CALIBRATION	CALIBRATION PERIOD	REMARK
CHASE BI-LOG ANTENNA	CBL6112B	2421	MAY 07, 2002	1 Year	FINAL
R/S TEST RECEIVER	ESMI	842088/005 841978/008	JUL. 18, 2002	1 Year	FINAL
OPEN SITE	-----	No.1	JUL. 10~12, 2002	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	JUL. 13, 2002	1 Year	FINAL
Horn Antenna	AH-118	10089	FEB. 25, 2002	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	OCT. 11, 2001	1 Year	FINAL
HP High pass filter	84300/80038	011	cal. on use	1 Year	FINAL
Horn Antenna	AH-840	03077	FEB. 25, 2002	1 Year	FINAL

#### 3.2 TEST SETUP

The diagram below shows the test setup which is utilized to make these measurements.



Antenna Elevation Variable



### 3.3 RADIATION LIMIT

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

FREQUENCY (MHz)	DISTANCE (METERS)	Radiated (dB $\mu$ V/M)	Radiated ( $\mu$ V/M)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.



### 3.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE :**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

### 3.5 UNCERTAINTY OF RADIATED EMISSION

The uncertainty of radiated emission is  $\pm 2.72\text{dB}$ .





### 3.6 RADIATED RF NOISE MEASUREMENT

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 31

Humidity : 53 % RH

FREQ- UENCY  (MHz)	ANTENNA FACTOR  (dB)	CABLE LOSS  (dB)	METER READING AT3m(dB $\mu$ V/M)		LIMITS  (dB $\mu$ V/M)	EMISSION LEVEL AT3m(dB $\mu$ V/M)	
			HORIZON- TAL	VERTICAL		HORIZON- TAL	VERTICAL
30.00	18.96	0.90	*	*	40.00	*	*
175.22	10.82	2.60	16.33	16.43	43.50	29.75	29.85
240.00	12.75	3.00	28.87	26.40	46.00	44.62	42.15
272.99	13.56	3.19	15.44	13.64	46.00	32.19	*
400.33	17.41	3.90	20.95	17.80	46.00	42.26	39.11
500.05	18.58	4.30	19.50	8.51	46.00	42.38	31.39
560.05	19.08	4.42	20.82	17.70	46.00	44.32	41.20
601.21	19.42	4.51	6.60	3.02	46.00	30.53	26.95
696.08	19.49	5.36	14.14	10.49	46.00	38.99	35.34
720.09	19.62	5.42	11.35	13.23	46.00	36.39	38.27
747.97	19.79	5.45	5.56	7.03	46.00	30.80	32.27
840.09	20.30	5.54	10.20	7.21	46.00	36.04	33.05
875.10	20.47	5.58	7.41	8.20	46.00	33.46	34.25
1000.00	21.24	6.40	*	*	54.00	*	*

REMARKS : 1. \* Undetectable

2. Emission level (dB  $\mu$  V/M) =Antenna Factor (dB/m) + Cable loss (dB)  
+ Meter Reading (dB  $\mu$  V).

3. According to technical experiences, all spurious emission at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representation for the test.



Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	RX	Test Date :	2002/7/26
Channel number	1,6,11	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Filter	Level	Limit	Margin	Mark	Pol	Height	Channel
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	(dBuV/m)	FCC_B	(dB)	(P/Q/A)	(H/V)	(Meter)	Number
2037.81	42.86	31.9	6.52	32.4	1	49.88	74	-24.12	P	V	1.2	1
2037.81	31.76	31.9	6.52	32.4	1	38.78	54	-15.22	A	V	1.2	1
2037.81	41.6	31.9	6.52	32.4	1	48.62	74	-25.38	P	H	1.2	1
2037.81	31.5	31.9	6.52	32.4	1	38.52	54	-15.48	A	H	1.2	1
4075.45*	44.3	33.6	8.5	35.8	1	51.6	74	-22.4	P	V	1.3	1
4075.45*	25.6	33.6	8.5	35.8	1	32.9	54	-21.1	A	V	1.3	1
4075.45*	44.1	33.6	8.5	35.8	1	51.4	74	-22.6	P	H	1.1	1
4075.45*	26.5	33.6	8.5	35.8	1	33.8	54	-20.2	A	H	1.1	1
2062.82	43.5	31.9	6.53	32.45	1	50.48	74	-23.52	P	V	1.1	6
2062.82	30.2	31.9	6.53	32.45	1	37.18	54	-16.82	A	V	1.1	6
2062.82	42.2	31.9	6.53	32.45	1	49.18	74	-24.82	P	H	1.1	6
2062.82	31.5	31.9	6.53	32.45	1	38.48	54	-15.52	A	H	1.1	6
4125.53*	44.52	33.65	8.5	35.8	1	51.87	74	-22.13	P	V	1.1	6
4125.53*	32.12	33.65	8.5	35.8	1	39.47	54	-14.53	A	V	1.1	6
4125.53*	42.35	33.65	8.5	35.8	1	49.7	74	-24.3	P	H	1.1	6
4125.53*	29.56	33.65	8.5	35.8	1	36.91	54	-17.09	A	H	1.1	6
2087.82	43.5	31.6	6.58	32.56	1	50.12	74	-23.88	P	V	1.1	11
2087.82	35.6	31.6	6.58	32.56	1	42.22	54	-11.78	A	V	1.1	11
2087.82	43.5	31.6	6.58	32.56	1	50.12	74	-23.88	P	H	1.1	11
2087.82	32.5	31.6	6.58	32.56	1	39.12	54	-14.88	A	H	1.1	11
4175.55	35.6	33.7	8.52	35.67	1	43.15	74	-30.85	P	V	1.1	11
4175.55	30.2	33.7	8.52	35.67	1	37.75	54	-16.25	A	V	1.1	11
4175.55	35.4	33.7	8.52	35.67	1	42.95	74	-31.05	P	H	1.1	11
4175.55	30.2	33.7	8.52	35.67	1	37.75	54	-16.25	A	H	1.1	11

Note :

1. The measurement was searched to 5GHz.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “\*” means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$



Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2002/7/26
Fundamental Frequency:	2412MHz (CH 1 )	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Filter	Level	Limit	Margin	Mark	Pol	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	(dBuV/m)	FCC_B	(dB)	(P/Q/A)	(H/V)	(Meter)
4824.29*	42.86	36.5	8.82	35.4	1	53.78	74	-20.22	P	V	1.2
4824.29*	31.76	36.5	8.82	35.4	1	42.68	54	-11.32	A	V	1.2
7237.53	34.52	39.4	11.2	35.5	1	50.62	74	-23.38	P	V	1.2
7237.53	26.5	39.4	11.2	35.5	1	42.6	54	-11.4	A	V	1.2
9647.88	44.3	40.1	12.5	35.8	1	62.1	74	-11.9	P	V	1.3
9647.88	25.6	40.1	12.5	35.8	1	43.4	54	-10.6	A	V	1.3
12059.93*	---	42.6	15.2	35.3	1	---	74	---	---	---	---
12059.93*	---	42.6	15.2	35.3	1	---	54	---	---	---	---
14471.97*	---	43.4	16.8	34	1	---	74	---	---	---	---
14471.97*	---	43.4	16.8	34	1	---	54	---	---	---	---
16884.01	---	45.2	17.6	34.3	1	---	74	---	---	---	---
16884.01	---	45.2	17.6	34.3	1	---	54	---	---	---	---
19296.05*	---	36.3	18.5	34.3	1	---	74	---	---	---	---
19296.05*	---	36.3	18.5	34.3	1	---	54	---	---	---	---
21708.09	---	36.2	19.2	34.6	1	---	74	---	---	---	---
21708.09	---	36.2	19.2	34.6	1	---	54	---	---	---	---
24120.13	---	36.8	21	34.2	1	---	74	---	---	---	---
24120.13	---	36.8	21	34.2	1	---	54	---	---	---	---

Note :

1. The measurement was up to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “\*” means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  
Level=Reading+AF+Closs-Preamp+Filter, Margin=Level-Limit



Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2002/7/26
Fundamental Frequency:	2412MHz (CH 1 )	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq. (MHz)	Reading (dBuV)	AF (dBuV)	Closs (dB)	Pre-amp (dB)	Filter dB	Level (dBuV/m)	Limit FCC_B	Margin (dB)	Mark (P/Q/A)	Pol (H/V)	Height (Meter)
4824.29*	46.44	36.5	8.82	35.4	1	57.36	74	-16.64	P	H	1.2
4824.29*	34.5	36.5	8.82	35.4	1	45.42	54	-8.58	A	H	1.2
7237.53	35.3	39.4	11.2	35.5	1	51.4	74	-22.6	P	H	1.2
7237.53	25.3	39.4	11.2	35.5	1	41.4	54	-12.6	A	H	1.2
9647.887	43.2	40.1	12.5	35.8	1	61	74	-13	P	H	1.3
9647.887	26.2	40.1	12.5	35.8	1	44	54	-10	A	H	1.3
12059.93*	---	42.6	15.2	35.3	1	---	74	---	---	---	---
12059.93*	---	42.6	15.2	35.3	1	---	54	---	---	---	---
14471.97*	---	43.4	16.8	34	1	---	74	---	---	---	---
14471.97*	---	43.4	16.8	34	1	---	54	---	---	---	---
16884.01	---	45.2	17.6	34.3	1	---	74	---	---	---	---
16884.01	---	45.2	17.6	34.3	1	---	54	---	---	---	---
19296.05*	---	36.3	18.5	34.3	1	---	74	---	---	---	---
19296.05*	---	36.3	18.5	34.3	1	---	54	---	---	---	---
21708.09	---	36.2	19.2	34.6	1	---	74	---	---	---	---
21708.09	---	36.2	19.2	34.6	1	---	54	---	---	---	---
24120.13	---	36.8	21	34.2	1	---	74	---	---	---	---
24120.13	---	36.8	21	34.2	1	---	54	---	---	---	---

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "\*" means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$



Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2002/7/26
Fundamental Frequency:	2437MHz (CH 6 )	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq. (MHz)	Reading (dBuV)	AF (dBuV)	Closs (dB)	Pre-amp (dB)	Filter dB	Level (dBuV/m)	Limit FCC_B	Margin (dB)	Mark (P/Q/A)	Pol (H/V)	Height (Meter)
4874.25*	43.44	36.6	8.9	35.4	1	54.54	74	-19.46	P	V	1.2
4874.25*	32.42	36.6	8.9	35.4	1	43.52	54	-10.48	A	V	1.2
7309.85	34.21	39.5	11.3	35.5	1	50.51	74	-23.49	P	V	1.2
7309.85	26.5	39.5	11.3	35.5	1	42.8	54	-11.2	A	V	1.2
9748.08	---	40.2	12.5	35.8	1	---	74	---	---	---	---
9748.08	---	40.2	12.5	35.8	1	---	54	---	---	---	---
12185.10*	---	42.6	15.2	35.3	1	---	74	---	---	---	---
12185.10*	---	42.6	15.2	35.3	1	---	54	---	---	---	---
14622.12	---	43.4	16.8	34	1	---	74	---	---	---	---
14622.12	---	43.4	16.8	34	1	---	54	---	---	---	---
17059.14	---	45.2	17.6	34.3	1	---	74	---	---	---	---
17059.14	---	45.2	17.6	34.3	1	---	54	---	---	---	---
19496.16*	---	36.3	18.5	34.3	1	---	74	---	---	---	---
19496.16*	---	36.3	18.5	34.3	1	---	54	---	---	---	---
21933.18	---	36.2	19.2	34.6	1	---	74	---	---	---	---
21933.18	---	36.2	19.2	34.6	1	---	54	---	---	---	---
24370.2	---	36.8	21	34.2	1	---	74	---	---	---	---
24370.2	---	36.8	21	34.2	1	---	54	---	---	---	---

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “\*” means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$



Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2002/7/26
Fundamental Frequency:	2437MHz (CH 6 )	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Filter	Level	Limit	Margin	Mark	Pol	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	(dBuV/m)	FCC_B	(dB)	(P/Q/A)	(H/V)	(Meter)
4874.25*	47.51	36.6	8.9	35.4	1	58.61	74	-15.39	P	H	1.2
4874.25*	35.16	36.6	8.9	35.4	1	46.26	54	-7.74	A	H	1.2
7309.85	35.2	39.5	11.3	35.5	1	51.5	74	-22.5	P	H	1.2
7309.85	26.5	39.5	11.3	35.5	1	42.8	54	-11.2	A	H	1.2
9748.08	---	40.2	12.5	35.8	1	---	74	---	---	---	---
9748.08	---	40.2	12.5	35.8	1	---	54	---	---	---	---
12185.10*	---	42.6	15.2	35.3	1	---	74	---	---	---	---
12185.10*	---	42.6	15.2	35.3	1	---	54	---	---	---	---
14622.12	---	43.4	16.8	34	1	---	74	---	---	---	---
14622.12	---	43.4	16.8	34	1	---	54	---	---	---	---
17059.14	---	45.2	17.6	34.3	1	---	74	---	---	---	---
17059.14	---	45.2	17.6	34.3	1	---	54	---	---	---	---
19496.16*	---	36.3	18.5	34.3	1	---	74	---	---	---	---
19496.16*	---	36.3	18.5	34.3	1	---	54	---	---	---	---
21933.18	---	36.2	19.2	34.6	1	---	74	---	---	---	---
21933.18	---	36.2	19.2	34.6	1	---	54	---	---	---	---
24370.2	---	36.8	21	34.2	1	---	74	---	---	---	---
24370.2	---	36.8	21	34.2	1	---	54	---	---	---	---

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “\*” means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$



Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2002/7/26
Fundamental Frequency:	2462MHz (CH 11 )	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Filter	Level	Limit	Margin	Mark	Pol	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	(dBuV/m)	FCC_B	(dB)	(P/Q/A)	(H/V)	(Meter)
4924.05*	45.81	36.8	9.01	35.4	1	57.22	74	-16.78	P	V	1.2
4924.05*	35.22	36.8	9.01	35.4	1	46.63	54	-7.37	A	V	1.2
7386.0*	34.21	39.8	11.5	35.5	1	51.01	74	-22.99	P	V	1.2
7386.0*	28.5	39.8	11.5	35.5	1	45.3	54	-8.7	A	V	1.2
9848.02	---	40.3	12.6	35.8	1	---	74	---	---	---	---
9848.02	---	40.3	12.6	35.8	1	---	54	---	---	---	---
12310.04*	---	42.6	15.2	35.3	1	---	74	---	---	---	---
12310.04*	---	42.6	15.2	35.3	1	---	54	---	---	---	---
14772.06	---	43.4	16.8	34	1	---	74	---	---	---	---
14772.06	---	43.4	16.8	34	1	---	54	---	---	---	---
17234.08	---	45.2	17.6	34.3	1	---	74	---	---	---	---
17234.08	---	45.2	17.6	34.3	1	---	54	---	---	---	---
19696.1*	---	36.3	18.5	34.3	1	---	74	---	---	---	---
19696.1*	---	36.3	18.5	34.3	1	---	54	---	---	---	---
22158.12*	---	36.2	19.2	34.6	1	---	74	---	---	---	---
22158.12*	---	36.2	19.2	34.6	1	---	54	---	---	---	---
24620.14	---	36.8	21	34.2	1	---	74	---	---	---	---
24620.14	---	36.8	21	34.2	1	---	54	---	---	---	---

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "\*" means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$



Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2002/7/26
Fundamental Frequency:	2462MHz (CH 11 )	Test By:	M.C. Huang
Temperature :	30	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Filter	Level	Limit	Margin	Mark	Pol	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	(dBuV/m)	FCC_B	(dB)	(P/Q/A)	(H/V)	(Meter)
4924.05*	47.73	36.8	9.01	35.4	1	59.14	74	-14.86	P	H	1.2
4924.05*	35.4	36.8	9.01	35.4	1	46.81	54	-7.19	A	H	1.2
7386.0*	35.2	39.8	11.5	35.5	1	52	74	-22	P	H	1.2
7386.0*	26.5	39.8	11.5	35.5	1	43.3	54	-10.7	A	H	1.2
9848.02	---	40.3	12.6	35.8	1	---	74	---	---	---	---
9848.02	---	40.3	12.6	35.8	1	---	54	---	---	---	---
12310.04*	---	42.6	15.2	35.3	1	---	74	---	---	---	---
12310.04*	---	42.6	15.2	35.3	1	---	54	---	---	---	---
14772.06	---	43.4	16.8	34	1	---	74	---	---	---	---
14772.06	---	43.4	16.8	34	1	---	54	---	---	---	---
17234.08	---	45.2	17.6	34.3	1	---	74	---	---	---	---
17234.08	---	45.2	17.6	34.3	1	---	54	---	---	---	---
19696.1*	---	36.3	18.5	34.3	1	---	74	---	---	---	---
19696.1*	---	36.3	18.5	34.3	1	---	54	---	---	---	---
22158.12*	---	36.2	19.2	34.6	1	---	74	---	---	---	---
22158.12*	---	36.2	19.2	34.6	1	---	54	---	---	---	---
24620.14	---	36.8	21	34.2	1	---	74	---	---	---	---
24620.14	---	36.8	21	34.2	1	---	54	---	---	---	---

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “\*” means that Restricted band.
5. The EUT of LAN SPEED=100M(WORSE CASE)
6. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$





### 3.7 PHOTOS OF OPEN SITE





### 3.7 PHOTOS OF OPEN SITE





## 4. 6dB BANDWIDTH MEASUREMENT


### 4.1 TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	JUL. 18, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

#### NOTE :

1. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.2 TEST SETUP



### 4.3 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is  $>500\text{KHz}$

### 4.4 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### 4.5 UNCERTAINTY OF CONDUCTED EMISSION

The uncertainty of conducted emission is  $\pm 200\text{KHz}$ .




## 4.6 TEST RESULTS

<b>EUT</b>	Wireless ADSL Router	<b>MODEL</b>	RTA300W
<b>INPUT POWER (SYSTEM)</b>	120VAC, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	27 , 70%RH,
<b>TESTED BY : M. C. Huang</b>			


<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS / FAIL</b>
1	2412	8.53	0.5	PASS
6	2437	8.71	0.5	PASS
11	2462	8.66	0.5	PASS




## 4.7 PHOTO OF 6DB BANDWIDTH MEASUREMENT



Channel 1



Channel 6



Channel 11



## 5. MAXIMUM PEAK OUTPUT POWER


### 5.1 TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	JUL. 18, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 5.2 TEST SETUP



### 5.3 LIMITS OF MAXIMUM PEAK OUTPUT POWER

The Maximum Peak Output Power Measurement is 30dBm.



## 5.4 TEST PROCEDURE

The RF power output was measured with a Power meter connected to the RF Antenna connector ( conducted measurement ) while EUT was operating in transmit mode at the appropriate center frequency.

## 5.5 UNCERTAINTY OF CONDUCTED EMISSION

The uncertainty of conducted emission is  $\pm 1.82\text{dB}$ .

## 5.6 TEST RESULTS

<b>EUT</b>	Wireless ADSL Router	<b>MODEL</b>	RTA300W
<b>INPUT POWER (SYSTEM)</b>	120VAC, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	27 , 70%RH,
<b>TESTED BY : M. C. Huang</b>			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS / FAIL</b>
1	2412	16.5	30	PASS
6	2437	16.4	30	PASS
11	2462	16.5	30	PASS



## 6. POWER SPECTRAL DENSITY MEASUREMENT


### 6.1 TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	JUL. 18, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 6.2 TEST SETUP



### 6.3 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum Power Spectral Density Measurement is 8dBm.





## 6.4 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 30KHz VBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

## 6.5 UNCERTAINTY OF CONDUCTED EMISSION

The uncertainty of conducted emission is  $\pm 1.82\text{dB}$ .

## 6.6 TEST RESULTS

<b>EUT</b>	Wireless ADSL Router	<b>MODEL</b>	RTA300W
<b>INPUT POWER (SYSTEM)</b>	120VAC, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	27 °C, 70%RH,
<b>TESTED BY : M. C. Huang</b>			


<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>RF POWER LEVEL IN 3KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS / FAIL</b>
1	2412	-28.16	8	PASS
6	2437	-28.19	8	PASS
11	2462	-28.75	8	PASS

Note:


1. The measurement value of RF Power Level + 6dB attenuator=Final RF Power Level




## 6.7 PHOTO OF POWER SPECTRAL DENSITY MEASUREMENT



Channel 1



Channel 6



Channel 11



## 7. OUT OF BAND MEASUREMENT


### 7.1 TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	JUL. 18, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

3. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
4. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 7.2 TEST SETUP



### 7.3 LIMITS OF OUT OF BAND EMISSIONS MEASUREMENT

1. Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.



## 7.4 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100KHz with suitable frequency span including 100KHz bandwidth from band edge. The band edges were measured and recorded.
2. Radiated emission test: Applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205. The maximum permitted average field strength is listed in Section 15.209. A pre-amp (and possibly a high-pass filter) is necessary for this measurement. For measurements above 1 GHz, set RBW= 1MHz, VBW= 10Hz, Sweep: Auto. If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

## 7.5 UNCERTAINTY OF CONDUCTED EMISSION

The uncertainty of conducted emission is  $\pm 1.82\text{dB}$ .

## 7.6 TEST RESULTS

### A. Conducted

Refer to 7.7 photo of out band Emission measurement

### B. Radiated


Refer to the section of Radiation Emission ; Test requirement 15.205 from P19 to P24 of the measurement data.

<b>EUT</b>	Wireless ADSL Router	<b>MODEL</b>	RTA300W
<b>INPUT POWER (SYSTEM)</b>	120VAC, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	27 °C, 70%RH,
<b>TESTED BY : M. C. Huang</b>			


<b>CHANNEL FREQUENCY (MHz)</b>	<b>Required Limit (dBc)</b>	<b>PASS / FAIL</b>
<2400	>20	PASS
>2483.5	>20	PASS
<2400	>20	PASS
>2483.5	>20	PASS



## 7.7 PHOTO OF OUT OF BAND MEASUREMENT



FRONT



BACK



## **8. ANTENNA REQUIREMENT**

### **8.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **8.2 ANTENNA CONNECTED CONSTRUCTION**

The antenna used in this product is PCB antenna. The antenna connector is MMSX. And the maximum Gain of this antenna is only 2dBi.



## 9. RF EXPOSURE EVALUATION

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)  
LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time
(A) Limits for Occupational / Control Exposures				
300-1,500	--	--	F/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300-1,500	--	--	F/1500	6
1,500-100,000	--	--	1	30

### 9.1 FRIIS FORMULA

Friis transmission formula :  $Pd = (P_{out} * G) / (4 * \pi * r^2)$

Where

$Pd$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$Pd$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 9.2 EUT OPERATING CONDITION

A software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## 9.3 TEST RESULT OF RF EXPOSURE EVALUATION

Product : Wireless ADSL Router  
Test Item : RF Exposure Evaluation Data  
Test Mode : Normal Operation

### 9.3.1 ANTENNA GAIN

Antenna Gain : The maximum Gain measured in fully anechoic chamber is 2dBi linear scale.

### 9.3.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE EVALUATION DISTANCE

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Minimum Allowable Distance ® From Skin(cm)
CH1	2412.00	16.5	2.373532
CH6	2437.00	16.4	2.346362
CH11	2462.00	16.5	2.401016

The distance r (4<sup>th</sup> column) calculated from the Friis transmission formula is far shorter than 20cm separation requirement. So, RF exposure limit warning or SAR test are not required.





## 10. PROCESSING GAIN

### 10.1 TEST CONDITION

Standard Temperature and Humidity, Standard Test Voltage  
And the test data is given by manufacture

### 10.2 MINIMUM STANDARD

The processing gain shall be at least 10dB.

### 10.3 METHOD OF MEASUREMENT

The processing gain of this spread spectrum was measured the CW jamming method. The Section 9.1 illustrates the measurement setup. The output power of the spread spectrum transmitter is fixed and the output power of jammer is adjustable. The frequency of jammer was stepped through the pass band of nominal channel in 50kHz steps. In each frequency step of the jammer, the output power of jammer is adjusted to cause the Bit Error Rate (BER) to be  $1.0 \times 10^{-6}$ . The power levels are recorded to calculate the J/S as shown in Table 1.

Material has been previously published, by other organizations supplying Integrated Circuits to implement IEEE802.11b compliant systems, that provides background theoretical calculations and test methods for measuring Jamming Margin, and using the results to infer Processing Gain. As that material, in conjunction with test results, has already been accepted by the FCC as sufficient proof that the systems comply with FCC Part 15.247(e) Processing Gain requirements, no attempt to reproduce that material in another form will be made in this report. The result of those theoretical calculations will be used here, and the same test method (in principle) will be applied.

This method can be summarized as follows:

The Signal-to-Jammer ratio is fixed at 8.4dB, with the Jammer frequency swept through the receiver pass-band (17MHz in this case) in 50kHz increments, and if the number of points at which the PER exceeds 8% is less than 20% of the total points then the test is passed. Otherwise, the test is failed.

This is repeated on each of the following channels:

Channel 1: 2412 MHz  
Channel 7: 2442 MHz  
Channel 11: 2462 MHz



## 10.4 CALCULATION OF PROCESSING GAIN

The processing gain was determined by measuring the jamming margin of the EUT and using the following formula :

$$G_p = (S/N)_0 + M_j + L_{sys}$$

Where  $(S/N)_0$  is the required signal to noise ratio at the receiver output

$M_j$  is the jammer to signal ratio (J/S)

$L_{sys}$  is the system loss

The  $(S/N)_0$  is calculated from :

$$P_e = 1/2 \exp(-1/2(S/N)_0) \quad ; \quad P_e = \text{probability of error (BER)}$$

For the  $P_e(\text{BER}) = 1.0 \times 10^{-6}$ , the required  $(S/N)_0$  is 16.4dB

From Measurement, the minimum J/S( $M_j$ ) is  $\geq 8.4\text{dB}$

We assume the system loss is 2dB.

Therefore the processing gain is calculated below :

$$G_p = (S/N)_0 + M_j + L_{sys} = 16.4 + (-8.4) + 2 = 10(\text{dB})$$



## 10.5 TEST RESULT OF PROCESSING GAIN

Product : Wireless ADSL Router  
Test Item : RF Exposure Evaluation Data  
Test Site : No.1 OATS  
Test Mode : Normal Operation

Jamming Margin test results.  
Tested on RD0314 S/N 0229022F

Jammer level: -8.4dB relative to On channel 11Mbps modulated signal  
2002/1/4 Chris Irwin

	Channel 1 2412 MHz	Channel 7 2442 MHz	Channel 11 2462 MHz
Number of jammer frequencies exceeding 8%	14	15	19
Percentage of frequencies exceeding 8%:	4.0%	4.3%	5.4%
Max allowed:	20%	20%	20%
Result:	PASS	PASS	PASS

## Conclusion

This data confirms that the device tested complied with the FCC Part 15.247(e) requirement that minimum Processing Gain be 10dB.