



FCC TEST REPORT

REPORT NO.: RF920114R04

MODEL NO.: WLC3010

RECEIVED: Jan. 14, 2003

TESTED: Jan. 20 ~ Feb. 06, 2003

APPLICANT: ASKEY COMPUTER CORP.

ADDRESS: 10F, NO. 119, CHIENKANG RD., CHUNG-HO,
TAIPEI TAIWAN R.O.C

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 63 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

| | | |
|-------|---|----|
| 1 | CERTIFICATION..... | 4 |
| 2 | SUMMARY OF TEST RESULTS..... | 5 |
| 3 | GENERAL INFORMATION..... | 6 |
| 3.1 | GENERAL DESCRIPTION OF EUT..... | 6 |
| 3.2 | DESCRIPTION OF TEST MODES..... | 7 |
| 3.3 | GENERAL DESCRIPTION OF APPLIED STANDARDS..... | 7 |
| 3.4 | DESCRIPTION OF SUPPORT UNITS..... | 8 |
| 4 | TEST TYPES AND RESULTS..... | 9 |
| 4.1 | CONDUCTED EMISSION MEASUREMENT..... | 9 |
| 4.1.1 | LIMITS OF CONDUCTED EMISSION MEASUREMENT..... | 9 |
| 4.1.2 | TEST INSTRUMENTS..... | 9 |
| 4.1.3 | TEST PROCEDURES..... | 10 |
| 4.1.4 | DEVIATION FROM TEST STANDARD..... | 10 |
| 4.1.5 | TEST SETUP..... | 11 |
| 4.1.6 | EUT OPERATING CONDITIONS..... | 11 |
| 4.1.7 | TEST RESULTS..... | 12 |
| 4.2 | RADIATED EMISSION MEASUREMENT..... | 18 |
| 4.2.1 | LIMITS OF RADIATED EMISSION MEASUREMENT..... | 18 |
| 4.2.2 | TEST INSTRUMENTS..... | 19 |
| 4.2.3 | TEST PROCEDURES..... | 20 |
| 4.2.4 | DEVIATION FROM TEST STANDARD..... | 20 |
| 4.2.5 | TEST SETUP..... | 21 |
| 4.2.6 | EUT OPERATING CONDITIONS..... | 21 |
| 4.2.7 | TEST RESULTS..... | 22 |
| 4.2.8 | TEST RESULTS (For CCK)..... | 23 |
| 4.2.9 | TEST RESULTS (For OFDM)..... | 26 |
| 4.3 | 6dB BANDWIDTH MEASUREMENT..... | 29 |
| 4.3.1 | LIMITS OF 6dB BANDWIDTH MEASUREMENT..... | 29 |
| 4.3.2 | TEST INSTRUMENTS..... | 29 |
| 4.3.3 | TEST PROCEDURE..... | 30 |
| 4.3.4 | DEVIATION FROM TEST STANDARD..... | 30 |
| 4.3.5 | TEST SETUP..... | 30 |
| 4.3.6 | EUT OPERATING CONDITIONS..... | 30 |
| 4.3.7 | TEST RESULTS (For CCK)..... | 31 |
| 4.3.8 | TEST RESULTS (For OFDM)..... | 35 |



4.4 MAXIMUM PEAK OUTPUT POWER 39

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 39

4.4.2 TEST INSTRUMENTS 39

4.4.3 TEST PROCEDURES 40

4.4.4 DEVIATION FROM TEST STANDARD 40

4.4.5 TEST SETUP 40

4.4.6 EUT OPERATING CONDITIONS 40

4.4.7 TEST RESULTS (For CCK) 41

4.4.8 TEST RESULTS (For OFDM) 42

4.5 POWER SPECTRAL DENSITY MEASUREMENT 43

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 43

4.5.2 TEST INSTRUMENTS 43

4.5.3 TEST PROCEDURE 44

4.5.4 DEVIATION FROM TEST STANDARD 44

4.5.5 TEST SETUP 44

4.5.6 EUT OPERATING CONDITIONS 44

4.5.7 TEST RESULTS (For CCK) 45

4.5.8 TEST RESULTS (For OFDM) 49

4.6 BAND EDGES MEASUREMENT 53

4.6.1 LIMITS OF BAND EDGES MEASUREMENT 53

4.6.2 TEST INSTRUMENTS 53

4.6.3 TEST PROCEDURE 53

4.6.4 DEVIATION FROM TEST STANDARD 53

4.6.5 EUT OPERATING CONDITION 54

4.6.6 TEST RESULTS (For CCK) 54

4.6.7 TEST RESULTS (For OFDM) 57

4.7 ANTENNA REQUIREMENT 60

4.7.1 STANDARD APPLICABLE 60

4.7.2 ANTENNA CONNECTED CONSTRUCTION 60

5 PHOTOGRAPHS OF THE TEST CONFIGURATION 61

6 INFORMATION ON THE TESTING LABORATORIES 63



1 CERTIFICATION

PRODUCT : Wireless LAN PCMCIA Card
BRAND NAME : Askey
MODEL NO. : WLC3010
APPLICANT : ASKEY COMPUTER CORP.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Jan. 20 ~ Feb. 06, 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY: Kelsey Chang **DATE:** Feb. 19, 2003
Kelsey Chang

APPROVED BY: Dr. Alan Lane **DATE:** Feb. 19, 2003
Dr. Alan Lane
Manager



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: 47 CFR Part 15, Subpart C | | | |
|--|---|---------------|---|
| Standard Section | Test Type and Limit | Result | REMARK |
| 15.207 | AC Power Conducted Emission | PASS | Meet the requirement of limit Minimum passing margin is -10.91dBuV at 0.170MHz |
| 15.247(a)(2) | Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz | PASS | Meet the requirement of limit |
| 15.247(b) | Maximum Peak Output Power Limit: max. 30dBm | PASS | Meet the requirement of limit |
| 15.247(c) | Transmitter Radiated Emissions Limit: Table 15.209 | PASS | Meet the requirement of limit Minimum passing margin is -8.50dBuV at 200.00MHz |
| 15.247(d) | Power Spectral Density Limit: max. 8dBm | PASS | Meet the requirement of limit |
| 15.247(c) | Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency | PASS | Meet the requirement of limit |



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | |
|------------------------------|-----------------------------|
| PRODUCT | Wireless LAN PCMCIA Card |
| MODEL NO. | WLC3010 |
| POWER SUPPLY | 3.3VDC from host equipment |
| MODULATION TYPE | DBPSK,DQPSK,CCK,16QAM,64QAM |
| MODULATION TECHNOLOGY | DSSS, OFDM |
| TRANSFER RATE | up to 54Mbps |
| FREQUENCY RANGE | 2412MHz ~ 2462MHz |
| NUMBER OF CHANNEL | 11 |
| OUTPUT POWER(CCK) | 15.23dBm |
| OUTPUT POWER (OFDM) | 14.97dBm |
| ANTENNA TYPE | Chip antenna |
| ANTENNA GAIN | 2dBi |
| DATA CABLE | NA |
| I/O PORTS | NA |
| ASSOCIATED DEVICES | NA |

NOTE:

1. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
2. The EUT complies with IEEE 802.11g draft standards, and backwards compatible with IEEE 802.11b products.
3. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1 | 2412 MHz | 7 | 2442 MHz |
| 2 | 2417 MHz | 8 | 2447 MHz |
| 3 | 2422 MHz | 9 | 2452 MHz |
| 4 | 2427 MHz | 10 | 2457 MHz |
| 5 | 2432 MHz | 11 | 2462 MHz |
| 6 | 2437 MHz | | |

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate of 11Mbps with CCK technique and 54Mbps with OFDM technique, the worst case, was chosen for final test.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless LAN PCMCIA Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | FCC ID |
|------------|----------------|--------------|------------------|--------------------------|------------------|
| 1 | NOTEBOOK | Dell | PP01L | TW-09C748-12800-190-B220 | FCC DOC APPROVED |
| 2 | PRINTER | EPSON | LQ-300+ | DCGY017096 | FCC DOC APPROVED |
| 3 | MODEM | ACEEX | 1414 | 980020569 | IFAXDM1414 |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|------------|--|
| 1 | NA |
| 2 | 1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core |
| 3 | 1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core. |

NOTE: All power cords of the above support units are non shielded (1.8m).



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB μ V) | |
|-----------------------------|------------------------------|----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56 | 56 to 46 |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--|-----------|--------------|------------------|
| ROHDE & SCHWARZ Test Receiver | ESCS30 | 847793/022 | Mar. 12, 2003 |
| ROHDE & SCHWARZ Artificial Mains Network (for EUT) | ESH2-Z5 | 828075/003 | July 23, 2003 |
| ROHDE & SCHWARZ 200-A Four-line V-Network | ENV4200 | 830326/018 | Oct. 30, 2003 |
| * ROHDE & SCHWARZ 4-wire ISN | ENY41 | 838119/028 | Nov. 29, 2003 |
| * ROHDE & SCHWARZ 2-wire ISN | ENY22 | 837497/018 | Nov. 29, 2003 |
| EMCO-L.I.S.N. (for peripheral) | 3825/2 | 90031627 | July 23, 2003 |
| Software | Cond-V2M1 | NA | NA |
| RF cable (JYEBAO) | 5D-FB | Cable-C05.01 | July 19, 2003 |
| LYNICS Terminator (For EMCO LISN) | 0900510 | E1-01-305 | Feb. 20, 2003 |
| LYNICS Terminator (For EMCO LISN) | 0900510 | E1-01-306 | Feb. 20, 2003 |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*”: These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Shielded Room No. 5.
 4. The VCCI Site Registration No. is C-1093.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Plug the EUT into the notebook computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.




4.1.7 TEST RESULTS

| | | | |
|---------------------------------|---------------------------|------------------------------|----------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 1 | 6dB BANDWIDTH | 9 kHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | PHASE | Line (L) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 60%RH, 1005 hPa | TESTED BY: Gary Chang | |

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|-------------|-------------------|-------------------------|-----|--------------------------|-----|-----------------|-------|-------------|-----|
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.170 | 0.10 | 53.97 | - | 54.07 | - | 64.98 | 54.98 | -10.91 | - |
| 2 | 0.224 | 0.10 | 46.16 | - | 46.26 | - | 62.66 | 52.66 | -16.40 | - |
| 3 | 0.452 | 0.11 | 28.93 | - | 29.04 | - | 56.83 | 46.83 | -27.79 | - |
| 4 | 0.958 | 0.19 | 19.65 | - | 19.84 | - | 56.00 | 46.00 | -36.16 | - |
| 5 | 11.578 | 0.66 | 23.51 | - | 24.17 | - | 60.00 | 50.00 | -35.83 | - |
| 6 | 24.473 | 1.19 | 19.00 | - | 20.19 | - | 60.00 | 50.00 | -39.81 | - |

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






| | | | |
|---------------------------------|---------------------------|------------------------------|-------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 1 | 6dB BANDWIDTH | 9 kHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | PHASE | Neutral (N) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 60%RH, 1005 hPa | TESTED BY: Gary Chang | |

| No | Freq. | Corr. Factor | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|--------|--------------|-------------------------|-----|--------------------------|-----|-----------------|-------|-------------|-----|
| | [MHz] | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.170 | 0.10 | 49.57 | - | 49.67 | - | 64.98 | 54.98 | -15.31 | - |
| 2 | 0.224 | 0.10 | 41.53 | - | 41.63 | - | 62.66 | 52.66 | -21.03 | - |
| 3 | 0.283 | 0.10 | 37.80 | - | 37.90 | - | 60.73 | 50.73 | -22.83 | - |
| 4 | 3.844 | 0.29 | 30.59 | - | 30.88 | - | 56.00 | 46.00 | -25.12 | - |
| 5 | 17.172 | 0.63 | 26.50 | - | 27.13 | - | 60.00 | 50.00 | -32.87 | - |
| 6 | 22.055 | 0.76 | 20.15 | - | 20.91 | - | 60.00 | 50.00 | -39.09 | - |

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value






| | | | |
|---------------------------------|---------------------------|------------------------------|----------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 6 | 6dB BANDWIDTH | 9 kHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | PHASE | Line (L) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 60%RH, 1005 hPa | TESTED BY: Gary Chang | |

| No | Freq. | Corr. Factor | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|--------|--------------|-------------------------|------|--------------------------|------|-----------------|-------|-------------|------|
| | [MHz] | | (dB) | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. |
| 1 | 0.170 | 0.10 | 49.45 | - | 49.55 | - | 64.98 | 54.98 | -15.43 | - |
| 2 | 0.224 | 0.10 | 41.63 | - | 41.73 | - | 62.66 | 52.66 | -20.93 | - |
| 3 | 0.283 | 0.10 | 38.33 | - | 38.43 | - | 60.73 | 50.73 | -22.30 | - |
| 4 | 1.244 | 0.20 | 17.70 | - | 17.90 | - | 56.00 | 46.00 | -38.10 | - |
| 5 | 3.852 | 0.39 | 29.01 | - | 29.40 | - | 56.00 | 46.00 | -26.60 | - |
| 6 | 15.645 | 0.84 | 21.17 | - | 22.01 | - | 60.00 | 50.00 | -37.99 | - |

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading value






| | | | |
|---------------------------------|---------------------------|------------------------------|-------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 6 | 6dB BANDWIDTH | 9 kHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | PHASE | Neutral (N) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 60%RH, 1005 hPa | TESTED BY: Gary Chang | |

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (Uv)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|-------------|-------------------|-------------------------|-----|--------------------------|-----|-----------------|-------|-------------|-----|
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.170 | 0.10 | 52.21 | - | 52.31 | - | 64.98 | 54.98 | -12.67 | - |
| 2 | 0.287 | 0.10 | 33.86 | - | 33.96 | - | 60.62 | 50.62 | -26.66 | - |
| 3 | 0.400 | 0.10 | 28.50 | - | 28.60 | - | 57.85 | 47.85 | -29.25 | - |
| 4 | 3.789 | 0.29 | 29.85 | - | 30.14 | - | 56.00 | 46.00 | -25.86 | - |
| 5 | 12.063 | 0.44 | 25.96 | - | 26.40 | - | 60.00 | 50.00 | -33.60 | - |
| 6 | 21.219 | 0.78 | 24.91 | - | 25.69 | - | 60.00 | 50.00 | -34.31 | - |

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading value






| | | | |
|---------------------------------|---------------------------|------------------------------|----------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 11 | 6dB BANDWIDTH | 9 kHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | PHASE | Line (L) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 60%RH, 1005 hPa | TESTED BY: Gary Chang | |

| No | Freq. | Corr. Factor | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|--------|--------------|-------------------------|-----|--------------------------|-----|-----------------|-------|-------------|-----|
| | [MHz] | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.170 | 0.10 | 49.13 | - | 49.23 | - | 64.98 | 54.98 | -15.75 | - |
| 2 | 0.224 | 0.10 | 40.97 | - | 41.07 | - | 62.66 | 52.66 | -21.59 | - |
| 3 | 0.283 | 0.10 | 39.63 | - | 39.73 | - | 60.73 | 50.73 | -21.00 | - |
| 4 | 3.914 | 0.39 | 25.86 | - | 26.25 | - | 56.00 | 46.00 | -29.75 | - |
| 5 | 12.266 | 0.69 | 20.06 | - | 20.75 | - | 60.00 | 50.00 | -39.25 | - |
| 6 | 19.621 | 1.08 | 27.57 | - | 28.65 | - | 60.00 | 50.00 | -31.35 | - |

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading value






| | | | |
|---------------------------------|---------------------------|------------------------------|-------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 11 | 6dB BANDWIDTH | 9 kHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | PHASE | Neutral (N) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 60%RH, 1005 hPa | TESTED BY: Gary Chang | |

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|-------------|-------------------|-------------------------|-----|--------------------------|-----|-----------------|-------|-------------|-----|
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.170 | 0.10 | 48.63 | - | 48.73 | - | 64.98 | 54.98 | -16.25 | - |
| 2 | 0.189 | 0.10 | 26.83 | - | 26.93 | - | 64.08 | 54.08 | -37.15 | - |
| 3 | 0.284 | 0.10 | 36.14 | - | 36.24 | - | 60.71 | 50.71 | -24.47 | - |
| 4 | 0.686 | 0.15 | 22.86 | - | 23.01 | - | 56.00 | 46.00 | -32.99 | - |
| 5 | 4.031 | 0.30 | 28.83 | - | 29.13 | - | 56.00 | 46.00 | -26.87 | - |
| 6 | 11.813 | 0.44 | 20.77 | - | 21.21 | - | 60.00 | 50.00 | -38.79 | - |

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading value





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

| Frequencies (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|------------------------------------|--------------------|--------------------------|------------------|
| * HP Spectrum Analyzer | 8590L | 3544A01176 | May 13, 2003 |
| * HP Preamplifier | 8447D | 2944A08485 | Apr. 29, 2003 |
| * HP Preamplifier | 8449B | 3008A01201 | Dec. 01, 2003 |
| * HP Preamplifier | 8449B | 3008A01292 | Aug. 07, 2003 |
| * ROHDE & SCHWARZ TEST RECEIVER | ESMI | 839013/007 839379/002 | Jan. 27, 2003 |
| SCHAFFNER Tunable Dipole Antenna | VHBA 9123 | 459 | Nov. 22, 2003 |
| SCHWARZBECK Tunable Dipole Antenna | UHA 9105 | 977 | |
| * CHASE BILOG Antenna | CBL6112A | 2221 | Aug. 2, 2003 |
| * SCHWARZBECK Horn Antenna | BBHA9120-D1 | D130 | July 3, 2003 |
| * EMCO Horn Antenna | 3115 | 9312-4192 | April 9, 2003 |
| * EMCO Turn Table | 1060 | 1115 | NA |
| * SHOSHIN Tower | AP-4701 | A6Y005 | NA |
| * Software | ADT_Radiated_V5.09 | NA | NA |
| * ANRITSU RF Switches | MP59B | M35046 | July 11, 2003 |
| * TIMES RF cable | LMR-600 | CABLE-ST5-01 | July. 11. 2003 |

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

2. "*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 5.
5. The VCCI Site Registration No. is R-1039.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



4.2.7 TEST RESULTS

| | | | |
|---------------------------------|------------------------------|------------------------------|----------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 11 | FREQUENCY RANGE | Below 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Quasi-Peak |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 160.00 | 31.5 QP | 43.50 | -12.00 | 1.49 H | 251 | 20.60 | 10.80 |
| 2 | 200.00 | 35.0 QP | 43.50 | -8.50 | 1.08 H | 33 | 24.00 | 11.00 |
| 3 | 240.03 | 31.1 QP | 46.00 | -14.90 | 1.36 H | 273 | 16.50 | 14.70 |
| 4 | 279.98 | 29.8 QP | 46.00 | -16.20 | 1.13 H | 184 | 13.30 | 16.50 |
| 5 | 480.00 | 28.0 QP | 46.00 | -18.00 | 1.26 H | 44 | 7.40 | 20.60 |
| 6 | 640.00 | 31.0 QP | 46.00 | -15.00 | 1.36 H | 45 | 8.20 | 22.80 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 160.00 | 33.5 QP | 43.50 | -10.00 | 1.13 V | 255 | 22.70 | 10.80 |
| 2 | 200.00 | 28.7 QP | 43.50 | -14.80 | 1.24 V | 247 | 17.70 | 11.00 |
| 3 | 240.00 | 30.0 QP | 46.00 | -16.00 | 1.12 V | 74 | 15.30 | 14.70 |
| 4 | 320.00 | 31.0 QP | 46.00 | -15.00 | 1.45 V | 122 | 13.90 | 17.10 |
| 5 | 480.00 | 27.0 QP | 46.00 | -19.00 | 1.27 V | 154 | 6.40 | 20.60 |
| 6 | 640.00 | 31.0 QP | 46.00 | -15.00 | 1.26 V | 180 | 8.20 | 22.80 |

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



4.2.8 TEST RESULTS (For CCK)

| | | | |
|-------------------------------------|---------------------------------|------------------------------|--------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 1 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Peak(PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1 | *2412.00 | 109.4 PK | | | 1.03 H | 274 | 76.60 | 32.80 |
| 1 | *2412.00 | 102.6 AV | | | 1.03 H | 274 | 69.80 | 32.80 |
| 2 | 3216.00 | 43.7 PK | 74.00 | -30.30 | 1.25 H | 27 | 9.80 | 33.90 |
| 3 | 4824.00 | 46.6 PK | 74.00 | -27.40 | 1.28 H | 228 | 9.70 | 36.90 |
| 4 | 7236.00 | 49.4 PK | 74.00 | -24.60 | 1.32 H | 352 | 8.00 | 41.40 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1 | 1608.00 | 42.1 PK | 74.00 | -31.90 | 1.28 V | 67 | 10.50 | 31.60 |
| 2 | *2412.00 | 104.0 PK | | | 1.23 V | 70 | 71.30 | 32.80 |
| 2 | *2412.00 | 96.6 AV | | | 1.23 V | 70 | 63.80 | 31.60 |
| 3 | 3216.00 | 43.8 PK | 74.00 | -30.20 | 1.32 V | 98 | 9.90 | 33.90 |
| 4 | 4824.00 | 46.6 PK | 74.00 | -27.40 | 1.33 V | 84 | 9.60 | 36.90 |
| 5 | 7236.00 | 50.9 PK | 74.00 | -23.10 | 1.27 V | 19 | 9.40 | 41.40 |
| 5 | 7236.00 | 38.2 AV | 54.00 | -15.80 | 1.27 V | 19 | -3.30 | 32.80 |

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The other emission levels were very low against the limit.



| | | | |
|---------------------------------|---------------------------------|------------------------------|--------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 6 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Peak(PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1624.00 | 42.5 PK | 74.00 | -31.50 | 1.30 H | 241 | 10.90 | 31.60 |
| 2 | *2437.00 | 111.1 PK | | | 1.06 H | 266 | 78.30 | 32.80 |
| 2 | *2437.00 | 102.6 AV | | | 1.06 H | 266 | 69.80 | 31.60 |
| 3 | 3248.00 | 43.3 PK | 74.00 | -30.70 | 1.22 H | 42 | 9.40 | 33.90 |
| 4 | 4874.00 | 46.1 PK | 74.00 | -27.90 | 1.42 H | 54 | 8.90 | 37.10 |
| 5 | 7319.00 | 50.3 PK | 74.00 | -23.70 | 1.46 H | 24 | 8.70 | 41.60 |
| 5 | 7319.00 | 41.5 AV | 54.00 | -12.50 | 1.46 H | 24 | -0.10 | 32.80 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1624.00 | 41.1 PK | 74.00 | -32.90 | 1.30 V | 244 | 9.50 | 31.60 |
| 2 | *2437.00 | 105.0 PK | | | 1.22 V | 78 | 72.20 | 32.80 |
| 2 | *2437.00 | 95.8 AV | | | 1.22 V | 78 | 63.00 | 31.60 |
| 3 | 3249.00 | 45.8 PK | 74.00 | -28.20 | 1.15 V | 32 | 11.90 | 33.90 |
| 4 | 4874.00 | 45.9 PK | 74.00 | -28.10 | 1.38 V | 32 | 8.70 | 37.10 |
| 5 | 7311.00 | 50.4 PK | 74.00 | -23.60 | 1.35 V | 28 | 8.80 | 41.50 |
| 5 | 7311.00 | 40.5 AV | 54.00 | -13.50 | 1.35 V | 28 | -1.10 | 32.80 |

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The other emission levels were very low against the limit.



| | | | |
|---------------------------------|---------------------------------|------------------------------|--------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 11 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Peak(PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1641.00 | 45.6 PK | 74.00 | -28.40 | 1.13 H | 341 | 13.90 | 31.60 |
| 2 | *2463.00 | 106.2 PK | | | 1.36 H | 262 | 73.30 | 32.90 |
| 2 | *2463.00 | 99.2 AV | | | 1.36 H | 262 | 66.30 | 31.60 |
| 3 | 3283.50 | 44.6 PK | 74.00 | -29.40 | 1.34 H | 19 | 10.70 | 33.90 |
| 4 | 4924.00 | 49.4 PK | 74.00 | -24.60 | 1.12 H | 41 | 12.00 | 37.30 |
| 5 | 7387.00 | 49.7 PK | 74.00 | -24.30 | 1.26 H | 324 | 8.10 | 41.70 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1641.50 | 39.0 PK | 74.00 | -35.00 | 1.33 V | 352 | 7.30 | 31.60 |
| 2 | *2463.00 | 102.9 PK | | | 1.00 V | 34 | 70.10 | 32.90 |
| 2 | *2463.00 | 95.9 AV | | | 1.00 V | 34 | 63.10 | 31.60 |
| 3 | 3282.00 | 43.6 PK | 74.00 | -30.40 | 1.40 V | 24 | 9.70 | 33.90 |
| 4 | 4924.00 | 45.1 PK | 74.00 | -28.90 | 1.33 V | 352 | 7.70 | 37.30 |
| 5 | 7387.00 | 49.9 PK | 74.00 | -24.10 | 1.15 V | 48 | 8.20 | 41.70 |

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency
6. The other emission levels were very low against the limit.



4.2.9 TEST RESULTS (For OFDM)

| | | | |
|-------------------------------------|---------------------------------|------------------------------|--------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 1 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Peak(PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1 | 1608.00 | 44.1 PK | 74.00 | -29.90 | 1.32 H | 15 | 12.50 | 31.60 |
| 2 | *2412.00 | 99.8 PK | | | 1.74 H | 352 | 67.10 | 32.80 |
| 2 | *2412.00 | 85.0 AV | | | 1.74 H | 352 | 52.30 | 31.60 |
| 3 | 3216.00 | 42.8 PK | 74.00 | -31.20 | 1.15 H | 44 | 8.90 | 33.90 |
| 4 | 4824.00 | 46.2 PK | 74.00 | -27.80 | 1.52 H | 37 | 9.20 | 36.90 |
| 5 | 7234.00 | 48.4 PK | 74.00 | -25.60 | 1.12 H | 84 | 6.90 | 41.40 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1 | 1608.00 | 44.1 PK | 74.00 | -29.90 | 1.14 V | 56 | 12.50 | 31.60 |
| 2 | *2412.00 | 97.8 PK | | | 1.20 V | 20 | 65.10 | 32.80 |
| 2 | *2412.00 | 83.0 AV | | | 1.20 V | 20 | 50.20 | 31.60 |
| 3 | 3216.00 | 43.8 PK | 74.00 | -30.20 | 1.41 V | 184 | 9.90 | 33.90 |
| 4 | 4824.00 | 48.2 PK | 74.00 | -25.80 | 1.30 V | 241 | 11.20 | 36.90 |
| 5 | 7234.00 | 48.4 PK | 74.00 | -25.60 | 1.17 V | 9 | 6.90 | 41.40 |

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The other emission levels were very low against the limit.



| | | | |
|---------------------------------|---------------------------------|------------------------------|--------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 6 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Peak(PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1624.00 | 43.1 PK | 74.00 | -30.90 | 1.57 H | 19 | 11.50 | 31.60 |
| 2 | *2437.00 | 106.7 PK | | | 1.00 H | 270 | 73.90 | 32.80 |
| 2 | *2437.00 | 94.7 AV | | | 1.00 H | 270 | 61.90 | 31.60 |
| 3 | 3249.00 | 45.6 PK | 74.00 | -28.40 | 1.39 H | 51 | 11.70 | 33.90 |
| 4 | 4874.00 | 47.9 PK | 74.00 | -26.10 | 1.21 H | 287 | 10.70 | 37.10 |
| 5 | 7310.00 | 49.5 PK | 74.00 | -24.50 | 1.32 H | 71 | 7.90 | 41.50 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1624.00 | 40.4 PK | 74.00 | -33.60 | 1.53 V | 14 | 8.80 | 31.60 |
| 2 | *2437.00 | 100.8 PK | | | 1.27 V | 115 | 68.00 | 32.80 |
| 2 | *2437.00 | 87.2 AV | | | 1.27 V | 115 | 54.40 | 31.60 |
| 3 | 3248.00 | 43.8 PK | 74.00 | -30.20 | 1.14 V | 54 | 9.90 | 33.90 |
| 4 | 4874.00 | 54.4 PK | 74.00 | -19.60 | 1.40 V | 79 | 17.20 | 37.10 |
| 4 | 4874.00 | 39.4 AV | 54.00 | -14.60 | 1.40 V | 79 | 2.20 | 32.80 |
| 5 | 7310.00 | 48.7 PK | 74.00 | -25.30 | 1.12 V | 360 | 7.10 | 41.50 |

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency
6. The other emission levels were very low against the limit.



| | | | |
|---------------------------------|---------------------------------|------------------------------|--------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| MODE | Channel 11 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | DETECTOR FUNCTION | Peak(PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25 deg. C, 60 % RH, 1050 hPa | TESTED BY: Gary Chang | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1641.00 | 41.0 PK | 74.00 | -33.00 | 1.25 H | 75 | 9.30 | 31.60 |
| 2 | *2463.00 | 97.7 PK | | | 1.09 H | 325 | 64.90 | 32.90 |
| 2 | *2463.00 | 81.2 AV | | | 1.09 H | 325 | 48.40 | 31.60 |
| 3 | 3282.00 | 43.8 PK | 74.00 | -30.20 | 1.52 H | 74 | 9.90 | 33.90 |
| 4 | 4924.00 | 47.6 PK | 74.00 | -26.40 | 1.15 H | 352 | 10.20 | 37.30 |
| 5 | 7388.00 | 48.7 PK | 74.00 | -25.30 | 1.52 H | 74 | 7.10 | 41.70 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1641.00 | 42.2 PK | 74.00 | -31.80 | 1.56 V | 41 | 10.50 | 31.60 |
| 2 | *2463.00 | 98.1 PK | | | 1.03 V | 133 | 65.30 | 32.90 |
| 2 | *2463.00 | 83.7 AV | | | 1.03 V | 133 | 50.90 | 31.60 |
| 3 | 3282.00 | 44.8 PK | 74.00 | -29.20 | 1.15 V | 355 | 10.90 | 33.90 |
| 4 | 4924.00 | 46.1 PK | 74.00 | -27.90 | 1.19 V | 222 | 8.70 | 37.30 |
| 5 | 7386.00 | 49.5 PK | 74.00 | -24.50 | 1.35 V | 54 | 7.90 | 41.70 |

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency
6. The other emission levels were very low against the limit.



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

| Description & Manufacturer | Model No. | Serial No. | Calibrated Until |
|----------------------------|-----------|------------|------------------|
| R&S SPECTRUM ANALYZER | FSEK30 | 100049 | July 24, 2003 |

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.7 TEST RESULTS (For CCK)

| | | | |
|---------------------------------|-----------------------------|-------------------------------------|------------------------------|
| EUT | Wireless LAN PCMCIA Card | MODEL | WLC3010 |
| INPUT POWER (SYSTEM) | 120Vac, 60 Hz | ENVIRONMENTAL CONDITIONS | 19deg. C, 54%RH, 1005 hPa |
| TESTED BY: Steven Lu | | | |

| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) | MINIMUM LIMIT (MHz) | PASS/FAIL |
|----------------|--|--------------------------------|------------------------------------|------------------|
| 1 | 2412 | 11.102 | 0.5 | PASS |
| 6 | 2437 | 11.062 | 0.5 | PASS |
| 11 | 2462 | 11.263 | 0.5 | PASS |



CH1





CH6

