Test Method:	FCC Part 15 Subpart C, Spurious Case Radiated Emissions, Paragraph 15.209(a)		
Customer:	Symbol Technologies	**Job No.**	R-8427-1
Test Sample:	2.4 GHz Pulsed Transmitter		
Model No.:	PDT6844 **FCC ID:** H9P	**Serial No.**	NA
Operating Mode:	Continuously scanning and sending data to printer at 2.4 GHz, 2.4 GHz SS also transmitting.		
Technician:	P.L.	**Date:**	March 1-2, 2000

Notes: Test Distance: 3 Meters Temp:7C Humidity:38%
Detector: Quasi-Peak Below 30 MHz to 1 GHz, Peak above 1 GHz

Test Freq.	Antenna Position	EUT Orientation	Meter Readings	Correction Factor	Corrected Reading	Converted Reading	**LIMIT**
MHz	(V/H) / Meters	Degrees	dBuV	dB	dBuV/m	uV/m	uV/m
30.00							100
|							|
88.00							100
88.00							150
|							|
216.00							150
216.00							200
|							|
260.0	H/1.0	135	48	-6.0	42.0	125.9	|
|							|
960.00							200
960.00							500
|							|
1100	V/1.0	180	55	-15.5	39.5	94.4	|
1230	V/1.0	180	39	-18.2	20.8	11.0	|
1500	V/1.0	180	38	-17.0	21.0	11.2	|
1600	V/1.0	180	38	-16.7	21.3	11.6	|
2000	V/1.0	180	35	-11.8	23.2	14.5	|
2060	V/1.0	180	41	-11.6	29.4	29.5	|
2580	V/1.0	180	38	-10.8	27.2	22.9	|
2650	V/1.0	180	33	-10.5	22.5	13.3	|
3050	V/1.0	180	23	-10.2	12.8	4.4	|
3170	V/1.0	180	26	-10.0	16.0	6.3	|
|							|
|							|
|							|
|							|
25000							500

The EUT was scanned from 30 MHz to 25 GHz
The emissions observed from the EUT do not exceed the specified limits. Emissions not recorded were more than 10dB under the specified limit

Retlif Testing Laboratories

Retlif Job Number R-8427-1