

Test Method:	FCC Part 15 Spurious Case Radiated Emissions, 30 MHz to 25 GHz, paragraph 15.209(a)						
Customer:	Symbol Technologies	Job No.:	R-8338-1				
Test Sample:	2.4 GHz Frequency Hopping Spread Spectrum Transmitter, FCC ID: H9PCST3040K088R1						
Model No.:	CST30XX	Serial No.:	N/A				
Operating Mode:	Continuously sending/receiving data to access point at 2.4 GHz						
Technician:	T. Schneider	Date:	January 11, 2000				
Notes:	Test Distance: 3 Meters Temp: 11 C Humidity: 51 % Detector: Quasi-Peak Below 1 GHz, Peak above 1 GHz						
Test Freq.	Antenna Position	EUT Orientation	Meter Readings	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H) / Meters	Degrees	dBuv	dB	dBuv/m	uV/m	uV/m
30.00							100
30.00							100
V							V
88.00							100
88.00							150
No Emissions Observed at specified test distance							
V							V
216.00							150
216.00							200
V							V
960.00							200
960.00							500
V							V
25,000.0							500
The EUT was scanned from 30 MHz to 25 GHz							
The emissions observed from the EUT do not exceed the specified limits. Emissions not recorded were more than 10dB under the specified limit							



Retlif Testing Laboratories

Retlif Job Number R-8338-1