The Measurement of Conducted Spurious Emissions

CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

1. LIMITS OF CONDUCTED SPURIOUS EMISSIONS EASUREMENT

Below 20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth, see Section 15.247(c)). Emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the limits specified in Section 15.209(a) (see Section 15.205(c)).

2. TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2003
HIGH PASS FILTER	WHK3.1/18G- 10SS	SN4	Jun. 12, 2004

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


3. TEST PROCEDURE

2.5GHz~13GHz:

The transmitter output was connected to the spectrum analyzer via a low lose cable and a high pass filter. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

13GHz~25GHz:

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




5. EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

TEST RESULTS - For 802.11b

The spectrum plots are attached on the following 2 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.





Report No. 930309H03



TEST RESULTS – For 802.11g

The spectrum plots are attached on the following 2 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.





TEST RESULTS – For 802.11a, Normal mode

The spectrum plots are attached on the following 4 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.

dBn GHz	dBm GKz	dBm GHz	dBm dBm	ZHO		2	
						Thereway we want to be and the	
"11] -43.28	T1 1 -47.7	[T1] -44.2	11-44-4	0		3 -	
- 0	er 1 [71] -47.79 10.36000000	er 2 [T1] -44.29 15 54000000	[1]	72000		3	
8H 4	5 1 10.3	5 5 5	en H	20.7		3	
Marker 4 25.90	Marker 10	Marker	Marker	ľ		mm l	
	×	x	N	-		3	
kH ₂ kH ₂						- mark	
100			+			3	++
• VBW 100 • VBW 100 8WT 3.5						2	
			+				
dB						m 🛃	
10				+		3	
* Att						The second	
•			1		GB	N. N	
	gB		-5.03 dBm		-25.03 dBm	53	
	21.		5.03			1	
21 dBm	Tset		- 10		D3	- Martin	
12	OFIS		T			1	
Ref	20_0			-10-	-30-	-05-	-60-
A		88					
Ø		1 PK					

