


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Symbol Technologies			Job No.	R-8504-1		
Test Sample:	916.5MHz Pulsed RF Transmitter			Paragraph:	249(a)		
Model No.:	LS4071			FCC ID:	H9PLS4071ITA		
Operating Mode:	Continuously Transmitting a 916.5MHz Signal						
Technician:	P. Lananna			Date:	May 1, 2000		
Notes:	Test Distance: 3 Meters Detector: Peak, Unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)/Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
916.5	H / 2.0	X	72.0	7.3	79.3	9225.7	50000
	H / 2.3	Y	77.6	7.3	84.9	17579.2	
	H / 1.0	Z	75.7	7.3	83.0	14125.4	
	V / 1.0	X	76.9	7.3	84.2	16218.1	
	V / 1.0	Y	76.0	7.3	83.3	14621.8	
916.5	V / 1.0	Z	73.6	7.3	80.9	11091.7	50000
1833	H / 1.0	X	38.0	-8.8	29.2	28.8*	500
	H / 1.0	Y	38.0	-8.8	29.2	28.8*	
	H / 1.0	Z	38.0	-8.8	29.2	28.8*	
	V / 1.0	X	38.0	-8.8	29.2	28.8*	
	V / 1.0	Y	38.0	-8.8	29.2	28.8*	
1833	V / 1.0	Z	38.0	-8.8	29.2	28.8*	500
2749.5	H / 1.0	X	37.0	-8.3	28.7	27.2*	500
	H / 1.0	Y	37.0	-8.3	28.7	27.2*	
	H / 1.0	Z	37.0	-8.3	28.7	27.2*	
	V / 1.0	X	37.0	-8.3	28.7	27.2*	
	V / 1.0	Y	37.0	-8.3	28.7	27.2*	
2749.5	V / 1.0	Z	37.0	-8.3	28.7	27.2*	500
3666	H / 1.0	X	37.0	-7.2	29.8	30.9*	500
	H / 1.0	Y	37.0	-7.2	29.8	30.9*	
	H / 1.0	Z	37.0	-7.2	29.8	30.9*	
	V / 1.0	X	37.0	-7.2	29.8	30.9*	
	V / 1.0	Y	37.0	-7.2	29.8	30.9*	
3666	V / 1.0	Z	37.0	-7.2	29.8	30.9*	500
4582.5	H / 1.0	X	38.0	-3.3	34.7	54.3*	500
	H / 1.0	Y	38.0	-3.3	34.7	54.3*	
	H / 1.0	Z	38.0	-3.3	34.7	54.3*	
	V / 1.0	X	38.0	-3.3	34.7	54.3*	
	V / 1.0	Y	38.0	-3.3	34.7	54.3*	
4582.5	V / 1.0	Z	38.0	-3.3	34.7	54.3*	500
The frequency range was scanned from 30 MHz to 9.2 GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8504-1


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Symbol Technologies	Job No.	R-8504-1				
Test Sample:	916.5MHz Pulsed RF Transmitter	Paragraph:	249(a)				
Model No.:	LS4071	FCC ID:	H9PLS4071ITA				
Operating Mode:	Continuously Transmitting a 916.5MHz Signal						
Technician:	P. Lananna	Date:	May 1, 2000				
Notes:	Test Distance: 3 Meters Detector: Peak, unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
5499	H / 1.0	X	36.0	-3.1	32.9	44.2*	500
	H / 1.0	Y	36.0	-3.1	32.9	44.2*	
	H / 1.0	Z	36.0	-3.1	32.9	44.2*	
	V / 1.0	X	36.0	-3.1	32.9	44.2*	
	V / 1.0	Y	36.0	-3.1	32.9	44.2*	
5499	V / 1.0	Z	36.0	-3.1	32.9	44.2*	500
6415.5	H / 1.0	X	36.0	-0.5	35.5	59.6*	500
	H / 1.0	Y	36.0	-0.5	35.5	59.6*	
	H / 1.0	Z	36.0	-0.5	35.5	59.6*	
	V / 1.0	X	36.0	-0.5	35.5	59.6*	
	V / 1.0	Y	36.0	-0.5	35.5	59.6*	
6415.5	V / 1.0	Z	36.0	-0.5	35.5	59.6*	500
7332	H / 1.0	X	34.0	-2.1	31.9	39.4*	500
	H / 1.0	Y	34.0	-2.1	31.9	39.4*	
	H / 1.0	Z	34.0	-2.1	31.9	39.4*	
	V / 1.0	X	34.0	-2.1	31.9	39.4*	
	V / 1.0	Y	34.0	-2.1	31.9	39.4*	
7332	V / 1.0	Z	34.0	-2.1	31.9	39.4*	500
8248.5	H / 1.0	X	36.0	-0.5	35.5	59.6*	500
	H / 1.0	Y	36.0	-0.5	35.5	59.6*	
	H / 1.0	Z	36.0	-0.5	35.5	59.6*	
	V / 1.0	X	36.0	-0.5	35.5	59.6*	
	V / 1.0	Y	36.0	-0.5	35.5	59.6*	
8248.5	V / 1.0	Z	36.0	-0.5	35.5	59.6*	500
9165	H / 1.0	X	35.0	2.0	37.0	70.8*	500
	H / 1.0	Y	35.0	2.0	37.0	70.8*	
	H / 1.0	Z	35.0	2.0	37.0	70.8*	
	V / 1.0	X	35.0	2.0	37.0	70.8*	
	V / 1.0	Y	35.0	2.0	37.0	70.8*	
9165	V / 1.0	Z	35.0	2.0	37.0	70.8*	500
The frequency range was scanned from 30 MHz to 9.2 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8504-1


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:				Job No.			
Test Sample:				Paragraph:			
Model No.:				FCC ID:			
Operating Mode:	Continuously Transmitting a MHz Signal						
Technician:				Date:			
Notes:	Test Distance: 3 Meters			Duty Cycle:			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
The frequency range was scanned from 30 MHz to XX GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:				Job No.			
Test Sample:				Paragraph:			
Model No.:				FCC ID:	N/A		
Operating Mode:	Continuously Transmitting a MHz Signal						
Technician:				Date:			
Notes:	Test Distance: 3 Meters			Duty Cycle:			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
	H/	X					
	H/	Y					
	H/	Z					
	V/	X					
	V/	Y					
	V/	Z					
The frequency range was scanned from 30 MHz to XX GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-