



Hearing Aid Compatibility (HAC) T-Coil Test Report

for

Symbol Technologies, Inc.

on the

EDA (Enterprise Digital Assistant)

Report Number : HA891706B
Trade Name : Symbol
Model Name : MC7508
FCC ID : H9PMC7508
Date of Testing : Sep. 25, 2008
Date of Report : Oct. 09, 2008
Date of Review : Oct. 09, 2008

- **Results Summary : T Category = T4**
- The test results refer exclusively to the presented test model/sample only.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- Report Version: Rev.03

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Table of Contents

- 1. **Statement of Compliance**3
- 2. **Administration Data**4
 - 2.1 Testing Laboratory4
 - 2.2 Applicant.....4
 - 2.3 Manufacturer4
 - 2.4 Application Details4
- 3. **General Information**5
 - 3.1 Description of Device Under Test (DUT).....5
 - 3.2 Applied Standards6
 - 3.3 Test Conditions6
 - 3.3.1 Ambient Condition6
 - 3.3.2 Test Configuration.....6
- 4. **Hearing Aid Compliance (HAC)**.....7
 - 4.1 Introduction.....7
- 5. **HAC T-Coil Measurement Setup**8
 - 5.1 System Configuration8
 - 5.2 AM1D probe9
 - 5.2.1 Probe Tip Description10
 - 5.2.2 Probe Calibration in AMCC.....11
 - 5.3 AMCC12
 - 5.4 AMMI12
 - 5.5 DATA Acquisition Electronics (DAE)13
 - 5.6 Robot.....13
 - 5.7 Measurement Server13
 - 5.8 Phone Positioner14
 - 5.8.1 Test Arch Phantom15
 - 5.9 Cabling of System16
 - 5.10 HAC Extension Software for DASY416
 - 5.11 Test Equipment List17
 - 5.12 Reference Input of Audio Signal Spectrum18
 - 5.13 Signal Verification19
 - 5.14 DUT Radio Configuration Selection20
- 6 **Description for DUT Testing Position**.....21
- 7 **T-Coil Test Procedure**22
- 8 **T-Coil Articulation Weighting Factor and Signal Quality Categories**.....24
 - 8.1 Articulation weighting factor (AWF)24
 - 8.2 Signal Quality Categories24
- 9 **Summary of Measurement Result**25
 - 9.1 Conducted Power25
 - 9.2 Test Result.....26
 - 9.2.1 Magnitude Result.....26
 - 9.2.2 Frequency Response27
 - 9.3 T-Coil Coupling Field Intensity.....31
 - 9.3.1 Axial Field Intensity.....31
 - 9.3.2 Radial Field Intensity31
 - 9.3.3 Frequency Response at Axial Measurement Point31
 - 9.3.4 Signal Quality31
- 10 **Uncertainty Assessment**32
- 11 **References**.....34

- Appendix A - HAC Measurement Data
- Appendix B - Calibration Date
- Appendix C - Product Photographs
- Appendix D - Setup Photographs



1. Statement of Compliance

The Hearing Aid Compliance (HAC) maximum results found during testing for the **Symbol Technologies, Inc. EDA (Enterprise Digital Assistant) Symbol MC7508** are as follows (with expanded uncertainty $\pm 8.1\%$ for AMB1 and $\pm 12.3\%$ for AMB2):

Reference (63.19)	Description	Verdict	Section
7.3.1.1	Axial Field Intensity	Pass	9.2.1
7.3.1.2	Radial Field Intensity	Pass	9.2.2
7.3.2	Frequency Response	Pass	9.2.3
7.3.3	Signal Quality	T4	9.2.4

Sample	Band	(S+N)/N in dB	T Rating
1 (EVDO 1D with Numeric Keypad)	Cellular	25.70	T4
	PCS	24.80	T4
2 (EVDO 2D with Qwerty Keypad)	Cellular	25.80	T4
	PCS	25.10	T4

They are in compliance with HAC limits specified in guidelines FCC 47CFR §20.19 and ANSI Standard ANSI C63.19 for HAC Rated category.

Results Summary : T Category = T4

Approved by

Roy Wu
Manager



2. Administration Data

2.1 Testing Laboratory

Company Name : Sporton International Inc.
Department : Antenna Design/SAR
Address : No.52, Hwa-Ya 1st RD., Hwa Ya Technology Park, Kwei-Shan Hsiang,
TaoYuan Hsien, Taiwan, R.O.C.
Telephone Number : 886-3-327-3456
Fax Number : 886-3-327-0973

2.2 Applicant

Company Name : Symbol Technologies, Inc.
Address : One Symbol Plaza, Holtsville, NY 11742-1300, USA

2.3 Manufacturer

Company Name : Wistron Corporation
Address: 21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

2.4 Application Details

Date of reception of application: Sep. 17, 2008
Start of test : Sep. 25, 2008
End of test : Sep. 26, 2008



3. General Information

3.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type :	EDA (Enterprise Digital Assistant)
Trade Name :	Symbol
Model Name :	MC7508
FCC ID :	H9PMC7508
Barcode Reader :	1D laser scanner / 2D Imager
Tx Frequency :	CDMA2000 Cellular : 824 ~ 849 MHz CDMA2000 PCS : 1850 ~ 1910 MHz
Rx Frequency :	CDMA2000 Cellular : 869 ~ 894 MHz CDMA2000 PCS : 1930 ~ 1990 MHz
Maximum Output Power to Antenna :	CDMA2000 Cellular : 24.45 dBm CDMA2000 PCS : 24.34 dBm
Antenna Type :	Monopole Antenna
HW Version :	MP
SW Version :	BSP_21.15
Type of Modulation :	QPSK
DUT Stage :	Identical Prototype



3.2 Applied Standards

The Standard ANSI C63.19-2006 represents performance requirements for acceptable interoperability of hearing aids with wireless communications devices. When these parameters are met, a hearing aid operates acceptably in close proximity to a wireless communications device.

3.3 Test Conditions

3.3.1 *Ambient Condition*

Ambient Temperature	20-24
Humidity	<60%
Acoustic Ambient Noise	>10dB below the measurement level

3.3.2 *Test Configuration*

The device was controlled by using a base station emulator R&S CMU200. Communication between the device and the emulator was established by coaxial connection.

The DUT was set from the emulator to radiate maximum output power during all testing.



4. Hearing Aid Compliance (HAC)

4.1 Introduction

The T-Coil requirements of ANSI C63.19-2006 Standard went into effect. The federal communication commission (FCC) adopted ANSI C63.19 as HAC test standard.

5. HAC T-Coil Measurement Setup

5.1 System Configuration



Fig. 5.1: T-Coil setup with HAC Test Arch and AMCC

The DASY4 system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY4 software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Dipole for evaluating the proper functioning of the system
- Arch Phantom

Some of the components are described in details in the following sub-sections.

5.2 AMID probe

The AMID probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6mm in diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V “phantom” voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degree from the vertical, the sensor is approximately vertical when the signal connector is at the underside of the probe (cable hanging downwards).

Specification:

Frequency range	0.1 ~ 20 kHz (RF sensitivity <-100dB, fully RF shielded)
Sensitivity	<-50dB A/m @ 1 kHz
Pre-amplifier	40 dB, symmetric
Dimensions	Tip diameter/ length: 6/ 290 mm, sensor according to ANSI-PC63.19

5.2.1 Probe Tip Description

HAC field measurements take place in the close near field with high gradients. Increasing the measuring distance from the source will generally decrease the measured field values (in case of the validation dipole approx. 10% per mm).

Magnetic field sensors are measuring the integral of the H-field across their sensor area surrounded by the loop. They are calibrated in a precise, homogeneous field. When measuring a gradient field, the result will be very close to the field in the center of the loop which is equivalent to the value of a homogeneous field equivalent to the center value. But it will be different from the field at the field at the border of the loop.

Consequently, two sensors with different loop diameters – both calibrated ideally – would give different results when measuring from the edge of the probe sensor elements. The behavior for electrically small E-field sensors is equivalent. See below for distance plots from a WD which show the conservative nature of field readings at the probe element center vs. measurements at the sensor end.




Fig. 5.2: Z-Axis Scan at maximum point above a typical wireless device for H-field

5.2.2 Probe Calibration in AMCC

The probe sensitivity at 1 kHz is 0.0625214V/(A/m) (-24.0dBV/(A/m)) was calibrated by AMCC coil for verification of setup performance. The evaluated probe sensitivity was able to be compared to the calibration of the AM1D probe. The frequency response and sensitivity was shown in Figure 5.3. The probe signal is represented after application of an ideal integrator. The green curve represents the current though the AMCC, the blue curve the integrated probe signal. The DIFFERENCE between the two curves is equivalent to the frequency response of the probe system and shows the characteristics. The probe/system complies with the frequency response and linearity requirements in C63.19 according to the Speag’s calibrated report as shown in Annex B (AM1D probe: SPAM100AF) (1)The frequency response has been tested within +/- 0.5 dB of ideal differentiator from 100 Hz to 10 kHz. (2)The linearity has also been tested within 0.1dB from 5 dB below limitation to 16 dB above noise level. The AMCC coil is qualified according to certificate report, SDHACPO02A as shown in Annex B.




Fig. 5.3: The frequency response and sensitivity of AM1D probe

5.3 AMCC

The Audio Magnetic Calibration coil is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 50Ohm, and a shunt resistor of 10 Ohm permits monitoring the current with a scale of 1:10.

Port description:

Signal	Connector	Resistance
Coil In	BNC	typically 50 Ohm
Coil Monitor	BNO	10Ohm \pm 1%(100mV corresponding to 1 A/m)

Specification:

Dimensions	370 x 370 x 196 mm, according to ANSI C63.19
-------------------	--

5.4 AMMI



Fig. 5.4: AMMI front panel

The Audio Magnetic Measuring Instrument (AMMI) is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.

Specification:

Sampling rate	48 kHz/24 bit
Dynamic range	85 dB
Test signal generation	User selectable and predefined (vis PC)
Calibration	Auto-calibration/full system calibration using AMCC with monitor output
Dimensions	482 x 65 x 270 mm

5.5 DATA Acquisition Electronics (DAE)

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE3 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.

5.6 Robot

The DASY4 system uses the high precision robots RX90BL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY4 system, the CS7MB robot controller version from Stäubli is used. The RX robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller

5.7 Measurement Server

The DASY4 measurement server is based on a PC/104 CPU board with
166 MHz CPU
32 MB chipset and
64 MB RAM.

Communication with
the DAE4 electronic box
the 16-bit AD-converter system for optical detection and digital I/O interface.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.

5.8 Phone Positioner

The phone positioner shown in Figure 5.5 is used to adjust DUT to the suitable position.



Fig. 5.5: Phone Positioner

5.8.1 Test Arch Phantom

Construction	Enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot.
Dimensions	370 x 370 x 370 mm




Fig. 5.6: Test Arch Phantom

5.9 Cabling of System

The principal cabling of the T-Coil setup is shown in Figure 5.6. All cables provided with the basic setup have a length of approximately 5 m.




Fig. 5.7: T-Coil setup cabling

5.10 HAC Extension Software for DASY4

Specification:

Precise teaching	Easy teaching with adaptive distance verification
Measurement area	Flexible selection of measurement area, predefined according to ANSI C63.19
Evaluation	ABM: spectral processing, filtering, weighting and evaluation according to ANSI C63.19
Report	Documentation ready for compliance report



5.11 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	Audio Magnetic 1D Field Probe	AM1DV2	1038	Jan. 23, 2008	Jan. 22, 2009
SPEAG	Audio Magnetic Calibration Coil	AMCC	1049	NCR	NCR
SPEAG	Audio Measuring Instrument	AMMI	1041	NCR	NCR
SPEAG	835MHz Calibration Dipole	CD835V3	1045	Sep. 25, 2007	Sep. 24, 2009
SPEAG	1880MHz Calibration Dipole	CD1880V3	1038	Sep. 27, 2007	Sep. 26, 2009
SPEAG	Data Acquisition Electronics	DAE3	577	Nov. 16, 2007	Nov. 15, 2008
SPEAG	Test Arch Phantom	N/A	N/A	NCR	NCR
SPEAG	Phone Positoiner	N/A	N/A	NCR	NCR
R&S	Universal Radio Communication Tester	CMU200	103937	Oct. 19, 2007	Oct. 18, 2008
Agilent	Dual Directional Coupler	778D	50422	NCR	NCR
AR	Power Amplifier	5S1G4M2	0328767	NCR	NCR
R&S	Power Meter	NRVD	101394	Oct. 31, 2007	Oct. 30, 2008
R&S	Power Sensor	NRV-Z1	100130	Oct. 31, 2007	Oct. 30, 2008

Table 5.1: Test Equipment List

5.12 Reference Input of Audio Signal Spectrum

With the reference job "use as reference" in the beginning of a procedure, measure the spectrum of the current when applied to the AMCC, i.e. the input magnetic field spectrum, as shown below Fig. 5.8 and Fig. 5.9. For this, the delay of the window shall be set to a multiple of the signal period and at least 2s. From the measurement on the device, using the same signal, the postprocessor deducts the input spectrum, so the result represents the net DUT response.




Fig. 5.8: Audio signal spectrum of the broadband signal (48KHz_voice_300Hz~3KHz)




Fig. 5.9: Audio signal spectrum of the narrowband signal (48KHz_voice_1KHz)



5.13 Signal Verification

According to ANSI C63.19:2006 section 6.3.2.1, the normal speech input level for HAC T-coil tests shall be set to -16 dBm0 for GSM and UMTS (WCDMA), and to -18 dBm0 for CDMA. This technical note shows a possibility to evaluate and set the correct level with the HAC T-Coil setup with a Rohde&Schwarz communication tester CMU200 with audio option B52 and B85.

Establish a call from the CMU200 to a wireless device. Select CMU200 Network Bitstream "Decoder Cal" to have a 1kHz signal with a level of 3.14 dBm0 at the speech output. Run the measurement job and read the voltage level at the multi-meter display "Coil signal". Read the RMS voltage corresponding to 3.14 dBm0 and note it. Calculate the desired signal levels of -18dBm0:

3.14 dBm0 = -2.37 dBV
-18 dBm0 = -23.51 dBV

Determine the 1 kHz input level to generate the desired signal level of -18 dBm0. Select CMU200 Network Bitstream "Codec Cal" to loop the input via the codec to the output. Run the measurement job (AMMI 1kHz signal with gain 10 inserted) and read the voltage level at the multimeter display "Coil signal". Calculate the required gain setting for the above levels:

Gain 10 = -20.04 dBV
Difference for -18 dBm0 = -23.51 - (-20.04) = -3.47 dB
Gain factor = $10^{((-3.8) / 20)} = 0.671$
Resulting Gain = $10 \times 0.67 = 6.71$

The predefined signal types have the following differences / factors compared to the 1kHz sine signal:

Signal Type	Duration (s)	Peak to RMS (dB)	RMS (dB)	Gain Factor	Gain Setting
1kHz	1	16.2	-12.7	4.33	29.05
300Hz ~ 3kHz	2	21.6	-18.6	8.48	56.88

5.14 DUT Radio Configuration Selection

During the ABM2 measurement, there was no audio signal passing through the DUT, meanwhile, the device was set at maximum RF power and high digital processing such as backlight on, display on, maximum volume, maximum panel contrast setting and without any external shielding case. The device was chosen from a variety of vocoders to be tested in the worst case ABM2 condition under RC1/SO3. The ABM2 summary as below:




Fig. 5.10: Vocoder Analysis for ABM Noise

The ABM2 measurement is implemented by applying digital filtering to the data stream of 48 kHz samples in the measurement window. The digital filters consist of an integrator, a high-pass and an A-filter. From the output, the numerical "ABM2" value is generated. This value is represented in the top of the data window in DASY. The intermediate results are not visible. The graphical representation of the ABM2 spectrum consists of the same data filtered with a bank of third-octave filters. In DASY system, the representation is directly in dB A/m without weighting. In the postprocessor representation, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, and those results are final as shown in this report.

6 Description for DUT Testing Position

Figure 6.1 illustrate the references and reference plane that shall be used in a typical DUT emissions measurement. The principle of this section is applied to DUT with similar geometry.

- The grid is 5 cm by 5 cm area that is divided into 9 evenly sized blocks or sub-grids.
- The grid is centered on the audio frequency output transducer of the DUT.
- The grid is in a reference plane, which is defined as the planar area that contains the highest point in the area of the phone that normally rests against the user’s ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the DUT handset, which, in normal handset use, rest against the ear.
- The measurement plane is parallel to, and 1.0 cm in front of, the reference plane.



Fig. 6.1: A typical DUT reference and plane for HAC measurements



7 T-Coil Test Procedure

The following illustrate a typical test scan over a wireless communications device:

1. Geometry and signal check: system probe alignment, proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed. A surface calibration was performed before each setup change to ensure repeatable spacing and proper maintenance of the measurement plane using the test Arch.
2. Set the reference drive level of signal voice defined in C63.19 per 6.3.2.1, as shown in this report of section 5.12.
3. The ambient and test system background noise (dB A/m) was measured as well as ABM2 over the full measurement. The maximum noise level must be at least 10dB below the limit of C63.19 per 7.3.2.
4. The DUT was positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.
5. The DUT operation for maximum rated RF output power was configured and connected by using of coaxial cable connection to the base station simulator at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test. The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The DUT audio output was positioned tangent (as physically possible) to the measurement plane.
6. The DUT's RF emission field was eliminated from T-coil results by using a well RF-shielding of the probe, AM1D, and by using of coaxial cable connection to a Base Station Simulator. One test channel was pre-measurement to avoid this possibility.
7. Determined the optimal measurement locations for the DUT by following the three steps, coarse resolution scan, fine resolution scans, and point measurement, as described in C63.19 per 6.3.4.4. At each measurement locations, samples in the measurement window duration were evaluated to get ABM1 and the signal spectrum. The noise measurement was performed after the scan with the signal, the same happened, just with the voice signal switched off. The ABM2 was calculated from this second scan.
 - (1) Coarse resolution scans (1 KHz signal at 50 x 50 mm grid area with 10 mm spacing). Only ABM1 was measured in order to find the location of T-Coil source.
 - (2) Fine resolution scans (1 KHz signal at 10 x 10 mm grid area with 2 mm spacing). The positioned appropriately based on optimal AMB1 of coarse resolution scan. Both ABM1 and ABM2 were measured in order to find the location of the SNR point.
 - (3) Point measurement (1 KHz signal) for ABM1 and ABM2 in axial, radial transverse and radial longitudinal. The positioned appropriately based on optimal SNR of fine resolution scan. The SNR was calculated for axial, radial transverse and radial longitudinal orientation.
 - (4) Point measurement (300Hz to 3 KHz signal) for frequency response in axial. The positioned appropriately based on optimal SNR of fine resolution axial scan.



8. All results resulting from a measurement point in a T-Coil job were calculated from the signal samples during this window interval. ABM values were averaged over the sequence of these samples.
9. At an optimal point measurement, the SNR (ABM1/ABM2) was calculated for axial, radial transverse and radial longitudinal orientation, and the frequency response was measured in axial axis.
10. Corrected for the frequency response after the DUT measurement since the DASY4 system had known the spectrum of the input signal by using a reference job, as shown in this report of section 5.12.
11. In SEMCAD post-processing, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, bandwidth compensated factor (BWC) and those results are final as shown in this report.
12. Classified the signal quality based on the table 8.1: T-Coil Signal Quality Categories.

8 T-Coil Articulation Weighting Factor and Signal Quality Categories

8.1 Articulation weighting factor (AWF)

The following AWF factors shall be used for the standard transmission protocols:

Standard	Technology	AWF (dB)
TIA/EIA/IS-2000	CDMA	0
TIA/EIA-136	TDMA (50Hz)	0
J-STD-007	GSM (217)	-5
T1/P1P1/3GPP	UMTS (WCDMA)	0
iDEN™	TDMA (22 and 11 Hz)	0

8.2 Signal Quality Categories

This section provides the signal quality requirement for the intended T-Coil signal from a WD. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. A device is assessed beginning by determining the category of the RF environment in the area of the T-Coil source.

The RF measurements made for the T-Coil evaluation are used to assign the category T1 through T4. The limitation is given in Table 8.1. This establishes the RF environment presented by the WD to a hearing aid.

Category	Telephone parameters WD signal quality ((signal + noise) to noise ratio in dB)	
	AWF = 0	AWF = -5
Category T1	-20 to -10 dB	-15 to -5 dB
Category T2	-10 to 0 dB	-5 to 5 dB
Category T3	0 to 10 dB	5 to 15 dB
Category T4	>10 dB	>15 dB
(Note: For cases where it can be shown that the audio-band interference is not dominated by the RF pulse rate of the phone, AWF does not apply)		

Table 8.1: T-Coil signal quality categories



9 Summary of Measurement Result

9.1 Conducted Power

CDMA2000 Cellular	RC	SO	Type	Data Rate	Conducted Power (dBm)	Conducted Power (dBm)	Conducted Power (dBm)
					Low Ch (1013)	Mid Ch (384)	High Ch (777)
CDMA 1xRTT	1	2	Loop	Full	23.85	23.92	23.64
				Eighth	24.00	24.07	23.76
	1	3	Voice	-	24.34	24.41	24.13
	1	55	Loop	Full	23.83	23.91	23.61
				Eighth	24.02	24.06	23.84
	2	17	Voice	-	24.38	24.43	24.09
	2	32768	Voice	-	24.35	24.45	24.12
	3	2	Loop	Full	23.80	23.89	23.59
				Eighth	X	X	X
	3	3	Voice	-	X	X	X
	3	55	Loop	Full	23.81	23.89	23.60
				Eighth	X	X	X
	4	3	Voice	-	X	X	X
	5	17	Voice	-	X	X	X
5	32768	Voice	-	X	X	X	

Remark: "x" = not supported

CDMA2000 PCS	RC	SO	Type	Data Rate	Conducted Power (dBm)	Conducted Power (dBm)	Conducted Power (dBm)
					Low Ch (25)	Mid Ch (600)	High Ch (1175)
CDMA 1xRTT	1	2	Loop	Full	23.79	23.67	23.55
				Eighth	23.99	23.91	23.67
	1	3	Voice	-	24.34	24.22	24.01
	1	55	Loop	Full	23.79	23.69	23.53
				Eighth	23.98	23.86	23.66
	2	17	Voice	-	24.31	24.16	24.02
	2	32768	Voice	-	24.30	24.18	24.00
	3	2	Loop	Full	23.83	23.73	23.57
				Eighth	X	X	X
	3	3	Voice	-	X	X	X
	3	55	Loop	Full	23.82	23.73	23.57
				Eighth	X	X	X
	4	3	Voice	-	X	X	X
	5	17	Voice	-	X	X	X
5	32768	Voice	-	X	X	X	

Remark: "x" = not supported

9.2 Test Result

9.2.1 Magnitude Result

The Table 9.1 shows testing result in position coordinates which are defined as deviation from earpiece center in millimeters. Axial measurement location was defined by the manufacture of the device. Signal strength measurement scans are presented in Annex A.

Probe Position	Sample	Band	Channel	Measurement Position (x mm, y mm)	Ambient Background Noise (dB A/m)	ABM2 (dB A/m)	ABM1 (dB A/m)	AWF	SNR (dB)
Radial 1 (Longitudinal)	2	Cellular	1013	(6,0)	-46.51	-43.49	-15.70	0	27.80
			384	(6,-2)	-46.54	-43.33	-15.90	0	27.50
			777	(6,0)	-46.62	-43.54	-15.40	0	28.10
	1		777	(-6,-4)	-46.63	-45.20	-16.50	0	28.70
	2	PCS	25	(6,-4)	-45.96	-42.90	-15.10	0	27.80
			600	(6,-2)	-46.26	-42.91	-14.90	0	28.00
			1175	(6,-2)	-45.70	-43.04	-16.00	0	27.00
1		25	(-10,-2)	-46.93	-44.99	-17.10	0	27.90	
Radial 2 (Transversal)	2	Cellular	1013	(0,4)	-41.72	-41.20	-15.00	0	26.20
			384	(-2,-8)	-41.55	-41.77	-15.50	0	26.30
			777	(0,6)	-41.40	-41.16	-15.40	0	25.80
	1		777	(0,4)	-41.51	-41.26	-15.60	0	25.70
	2	PCS	25	(0,4)	-41.60	-41.59	-16.50	0	25.10
			600	(-2,4)	-42.02	-41.82	-16.10	0	25.70
			1175	(0,6)	-42.15	-41.94	-15.90	0	26.00
1		25	(0,6)	-41.38	-41.07	-16.20	0	24.80	
Axial	2	Cellular	1013	(-2,-2)	-52.28	-42.61	-6.01	0	36.60
			384	(-2,0)	-52.44	-42.85	-7.07	0	35.80
			777	(-2,-2)	-52.39	-42.47	-9.99	0	32.50
	1		777	(0,-2)	-52.32	-42.21	-9.27	0	32.90
	2	PCS	25	(0,-2)	-51.83	-41.41	-6.86	0	34.60
			600	(0,-2)	-52.23	-41.95	-6.96	0	35.00
			1175	(0,-2)	-52.17	-41.73	-6.48	0	35.20
1		25	(0,-2)	-52.39	-41.45	-7.28	0	34.20	

Table 9.1: Test Result for Various Positions

Remark:

1. The device was chosen to be tested in the worst case ABM2 condition under RC1/SO3.
2. The LCD backlight is turned on, Bluetooth functions is turned off and volume is adjusted to maximum level during T-Coil test.

9.2.2 Frequency Response




Fig. 9.1: Frequency Response of CDMA2000 Cellular Ch1013 for Sample 2




Fig. 9.2: Frequency Response of CDMA2000 Cellular Ch384 for Sample 2




Fig. 9.3: Frequency Response of CDMA2000 Cellular Ch777 for Sample 2




Fig. 9.4: Frequency Response of CDMA2000 Cellular Ch777 for Sample 1




Fig. 9.5: Frequency Response of CDMA2000 PCS Ch25 for Sample 2




Fig. 9.6: Frequency Response of CDMA2000 PCS Ch600 for Sample 2




Fig. 9.7: Frequency Response of CDMA2000 PCS Ch1175 for Sample 2




Fig. 9.8: Frequency Response of CDMA2000 PCS Ch25 for Sample 1



9.3 T-Coil Coupling Field Intensity

9.3.1 Axial Field Intensity

Sample	Band	Minimum limit (dB A/m)	Result (dB A/m)	Verdict
2	CDMA2000 Cellular	-13	-9.99	Pass
	CDMA2000 PCS	-13	-6.96	Pass
1	CDMA2000 Cellular	-13	-9.27	Pass
	CDMA2000 PCS	-13	-7.28	Pass

9.3.2 Radial Field Intensity

Sample	Band	Minimum limit (dB A/m)	Result (dB A/m)	Verdict
2	CDMA2000 Cellular	-18	-15.90	Pass
	CDMA2000 PCS	-18	-16.50	Pass
1	CDMA2000 Cellular	-18	-16.50	Pass
	CDMA2000 PCS	-18	-17.10	Pass

9.3.3 Frequency Response at Axial Measurement Point

Sample	Band	Verdict
2	CDMA2000 Cellular	Pass
	CDMA2000 PCS	Pass
1	CDMA2000 Cellular	Pass
	CDMA2000 PCS	Pass

9.3.4 Signal Quality

Sample	Band	Minimum limit (dB)				Minimum Result (dB)	Verdict
		T1	T2	T3	T4		
2	CDMA2000 Cellular	-20	-10	0	10	25.80	T4
	CDMA2000 PCS	-20	-10	0	10	25.10	T4
1	CDMA2000 Cellular	-20	-10	0	10	25.70	T4
	CDMA2000 PCS	-20	-10	0	10	24.80	T4

10 Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 10.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-shape
Multiplying factor^(a)	1/k ^(b)	1/ 3	1/ 6	1/ 2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) is the coverage factor

Table 10.1: Uncertainty classification

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASy4 uncertainty Budget is showed in Table 10.2.



Error Description	Uncertainty Value (\pm %)	Probability Distribution	Divisor	(Ci) ABM1	(Ci) ABM2	Std. Unc. ABM1	Std. Unc. ABM2
Probe Sensitivity							
Reference Level	$\pm 3.0\%$	Normal	1	1	1	$\pm 3.0\%$	$\pm 3.0\%$
AMCC Geometry	$\pm 0.4\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.2\%$	$\pm 0.2\%$
AMCC Current	$\pm 0.6\%$	Rectangular	$\sqrt{3}$	1	0.145	$\pm 0.4\%$	$\pm 0.4\%$
Probe Positioning during Calibration	$\pm 0.1\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.1\%$	$\pm 0.1\%$
Noise Contribution	$\pm 0.7\%$	Rectangular	$\sqrt{3}$	0.0143	1	$\pm 0.0\%$	$\pm 0.4\%$
Frequency Slope	$\pm 5.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.3\%$	$\pm 3.5\%$
Probe System							
Repeatability/Drift	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$
Linearity/Dynamic Range	$\pm 0.6\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.4\%$	$\pm 0.4\%$
Acoustic Noise	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	0.1	1	$\pm 0.1\%$	$\pm 0.6\%$
Probe Angle	$\pm 2.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.4\%$	$\pm 1.4\%$
Spectral Processing	$\pm 0.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.5\%$	$\pm 0.5\%$
Integration Time	$\pm 0.6\%$	Normal	1	1	5	$\pm 0.6\%$	$\pm 3.0\%$
Field Distribution	$\pm 0.2\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.1\%$	$\pm 0.1\%$
Test Signal							
Ref. Signal Spectral Response	$\pm 0.6\%$	Rectangular	$\sqrt{3}$	0	1	$\pm 0.0\%$	$\pm 0.4\%$
Positioning							
Probe Positioning	$\pm 1.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.1\%$	$\pm 1.1\%$
Phantom Thickness	$\pm 0.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.5\%$	$\pm 0.5\%$
DUT Positioning	$\pm 1.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.1\%$	$\pm 1.1\%$
External Contributions							
RF Interference	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	0.3	$\pm 0.0\%$	$\pm 0.0\%$
Test Signal Variation	$\pm 2.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.2\%$	$\pm 1.2\%$
Combined Uncertainty							
Combined Std. Uncertainty (ABM Field)						$\pm 4.1\%$	$\pm 6.1\%$
Expanded Std. Uncertainty						$\pm 8.1\%$	$\pm 12.3\%$

Table 10.2: Uncertainty of audio band magnetic measurements



11 References

- [1] NSI C63.19-2006, “American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids”
- [2] DASY4 System Hand book.
- [3] SAR Measurement Procedures for 3G Devices CDMA 2000/Ev-Do/WCDMA/HSDPA, June 2006 Laboratory Division Office of Engineering and Technology Federal Communications Commission
- [4] 3.1.2.3.4 Maximum RF Output Power 3GPP2 C.S0033-0 Version 2.0, Date: 12 December 2003 Recommended Minimum Performance Standards for cdma2000 High Rate Packet Data Access Terminal
- [5] May 9, 2006 Preliminary Guidance for Reviewing Applications for Certification of 3G Devices.



Appendix A – HAC Measurement Data

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA850 CH777_RC1_SO3_Voice_Sample 2_longitudinal

DUT: 891706

Communication System: CDMA ; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.6 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/x (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.103009 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -17.0 dB A/m
BWC Factor = 0.103009 dB
Location: 5, -5, 363.7 mm

Fine scan/x (longitudinal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.140011 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -15.6 dB A/m
BWC Factor = 0.140011 dB
Location: 6, 0, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -15.4 dB A/m
BWC Factor = 0.100005 dB
Location: 6, 0, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 28.1 dB
ABM1 comp = -15.4 dB A/m
BWC Factor = 0.100005 dB
Location: 6, 0, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA850 CH777_RC1_SO3_Voice_Sample 2_transversal

DUT: 891706

Communication System: CDMA ; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.7 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/y (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.103009 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -17.4 dB A/m
BWC Factor = 0.103009 dB
Location: -5, 5, 363.7 mm

Fine scan/y (transversal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.140011 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -15.8 dB A/m
BWC Factor = 0.140011 dB
Location: 0, 6, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -15.4 dB A/m
BWC Factor = 0.100005 dB
Location: 0, 6, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 25.8 dB
ABM1 comp = -15.4 dB A/m
BWC Factor = 0.100005 dB
Location: 0, 6, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA850 CH777_RC1_SO3_Voice_Sample 2_Axial

DUT: 891706

Communication System: CDMA ; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.8 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/z (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.103009 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -10.5 dB A/m
BWC Factor = 0.103009 dB
Location: -5, -5, 363.7 mm

Fine scan/z (axial) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.140011 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -5.90 dB A/m
BWC Factor = 0.140011 dB
Location: -2, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:

ABM1 comp = -9.99 dB A/m
BWC Factor = 0.100005 dB
Location: -2, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:


ABM1/ABM2 = 32.5 dB
ABM1 comp = -9.99 dB A/m
BWC Factor = 0.100005 dB
Location: -2, -2, 363.7 mm

Point scan/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 56.897
Measure Window Start: 2000ms
Measure Window Length: 2000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

Diff = 0.970 dB
BWC Factor = 10.8 dB
Location: -2, -2, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA850 CH777_RC1_SO3_Voice_Sample 1_longitudinal

DUT: 891706

Communication System: CDMA ; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.8 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/x (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.107043 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -16.5 dB A/m
BWC Factor = 0.107043 dB
Location: -5, -5, 363.7 mm

Fine scan/x (longitudinal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.101979 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -14.2 dB A/m
BWC Factor = 0.101979 dB
Location: -6, -4, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.122986 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -16.5 dB A/m
BWC Factor = 0.122986 dB
Location: -6, -4, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.122986 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 28.7 dB
ABM1 comp = -16.5 dB A/m
BWC Factor = 0.122986 dB
Location: -6, -4, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA850 CH777_RC1_SO3_Voice_Sample 1_transversal

DUT: 891706

Communication System: CDMA ; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.7 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/y (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.107043 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -18.5 dB A/m
BWC Factor = 0.107043 dB
Location: 5, 5, 363.7 mm

Fine scan/y (transversal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.101979 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -14.8 dB A/m
BWC Factor = 0.101979 dB
Location: 0, 4, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.122986 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -15.6 dB A/m
BWC Factor = 0.122986 dB
Location: 0, 4, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.122986 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 25.7 dB
ABM1 comp = -15.6 dB A/m
BWC Factor = 0.122986 dB
Location: 0, 4, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA850 CH777_RC1_SO3_Voice_Sample 1_Axial

DUT: 891706

Communication System: CDMA ; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.7 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/z (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.107043 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -10.3 dB A/m
BWC Factor = 0.107043 dB
Location: 5, -5, 363.7 mm

Fine scan/z (axial) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.101979 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -6.22 dB A/m
BWC Factor = 0.101979 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.122986 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:

ABM1 comp = -9.27 dB A/m
BWC Factor = 0.122986 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.122986 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:


ABM1/ABM2 = 32.9 dB
ABM1 comp = -9.27 dB A/m
BWC Factor = 0.122986 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 56.897
Measure Window Start: 2000ms
Measure Window Length: 2000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

Diff = 0.104 dB
BWC Factor = 10.8 dB
Location: 0, -2, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/25

T-Coil_CDMA 1900 CH25_RC1_SO3_Voice_Sample 2_longitudinal

DUT: 891706

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.6 °C

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/x (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.141977 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -15.6 dB A/m
BWC Factor = 0.141977 dB
Location: 5, -5, 363.7 mm

Fine scan/x (longitudinal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.11896 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -14.5 dB A/m
BWC Factor = 0.11896 dB
Location: 6, -4, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -15.1 dB A/m
BWC Factor = 0.100005 dB
Location: 6, -4, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 27.8 dB
ABM1 comp = -15.1 dB A/m
BWC Factor = 0.100005 dB
Location: 6, -4, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/25

T-Coil_CDMA 1900 CH25_RC1_SO3_Voice_Sample 2_transversal

DUT: 891706

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.6

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/y (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.141977 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -17.5 dB A/m
BWC Factor = 0.141977 dB
Location: -5, 5, 353.7 mm

Fine scan/y (transversal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.11896 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -15.4 dB A/m
BWC Factor = 0.11896 dB
Location: 0, 4, 353.7 mm

Point scan/y (transversal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -16.5 dB A/m
BWC Factor = 0.100005 dB
Location: 0, 4, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 25.1 dB
ABM1 comp = -16.5 dB A/m
BWC Factor = 0.100005 dB
Location: 0, 4, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/25

T-Coil_CDMA 1900 CH25_RC1_SO3_Voice_Sample 2_Axial

DUT: 891706

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.7

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/z (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.141977 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -10.6 dB A/m
BWC Factor = 0.141977 dB
Location: -5, -5, 363.7 mm

Fine scan/z (axial) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.11896 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -5.21 dB A/m
BWC Factor = 0.11896 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:

ABM1 comp = -6.86 dB A/m
BWC Factor = 0.100005 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.100005 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:


ABM1/ABM2 = 34.6 dB
ABM1 comp = -6.86 dB A/m
BWC Factor = 0.100005 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 56.897
Measure Window Start: 2000ms
Measure Window Length: 2000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

Diff = 0.178 dB
BWC Factor = 10.8 dB
Location: 0, -2, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA1900 CH25_RC1_SO3_Voice_Sample 1_longitudinal

DUT: 891706

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.6

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/x (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.133 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -16.9 dB A/m
BWC Factor = 0.133 dB
Location: -5, -5, 363.7 mm

Fine scan/x (longitudinal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.128979 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -14.4 dB A/m
BWC Factor = 0.128979 dB
Location: -10, -2, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.118018 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -17.1 dB A/m
BWC Factor = 0.118018 dB
Location: -10, -2, 363.7 mm

Point scan/x (longitudinal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.118018 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 27.9 dB
ABM1 comp = -17.1 dB A/m
BWC Factor = 0.118018 dB
Location: -10, -2, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA1900 CH25_RC1_SO3_Voice_Sample 1_transversal

DUT: 891706

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.6

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/y (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.133 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -16.8 dB A/m
BWC Factor = 0.133 dB
Location: 5, 5, 363.7 mm

Fine scan/y (transversal) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.128979 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -14.7 dB A/m
BWC Factor = 0.128979 dB
Location: 0, 6, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.118018 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:


ABM1 comp = -16.2 dB A/m
BWC Factor = 0.118018 dB
Location: 0, 6, 363.7 mm

Point scan/y (transversal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.118018 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1/ABM2 = 24.8 dB
ABM1 comp = -16.2 dB A/m
BWC Factor = 0.118018 dB
Location: 0, 6, 363.7 mm



0 dB = 1.00A/m



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/9/26

T-Coil_CDMA1900 CH25_RC1_SO3_Voice_Sample 1_Axial

DUT: 891706

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Ambient Temperature : 22.6

DASY4 Configuration:

- Probe: AM1DV2 - 1038; ; Calibrated: 2008/1/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn577; Calibrated: 2007/11/16
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA; Serial: 100x
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Coarse Scans/z (axial) scan 50 x 50 (grid 10) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.133 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -11.6 dB A/m
BWC Factor = 0.133 dB
Location: -5, -5, 363.7 mm

Fine scan/z (axial) scan 10 x 10 (grid 2) with noise/ABM Signal(x,y,z) (6x6x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.128979 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

ABM1 comp = -5.88 dB A/m
BWC Factor = 0.128979 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.118018 dB
Device Reference Point: 0.000, 0.000, 353.7 mm



Cursor:

ABM1 comp = -7.28 dB A/m
BWC Factor = 0.118018 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 29.052
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: 0.118018 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:


ABM1/ABM2 = 34.2 dB
ABM1 comp = -7.28 dB A/m
BWC Factor = 0.118018 dB
Location: 0, -2, 363.7 mm

Point scan/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 56.897
Measure Window Start: 2000ms
Measure Window Length: 2000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, 353.7 mm

Cursor:

Diff = 0.667 dB
BWC Factor = 10.8 dB
Location: 0, -2, 363.7 mm



0 dB = 1.00A/m

Appendix B – Calibration Data

Schmid & Partner Engineering AG

s p e a g

Zougoustrasse 43, 8004 Zurich, Switzerland
 Phone +41 44 245 9700, Fax +41 44 245 9779
 info@spaug.com, http://www.spaug.com

Client **Sporton (Auden)**

Certificate of test and configuration

Item	AM1DV2 Audio Magnetic 1D Field Probe
Type No	SP AM1 001 AF
Series No	1038
Manufacturer / Origin	Schmid & Partner Engineering AG, Zürich, Switzerland

Description of the item

The Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1]. The probe includes a symmetric 40dB low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface. The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted 35.3° above the measurement plane, using the connector rotation and Sensor angle stated below. The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in the DASY system, the probe must be operated with the special probe cup provided (larger diameter). Verify that the probe can slide in the probe cup rubber smoothly.

Functional test, configuration data and sensitivity

The probe configuration data were evaluated after a functional test including noise level and RF immunity. Connector rotation, sensor angle and sensitivity are specific for this probe.

DASY configuration data for the probe

Configuration item	Condition	Configuration Data	Dimension
Overall length	mounted on DAE in DASY system	296	mm
Tip diameter	at the cylindrical part	6	mm
Sensor offset	center of sensor, from tip	3	mm
Connector rotation	Evaluated in homogeneous 1 kHz magnetic field generated with AMCC Helmholtz Calibration Coil	39.8	°
Sensor angle		3.09	°
Sensitivity	at 1 kHz	0.0566	V / (A/m)

Standards

[1] ANSI-C83.19-2007

Test date 23.1.2008 MM

Issue date 25.1.2008

Signature



Schmid & Partner Engineering AG

s p e a g

 Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 1 245 9700, Fax +41 1 245 9779
 info@speag.com, http://www.speag.com

Certificate of conformity

Item	Audio Magnetic Calibration Coil AMCC
Type No	SD HAC P02 A
Series No	1001 ff.
Manufacturer / Origin	Schmid & Partner Engineering AG Zurich, Switzerland

Description of the item

The Audio Magnetic Calibration coil (AMCC) is a Helmholtz Coil designed according to standard [1], section D.9 for calibration of the AM1D probe. Two horizontal coils are positioned above a non-metallic base plate and generate a homogeneous magnetic field in the z direction (normal to it).

Configuration

The AMCC consists of two parallel coils of 20 turns with radius 143 mm connected in parallel in a distance of 143 mm. With this design, a current of 10 mA produces a field of 1 A/m. The DC input resistance at the input BNC socket is adjusted by a series resistor to a DC resistance of approximately 50 Ohm. The voltage required to produce a field of 1 A/m is consequently approx. 500 mV. The current through the coil is monitored via a shunt resistor of 10 Ohm +/- 1%. The voltage is available on a BNO socket with 100 mV corresponding to 1 A/m.

Handling of the item

The coil shall be positioned in a non-metallic environment to avoid distortion of the magnetic field.

Tests

Test	Requirement	Details	Units tested
Number of turns	N = 20 per coil	Resistance measurement	all
Orientation of coils	parallel coils with same direction of windings	Magnetic field variation in the AMCC axis	all
Coil radius	r = 143 mm	mechanical dimension	First article
Coil distance	d = 143 mm distance between coil centers	mechanical dimension	First article
Input resistance	51.7 +/- 2 Ohm	DC resistance at BNC input connector	all
Shunt resistance	R = 10.0 Ohm +/- 1 %	DC resistance at BNO output connector	all
Shunt sensitivity	Hc = 1 A/m per 100 mV according to formula $H_c = (U / R) * N / r / (1.25^{*1.5})$	Field measurement compared with Narda ELT400 + BN2300/90.10	First article

Standards

[1] ANSI PC63.19-2006 Draft 3.12

Conformity

Based on the tests above, we certify that this item is in compliance with the requirements of [1].

Date 22.5.2006

Stamp / Signature

s p e a g

 Schmid & Partner Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 1 245 9700, Fax +41 1 245 9779
 info@speag.com, http://www.speag.com