

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
<b>Customer:</b>	Symbol Technologies, Inc	<b>Job No.</b>	R-8060				
<b>Test Sample:</b>	Wireless Barcode Scanner	<b>FCC ID:</b>	H9PP470				
<b>Model No.:</b>	P470	<b>Serial No.</b>	N/A				
<b>Operating Mode:</b>	Continuously Transmitter 2.402 Ghz Signal						
<b>Technician:</b>	Dennis Cortes	<b>Date:</b>	June 3,1999				
<b>Notes:</b>	Test Distance: 3 Meters	Temp: 30C	Humidity:35%				
	Detector: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
Mhz	(V/H) / Degrees	X / Y / Z	dBuv	dB	dBuV/m	uV/m	uV/m
2402	H / 1.2	X	60.8	33.9	94.7	54325.0	50000
2402	H / 1.2	Y	64.7	33.9	98.6	85113.8	50000
2402	H / 1.4	Z	62.2	33.9	96.1	63826.3	50000
2402	V / 1.4	X	66.3	33.9	100.2	102329.3	50000
2402	V / 1.0	Y	61.6	33.9	95.5	59566.2	50000
2402	V / 1.0	Z	61.2	33.9	95.1	56885.3	50000
4804	H / 1.0	X	43.0	-0.6	42.4	131.8	5000
4804	H / 1.4	Y	47.6	-0.6	47.0	223.9	5000
4804	H / 1.3	Z	46.4	-0.6	45.8	195.0	5000
4804	V / 1.3	X	44.2	-0.6	43.6	151.4	5000
4804	V / 1.2	Y	42.8	-0.6	42.2	128.8	5000
4804	V / 1.3	Z	41.8	-0.6	41.2	114.8	5000
7206	H / 1.2	X	42.1	-6.6	35.5	59.6	5000
7206	H / 1.0	Y	44.7	-6.6	38.1	80.4	5000
7206	H / 1.2	Z	41.6	-6.6	35.0	56.2	5000
7206	V / 1.3	X	44.5	-6.6	37.9	78.5	5000
7206	V / 1.0	Y	40.6	-6.6	34.0	50.1	5000
7206	V / 1.0	Z	42.0	-6.6	35.4	58.9	5000
9608	H / 1.0	X	43.4	-2.8	40.6	*107.2	5000
9608	H / 1.0	Y	43.4	-2.8	40.6	*107.2	5000
9608	H / 1.0	Z	43.4	-2.8	40.6	*107.2	5000
9608	V / 1.0	X	43.4	-2.8	40.6	*107.2	5000
9608	V / 1.0	Y	43.4	-2.8	40.6	*107.2	5000
9608	V / 1.0	Z	43.4	-2.8	40.6	*107.2	5000
12010	H / 1.0	X	43.7	0.4	44.1	*160.3	5000
12010	H / 1.0	Y	43.7	0.4	44.1	*160.3	5000
12010	H / 1.0	Z	43.7	0.4	44.1	*160.3	5000
12010	V / 1.0	X	43.7	0.4	44.1	*160.3	5000
12010	V / 1.0	Y	43.7	0.4	44.1	*160.3	5000
12010	V / 1.0	Z	43.7	0.4	44.1	*160.3	5000
	The frequency range was scanned from 30 Mhz to 25 Ghz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	* =Noise Floor Measurements ( Minimum system sensitivity)						

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
<b>Customer:</b>	Symbol Technologies, Inc	<b>Job No.</b>	R-8060				
<b>Test Sample:</b>	Wireless Barcode Scanner	<b>FCC ID:</b>	H9PP470				
<b>Model No.:</b>	P470	<b>Serial No.</b>	N/A				
<b>Operating Mode:</b>	Continuously Transmitter 2.402 Ghz Signal						
<b>Technician:</b>	Dennis Cortes	<b>Date:</b>	June 3,1999				
<b>Notes:</b>	Test Distance: 3 Meters      Temp: 30C      Humidity:35% Detector: Quasi-Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
Mhz	(V/H) / Degrees	X / Y / Z	dBuv	dB	dBuV/m	UV/m	uV/m
14412	H / 1.0	X	37.8	3.7	41.5	*118.9	5000
14412	H / 1.0	Y	37.8	3.7	41.5	*118.9	5000
14412	H / 1.0	Z	37.8	3.7	41.5	*118.9	5000
14412	V / 1.0	X	37.8	3.7	41.5	*118.9	5000
14412	V / 1.0	Y	37.8	3.7	41.5	*118.9	5000
14412	V / 1.0	Z	37.8	3.7	41.5	*118.9	5000
16814	H / 1.0	X	37.1	9.4	46.5	*211.3	5000
16814	H / 1.0	Y	37.1	9.4	46.5	*211.3	5000
16814	H / 1.0	Z	37.1	9.4	46.5	*211.3	5000
16814	V / 1.0	X	37.1	9.4	46.5	*211.3	5000
16814	V / 1.0	Y	37.1	9.4	46.5	*211.3	5000
16814	V / 1.0	Z	37.1	9.4	46.5	*211.3	5000
19216	H / 1.0	X	32.2	22.7	54.9	*555.9	5000
19216	H / 1.0	Y	32.2	22.7	54.9	*555.9	5000
19216	H / 1.0	Z	32.2	22.7	54.9	*555.9	5000
19216	V / 1.0	X	32.2	22.7	54.9	*555.9	5000
19216	V / 1.0	Y	32.2	22.7	54.9	*555.9	5000
19216	V / 1.0	Z	32.2	22.7	54.9	*555.9	5000
21618	H / 1.0	X	32.5	23.0	55.5	*595.7	5000
21618	H / 1.0	Y	32.5	23.0	55.5	*595.7	5000
21618	H / 1.0	Z	32.5	23.0	55.5	*595.7	5000
21618	V / 1.0	X	32.5	23.0	55.5	*595.7	5000
21618	V / 1.0	Y	32.5	23.0	55.5	*595.7	5000
21618	V / 1.0	Z	32.5	23.0	55.5	*595.7	5000
24020	H / 1.0	X	32.9	23.4	56.3	*653.1	5000
24020	H / 1.0	Y	32.9	23.4	56.3	*653.1	5000
24020	H / 1.0	Z	32.9	23.4	56.3	*653.1	5000
24020	V / 1.0	X	32.9	23.4	56.3	*653.1	5000
24020	V / 1.0	Y	32.9	23.4	56.3	*653.1	5000
24020	V / 1.0	Z	32.9	23.4	56.3	*653.1	5000
The frequency range was scanned from 30 Mhz to 25.0 Ghz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
* =Noise Floor Measurements ( Minimum system sensitivity)							

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
<b>Customer:</b>	Symbol Technologies, Inc	<b>Job No.</b>	R-8060				
<b>Test Sample:</b>	Wireless Barcode Scanner	<b>FCC ID:</b>	H9PP470				
<b>Model No.:</b>	P470	<b>Serial No.</b>	N/A				
<b>Operating Mode:</b>	Continuously Transmitter 2.402 Ghz Signal						
<b>Technician:</b>	Dennis Cortes	<b>Date:</b>	June 3,1999				
<b>Notes:</b>	Test Distance: 3 Meters	Duty Cycle: 30%					
	Detector: Peak	Duty Cycle Correction: -10.5 dB					
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Average Limit
Mhz	(V/H) / Degrees	X / Y / Z	dBuv	dB	dBuV/m	uV/m	uV/m
2402	H / 1.2	X	94.7	-10.5	84.2	16218.1	50000
2402	H / 1.2	Y	98.6	-10.5	88.1	25409.7	50000
2402	H / 1.4	Z	96.1	-10.5	85.6	19054.6	50000
2402	V / 1.4	X	100.2	-10.5	89.7	30549.2	50000
2402	V / 1.0	Y	95.5	-10.5	85.0	17782.8	50000
2402	V / 1.0	Z	95.1	-10.5	84.6	16982.4	50000
4804	H / 1.0	X	42.4	-10.5	31.9	39.4	500
4804	H / 1.4	Y	47.0	-10.5	36.5	66.8	500
4804	H / 1.3	Z	45.8	-10.5	35.3	58.2	500
4804	V / 1.3	X	43.6	-10.5	33.1	45.2	500
4804	V / 1.2	Y	42.2	-10.5	31.7	38.5	500
4804	V / 1.3	Z	41.2	-10.5	30.7	34.3	500
7206	H / 1.2	X	35.5	-10.5	25.0	17.8	500
7206	H / 1.0	Y	38.1	-10.5	27.6	24.0	500
7206	H / 1.2	Z	35.0	-10.5	24.5	16.8	500
7206	V / 1.3	X	37.9	-10.5	27.4	23.4	500
7206	V / 1.0	Y	34.0	-10.5	23.5	15.0	500
7206	V / 1.0	Z	35.4	-10.5	24.9	17.6	500
9608	H / 1.0	X	40.6	-10.5	30.1	*32.0	500
9608	H / 1.0	Y	40.6	-10.5	30.1	*32.0	500
9608	H / 1.0	Z	40.6	-10.5	30.1	*32.0	500
9608	V / 1.0	X	40.6	-10.5	30.1	*32.0	500
9608	V / 1.0	Y	40.6	-10.5	30.1	*32.0	500
9608	V / 1.0	Z	40.6	-10.5	30.1	*32.0	500
12010	H / 1.0	X	44.1	-10.5	33.6	*47.9	500
12010	H / 1.0	Y	44.1	-10.5	33.6	*47.9	500
12010	H / 1.0	Z	44.1	-10.5	33.6	*47.9	500
12010	V / 1.0	X	44.1	-10.5	33.6	*47.9	500
12010	V / 1.0	Y	44.1	-10.5	33.6	*47.9	500
12010	V / 1.0	Z	44.1	-10.5	33.6	*47.9	500
	The frequency range was scanned from 30 Mhz to 25 Ghz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements ( Minimum system sensitivity)						

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
<b>Customer:</b>	Symbol Technologies, Inc	<b>Job No.</b>	R-8060				
<b>Test Sample:</b>	Wireless Barcode Scanner	<b>FCC ID:</b>	H9PP470				
<b>Model No.:</b>	P470	<b>Serial No.</b>	N/A				
<b>Operating Mode:</b>	Continuously Transmitter 2.402 Ghz Signal						
<b>Technician:</b>	Dennis Cortes	<b>Date:</b>	June 3,1999				
<b>Notes:</b>	Test Distance: 3 Meters	Duty Cycle: 30%					
	Detector: Peak	Duty Cycle Correction: -10.5 dB					
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Average Limit
Mhz	(V/H) / Degrees	X / Y / Z	dBuv	dB	dBuV/m	UV/m	uV/m
14412	H / 1.0	X	41.5	-10.5	31.0	*35.5	500
14412	H / 1.0	Y	41.5	-10.5	31.0	*35.5	500
14412	H / 1.0	Z	41.5	-10.5	31.0	*35.5	500
14412	V / 1.0	X	41.5	-10.5	31.0	*35.5	500
14412	V / 1.0	Y	41.5	-10.5	31.0	*35.5	500
14412	V / 1.0	Z	41.5	-10.5	31.0	*35.5	500
16814	H / 1.0	X	46.5	-10.5	36.0	*63.1	500
16814	H / 1.0	Y	46.5	-10.5	36.0	*63.1	500
16814	H / 1.0	Z	46.5	-10.5	36.0	*63.1	500
16814	V / 1.0	X	46.5	-10.5	36.0	*63.1	500
16814	V / 1.0	Y	46.5	-10.5	36.0	*63.1	500
16814	V / 1.0	Z	46.5	-10.5	36.0	*63.1	500
19216	H / 1.0	X	54.9	-10.5	44.4	*166.0	500
19216	H / 1.0	Y	54.9	-10.5	44.4	*166.0	500
19216	H / 1.0	Z	54.9	-10.5	44.4	*166.0	500
19216	V / 1.0	X	54.9	-10.5	44.4	*166.0	500
19216	V / 1.0	Y	54.9	-10.5	44.4	*166.0	500
19216	V / 1.0	Z	54.9	-10.5	44.4	*166.0	500
21618	H / 1.0	X	55.5	-10.5	45.0	*177.8	500
21618	H / 1.0	Y	55.5	-10.5	45.0	*177.8	500
21618	H / 1.0	Z	55.5	-10.5	45.0	*177.8	500
21618	V / 1.0	X	55.5	-10.5	45.0	*177.8	500
21618	V / 1.0	Y	55.5	-10.5	45.0	*177.8	500
21618	V / 1.0	Z	55.5	-10.5	45.0	*177.8	500
24020	H / 1.0	X	56.3	-10.5	45.8	*195.0	500
24020	H / 1.0	Y	56.3	-10.5	45.8	*195.0	500
24020	H / 1.0	Z	56.3	-10.5	45.8	*195.0	500
24020	V / 1.0	X	56.3	-10.5	45.8	*195.0	500
24020	V / 1.0	Y	56.3	-10.5	45.8	*195.0	500
24020	V / 1.0	Z	56.3	-10.5	45.8	*195.0	500
	The frequency range was scanned from 30 Mhz to 25 Ghz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	* =Noise Floor Measurements ( Minimum system sensitivity)						

