


<b>Test Method:</b>	Spurious Case Radiated Emissions, 30 MHz to 8.5 GHz, Paragraph 2.1053						
<b>Customer:</b>	Symbol Technologies	<b>Job No.:</b>	R-8594-1				
<b>Test Sample:</b>	Hand-held scanner with RF transmitter.	<b>FCC ID:</b>	H9PPDT7532				
<b>Model No.:</b>	PDT7532	<b>Serial No.:</b>	N/A				
<b>Operating Mode</b>	Continuously transmitting at 837 MHz						
<b>Test Specification</b>	FCC Part 2, Paragraph 2.1053, Field Strength of Spurious Radiation						
<b>Technician:</b>	Peter Lananna	<b>Date:</b>	June 29, 2000				
<b>Notes:</b>	Test Distance: D=3 M; Limit in dBuV= 20 log{[(49.2 x P) <sup>1/2</sup> /D] x 10 <sup>6</sup> } - (43+10 log P); P=Power in Watts Detector: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Limit
MHz	(V/H) / Meters	Degrees	dBuV	dB	dBuV/m	uv/m	uv/m
30.00							16,596
530.5	V/1.1	180	38.0	1.7	39.7	96.6	
730.5	V/1.3	045	49.0	5.5	54.5	530.9	
739.0	V/1.3	045	51.0	5.6	56.6	676.1	
747.5	V/1.3	045	51.0	5.9	56.9	699.8	
1674.0	V/1.0	180	49.1	-2.8	46.3	206.5	
2511.0	V/1.0	180	61.7	3.8	65.5	1883.6	
3348.0	V/1.0	180	54.9	7.9	62.8	1380.4	
4185.0	V/1.0	180	41.6	10.2	51.8	389.0	
5022.0	V/1.0	180	44.6	3.7	48.3	260.0	
5859.0	V/1.0	180	36.0	5.5	41.5	118.9	
6696.0	V/1.0	180	36.0	10.8	46.8	218.8	
7533.0	V/1.0	180	36.0	10.0	46.0	199.5	
8370.0	V/1.0	180	36.0	10.3	46.3	206.5	
V							V
9000.0							16,596
The EUT was scanned from 30 MHz to 8.5 GHz							
The emissions observed from the EUT do not exceed the specified limits.							
All emissions not recorded were more than 20dB below the specified limit.							



**Retlif Testing Laboratories**

Retlif Job Number R-8594-1