

<u>APPLICANT</u> Symbol Technologies, Inc. One Symbol Plaza Holtsville, NY 11742	<u>Manufacturer</u> Symbol Technologies, Inc. One Symbol Plaza Holtsville, NY 11742
---	--

TEST SPECIFICATION: FCC Rules and Regulations Part 15, Subpart C

TEST PROCEDURE: FCC 15.249(a)

TEST SAMPLE DESCRIPTION

BRANDNAME: Symbol

MODEL: WWC1049 FCC ID: H9PWWC1049A

TYPE: Pulsed RF Transmitter

FREQUENCY RANGE: 916 MHz

POWER REQUIREMENTS: 3.6 VDC derived from Lithium rechargeable batteries,
P/N: 20-16228-09

TESTS PERFORMED

- 15.209(a) Radiated Emissions, Spurious Case
- 15.249(a) Radiated Emissions, Fundamental and Harmonics
- 15.249(c) Occupied Bandwidth

REPORT OF MEASUREMENTS

Applicant: Symbol Technologies, Inc..

Device: Pulsed RF Transmitter

FCC ID: H9PWWC1049A

Power Requirements: 3.6 VDC derived from Lithium rechargeable batteries, P/N: 20-16228-09

Applicable Rule Section: Part 15, Subpart C, Section 15.249

TEST RESULTS

- 15.249(a): Field strength of emissions from the intentional radiator operating in the 902 to 928 MHz frequency band did not exceed 50 mV/m average for the fundamental and 500 uV/m average for harmonics.
- 15.249(b): Field strength readings were recorded at a distance of three meters from the Intentional Radiator unless otherwise specified.
- 15.249(c): Emissions radiated outside the specified frequency band except for harmonics, were attenuated by at least 50dB or to the emissions limits of 15.209, whichever was the lesser attenuation.
- 15.249(d): All measurements were taken utilizing a peak detector. The peak field strength did not exceed the average limits under any condition of modulation.

GENERAL NOTES

1. All user accessible controls were adjusted to produce maximum emissions.
2. The unit operates in the band of 902 to 928 MHz band at a single frequency of 916 MHz.
3. The frequency range was scanned from 30 MHz to 9.2 GHz. All emissions not reported were more than 20dB below the specified limit.

EXHIBIT 4

Radiated Emissions, Spurious Case

Para. 15.209(a)

(Please see separate e-file attachment named RE Spur.doc)

EXHIBIT 4

Radiated Emissions, Fundamental & Harmonic

Para. 15.249(a)

(Please see separate e-file attachment named REFundHarm.doc)

EXHIBIT 4

Occupied Bandwidth

Para. 15.249(c)

(Please see separate e-file attachment named OccBw.pdf)

EQUIPMENT LISTS

Radiated Emissions, Spurious Case, 30MHz-9.2GHz Radiated Emissions, Fundamental and Harmonics, 916MHz

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
062	High Gain Horn Antenna	Microlab/FXR	1.7 GHz - 2.6 GHz	R638A	01/25/2000	01/25/2001
063	High Gain Horn Antenna	Microlab/FXR	2.6 GHz-3.95 GHz	S638A	01/26/2000	01/26/2001
064	High Gain Horn Antenna	Microlab/FXR	3.95 GHz - 5.85 GHz	H638A	01/26/2000	01/26/2001
065	High Gain Horn Antenna	Microlab/FXR	5.85 GHz - 8.2 GHz	C638A	01/26/2000	01/26/2001
066	High Gain Horn Antenna	Microlab/FXR	8.2 GHz - 12.4 GHz	X638A	01/26/2000	01/26/2001
067	Open Area Test Site	Retlif	3 Meter	RNY	10/15/1997	10/15/2000
133	Broadband Pre-Amplifier	Electro-Metrics	10 kHz - 1 GHz, 26dB	BPA-1000	06/13/2000	06/13/2001
141	Spectrum Analyzer	Hewlett Packard	100 Hz - 40 GHz	8566B	08/03/2000	02/03/2001
141A	Graphics Plotter	Hewlett Packard	N/A	7470A	03/08/2000	03/08/2001
141B	Quasi-Peak Adaptor	Hewlett Packard	100 Hz - 1 GHz	85650A	08/02/2000	02/02/2001
206B	6.0 dB Attenuator	Texscan	0 - 1.0 GHz	FP-50 - 6 dB	06/13/2000	06/13/2001
523	Biconilog	Electro-Mechanics	26 - 2000 MHz	3142B	06/08/2000	06/08/2001
543	Preamplifier	Hewlett Packard	1.0 GHz - 26.5 GHz	8449B	06/16/1999	06/16/2001