


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Symbol Technologies	Job No.		R-8706-1			
Test Sample:	Pulsed RF Transmitter	Paragraph:		15.249(a)			
Model No.:	WWC1049	FCC ID:		H9PWWC1049A			
Operating Mode:	Continuously Transmitting a 916 MHz Signal						
Technician:	Peter Lananna	Date:		September 12, 2000			
Notes:	Test Distance: 3 Meters Detector: Peak, passes Average limit.						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)/Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
916	H / 1.3	X	65.6	8.6	74.2	5128.6	50000
	H / 1.0	Y	67.1	8.6	75.7	6095.4	
	H / 2.0	Z	71.5	8.6	80.1	10115.8	
	V / 1.0	X	77.0	8.6	85.6	19054.6	
	V / 1.5	Y	73.4	8.6	82.0	12589.3	
916	V / 1.0	Z	67.0	8.6	75.6	6025.6	50000
1832	H / 1.0	X	40.0	-6.8	33.2	45.7*	500
	H / 1.0	Y	40.0	-6.8	33.2	45.7*	
	H / 1.0	Z	40.0	-6.8	33.2	45.7*	
	V / 1.0	X	40.0	-6.8	33.2	45.7*	
	V / 1.0	Y	40.0	-6.8	33.2	45.7*	
1832	V / 1.0	Z	40.0	-6.8	33.2	45.7*	500
2748	H / 1.0	X	39.0	-1.7	37.3	73.3*	500
	H / 1.0	Y	39.0	-1.7	37.3	73.3*	
	H / 1.0	Z	39.0	-1.7	37.3	73.3*	
	V / 1.0	X	39.0	-1.7	37.3	73.3*	
	V / 1.0	Y	39.0	-1.7	37.3	73.3*	
2748	V / 1.0	Z	39.0	-1.7	37.3	73.3*	500
3664	H / 1.0	X	38.0	-0.8	37.2	72.4*	500
	H / 1.0	Y	38.0	-0.8	37.2	72.4*	
	H / 1.0	Z	38.0	-0.8	37.2	72.4*	
	V / 1.0	X	38.0	-0.8	37.2	72.4*	
	V / 1.0	Y	38.0	-0.8	37.2	72.4*	
3664	V / 1.0	Z	38.0	-0.8	37.2	72.4*	500
4580	H / 1.0	X	38.0	-3.3	34.7	54.3*	500
	H / 1.0	Y	38.0	-3.3	34.7	54.3*	
	H / 1.0	Z	38.0	-3.3	34.7	54.3*	
	V / 1.0	X	38.0	-3.3	34.7	54.3*	
	V / 1.0	Y	38.0	-3.3	34.7	54.3*	
4580	V / 1.0	Z	38.0	-3.3	34.7	54.3*	500
The frequency range was scanned from 30 MHz to 9.2 GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
* = Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8706-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Symbol Technologies	Job No.:	R-8706-1				
Test Sample:	Pulsed RF Transmitter	Paragraph:	15.249(a)				
Model No.:	WWC1049	FCC ID:	H9PWWC1049A				
Operating Mode:	Continuously Transmitting a 916 MHz Signal						
Technician:	Peter Lananna	Date:	September 12, 2000				
Notes:	Test Distance: 3 Meters Detector: Peak, passes Average limit.						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
5496	H / 1.0	X	35.0	-3.1	31.9	39.4*	500
	H / 1.0	Y	35.0	-3.1	31.9	39.4*	
	H / 1.0	Z	35.0	-3.1	31.9	39.4*	
	V / 1.0	X	35.0	-3.1	31.9	39.4*	
	V / 1.0	Y	35.0	-3.1	31.9	39.4*	
5496	V / 1.0	Z	35.0	-3.1	31.9	39.4*	500
6412	H / 1.0	X	35.0	-0.1	34.9	55.6*	500
	H / 1.0	Y	35.0	-0.1	34.9	55.6*	
	H / 1.0	Z	35.0	-0.1	34.9	55.6*	
	V / 1.0	X	35.0	-0.1	34.9	55.6*	
	V / 1.0	Y	35.0	-0.1	34.9	55.6*	
6412	V / 1.0	Z	35.0	-0.1	34.9	55.6*	500
7328	H / 1.0	X	35.0	-1.9	33.1	45.2*	500
	H / 1.0	Y	35.0	-1.9	33.1	45.2*	
	H / 1.0	Z	35.0	-1.9	33.1	45.2*	
	V / 1.0	X	35.0	-1.9	33.1	45.2*	
	V / 1.0	Y	35.0	-1.9	33.1	45.2*	
7328	V / 1.0	Z	35.0	-1.9	33.1	45.2*	500
8244	H / 1.0	X	35.0	-0.5	34.5	53.1*	500
	H / 1.0	Y	35.0	-0.5	34.5	53.1*	
	H / 1.0	Z	35.0	-0.5	34.5	53.1*	
	V / 1.0	X	35.0	-0.5	34.5	53.1*	
	V / 1.0	Y	35.0	-0.5	34.5	53.1*	
8244	V / 1.0	Z	35.0	-0.5	34.5	53.1*	500
9160	H / 1.0	X	35.0	1.9	36.9	70.0*	500
	H / 1.0	Y	35.0	1.9	36.9	70.0*	
	H / 1.0	Z	35.0	1.9	36.9	70.0*	
	V / 1.0	X	35.0	1.9	36.9	70.0*	
	V / 1.0	Y	35.0	1.9	36.9	70.0*	
9160	V / 1.0	Z	35.0	1.9	36.9	70.0*	500
The frequency range was scanned from 30 MHz to 9.2 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8706-1
Retlif Job Number R-