

F C C - TEST REPORT

REPORT NO.: 25596B/1/400F

FCC – Test Report

Date: 2001-03-27

No. 25596B/1/400F

Page 2 of 10

FCC listed testlab
acc. to Section 2.948 of the FCC - Rules

in compliance with the requirements of
ANSI C63.4 - 1992

Product : Winged Outlaw -- 49 MHz Receiver

Model : 91219R49

Importer : ECHO TOYS LTD

Manufacturer : ECHO TOYS LTD

FCC – Test Report

No. 25596B/1/400F

Date: 2001-03-27

Page 3 of 10

TABLE OF CONTENTS

1. Cover sheet
2. Introduction
3. Table of Contents
4. Laboratory Report
5. Summary of Testresults
6. Test Equipment List
7. Radiated Emission Test procedure
8. Interference Radiation (Datasheet)
9. Cohere Plot at Fundamental Frequency
10. Notes for Radiation Measurement (acc. to ANSI C63.4 - 1992)

FCC – Test Report

No. 25596B/1/400F

Date: 2001-03-27

Page 4 of 10

LABORATORY - REPORT

APPLICANT: ECHO TOYS LTD
ADDRESS: 8 A&B, Block 1, Tai Ping Industrial Centre
57 Ting Kok Road
Taipo, NT
HONG KONG

DATE OF SAMPLE RECEIVED: 2001-03-05

DATE OF TESTING: 2001-03-27

DESCRIPTION OF SAMPLE:

Product: Winged Outlaw -- 49 MHz Receiver
Manufacturer: ECHO TOYS LTD
Model number: 91219R49
Rating: DC 6V ('AA' Size Battery x 4)
Country of Origin: P.R. CHINA

INVESTIGATIONS REQUESTED: Measurements to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B – 'Unintentional Radiators'

RESULTS: See the attached test sheets

CONCLUSIONS From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

Authorized Signature

Remark: Purpose of those tests in this report is to provide the applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under the FCC Equipment Authorization Program. The tests themselves are not Approval Tests

FCC – Test Report

No. 25596B/1/400F

Date: 2001-03-27

Page 5 of 10

Summary of Test Results

Interference Radiation:

Test result: O.K.
Test data: See attached data sheet

Interference Voltage:

Test result: N.A.
Test data: N.A.

PHOTOGRAPH OF THE SAMPLE



FCC – Test Report

Date: 2001-03-27

No. 25596B/1/400F

Page 6 of 10

TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Remark
Test Receiver	Rohde & Schwarz	ESH 3	863497/015	10KHz – 30MHz
Test Receiver	Rohde & Schwarz	ESVP	860688/022	25MHz – 1,300 MHz
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127	--	2 x 10A, 50Ω, 50μH 10KHz-30MHz
Antenna System	Schwarzbeck	BBA 9106 / UHALP 9107	--	30MHz – 1000MHz
Antenna Mast System	Schwarzbeck	AM9104	--	Max. 4 meters height
Spectrum Analyzer with Q. Peak	Tektronix	2712	B023006	9KHz – 1.8GHz
Interface for Spectrum 2712	Tektronix	TD3F14A	--	
Test Receiver	Rohde & Schwarz	ESH 3	892580/006	10KHz – 30MHz
Test Receiver	Rohde & Schwarz	ESVP	863512/012	25MHz – 1,300 MHz
Impulse Limiter	Rohde & Schwarz	ESH-3-Z2	--	
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127	--	2 x 10A, 50Ω, 50μH 10KHz-30MHz
Antenna System	Schwarzbeck	BBA 9106 / UHALP 9107	--	30MHz – 1000MHz
Signal Generator	Rohde & Schwarz	SWS 2	879113/42	100KHz – 1040 MHz
Digital Multimeter	Tektronix	DM2510G	DM- 2510GTW105 55	10KHz – 30MHz
Turntable with Controller	Drehtisch	DT312	--	φ120 cm


FCC – Test Report

No. 25596B/1/400F

Date: 2001-03-27

Page 7 of 10

Radiated Emission Testprocedure



Unintentional Radiators

Measurement of Radiated Emissions (30MHz-1000MHz)

Acc: FCC Part 15 Subpart B

IECC Ref: 25596B/1/400F
 Model: 91219R49
 Applicant: ECHO TOYS LTD
 Ser.Nr.: 1
 Set under test: Winged Outlaw
 Connected sets: -
 Operating mode: Power "On"

Test Equipment
 Receiver: ESVP Rohde & Schwarz
 Antenna: Schwarzbeck BBA 9106
 and UHALP 9107

1. Standby mode

Frequency (MHz)	Horz. Reading dB(μV)	Vert. Reading dB(μV)	Antenna Factor (dB)	Horiz. Test Result (μV/m)	Vert. Test Result (μV/m)	Limit (μV/m)
30	< 16	< 16	18.4	< 52.5	< 52.5	100.0
200	< 16	< 16	16.5	< 42.2	< 42.2	150.0
400	< 16	< 16	18.3	< 51.9	< 51.9	200.0
1000	< 16	< 16	26.5	< 133.4	< 133.4	500.0

2. Motor running mode (motor noise measurement)

Frequency (MHz)	Horz. Reading dB(μV)	Vert. Reading dB(μV)	Antenna Factor (dB)	Horiz. Test Result (μV/m)	Vert. Test Result (μV/m)	Limit (μV/m)
30	< 16	< 16	18.4	< 52.5	< 52.5	100.0
200	< 16	< 16	16.5	< 42.2	< 42.2	150.0
258	26	22	18.0	157.6	99.4	200.0
336	26	22	17.1	142.4	89.8	200.0
486	24	< 16	19.5	149.8	< 59.6	200.0
509	20	< 16	19.8	97.7	< 61.6	200.0
654	18	< 16	21.7	96.2	< 76.4	200.0
1000	< 16	< 16	26.5	< 133.4	< 133.4	500.0

Note: A further test was performed with the signal generator set at -60dBm at the fundamental frequency to cohere the missions as specified in section 12.1.1.1 of ANSI C63.4-1992. All emissions observed complies with the FCC limits (refer to the cohere plot on page 9).

Test result:

☒ O.K.

Date: _____

Operator: _____

Notes for Radiation Measurement

1. Measurement facility:

Measurement facility located at Fanling (Hong Kong), placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules.

2. Distance between the EUT and measuring antenna:

3 meters.

3. Measuring instrumentations:

Rohde & Schwarz ESVP Test Receiver (20 - 1300 MHz) with a CISPR weighting QP detector, 6 dB bandwidth set at 120 KHz.

4. Measuring antenna:

Broad-band antenna for the frequency range 30 - 300 MHz and frequency range 300 - 1000 MHz, connected with 10 meters coaxial cable. Cable loss of the coaxial cable included in the Antenna Factor for measurement data. The antennas are capable of measuring both horizontal and vertical polarizations.

5. Frequency range scanned:

The frequency range 30 - 1000 MHz has been scanned. Readings of the highest emissions relating to the limit were reported as above.

6. Arrangement of EUT:

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.

7. Measuring Procedure:

In **accordance** with the relevant sections of the American National Standards Institute (ANSI) C63.4-1992 'Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9KHz to 40GHz'.