



SGS-CSTC Standards
Technical Services Ltd.

1
Road, Shipai, Tianhe District, Guangzhou, China
Telephone: +86 (0) 20 3848 1001 Fax: +86 (0) 20 3848 1006
kent_hsu@sgs.com



FEDERAL COMMUNICATIONS COMMISSION
Registration number: 282399

Report No.: GLEMO040600337RFR
Page: 1 of 13
FCC ID: HAP91311R49

FCC TEST REPORT

Application No.: GLEMO040600337RFR
Applicant: ECHO TOYS LTD.
FCC ID: HAP91311R49
Equipment Under Test (EUT):
EUT Name: Sound Bouncer / Sound Jumper
Item No.: 91311
Serial No.: Not supplied by client
Standards: FCC PAR15 SUBPART B
Date of Receipt: 21 June 2004
Date of Test: 24 June 2004 & 05 July 2004
Date of Issue: 16 July 2004

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Kent Hsu
Laboratory Manager

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the SGS PRODUCT CERTIFICATION MARK.. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

All test results in this report can be traceable to National or International Standards.



**SGS-CSTC Standards
Technical Services Ltd.**

Report No.: GLEMO04060119RFR

Page: 2 of 13

2 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 1GHz)	FCC PART 15, SUBPART B: 2003	ANSI C63.4.: 2001	Class B	PASS



3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY.....	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF E.U.T.....	4
4.3 DETAILS OF E.U.T.	4
4.4 DESCRIPTION OF SUPPORT UNITS.....	4
4.5 STANDARDS APPLICABLE FOR TESTING	4
4.6 TEST LOCATION	4
4.7 TEST FACILITY	5
4.8 DEVIATION FROM STANDARDS	5
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	5
5 EQUIPMENTS USED DURING TEST	6
6 TEST RESULTS.....	7
6.1 RADIATED EMISSIONS, 30MHZ TO 1GHZ	7
6.1.1 E.U.T. Operation.....	7
6.1.2 Measurement Data	8
7 PHOTOGRAPHS.....	9
7.1 RADIATED EMISSION TEST SETUP	9
7.2 EUT CONSTRUCTIONAL DETAILS	10-13

4 General Information

4.1 Client Information

Applicant: ECHO TOYS LTD.
Address of Applicant: ROOM 1108, PENINSULA CENTRE, 67 MODY ROAD, TSIM SHA TSUI EAST, KOWLOON HONG KONG.

4.2 General Description of E.U.T.

EUT Name: Sound Bouncer / Sound Jumper
Item No.: 91311
Serial No.: Not supplied by client

4.3 Details of E.U.T.

Power Supply: 9V DC (1 x '6F22' Size Battery) for TX
6V DC (1 x 'TC105' Rechargeable Battery) for RX
Power Cord: None

4.4 Description of Support Units

None.

4.5 Standards Applicable for Testing

The customer requested FCC tests as a receiver for 49MHz Toys transmitter.
The standard used was FCC PART 15, SUBPART B, CLASS B (2003)

4.6 Test Location

All tests were performed at: -
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Safety & EMC Laboratory,
1/F, Building No. 1, Agriculture Machinery Materials Company Warehouse Ltd., Wushan
Road Shipai, Tianhe District, Guangzhou, China. P.C. 510630.
Tel: +86 20 3848 1001 Fax: +86 20 3848 1006
No tests were sub-contracted.

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP – Lab Code: 200611-0**
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0. Effective through December 31, 2004.
- **ACA**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.
- **VCCI**
The 3m Semi-anechoic chamber and Shielded Room (11.5m x 4m x 4m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1599 and C-1706 respectively.
Date of Registration: February 28, 2003. Valid until May 30, 2005
- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**
Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.
- **CNAL – LAB Code: L0141**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.
- **FCC – Registration No.: 282399**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP's accreditation, SGS-CSTC is an authorised test laboratory for the DoC process.
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.
- **Industry Canada (IC)**
The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5169.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

5 Equipments Used during Test

Radiated Emission Test in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi- Anechoic Chamber	Frankonia	N/A	N/A	16-02-2004	15-02-2005
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	05-11-2003	04-11-2004
3	EMI Test Software	Rohde & Schwarz	ES-K1	N/A	N/A	N/A
4	Coaxial cable	SGS	N/A	N/A	05-12-2003	04-12-2004
5	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	18-01-2004	17-01-2005
6	Horn Antenna	Rohde & Schwarz	HF906	100095	02-04-2004	01-04-2005
7	Spectrum Analyzer	Rohde & Schwarz	FSP30	100324	23-12-2003	22-12-2004
8	0.1-1300 MHz Pre-Amplifier	HP	8447DOPT 010	2944A06252	31-05-2003	30-05-2004

General Equipment						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	Temperature, Humidity & Barometer	Oregon Scientific	BA-888	EMC0001 to EMC0004	25-07-2003	24-07-2004
2	DMM	Fluke	73	70681569 or 70671122	23-07-2003	22-07-2004

6 Test Results

6.1 Radiated Emissions, 30MHz to 1GHz

Test Requirement:	FCC Part15 B
Test Method:	ANSI C63.4
Test Date:	24 June 2004
Frequency Range:	30MHz to 1GHz
Measurement Distance:	3m
Class:	Class B
Limit:	40.0 dB μ V/m between 30MHz & 88MHz 43.5 dB μ V/m between 88MHz & 216MHz 46.0 dB μ V/m between 216MHz & 960MHz 54.0 dB μ V/m zbove 960MHz
Detector:	Peak for pre-scan (120kHz resolution bandwidth) Quasi-Peak if maximised peak within 6dB of limit

6.1.1 E.U.T. Operation

Operating Environment:			
Temperature:	26.0 °C	Humidity:	57% RH Atmospheric Pressure: 1009 mbar
EUT Operation:	Test the EUT in On Mode.		

6.1.2 Measurement Data

An initial pre-scan was performed in peak detection mode. Quasi-Peak was performed at the frequencies with maximized peak emission were detected.

The following quasi-peak measurements were performed on the EUT on 24 June 2004:

Vertical:

Frequency (MHz)	Transducer (dB)	Receiver QP Reading (dBuV)	Receiver QP Level (dBuV)	Limit (dBuV)	Margin (dB)	Antenna High	Turntable Angle
172.800	15.2	8.3	23.5	43.5	20.0	1.00	232
327.063	17.0	19.5	36.5	46.0	9.5	2.00	98
463.688	18.4	13.8	32.2	46.0	13.8	2.15	125
557.063	20.5	15.1	35.6	46.0	10.4	2.65	325
624.125	22.4	11.3	33.7	46.0	12.3	1.00	210
636.187	22.4	17.5	39.9	46.0	6.1	1.00	234

Horizontal:

Frequency (MHz)	Transducer (dB)	Receiver QP Reading (dBuV)	Receiver QP Level (dBuV)	Limit (dBuV)	Margin (dB)	Antenna High	Turntable Angle
143.813	13.8	13.5	27.3	43.5	16.2	1.00	78
215.125	9.4	29.5	38.9	43.5	4.6	1.98	206
243.688	16.4	20.3	36.7	46.0	9.3	1.65	125
257.438	17.2	12.9	30.1	46.0	15.9	2.15	64
369.125	18.9	9.5	28.4	46.0	17.6	3.21	158
502.875	18.7	21.6	40.3	46.0	5.7	2.04	191

1. All readings are Quasi-Peak values.

2. Transducer = Antenna Factor + Cable Loss.

3. 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.