FCC ID: HBO4880

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]- $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	3.62	2.301	4±1	5	3.162	<5	0.98020	3.00	YES
	2.441	4.03	2.529	4±1	5	3.162	<5	0.98813	3.00	YES
	2.480	4.48	2.805	4±1	5	3.162	<5	0.99599	3.00	YES
π/4- DQPSK	2.402	3.43	2.203	4±1	5	3.162	<5	0.98020	3.00	YES
	2.441	4.22	2.642	4±1	5	3.162	<5	0.98813	3.00	YES
	2.480	4.71	2.958	4±1	5	3.162	<5	0.99599	3.00	YES
8DPSK	2.402	3.19	2.084	4±1	5	3.162	<5	0.98020	3.00	YES
	2.441	4.21	2.636	4±1	5	3.162	<5	0.98813	3.00	YES
	2.480	4.74	2.979	4±1	5	3.162	<5	0.99599	3.00	YES

Conclusion:

For the max result: 0.99599≤ 3.0 for 1-g SAR, No SAR is required.

Jason chen

Signature: Date: 2017-04-27

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.