

RF EXPOSURE EVALUATION

EUT Specification

EUT	Wireless Subwoofer
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	-2.85dBm(0.52mW)
Antenna gain	0dBi (declared by manufacturer)
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $Pd=(Pout \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd = Power density in mW/cm^2

$Pout$ =output power to antenna in Mw

G = gain of antenna in linear scale

$\pi=3.1416$

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
GFSK						
Low	2402.00	-4.10	± 0.1	0.40	$7.92e-5$	1
Middle	2441.00	-4.39	± 0.1	0.37	$7.41e-5$	1
High	2480.00	-4.61	± 0.1	0.35	$7.04e-5$	1
$\pi/4$-DQPSK						
Low	2402.00	-3.49	± 0.1	0.46	$9.11e-5$	1
Middle	2441.00	-3.69	± 0.1	0.44	$8.70e-5$	1
High	2480.00	-3.93	± 0.1	0.41	$8.24e-5$	1
8DPSK						
Low	2402.00	-2.85	± 0.1	0.53	$1.06e-4$	1
Middle	2441.00	-3.14	± 0.1	0.50	$9.88e-5$	1
High	2480.00	-3.31	± 0.1	0.48	$9.50e-5$	1