



<b>Prüfbericht-Nr.:</b> <i>Test Report No.:</i>	<b>50082008 001</b>	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	<b>164087995</b>	<b>Seite 1 von 96</b> <i>Page 1 of 96</i>	
<b>Kunden-Referenz-Nr.:</b> <i>Client Reference No.:</i>	<b>N/A</b>	<b>Auftragsdatum:</b> <i>Order date:</i>	<b>16.03.2017</b>		
<b>Auftraggeber:</b> <i>Client:</i>	<b>SHENZHEN FENDA TECHNOLOGY CO., LTD.</b> Fenda Hi-Tech Park, Zhoushi Road, Shiyuan Town, Baoan District, Shenzhen City, Guangdong, China				
<b>Prüfgegenstand:</b> <i>Test item:</i>	<b>Portable Bluetooth Stereo Speaker</b>				
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	<b>NS-CSPBTWP1</b>				
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	<b>FCC/IC Certification</b>				
<b>Prüfgrundlage:</b> <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 15: Subpart B Section 15.109 RSS-247 Issue 1 May 2015 ICES-003 Issue 6 January 2016	CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart B Section 15.107 FCC KDB Publication 447498 D01 v06 RSS-Gen Issue 4 November 2014 RSS-102 Issue 5 March 2015			
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	<b>16.03.2017</b>				
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	<b>A000513350-001, A000513350-002, A000513350-003, A000513350-004</b>				
<b>Prüfzeitraum:</b> <i>Testing period:</i>	<b>01.04.2017 - 01.06.2017</b>				
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	<b>Shenzhen EMTEK Co., Ltd.</b>				
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	<b>TÜV Rheinland (Shenzhen) Co., Ltd.</b>				
<b>Prüfergebnis*:</b> <i>Test result*:</i>	<b>Pass</b>				
<b>geprüft von / tested by:</b>			<b>kontrolliert von / reviewed by:</b>		
<b>03-06-2017</b>	<b>Andy Yan/Project Manager</b>		<b>03-06-2017</b>	<b>Owen Tian/Technical Certifier</b>	
<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>	<b>Unterschrift</b> <i>Signature</i>
<b>Sonstiges / Other:</b>	<b>FCC ID: HBONSCSPBTWP1</b> <b>IC: 10550A-NSCSPBTWP1</b>				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	<b>Prüfmuster vollständig und unbeschädigt</b> <i>Test item complete and undamaged</i>				
<b>* Legende:</b>	<b>1 = sehr gut</b> P(ass) = entspricht o.g. Prüfgrundlage(n)	<b>2 = gut</b>	<b>3 = befriedigend</b> F(all) = entspricht nicht o.g. Prüfgrundlage(n)	<b>4 = ausreichend</b> N/A = nicht anwendbar	<b>5 = mangelhaft</b> N/T = nicht getestet
<b>Legend:</b>	<b>1 = very good</b> P(ass) = passed a.m. test specification(s)	<b>2 = good</b>	<b>3 = satisfactory</b> F(all) = failed a.m. test specification(s)	<b>4 = sufficient</b> N/A = not applicable	<b>5 = poor</b> N/T = not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

v04

## TEST SUMMARY

**5.1.1 ANTENNA REQUIREMENT***RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 20dB BANDWIDTH AND 99% BANDWIDTH***RESULT: Pass***5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100KHZ BANDWIDTH***RESULT: Pass***5.1.5 SPURIOUS EMISSION***RESULT: Pass***5.1.6 FREQUENCY SEPARATION***RESULT: Pass***5.1.7 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.8 TIME OF OCCUPANCY***RESULT: Pass***5.1.9 CONDUCTED EMISSIONS***RESULT: Pass***5.1.10 RADIATED EMISSION***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

## Contents

<b>1.</b>	<b>GENERAL REMARKS .....</b>	<b>5</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>5</b>
<b>2.</b>	<b>TEST SITES .....</b>	<b>5</b>
<b>2.1</b>	<b>TEST FACILITIES .....</b>	<b>5</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>6</b>
<b>2.3</b>	<b>TRACEABILITY .....</b>	<b>7</b>
<b>2.4</b>	<b>CALIBRATION .....</b>	<b>7</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY.....</b>	<b>7</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA.....</b>	<b>7</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING.....</b>	<b>8</b>
<b>3.</b>	<b>GENERAL PRODUCT INFORMATION .....</b>	<b>9</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>9</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>9</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>11</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>11</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS .....</b>	<b>11</b>
<b>4.</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>12</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION.....</b>	<b>12</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE .....</b>	<b>12</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>12</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>12</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>13</b>
<b>5.</b>	<b>TEST RESULTS .....</b>	<b>15</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>	<b>15</b>
5.1.1	<i>Antenna Requirement .....</i>	<i>15</i>
5.1.2	<i>Maximum Peak Conducted Output Power.....</i>	<i>16</i>
5.1.3	<i>20dB Bandwidth and 99% Bandwidth.....</i>	<i>17</i>
5.1.4	<i>Conducted Spurious Emissions measured in 100kHz Bandwidth.....</i>	<i>18</i>
5.1.5	<i>Spurious Emission .....</i>	<i>27</i>
5.1.6	<i>Frequency Separation.....</i>	<i>72</i>
5.1.7	<i>Number of hopping frequency.....</i>	<i>73</i>
5.1.8	<i>Time of Occupancy .....</i>	<i>74</i>
5.1.9	<i>Conducted emissions.....</i>	<i>75</i>
5.1.10	<i>Radiated Emission.....</i>	<i>80</i>
<b>6.</b>	<b>SAFETY HUMAN EXPOSURE .....</b>	<b>93</b>
<b>6.1</b>	<b>RADIO FREQUENCY EXPOSURE COMPLIANCE.....</b>	<b>93</b>
6.1.1	<i>Electromagnetic Fields.....</i>	<i>93</i>
<b>7.</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP .....</b>	<b>94</b>

**Prüfbericht - Nr.: 50082008 001**  
*Test Report No.*

**Seite 4 von 96**  
*Page 4 of 96*

<b>8.</b>	<b>LIST OF TABLES .....</b>	<b>96</b>
<b>9.</b>	<b>LIST OF PHOTOGRAPHS .....</b>	<b>96</b>

## 1. General Remarks

### 1.1 Complementary Materials

None.

## 2. Test Sites

### 2.1 Test Facilities

Shenzhen EMTEK Co., Ltd.

**(FCC Registration No.: 709623)**

**(Test site Industry Canada No.: 4480A-2)**

Bldg 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, P.R. China

The tests at the test site have been conducted under the supervision of a TÜV engineer.

## 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
<b>Transmitter spurious emissions</b>				
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	2018-05-16
Loop Antenna	Schwarzbeck	FMZB 1519	1519-012	2018-05-16
Cable	H+B	3M SF104-26.5	295838/4	2018-05-28
Cable	H+B	6M SF104-26.5	295840/4	2018-05-28
Pre-Amplifier	HP	8447F	2944A07999	2018-05-16
Bilog Antenna	Schwarzbeck	VULB9163	142	2018-05-28
Cable	Schwarzbeck	AK9513	ACRX1	2018-05-16
Cable	Rosenberger	N/A	FP2RX2	2018-05-16
Cable	Schwarzbeck	AK9513	CRPX1	2018-05-28
Cable	Schwarzbeck	AK9513	CRRX2	2018-05-28
Pre-Amplifier	A.H.	PAM-0126	1415261	2018-05-16
Horn Antenna	Schwarzbeck	BBHA 9120	707	2018-05-28
Pre-Amplifier	A.H.	PAM-0126	1415261	2018-05-16
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA91703 99	2018-05-16
EMI Test Receiver	Rohde & Schwarz	FSV40	132.1- 3008K39- 100967-AP	2018-05-16
Pre-Amplifier	Lunar EM	LNA26G40-40	J101313102 8001	2018-05-16
Horn Antenna	AHS/USA	SAS-573	184	2018-05-16
Cable	H+B	0.5M SF104- 26.5	289147/4	2018-05-16
Cable	H+B	3M SF104-26.5	295838/4	2018-05-16
Cable	H+B	6M SF104-26.5	295840/4	2018-05-16
<b>Radio Spectrum Test</b>				
EMI Test Receiver	Rohde & Schwarz	ESCI	101045	2017-05-16
Vector Signal Generator	Agilent	N5182B	My53050553	2017-05-28
Analog Signal Generator	Agilent	N5171B	My53050878	2017-05-28
Signal Analyzer	Agilent	N9010A	My53470879	2017-05-28
Power Meter	Agilent	PS-X10-100	N/A	2017-05-28
Temp. / Humidity Chamber	Kingson	THS-M1	242	2017-05-28
<b>Conducted Emission</b>				
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	2017-05-16
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	2017-05-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	2017-05-16
Voltage Probe	Rohde & Schwarz	TK9416	N/A	2017-05-16
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	2017-05-16
50Ω Coaxial Switch	Anritsu	MP59B	M20531	2017-05-16

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

**Prüfbericht - Nr.: 50082008 001***Test Report No.***Seite 8 von 96***Page 8 of 96*

## 2.7 Status of Facility Used for Testing

Shenzhen EMTEK Co., Ltd. test facility located at Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.



## 3. General Product Information

### 3.1 Product Function and Intended Use

The EUT is portable Bluetooth stereo speaker used for audio entertainment in house or similar environment. It operates at 2.4GHz ISM frequency band. For details refer to the User Manual and Circuit Diagram.

### 3.2 Ratings and System Details

**Table 3: Technical Specification of Bluetooth**

Technical Specification	Value
Kind of Equipment	Portable Bluetooth Stereo Speaker
Type Designation	NS-CSPBTWP1
FCC ID	HBONSCSPBTWP1
IC	10550A-NSCSPBTWP1
Operating Frequency band	2402 – 2480MHz
Channel separation	1MHz
Extreme Temperature Range	-10~+55°C
Operation Voltage	DC 18V, 3A (via AC/DC adapter)
Modulation	FHSS, GFSK, 8DPSK, $\pi/4$ DQPSK
Bluetooth version	3.0
Antenna Gain	3.1dBi

**Table 4: RF channel and frequency of Bluetooth**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402.00	21	2423.00	42	2444.00	63	2465.00
1	2403.00	22	2424.00	43	2445.00	64	2466.00
2	2404.00	23	2425.00	44	2446.00	65	2467.00
3	2405.00	24	2426.00	45	2447.00	66	2468.00
4	2406.00	25	2427.00	46	2448.00	67	2469.00
5	2407.00	26	2428.00	47	2449.00	68	2470.00
6	2408.00	27	2429.00	48	2450.00	69	2471.00
7	2409.00	28	2430.00	49	2451.00	70	2472.00
8	2410.00	29	2431.00	50	2452.00	71	2473.00
9	2411.00	30	2432.00	51	2453.00	72	2474.00
10	2412.00	31	2433.00	52	2454.00	73	2475.00
11	2413.00	32	2434.00	53	2455.00	74	2476.00

**Produkte***Products***Prüfbericht - Nr.: 50082008 001****Seite 10 von 96***Test Report No.**Page 10 of 96*

12	2414.00	33	2435.00	54	2456.00	75	2477.00
13	2415.00	34	2436.00	55	2457.00	76	2478.00
14	2416.00	35	2437.00	56	2458.00	77	2479.00
15	2417.00	36	2438.00	57	2459.00	78	2480.00
16	2418.00	37	2439.00	58	2460.00		
17	2419.00	38	2440.00	59	2461.00		
18	2420.00	39	2441.00	60	2462.00		
19	2421.00	40	2442.00	61	2463.00		
20	2422.00	41	2443.00	62	2464.00		

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On
  - 1. Bluetooth mode
    - a. Transmitting
      - i. Low Channel
      - ii. Middle Channel
      - iii. High Channel
    - b. Receiving
- B. AUX input
- C. Standby
- D. Off

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

### 3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.4: 2014 & ANSI C63.10: 2013.

### 4.3 Special Accessories and Auxiliary Equipment

The EUT was tested together with the following accessories:


Description	Manufacturer	Part No.	Rating
AC/DC adapter	MASS POWER	NBS65A180300M2	Input: AC 100-240V, 50/60Hz, 1.5A; Output: DC 18V, 3A



### 4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



**Diagram of Measurement Equipment Configuration for Conduction Measurement**

**Diagram of Measurement Equipment Configuration for Transmitter Measurement**


## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:****Pass**

Test standard : Part 15.203  
RSS-Gen Clause 8.3  
Limit The use of antennas with directional gains that do not exceed 6dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 3.1dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

## 5.1.2 Maximum Peak Conducted Output Power

**RESULT:**
**Pass**

Test date : 2017-04-01  
 Test standard : FCC Part 15.247(b)(1)  
                   : FCC Part 15.247(b)(3)  
                   : RSS-247 clause 5.4(2)  
                   : RSS-247 clause 5.4(4)  
 Basic standard : ANSI C63.10: 2013  
                   : Clause 9.1 of KDB 558074 v03r05  
 Limit : 125mW, 1W  
 Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ Middle/ High  
 Operation Mode : A.1.a  
 Ambient temperature : 25°C  
 Relative humidity : 50%  
 Atmospheric pressure : 101kPa

**Table 5: Test result of Peak Output Power of Bluetooth (BDR mode)**

Channel	Channel Frequency (MHz)	Peak Output Power	Limit	e.i.r.p.	Limit
		(dBm)	(dBm)	(dBm)	(dBm)
Low Channel	2402	1.428	21	4.528	36
Middle Channel	2441	0.823	21	3.923	36
High Channel	2480	2.191	21	5.291	36

**Table 6: Test result of Peak Output Power of Bluetooth (EDR mode)**

Channel	Channel Frequency (MHz)	Peak Output Power	Limit	e.i.r.p.	Limit
		(dBm)	(dBm)	(dBm)	(dBm)
Low Channel	2402	-0.254	21	2.846	36
Middle Channel	2441	-2.520	21	0.580	36
High Channel	2480	-1.204	21	1.896	36



**Prüfbericht - Nr.: 50082008 001**

Test Report No.

Seite 17 von 96

Page 17 of 96

**5.1.3 20dB Bandwidth and 99% Bandwidth****RESULT:****Pass**

Date of testing : 2017-04-01  
Test standard : FCC Part 15.247(a)(1)  
RSS-210 clause 5.1(2)  
RSS-Gen clause 6.6  
Basic standard : ANSI C63.10: 2013  
Clause 8 of KDB 558074 v03r05  
Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ Middle/ High  
Operation Mode : A.1.a  
Ambient temperature : 25°C  
Relative humidity : 50%  
Atmospheric pressure : 101kPa

**Table 7: Test result of 20dB & 99% Bandwidth of BDR mode**

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	2402	0.912	0.838
Mid Channel	2441	0.888	0.836
High Channel	2480	0.889	0.833

**Table 8: Test result of 20dB & 99% Bandwidth of EDR mode**

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	2402	1.211	1.149
Mid Channel	2441	1.227	1.263
High Channel	2480	1.239	1.277

**Prüfbericht - Nr.: 50082008 001**

Test Report No.

Seite 18 von 96

Page 18 of 96

**5.1.4 Conducted Spurious Emissions measured in 100kHz Bandwidth****RESULT:****Pass**

Date of testing : 2017-04-01  
Test standard : FCC part 15.247(d)  
RSS-247 clause 5.5  
Basic standard : ANSI C63.10: 2013  
Limit : 20dB (below that in the 100kHz bandwidth within  
the band that contains the highest level of the  
desired power);  
Kind of test site : Shield room


**Test setup**


Test Channel : Low/ Middle/ High  
Operation mode : A.1.a  
Ambient temperature : 25°C  
Relative humidity : 50%  
Atmospheric pressure : 101kPa

For details refer to following test plot.

### Test Plot of Conducted spurious emissions measured in 100kHz Bandwidth of BDR mode Low Channel



**Middle Channel**


**High Channel**


**Band Edge**



## Test Plot of Conducted spurious emissions measured in 100kHz Bandwidth of EDR mode

### Low Channel



**Middle Channel**




**High Channel**


**Band Edge**


**Prüfbericht - Nr.: 50082008 001**

Test Report No.

**Seite 27 von 96**

Page 27 of 96

### 5.1.5 Spurious Emission

**RESULT:****Pass**

Date of testing : 2017-04-17 to 2017-04-19  
Test standard : FCC part 15.247(d)  
RSS-Gen  
Basic standard : ANSI C63.10: 2013  
Clause 11 of KDB 558074 v03r05  
Limits : FCC part 15.209(a)  
Kind of test site : 3m Semi-Anechoic Chamber & Anechoic Chamber

**Test setup**

Test Channel : Low/ Middle/ High  
Operation mode : A.1.a  
Ambient temperature : 23°C  
Relative humidity : 48%  
Atmospheric pressure : 101kPa

For details refer to following test plot.


## Test Plot of Spurious Emission

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



### Radiated Emission Measurement

File :TUV Data :#2283 Date: 2017/04/19



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: GFSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		159.0100	46.20	-15.22	30.98	43.50	-12.52	QP		
2		282.2000	49.44	-10.48	38.96	46.00	-7.04	QP		
3	*	344.2800	50.16	-9.20	40.96	46.00	-5.04	QP		
4		639.1600	39.46	-1.77	37.69	46.00	-8.31	QP		
5		701.2400	41.51	-1.97	39.54	46.00	-6.46	QP		
6	!	762.3500	40.73	-0.58	40.15	46.00	-5.85	QP		


\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUV\Data :#2283

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: *Vertical* Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: GFSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		454.8600	40.55	-7.54	33.01	46.00	-12.99	QP		
2	!	578.0500	44.46	-3.92	40.54	46.00	-5.46	QP		
3	*	664.3800	42.67	-1.74	40.93	46.00	-5.07	QP		
4		676.0200	42.16	-2.17	39.99	46.00	-6.01	QP		
5		701.2400	40.65	-1.97	38.68	46.00	-7.32	QP		
6		914.6400	36.41	1.75	38.16	46.00	-7.84	QP		

\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUVData :#2282

Page: 1


Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


**Radiated Emission Measurement**

File :TUV

Data :#2284

Date: 2017/04/19



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: ( RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Bluetooth Stereo Speaker

M/N: NS-CSPBTWP1

Mode: GFSK(2441MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	!	282.2000	50.58	-10.48	40.10	46.00	-5.90	QP			
2		307.4200	49.65	-9.92	39.73	46.00	-6.27	QP			
3	*	344.2800	51.04	-9.20	41.84	46.00	-4.16	QP			
4		639.1600	41.09	-1.77	39.32	46.00	-6.68	QP			
5		701.2400	41.63	-1.97	39.66	46.00	-6.34	QP			
6		762.3500	40.44	-0.58	39.86	46.00	-6.14	QP			

\*:Maximum data    x:Over limit    !:over margin

Operator: XF


File :TUVData :#2284

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File :TUV Data :#2285 Date: 2017/04/19



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: GFSK(2441MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		51.3400	44.67	-11.73	32.94	40.00	-7.06	QP		
2		88.2000	50.76	-13.28	37.48	43.50	-6.02	QP		
3	!	578.0500	44.85	-3.92	40.93	46.00	-5.07	QP		
4		614.9100	42.08	-2.36	39.72	46.00	-6.28	QP		
5	!	639.1600	42.01	-1.77	40.24	46.00	-5.76	QP		
6	*	676.0200	43.79	-2.17	41.62	46.00	-4.38	QP		

\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUVData :#2285

Page: 1


Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File :TUV

Data :#2287

Date: 2017/04/19



Site 3m Chamber #1

 Polarization: *Horizontal*

Temperature: 22 C

Limit: ( RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Bluetooth Stereo Speaker

M/N: NS-CSPBTWP1

Mode: GFSK(2480MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		282.2000	45.04	-10.48	34.56	46.00	-11.44	QP		
2		344.2800	43.27	-9.20	34.07	46.00	-11.93	QP		
3		618.7900	36.07	-2.00	34.07	46.00	-11.93	QP		
4		639.1600	37.01	-1.77	35.24	46.00	-10.76	QP		
5		910.7600	34.18	1.73	35.91	46.00	-10.09	QP		
6	*	946.6500	34.86	1.43	36.29	46.00	-9.71	QP		

\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUVData :#2287


Page: 1



Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File:TUV Data:#2286 Date:2017/04/19



Site: 3m Chamber #1 Polarization: *Vertical* Temperature: 22 C  
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: GFSK(2480MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		52.3100	44.43	-11.84	32.59	40.00	-7.41	QP		
2		88.2000	49.39	-13.28	36.11	43.50	-7.39	QP		
3		578.0500	41.69	-3.92	37.77	46.00	-8.23	QP		
4	*	589.6900	42.51	-3.48	39.03	46.00	-6.97	QP		
5		614.9100	38.87	-2.36	36.51	46.00	-9.49	QP		
6		946.6500	35.76	1.43	37.19	46.00	-8.81	QP		

\*:Maximum data x:Over limit !:over margin

Operator: XF


File:TUVData:#2286

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File :TUV Data :#2288 Date: 2017/04/19



Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: 8DPSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	344.2800	50.92	-9.20	41.72	46.00	-4.28	QP			
2		651.7700	39.92	-1.19	38.73	46.00	-7.27	QP			
3		676.0200	40.34	-2.17	38.17	46.00	-7.83	QP			
4		799.2100	40.00	-0.22	39.78	46.00	-6.22	QP			
5		861.2900	39.91	-0.29	39.62	46.00	-6.38	QP			
6	!	910.7600	38.72	1.73	40.45	46.00	-5.55	QP			


\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUVData :#2288

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: 8DPSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		52.3100	44.32	-11.84	32.48	40.00	-7.52	QP		
2	*	88.2000	49.56	-13.28	36.28	43.50	-7.22	QP		
3		454.8600	41.78	-7.54	34.24	46.00	-11.76	QP		
4		578.0500	41.38	-3.92	37.46	46.00	-8.54	QP		
5		589.6900	42.20	-3.48	38.72	46.00	-7.28	QP		
6		914.6400	33.96	1.75	35.71	46.00	-10.29	QP		


\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUVData :#2289

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


**Radiated Emission Measurement**


Site: 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C  
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: 8DPSK(2441MHz)  
 Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	344.2800	46.42	-9.20	37.22	46.00	-8.78	QP		
2 *	434.4900	46.45	-7.50	38.95	46.00	-7.05	QP		
3	639.1600	37.86	-1.77	36.09	46.00	-9.91	QP		
4	651.7700	38.36	-1.19	37.17	46.00	-8.83	QP		
5	899.1200	37.68	1.14	38.82	46.00	-7.18	QP		
6	910.7600	35.58	1.73	37.31	46.00	-8.69	QP		


\*:Maximum data x:Over limit !:over margin

Operator: XF

File : TUVData #2291

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: 8DPSK(2441MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		47.4600	42.52	-11.48	31.04	40.00	-8.96	QP		
2		88.2000	50.76	-13.28	37.48	43.50	-6.02	QP		
3		578.0500	41.53	-3.92	37.61	46.00	-8.39	QP		
4		589.6900	40.76	-3.48	37.28	46.00	-8.72	QP		
5		614.9100	39.82	-2.36	37.46	46.00	-8.54	QP		
6	*	910.7600	39.48	1.73	41.21	46.00	-4.79	QP		

\*:Maximum data x:Over limit !:over margin

Operator: XF


File :TUVData #2290

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File :TUV Data :#2292 Date: 2017/04/19



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode: 8DPSK(2480MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		282.2000	49.94	-10.48	39.46	46.00	-6.54	QP			
2		307.4200	48.99	-9.92	39.07	46.00	-6.93	QP			
3		319.0600	48.35	-10.06	38.29	46.00	-7.71	QP			
4	*	344.2800	50.81	-9.20	41.61	46.00	-4.39	QP			
5		618.7900	36.44	-2.00	34.44	46.00	-11.56	QP			
6		701.2400	35.85	-1.97	33.88	46.00	-12.12	QP			

\*:Maximum data x:Over limit !:over margin

Operator: XF

File :TUVData :#2292

Page: 1


Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


**Radiated Emission Measurement**

File :TUV

Data :#2293

Date: 2017/04/19



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: ( RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Bluetooth Stereo Speaker

M/N: NS-CSPBTWP1

Mode: 8DPSK(2480MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		52.3100	44.28	-11.84	32.44	40.00	-7.56	QP		
2		88.2000	49.30	-13.28	36.02	43.50	-7.48	QP		
3		123.1200	45.16	-14.75	30.41	43.50	-13.09	QP		
4		466.5000	41.87	-7.51	34.36	46.00	-11.64	QP		
5		578.0500	41.21	-3.92	37.29	46.00	-8.71	QP		
6	*	589.6900	42.93	-3.48	39.45	46.00	-6.55	QP		


\*:Maximum data    x:Over limit    !:over margin

Operator: XF

File :TUVData :#2293

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.entek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C  
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:GFSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		16844.00	39.22	15.89	55.11	74.00	-18.89	peak			
2	*	16844.00	23.41	15.89	39.30	54.00	-14.70	AVG			

\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2382

Page: 1



Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.entek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**

File :TUV

Data :#2381

Date: 17/04/17/

80.0 dBuV/m



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Bluetooth Stereo Speaker

M/N: NS-CSPBTWP1

Mode:GFSK(2402MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		7205.000	50.83	2.71	53.54	74.00	-20.46	peak			
2	*	7205.000	34.39	2.71	37.10	54.00	-16.90	AVG			


\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2381

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 22 C  
 Limit: ( RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:GFSK(2441MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		16878.00	38.95	16.14	55.09	74.00	-18.91	peak			
2	*	16878.00	23.56	16.14	39.70	54.00	-14.30	AVG			


\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2384

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong 518052 P.R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C  
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:GFSK(2441MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		16827.00	39.16	15.78	54.94	74.00	-19.06	peak			
2	*	16827.00	22.62	15.78	38.40	54.00	-15.60	AVG			


\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2383

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C  
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:GFSK(2480MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		16861.00	38.95	16.03	54.98	74.00	-19.02	peak			
2	*	16861.00	23.17	16.03	39.20	54.00	-14.80	AVG			

\*:Maximum data x:Over limit !:over margin

Operator:


File :TUVData :#2386

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4283 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File :TUV Data :#2385 Date: 17/04/17/



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:GFSK(2480MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		17490.00	36.99	17.67	54.66	74.00	-19.34	peak			
2	*	17490.00	20.83	17.67	38.50	54.00	-15.50	AVG			

\*:Maximum data x:Over limit !:over margin

Operator:


File :TUVData :#2385

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong 518052 P.R. China  
 www.entek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**

File :TUV Data :#2391 Date: 17/04/17



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:8DPSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		15280.00	41.93	11.78	53.71	74.00	-20.29	peak			
2	*	15280.00	24.92	11.78	36.70	54.00	-17.30	AVG			


\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2391

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


**Radiated Emission Measurement**


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C  
 Limit: ( RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %  
 EUT: Bluetooth Stereo Speaker  
 M/N: NS-CSPBTWP1  
 Mode:8DPSK(2402MHz)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		15365.00	41.89	11.57	53.46	74.00	-20.54	peak			
2	*	15365.00	27.03	11.57	38.60	54.00	-15.40	AVG			

\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2392

Page: 1

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**

File :TUV

Data :#2390

Date: 17/04/17/

80.0 dBuV/m



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: ( RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Bluetooth Stereo Speaker

M/N: NS-CSPBTWP1

Mode:8DPSK(2441MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		17252.00	36.99	17.34	54.33	74.00	-19.67	peak			
2	*	17252.00	26.28	17.34	43.62	54.00	-10.38	AVG			

\*:Maximum data x:Over limit !:over margin

Operator:

File :TUVData :#2390

Page: 1