

Test Model

Conducted Spurious RF Conducted Emission

Channel 78: 2480MHz

8DPSK




Test Model

Band-edge Conducted Emissions

Channel 78: 2480MHz

8DPSK




Test Model

Maximum Conducted Level RBW=100kHz

Hopping

8DPSK




Test Model

Conducted Spurious RF Conducted Emission

Hopping

8DPSK




Test Model

Band-edge Conducted Emissions

Hopping

8DPSK




Test Model

Band-edge Conducted Emissions

Hopping

8DPSK



9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V/m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V/m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);


Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission below 1GHz (30MHz to 1GHz)




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode:BT DH1 2402MHz
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		64.9200	36.06	-13.51	22.55	40.00	-17.45			QP
2		139.6100	31.03	-15.60	15.43	43.50	-28.07			QP
3		200.7200	30.86	-11.47	19.39	43.50	-24.11			QP
4		684.7500	30.16	-1.22	28.94	46.00	-17.06			QP
5	*	846.7400	30.20	0.90	31.10	46.00	-14.90			QP
6		984.4800	29.24	3.63	32.87	54.00	-21.13			QP




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT DH1 2480MHz
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		54.2500	33.56	-11.46	22.10	40.00	-17.90	QP		
2		139.6100	32.96	-15.60	17.36	43.50	-26.14	QP		
3		200.7200	36.51	-11.47	25.04	43.50	-18.46	QP		
4	*	728.4000	34.58	-0.58	34.00	46.00	-12.00	QP		
5		832.1900	30.92	0.62	31.54	46.00	-14.46	QP		
6		994.1800	28.48	3.84	32.32	54.00	-21.68	QP		




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT 2DH1 2402MHz
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		63.9500	35.23	-13.37	21.86	40.00	-18.14	QP		
2		138.6400	31.62	-15.60	16.02	43.50	-27.48	QP		
3		348.1600	27.62	-6.83	20.79	46.00	-25.21	QP		
4		554.7700	28.96	-3.73	25.23	46.00	-20.77	QP		
5	*	728.4000	29.44	-0.58	28.86	46.00	-17.14	QP		
6		967.0200	29.71	3.24	32.95	54.00	-21.05	QP		




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT 2DH1 2402MHz
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		46.4900	34.55	-11.27	23.28	40.00	-16.72	QP		
2		201.6900	37.65	-11.49	26.16	43.50	-17.34	QP		
3		449.0400	29.21	-5.36	23.85	46.00	-22.15	QP		
4	*	728.4000	33.32	-0.58	32.74	46.00	-13.26	QP		
5		870.9900	30.12	1.45	31.57	46.00	-14.43	QP		
6		990.3000	29.26	3.78	33.04	54.00	-20.96	QP		




Site 3m Chamber #1 Polarization: *Vertical* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT 2DH1 2441MHz
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		56.1900	34.12	-11.94	22.18	40.00	-17.82	QP		
2		108.5700	28.58	-12.48	16.10	43.50	-27.40	QP		
3		410.2400	28.43	-5.75	22.68	46.00	-23.32	QP		
4		635.2800	28.86	-1.82	27.04	46.00	-18.96	QP		
5	*	825.4000	29.13	0.51	29.64	46.00	-16.36	QP		
6		967.9900	29.24	3.25	32.49	54.00	-21.51	QP		




Site: 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT 2DH1 2480MHz
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		64.9200	35.91	-13.51	22.40	40.00	-17.60	QP		
2		147.3700	31.91	-15.48	16.43	43.50	-27.07	QP		
3		193.9300	30.41	-12.01	18.40	43.50	-25.10	QP		
4		615.8800	28.91	-1.96	26.95	46.00	-19.05	QP		
5	*	822.4900	29.60	0.47	30.07	46.00	-15.93	QP		
6		999.0300	28.40	3.92	32.32	54.00	-21.68	QP		




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT 2DH1 2480MHz
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		62.0100	35.15	-13.09	22.06	40.00	-17.94	QP		
2		201.6900	38.99	-11.49	27.50	43.50	-16.00	QP		
3		394.7200	28.98	-6.20	22.78	46.00	-23.22	QP		
4	*	728.4000	34.69	-0.58	34.11	46.00	-11.89	QP		
5		800.1800	30.29	0.28	30.57	46.00	-15.43	QP		
6		973.8100	29.63	3.36	32.99	54.00	-21.01	QP		



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode: BT 3DH1 2402MHz
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		54.2500	35.25	-11.46	23.79	40.00	-16.21			QP
2		98.8700	28.78	-12.83	15.95	43.50	-27.55			QP
3		199.7500	37.39	-11.46	25.93	43.50	-17.57			QP
4		350.1000	28.61	-6.77	21.84	46.00	-24.16			QP
5	*	728.4000	33.38	-0.58	32.80	46.00	-13.20			QP
6		959.2600	29.48	3.19	32.67	46.00	-13.33			QP



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %
 Mode:BT 3DH1 2441MHz
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		55.2200	34.28	-11.68	22.60	40.00	-17.40	QP		
2		202.6600	36.84	-11.53	25.31	43.50	-18.19	QP		
3		674.0800	30.04	-1.41	28.63	46.00	-17.37	QP		
4	*	728.4000	34.49	-0.58	33.91	46.00	-12.09	QP		
5		806.0000	31.66	0.35	32.01	46.00	-13.99	QP		
6		977.6900	29.02	3.45	32.47	54.00	-21.53	QP		

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1625.600	V	43.35	31.05	74	54	-30.65	-22.95
9648.750	V	53.43	39.02	74	54	-20.57	-14.98
13509.45	V	54.17	40.16	74	54	-19.83	-13.84
1628.150	H	44.17	32.14	74	54	-29.83	-21.86
9664.050	H	53.87	39.24	74	54	-20.13	-14.76
13455.90	H	55.38	41.28	74	54	-18.62	-12.72

Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1699.550	V	42.76	30.25	74	54	-31.24	-23.75
8110.250	V	51.41	37.26	74	54	-22.59	-16.74
14614.45	V	54.17	39.26	74	54	-19.83	-14.74
1666.400	H	42.30	30.14	74	54	-31.70	-23.86
12333.05	H	53.99	39.14	74	54	-20.01	-14.86
17942.20	H	59.60	42.68	74	54	-14.40	-11.32

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1737.800	V	42.64	30.14	74	54	-31.36	-23.86
8510.600	V	51.74	37.38	74	54	-22.26	-16.62
15789.15	V	54.50	40.06	74	54	-19.50	-13.94
1566.950	H	42.31	30.26	74	54	-31.69	-23.74
8035.450	H	36.47	-17.53	74	54	-21.07	-15.94
17927.75	H	58.97	42.43	74	54	-15.03	-11.57

Test mode: $\pi/4$ DQPSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1686.800	V	42.21	31.54	74	54	-31.79	-22.46
9391.200	V	52.90	38.02	74	54	-21.10	-15.98
14967.20	V	54.73	40.17	74	54	-19.27	-13.83
1607.750	H	41.31	31.24	74	54	-32.69	-22.76
11568.90	H	54.17	39.08	74	54	-19.83	-14.92
17984.70	H	57.31	42.67	74	54	-16.69	-11.33

Test mode: $\pi/4$ DQPSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1634.100	V	42.95	31.25	74	54	-31.05	-22.75
9500.850	V	53.38	39.22	74	54	-20.62	-14.78
17980.45	V	57.05	42.63	74	54	-16.95	-11.37
1539.750	H	41.19	30.24	74	54	-32.81	-23.76
10274.35	H	53.13	39.58	74	54	-20.87	-14.42
17965.15	H	58.06	42.16	74	54	-15.94	-11.84

Test mode: $\pi/4$ DQPSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1619.650	V	42.01	31.11	74	54	-31.99	-22.89
10093.30	V	53.07	39.42	74	54	-20.93	-14.58
17998.30	V	56.43	41.08	74	54	-17.57	-12.92
1773.500	H	39.42	29.67	74	54	-34.58	-24.33
10146.85	H	53.37	38.76	74	54	-20.63	-15.24
17935.40	H	57.69	42.06	74	54	-16.31	-11.94

Test mode: 8DPSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1711.450	V	41.56	31.45	74	54	-32.44	-22.55
8067.750	V	50.09	37.02	74	54	-23.91	-16.98
14833.75	V	53.80	39.09	74	54	-20.20	-14.91
1740.350	H	40.48	30.14	74	54	-33.52	-23.86
11375.95	H	54.28	40.17	74	54	-19.72	-13.83
17984.70	H	57.40	42.56	74	54	-16.60	-11.44

Test mode: 8DPSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1559.300	V	41.81	31.07	74	54	-32.19	-22.93
8131.500	V	50.36	37.26	74	54	-23.64	-16.74
17947.30	V	56.61	41.19	74	54	-17.39	-12.81
1691.050	H	41.12	31.09	74	54	-32.88	-22.91
8128.950	H	50.39	37.22	74	54	-23.61	-16.78
14812.50	H	54.60	40.31	74	54	-19.40	-13.69

Test mode: 8DPSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1545.700	V	40.28	30.27	74	54	-33.72	-23.73
8100.900	V	49.12	36.92	74	54	-24.88	-17.08
17707.60	V	56.69	41.06	74	54	-17.31	-12.94
1680.850	H	39.38	30.07	74	54	-34.62	-23.93
8131.500	H	48.53	35.01	74	54	-25.47	-18.99
17940.50	H	57.04	42.32	74	54	-16.96	-11.68

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test mode: GFSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.160	H	52.29	74	36.26	54
2378.856	V	52.03	74	35.44	54

Test mode: GFSK Frequency: Channel 78: 2480MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.519	H	53.25	74	36.58	54
2483.614	V	52.56	74	35.07	54

Test mode: GFSK Frequency: Hopping

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2390.000	H	50.18	74	35.01	54
2483.500	H	50.74	74	34.56	54
2390.000	V	50.47	74	35.17	54
2483.500	V	53.07	74	37.03	54

Test mode: $\pi/4$ DQPSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2385.576	H	52.06	74	36.24	54
2385.892	V	51.68	74	35.06	54

Test mode: $\pi/4$ DQPSK Frequency: Channel 78: 2480MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.700	H	53.00	74	35.74	54
2484.563	V	52.33	74	36.22	54

Test mode: $\pi/4$ DQPSK Frequency: Hopping

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2390.000	H	49.93	74	34.59	54
2483.500	H	52.50	74	36.08	54
2390.000	V	50.64	74	35.16	54
2483.500	V	51.39	74	36.82	54

Test mode: 8DPSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2384.564	H	51.70	74	36.06	54
2389.080	V	51.63	74	35.47	54

Test mode: 8DPSK Frequency: Channel 78: 2480MHz


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2485.149	H	52.04	74	35.13	54
2485.468	V	52.64	74	35.48	54

Test mode: 8DPSK Frequency: Hopping

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2390.000	H	50.18	74	34.68	54
2483.500	H	52.24	74	35.26	54
2390.000	V	50.47	74	35.16	54
2483.500	V	51.57	74	36.09	54


- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Spurious Emission in Restricted Band 2310-2390MHz
 Test Model Channel 0: 2402MHz GFSK H




Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz
 Test Model Channel 0: 2402MHz GFSK V




Site 3m Chamber #1 Polarization: *Vertical* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2483.5-2500MHz
 Test Model Channel 78: 2480MHz GFSK H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2483.5-2500MHz
 Test Model Channel 78: 2480MHz GFSK V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz
 Test Model Hopping GFSK H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz
 Test Model Hopping GFSK V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz
 Test Model Channel 0: 2402MHz π /4DQPSK H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz
 Test Model Channel 0: 2402MHz π /4DQPSK V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2483.5-2500MHz
 Test Model Channel 78: 2480MHz π /4DQPSK H



Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %


Spurious Emission in Restricted Band 2483.5-2500MHz
 Test Model Channel 78: 2480MHz π /4DQPSK V



Site 3m Chamber #1 Polarization: *Vertical* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz


Test Model Hopping π /4DQPSK H



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: FCC PART 15C Power: Humidity: 48 %


Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz

Test Model Hopping π /4DQPSK V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz
 Test Model Channel 0: 2402MHz 8DPSK H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz
 Test Model Channel 0: 2402MHz 8DPSK V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2483.5-2500MHz
 Test Model Channel 78: 2480MHz 8DPSK H



Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %


Spurious Emission in Restricted Band 2483.5-2500MHz
 Test Model Channel 78: 2480MHz 8DPSK V



Site 3m Chamber #1 Polarization: *Vertical* Temperature: 29.5 C
 Limit: (RE)FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz


Test Model Hopping 8DPSK H



Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 29.5 C
 Limit: FCC PART 15C Power: Humidity: 48 %

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz

Test Model Hopping 8DPSK V



Site 3m Chamber #1 Polarization: *Vertical* Temperature: 29.5 C
 Limit: FCC PART 15C Power: Humidity: 48 %

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.
 Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

Pass

The 120V &240V voltagehave been tested, and the worst result recorded was report as below:




Site Conduction #1
Limit: FCC PART 15C
Mode: BT mode
Note:

Phase: **L1**
Power: AC 120V/60Hz

Temperature: 24.9
Humidity: 54 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	37.70	9.67	47.37	66.00	-18.63	QP	
2		0.1500	19.04	9.67	28.71	56.00	-27.29	AVG	
3		0.4300	27.19	9.57	36.76	57.25	-20.49	QP	
4	*	0.4300	23.41	9.57	32.98	47.25	-14.27	AVG	
5		0.5220	30.04	9.57	39.61	56.00	-16.39	QP	
6		0.5220	20.75	9.57	30.32	46.00	-15.68	AVG	
7		0.6940	23.23	9.57	32.80	56.00	-23.20	QP	
8		0.6940	15.46	9.57	25.03	46.00	-20.97	AVG	
9		1.6220	27.07	9.59	36.66	56.00	-19.34	QP	
10		1.6220	19.49	9.59	29.08	46.00	-16.92	AVG	
11		13.4580	32.40	9.87	42.27	60.00	-17.73	QP	
12		13.4580	24.77	9.87	34.64	50.00	-15.36	AVG	



Site Conduction #1
Limit: FCC PART 15C
Mode: BT mode
Note:

Phase: **N**

Temperature: 24.9

Power: AC 120V/60Hz

Humidity: 54 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	35.38	9.62	45.00	65.57	-20.57	QP	
2		0.1580	18.82	9.62	28.44	55.57	-27.13	AVG	
3		0.4300	27.31	9.57	36.88	57.25	-20.37	QP	
4		0.4300	19.88	9.57	29.45	47.25	-17.80	AVG	
5		0.5300	28.23	9.57	37.80	56.00	-18.20	QP	
6	*	0.5300	19.65	9.57	29.22	46.00	-16.78	AVG	
7		0.9940	22.96	9.59	32.55	56.00	-23.45	QP	
8		0.9940	9.92	9.59	19.51	46.00	-26.49	AVG	
9		1.3820	23.34	9.59	32.93	56.00	-23.07	QP	
10		1.3820	12.10	9.59	21.69	46.00	-24.31	AVG	
11		14.0780	27.34	9.88	37.22	60.00	-22.78	QP	
12		14.0780	16.53	9.88	26.41	50.00	-23.59	AVG	

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.9.2 Result

PASS.

The EUT is PCB Antenna, the gain is 2 dBi.

- Note:
- Antenna use a permanently attached antenna which is not replaceable.
 - Not using a standard antenna jack or electrical connector for antenna replacement
 - The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

----- End of Report -----