

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.	R-8518-1				
Test Sample:	300 MHz Pulsed RF Transmitter (four button)	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 4	FCC ID:					
Operating Mode:	Continuously Transmitting a 300MHz Pulsed Signal						
Technician:	Peter Lananna	Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters Detector: Peak, Unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)/Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
300	H / 1.0	X	85.2	-4.4	80.8	10964.8	54200
	H / 1.0	Y	70.9	-4.4	66.5	2113.5	
	H / 1.0	Z	85.3	-4.4	80.9	11091.7	
	V / 1.5	X	68.4	-4.4	64.0	1584.9	
	V / 1.8	Y	80.7	-4.4	76.3	6531.3	
300	V / 1.5	Z	71.5	-4.4	67.1	2264.6	54200
600	H / 1.0	X	50.4	2.4	52.8	436.5	5420
	H / 1.0	Y	43.0	2.4	45.4	186.2	
	H / 1.0	Z	48.5	2.4	50.9	350.8	
	V / 1.0	X	44.2	2.4	46.6	213.8	
	V / 1.0	Y	51.3	2.4	53.7	484.2	
600	V / 1.0	Z	51.2	2.4	53.6	478.6	5420
900	H / 1.0	X	35.7	7.2	42.9	139.6	5420
	H / 1.0	Y	34.6	7.2	41.8	123.0	
	H / 1.0	Z	36.3	7.2	43.5	149.6	
	V / 1.5	X	33.3	7.2	40.5	105.9	
	V / 1.0	Y	36.6	7.2	43.8	154.9	
900	V / 1.0	Z	40.0	7.2	47.2	229.1	5420
1200	H / 1.5	X	52.0	-4.6	47.4	234.4	5000
	H / 1.5	Y	52.6	-4.6	48.0	251.2	
	H / 1.5	Z	52.1	-4.6	47.5	237.1	
	V / 1.5	X	53.5	-4.6	48.9	278.6	
	V / 1.5	Y	55.1	-4.6	50.5	335.0	
1200	V / 1.0	Z	55.9	-4.6	51.3	367.3	5000
1500	H / 1.5	X	55.8	-1.3	54.5	530.9	5000
	H / 1.5	Y	53.8	-1.3	52.5	421.7	
	H / 1.5	Z	50.9	-1.3	49.6	302.0	
	V / 1.5	X	50.8	-1.3	49.5	298.5	
	V / 1.3	Y	55.3	-1.3	54.0	501.2	
1500	V / 1.3	Z	53.9	-1.3	52.6	426.6	5000
The frequency range was scanned from 30 MHz to 3.0 GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
* = Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.	R-8518-1				
Test Sample:	300 MHz Pulsed RF Transmitter (four button).	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 4	FCC ID:					
Operating Mode:	Continuously Transmitting a 300 MHz Pulsed Signal						
Technician:	Peter Lananna	Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters Detector: Peak, unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
1800	H/1.0	X	41.0	1.9	42.9	139.6*	5420
	H/1.0	Y	41.0	1.9	42.9	139.6*	
	H/1.0	Z	41.0	1.9	42.9	139.6*	
	V/1.0	X	41.0	1.9	42.9	139.6*	
	V/1.0	Y	41.0	1.9	42.9	139.6*	
1800	V/1.0	Z	41.0	1.9	42.9	139.6*	5420
2100	H/1.0	X	40.4	-8.0	32.4	41.7*	5420
	H/1.0	Y	40.4	-8.0	32.4	41.7*	
	H/1.0	Z	40.4	-8.0	32.4	41.7*	
	V/1.0	X	40.4	-8.0	32.4	41.7*	
	V/1.0	Y	40.4	-8.0	32.4	41.7*	
2100	V/1.0	Z	40.4	-8.0	32.4	41.7*	5420
2400	H/1.0	X	40.5	-7.3	33.2	45.7*	5420
	H/1.0	Y	40.5	-7.3	33.2	45.7*	
	H/1.0	Z	40.5	-7.3	33.2	45.7*	
	V/1.0	X	40.5	-7.3	33.2	45.7*	
	V/1.0	Y	40.5	-7.3	33.2	45.7*	
2400	V/1.0	Z	40.5	-7.3	33.2	45.7*	5420
2700	H/1.0	X	35.2	-6.8	28.4	26.3*	5000
	H/1.0	Y	35.2	-6.8	28.4	26.3*	
	H/1.0	Z	35.2	-6.8	28.4	26.3*	
	V/1.0	X	35.2	-6.8	28.4	26.3*	
	V/1.0	Y	35.2	-6.8	28.4	26.3*	
2700	V/1.0	Z	35.2	-6.8	28.4	26.3*	5000
3000	H/1.0	X	38.1	-5.5	32.6	42.7*	5420
	H/1.0	Y	38.1	-5.5	32.6	42.7*	
	H/1.0	Z	38.1	-5.5	32.6	42.7*	
	V/1.0	X	38.1	-5.5	32.6	42.7*	
	V/1.0	Y	38.1	-5.5	32.6	42.7*	
3000	V/1.0	Z	38.1	-5.5	32.6	42.7*	5420
The frequency range was scanned from 30 MHz to 3.0 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.	R-8518-1				
Test Sample:	300 MHz Pulsed RF Transmitter (four button)	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 4	FCC ID:					
Operating Mode:	Continuously Transmitting a 300MHz Pulsed Signal						
Technician:		Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters			Duty Cycle: 23.5%			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - 12.6 dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
300	H / 1.0	X	80.8	-12.6	68.2	2570.4	5420
	H / 1.0	Y	66.5	-12.6	53.9	495.5	
	H / 1.0	Z	80.9	-12.6	68.3	2600.2	
	V / 1.5	X	64.0	-12.6	51.4	371.5	
	V / 1.8	Y	76.3	-12.6	63.7	1531.1	
300	V / 1.5	Z	67.1	-12.6	54.5	530.9	5420
600	H / 1.0	X	52.8	-12.6	40.2	102.3	542
	H / 1.0	Y	45.4	-12.6	32.8	43.7	
	H / 1.0	Z	50.9	-12.6	38.3	82.2	
	V / 1.0	X	46.6	-12.6	34.0	50.1	
	V / 1.0	Y	53.7	-12.6	41.1	113.5	
600	V / 1.0	Z	53.6	-12.6	41.0	112.2	542
900	H / 1.0	X	42.9	-12.6	30.3	32.7	542
	H / 1.0	Y	41.8	-12.6	29.2	28.8	
	H / 1.0	Z	43.5	-12.6	30.9	35.1	
	V / 1.5	X	40.5	-12.6	27.9	24.8	
	V / 1.0	Y	43.8	-12.6	31.2	36.3	
900	V / 1.0	Z	47.2	-12.6	34.6	53.7	542
1200	H / 1.5	X	47.4	-12.6	34.8	55.0	500
	H / 1.5	Y	48.0	-12.6	35.4	58.9	
	H / 1.5	Z	47.5	-12.6	34.9	55.6	
	V / 1.5	X	48.9	-12.6	36.3	65.3	
	V / 1.5	Y	50.5	-12.6	37.9	78.5	
1200	V / 1.0	Z	51.3	-12.6	38.7	86.1	500
1500	H / 1.5	X	54.5	-12.6	41.9	124.5	500
	H / 1.5	Y	52.5	-12.6	39.9	98.9	
	H / 1.5	Z	49.6	-12.6	37.0	70.8	
	V / 1.5	X	49.5	-12.6	36.9	70.0	
	V / 1.3	Y	54.0	-12.6	41.4	117.5	
1500	V / 1.3	Z	52.6	-12.6	40.0	100.0	500
The frequency range was scanned from 30 MHz to 3.0GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.:	R-8518-1				
Test Sample:	300 MHz Pulsed RF Transmitter (four button)	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 4	FCC ID:					
Operating Mode:	Continuously Transmitting a 300 MHz Pulsed Signal						
Technician:	Peter Lananna	Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters		Duty Cycle: 23.5%				
	Detector: Peak, unless otherwise specified		Duty Cycle Correction: -12.6 dB				
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
1800	H/1.0	X	42.9	-12.6	30.3	32.7*	542
	H/1.0	Y	42.9	-12.6	30.3	32.7*	
	H/1.0	Z	42.9	-12.6	30.3	32.7*	
	V/1.0	X	42.9	-12.6	30.3	32.7*	
	V/1.0	Y	42.9	-12.6	30.3	32.7*	
1800	V/1.0	Z	42.9	-12.6	30.3	32.7*	542
2100	H/1.0	X	32.4	-12.6	19.8	9.8*	542
	H/1.0	Y	32.4	-12.6	19.8	9.8*	
	H/1.0	Z	32.4	-12.6	19.8	9.8*	
	V/1.0	X	32.4	-12.6	19.8	9.8*	
	V/1.0	Y	32.4	-12.6	19.8	9.8*	
2100	V/1.0	Z	32.4	-12.6	19.8	9.8*	542
2400	H/1.0	X	33.2	-12.6	20.6	10.7*	542
	H/1.0	Y	33.2	-12.6	20.6	10.7*	
	H/1.0	Z	33.2	-12.6	20.6	10.7*	
	V/1.0	X	33.2	-12.6	20.6	10.7*	
	V/1.0	Y	33.2	-12.6	20.6	10.7*	
2400	V/1.0	Z	33.2	-12.6	20.6	10.7*	542
2700	H/1.0	X	28.4	-12.6	15.8	6.2*	500
	H/1.0	Y	28.4	-12.6	15.8	6.2*	
	H/1.0	Z	28.4	-12.6	15.8	6.2*	
	V/1.0	X	28.4	-12.6	15.8	6.2*	
	V/1.0	Y	28.4	-12.6	15.8	6.2*	
2700	V/1.0	Z	28.4	-12.6	15.8	6.2*	500
3000	H/1.0	X	32.6	-12.6	20.0	10.0*	542
	H/1.0	Y	32.6	-12.6	20.0	10.0*	
	H/1.0	Z	32.6	-12.6	20.0	10.0*	
	V/1.0	X	32.6	-12.6	20.0	10.0*	
	V/1.0	Y	32.6	-12.6	20.0	10.0*	
3000	V/1.0	Z	32.6	-12.6	20.0	10.0*	542
The frequency range was scanned from 30 MHz to 3.0 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain			Job No.	R-8518-1		
Test Sample:	310 MHz Pulsed RF Transmitter (one button)			Paragraph:	15.231(b)		
Model No.:	Tricode Tx 1			FCC ID:			
Operating Mode:	Continuously Transmitting a 310MHz Pulsed Signal						
Technician:	Peter Lananna			Date:	May 8, 2000		
Notes:	Test Distance: 3 Meters Detector: Peak, Unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)/Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
310	H / 1.0	X	81.2	-3.9	77.3	7328.2	58300
	H / 1.3	Y	66.3	-3.9	62.4	1318.3	
	H / 1.5	Z	78.9	-3.9	75.0	5623.4	
	V / 1.0	X	63.4	-3.9	59.5	944.1	
	V / 1.8	Y	82.7	-3.9	78.8	8709.6	
310	V / 1.8	Z	79.1	-3.9	75.2	5754.4	58300
620	H / 1.5	X	47.3	3.3	50.6	338.8	5830
	H / 1.3	Y	49.0	3.3	52.3	412.1	
	H / 1.5	Z	45.2	3.3	48.5	266.1	
	V / 1.0	X	44.5	3.3	47.8	245.5	
	V / 1.0	Y	43.6	3.3	46.9	221.3	
620	V / 1.0	Z	49.4	3.3	52.7	431.5	5830
930	H / 1.0	X	36.4	7.3	43.7	153.1*	5830
	H / 1.0	Y	36.4	7.3	43.7	153.1*	
	H / 1.0	Z	36.4	7.3	43.7	153.1*	
	V / 1.0	X	36.4	7.3	43.7	153.1*	
	V / 1.0	Y	36.4	7.3	43.7	153.1*	
930	V / 1.0	Z	36.4	7.3	43.7	153.1*	5830
1240	H / 1.0	X	57.2	-3.9	53.3	462.4	5000
	H / 1.0	Y	57.6	-3.9	53.7	484.2	
	H / 1.0	Z	51.8	-3.9	47.9	248.3	
	V / 1.0	X	51.2	-3.9	47.3	231.7	
	V / 1.0	Y	53.9	-3.9	50.0	316.2	
1240	V / 1.0	Z	57.6	-3.9	53.7	484.2	5000
1550	H / 1.0	X	63.4	-0.7	62.7	1364.6	5000
	H / 1.0	Y	62.3	-0.7	61.6	1202.3	
	H / 1.0	Z	54.0	-0.7	53.3	462.4	
	V / 1.0	X	56.0	-0.7	55.3	582.1	
	V / 1.0	Y	55.8	-0.7	55.1	568.9	
1550	V / 1.0	Z	65.0	-0.7	64.3	1640.6	5000
The frequency range was scanned from 30 MHz to 3.1 GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
* = Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.	R-8518-1				
Test Sample:	310 MHz Pulsed RF Transmitter (one button).	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 1	FCC ID:					
Operating Mode:	Continuously Transmitting a 310MHz Pulsed Signal						
Technician:	Peter Lananna	Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters Detector: Peak, unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
1860	H/1.0	X	40.0	2.4	42.4	131.8*	5830
	H/1.0	Y	40.0	2.4	42.4	131.8*	
	H/1.0	Z	40.0	2.4	42.4	131.8*	
	V/1.0	X	40.0	2.4	42.4	131.8*	
	V/1.0	Y	40.0	2.4	42.4	131.8*	
1860	V/1.0	Z	40.0	2.4	42.4	131.8*	5830
2170	H/1.0	X	37.3	-8.0	29.3	29.2*	5830
	H/1.0	Y	37.3	-8.0	29.3	29.2*	
	H/1.0	Z	37.3	-8.0	29.3	29.2*	
	V/1.0	X	37.3	-8.0	29.3	29.2*	
	V/1.0	Y	37.3	-8.0	29.3	29.2*	
2170	V/1.0	Z	37.3	-8.0	29.3	29.2*	5830
2480	H/1.0	X	37.3	-7.3	30.0	31.6*	5830
	H/1.0	Y	37.3	-7.3	30.0	31.6*	
	H/1.0	Z	37.3	-7.3	30.0	31.6*	
	V/1.0	X	37.3	-7.3	30.0	31.6*	
	V/1.0	Y	37.3	-7.3	30.0	31.6*	
2480	V/1.0	Z	37.3	-7.3	30.0	31.6*	5830
2790	H/1.0	X	35.2	-6.8	28.4	26.3*	5000
	H/1.0	Y	35.2	-6.8	28.4	26.3*	
	H/1.0	Z	35.2	-6.8	28.4	26.3*	
	V/1.0	X	35.2	-6.8	28.4	26.3*	
	V/1.0	Y	35.2	-6.8	28.4	26.3*	
2790	V/1.0	Z	35.2	-6.8	28.4	26.3*	5000
3100	H/1.0	X	38.1	-5.5	32.6	42.7*	5830
	H/1.0	Y	38.1	-5.5	32.6	42.7*	
	H/1.0	Z	38.1	-5.5	32.6	42.7*	
	V/1.0	X	38.1	-5.5	32.6	42.7*	
	V/1.0	Y	38.1	-5.5	32.6	42.7*	
3100	V/1.0	Z	38.1	-5.5	32.6	42.7*	5830
The frequency range was scanned from 30 MHz to 3.1 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.:	R-8518-1				
Test Sample:	310 MHz Pulsed RF Transmitter (one button)	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 1	FCC ID:					
Operating Mode:	Continuously Transmitting a 310MHz Pulsed Signal						
Technician:		Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters			Duty Cycle: 23.5%			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - 12.6 dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
310	H / 1.0	X	77.3	-12.6	64.7	1717.9	5830
	H / 1.3	Y	62.4	-12.6	49.8	309.0	
	H / 1.5	Z	75.0	-12.6	62.4	1318.3	
	V / 1.0	X	59.5	-12.6	46.9	221.3	
	V / 1.8	Y	78.8	-12.6	66.2	2041.7	
310	V / 1.8	Z	75.2	-12.6	62.6	1349.0	5830
620	H / 1.5	X	50.6	-12.6	38.0	79.4	583
	H / 1.3	Y	52.3	-12.6	39.7	96.6	
	H / 1.5	Z	48.5	-12.6	35.9	62.4	
	V / 1.0	X	47.8	-12.6	35.2	57.5	
	V / 1.0	Y	46.9	-12.6	34.3	51.9	
620	V / 1.0	Z	52.7	-12.6	40.1	101.2	583
930	H / 1.0	X	43.7	-12.6	31.1	35.9*	583
	H / 1.0	Y	43.7	-12.6	31.1	35.9*	
	H / 1.0	Z	43.7	-12.6	31.1	35.9*	
	V / 1.0	X	43.7	-12.6	31.1	35.9*	
	V / 1.0	Y	43.7	-12.6	31.1	35.9*	
930	V / 1.0	Z	43.7	-12.6	31.1	35.9*	583
1240	H / 1.0	X	53.3	-12.6	40.7	108.4	500
	H / 1.0	Y	53.7	-12.6	41.1	113.5	
	H / 1.0	Z	47.9	-12.6	35.3	58.2	
	V / 1.0	X	47.3	-12.6	34.7	54.3	
	V / 1.0	Y	50.0	-12.6	37.4	74.1	
1240	V / 1.0	Z	53.7	-12.6	41.1	113.5	500
1550	H / 1.0	X	62.7	-12.6	50.1	319.9	500
	H / 1.0	Y	61.6	-12.6	49.0	281.8	
	H / 1.0	Z	53.3	-12.6	40.7	108.4	
	V / 1.0	X	55.3	-12.6	42.7	136.5	
	V / 1.0	Y	55.1	-12.6	42.5	133.4	
1550	V / 1.0	Z	64.3	-12.6	51.7	384.6	500
The frequency range was scanned from 30 MHz to 3.1GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
* = Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chamberlain	Job No.:	R-8518-1				
Test Sample:	310 MHz Pulsed RF Transmitter (one button)	Paragraph:	15.231(b)				
Model No.:	Tricode Tx 1	FCC ID:					
Operating Mode:	Continuously Transmitting a 310 MHz Pulsed Signal						
Technician:	Peter Lananna	Date:	May 8, 2000				
Notes:	Test Distance: 3 Meters		Duty Cycle: 23.5%				
	Detector: Peak, unless otherwise specified		Duty Cycle Correction: -12.6 dB				
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
1860	H/1.0	X	42.4	-12.6	29.8	30.9*	583
	H/1.0	Y	42.4	-12.6	29.8	30.9*	
	H/1.0	Z	42.4	-12.6	29.8	30.9*	
	V/1.0	X	42.4	-12.6	29.8	30.9*	
	V/1.0	Y	42.4	-12.6	29.8	30.9*	
1860	V/1.0	Z	42.4	-12.6	29.8	30.9*	583
2170	H/1.0	X	29.3	-12.6	16.7	6.8*	583
	H/1.0	Y	29.3	-12.6	16.7	6.8*	
	H/1.0	Z	29.3	-12.6	16.7	6.8*	
	V/1.0	X	29.3	-12.6	16.7	6.8*	
	V/1.0	Y	29.3	-12.6	16.7	6.8*	
2170	V/1.0	Z	29.3	-12.6	16.7	6.8*	583
2480	H/1.0	X	30.0	-12.6	17.4	7.4*	583
	H/1.0	Y	30.0	-12.6	17.4	7.4*	
	H/1.0	Z	30.0	-12.6	17.4	7.4*	
	V/1.0	X	30.0	-12.6	17.4	7.4*	
	V/1.0	Y	30.0	-12.6	17.4	7.4*	
2480	V/1.0	Z	30.0	-12.6	17.4	7.4*	583
2790	H/1.0	X	28.4	-12.6	15.8	6.2*	500
	H/1.0	Y	28.4	-12.6	15.8	6.2*	
	H/1.0	Z	28.4	-12.6	15.8	6.2*	
	V/1.0	X	28.4	-12.6	15.8	6.2*	
	V/1.0	Y	28.4	-12.6	15.8	6.2*	
2790	V/1.0	Z	28.4	-12.6	15.8	6.2*	500
3100	H/1.0	X	32.6	-12.6	20.0	10.0*	583
	H/1.0	Y	32.6	-12.6	20.0	10.0*	
	H/1.0	Z	32.6	-12.6	20.0	10.0*	
	V/1.0	X	32.6	-12.6	20.0	10.0*	
	V/1.0	Y	32.6	-12.6	20.0	10.0*	
3100	V/1.0	Z	32.6	-12.6	20.0	10.0*	583
The frequency range was scanned from 30 MHz to 3.1 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8518-1