



**Engineering Test Report No. 2004380-03 Rev. C**

Report Date	January 5, 2021	
Manufacturer Name	Chamberlain Group, Inc.	
Manufacturer Address	300 Windsor Dr Oak Brook, IL 60523	
Model No.	CDMRAA0101E3 (ARQ2-UGDO)	
Date Received	November 16, 2020	
Test Dates	November 17 – December 1, 2020	
Specifications	FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 Innovation, Science, and Economic Development Canada, RSS-247 Innovation, Science, and Economic Development Canada, RSS-GEN	
Test Facility	Elite Electronic Engineering, Inc. 1516 Centre Circle, Downers Grove, IL 60515	FCC Reg. Number: 269750 IC Reg. Number: 2987A
Signature		
Tested by	Tylar Jozefczyk	
Signature		
Approved by	Raymond J. Klouda, Registered Professional Engineer of Illinois – 44894	
PO Number	4900071557	

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

This report shall not be reproduced, except in full, without the written approval of Elite Electronic Engineering Inc.

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247, Innovation, Science, and Economic Development Canada, RSS-247, and RSS-GEN test specifications. The data presented in this test report pertains to the EUT on the test dates specified. Any electrical or mechanical modifications made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification. This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

## Table of Contents

1.	Report Revision History .....	3
2.	Introduction .....	4
2.1.	Scope of Tests .....	4
2.2.	Purpose .....	4
2.3.	Identification of the EUT .....	4
3.	Power Input .....	4
4.	Grounding .....	4
5.	Support Equipment .....	4
6.	Interconnect Leads .....	5
7.	Modifications Made to the EUT .....	5
8.	Modes of Operation .....	5
9.	Test Specifications .....	5
10.	Test Plan .....	5
11.	Deviation, Additions to, or Exclusions from Test Specifications .....	5
12.	Laboratory Conditions .....	6
13.	Summary .....	6
14.	Sample Calculations .....	6
15.	Statement of Conformity .....	6
16.	Certification .....	7
17.	Photographs of EUT .....	8
18.	Equipment List .....	9
19.	Block Diagram of Test Setup .....	10
20.	Antenna Port Conducted Emissions Tests .....	11
21.	Radiated Emissions Tests .....	22
22.	Scope of Accreditation .....	59

**This report shall not be reproduced, except in full,  
without the written approval of Elite Electronic Engineering Inc.**

## 1. Report Revision History

Revision	Date	Description
–	19 JAN 2021	Initial Release of Engineering Test Report No. 2004380-03
A	25 JAN 2021 By TMJ	<ul style="list-style-type: none"> <li>- Report number updated from 2004380-03 to 2004380-03 Rev. A throughout test report.</li> <li>- Section 2.3: updated ISED UPN from “266A-9757” to “2666A-9757”.</li> </ul>
B	01 FEB 2021 By TMJ	<ul style="list-style-type: none"> <li>- Report number updated from 2004380-03 Rev. A to 2004380-03 Rev. B throughout test report.</li> <li>- Section 2.3: updated and edited “EUT Identification” table with the following:               <ul style="list-style-type: none"> <li>• Corrected value in “Conducted Output Power” row from “10dBm (set in firmware); 3.5dBm after filtering and loss” to 4.9dBm (0.003W).</li> <li>• Removed “Rated Output Power” row.</li> </ul> </li> </ul>
C	02 FEB 2021 By TMJ	<ul style="list-style-type: none"> <li>- Report number updated from 2004380-03 Rev. B to 2004380-03 Rev. C throughout test report.</li> <li>- Revision History Table:               <ul style="list-style-type: none"> <li>• Updated first row for initial release (showed as “Initial Release of Engineering Test Report No. 2004380-03 Rev. B”, has been updated to the correct “Initial Release of Engineering Test Report No. 2004380-03”).</li> <li>• Updated second row for Revision A (showed incorrectly as “Report number updated from 2004380-03 to 2004380-03 Rev. B throughout test report”; has been updated to the correct “Report number updated from 2004380-03 to 2004380-03 Rev. A throughout test report”).</li> <li>• Revision B incorrectly stated that Section 3.1 was updated. Section was updated to reflect the correct section that was updated (Section 2.3) in that revision.</li> </ul> </li> </ul>

## 2. Introduction

### 2.1. Scope of Tests

This document presents the results of a series of RF emissions tests that were performed on the Chamberlain Group, Inc. Automotive Mirror (hereinafter referred to as the Equipment Under Test (EUT)). The EUT was manufactured and submitted for testing by Chamberlain Group, Inc. located in Oak Brook, IL.

### 2.2. Purpose

The test series was performed to determine if the EUT meets the RF emission requirements of the FCC “Code of Federal Regulations” Title 47, Part 15, Subpart C, Sections 15.247 for a Digital Modulation intentional radiator operating within the 2400-2483.5MHz band.

The test series was also performed to determine if the EUT meets the RF emission requirements of the Innovation, Science, and Economic Development Canada Radio Standards Specification RSS-Gen and Innovation, Science, and Economic Development Canada Radio Standards Specification RSS-247 for a Digital Modulation intentional radiator operating within the 2400-2483.5MHz band.

Testing was performed in accordance with ANSI C63.10-2013.

### 2.3. Identification of the EUT

The EUT was identified as follows:

EUT Identification	
Product Description	ARQ2 Automotive Transceiver for Garage Door Control
Model Number	CDMRAA0101E3 (ARQ2-UGDO)
Serial Number	SMP-77482
Device Type	Digitally Modulated Transmission Device
Band of Operation	2400 – 2483.5MHz
Firmware Version	0.26
Conducted Output Power	4.9dBm (0.003W)
Antenna Type	Copper trace monopole; Chip
Antenna Gain (dBi)	0.5dBi
6dB Bandwidth	900kHz
Occupied Bandwidth (99% CBW)	1.04MHz
Size of EUT	1.75” x 1.5”
Product FCC ID & ISED UPN	FCC ID: HBW9757 ISED UPN: 2666A-9757

The EUT listed above was used throughout the test series.

## 3. Power Input

The EUT was powered by 12VDC through a twisted pair of a 1m wire harness.

## 4. Grounding

The EUT was not connected to ground.

## 5. Support Equipment

The EUT was submitted for testing along with the following support equipment:

Description	Model #	S/N
Elite Laptop	hp	N/A

### 6. Interconnect Leads

The following interconnect cables were submitted with the EUT:

Item	Description
Wire Harness	1 meter
USB to Serial Cable	Used to connect EUT to test laptop to control modes.

### 7. Modifications Made to the EUT

No modifications were made to the EUT during the testing.

### 8. Modes of Operation

The EUT and all peripheral equipment were energized. The unit was programmed to transmit in one of the following modes:

Mode	Description
Tx	The EUT was powered on and set to transmit at the following frequencies: - 2402MHz - 2440MHz - 2480MHz

### 9. Test Specifications

The tests were performed to selected portions of, and in accordance with the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 test specifications.

- Federal Communications Commission "Code of Federal Regulations", Title 47, Part 15, Subpart C
- ANSI C63.4-2014, "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz"
- ANSI C63.10-2013, "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices"
- RSS-247 Issue 2, February 2017, "Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices"
- RSS-Gen Issue 5, March 2019, Amendment 1, Innovation, Science, and Economic Development Canada, "Spectrum Management and Telecommunications, Radio Standards Specification, General Requirements for Compliance of Radio Apparatus"

### 10. Test Plan

No test plan was provided. Instructions were provided by personnel from Chamberlain Group, Inc. and used in conjunction with the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247, Innovation, Science, and Economic Development Canada, RSS-247, and ANSI C63.4-2014 specifications.

### 11. Deviation, Additions to, or Exclusions from Test Specifications

There were no deviations, additions to, or exclusions from the test specifications during this test series.

## 12. Laboratory Conditions

Ambient Parameters	Value
Temperature	22.3°C
Relative Humidity	20.4%
Atmospheric Pressure	1034.54mb

## 13. Summary

The following EMC tests were performed, and the results are shown below:

Test Description	Requirements	Test Methods	S/N	Results
6dB Bandwidth	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
99% Bandwidth	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
Output Power	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
Power Spectral Density	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
Low Band Edge	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
EIRP	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
Spurious Radiated Emissions	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms
High Band Edge	FCC 15C 15.247 ISED RSS-247	ANSI C63.10:2013	SMP-77482	Conforms

## 14. Sample Calculations

For Powerline Conducted Emissions:

The resultant voltage level (VL) is a summation in decibels (dB) of the receiver meter reading (MTR) and the cable loss factor (CF).

$$\text{Formula 1: } VL \text{ (dB}\mu\text{V)} = \text{MTR (dB}\mu\text{V)} + \text{CF (dB)}.$$

For Radiated Emissions:

The resultant field strength (FS) is a summation in decibels (dB) of the receiver meter reading (MTR), the antenna correction factor (AF), and the cable loss factor (CF). If an external preamplifier is used, the total is reduced by its gain (-PA). If a distance correction (DC) is required, it is added to the total.

$$\text{Formula 1: } FS \text{ (dB}\mu\text{V/m)} = \text{MTR (dB}\mu\text{V)} + \text{AF (dB/m)} + \text{CF (dB)} + (-\text{PA (dB)}) + \text{DC (dB)}$$

To convert the Field Strength dB $\mu$ V/m term to  $\mu$ V/m, the dB $\mu$ V/m is first divided by 20. The Base 10 AntiLog is taken of this quotient. The result is the Field Strength value in  $\mu$ V/m terms.

$$\text{Formula 2: } FS \text{ (}\mu\text{V/m)} = \text{AntiLog} [(FS \text{ (dB}\mu\text{V/m)})/20]$$


## 15. Statement of Conformity

The Chamberlain Group, Inc. Automotive Mirror, Model No. CDMRAA0101E3 (ARQ2-UGDO), Serial No. SMP-77482, did fully conform to the selected requirements of FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247.

## 16. Certification

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247 test specifications. The data presented in this test report pertains to the EUT on the test date specified. Any electrical or mechanical modifications made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification.

17. Photographs of EUT





## 18. Equipment List

Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Due Date
APW0	PREAMPLIFIER	PLANAR ELECTRONICS	PE2-30-20G20R6G	PL2926/0646	20GHZ-26.5GHZ	9/24/2020	9/24/2021
APW3	PREAMPLIFIER	PLANAR ELECTRONICS	PE2-35-120-5R0-10-12	PL2924	1GHZ-20GHZ	3/23/2020	3/23/2021
CDX8	COMPUTER	ELITE	WORKSTATION			N/A	
NHG0	STANDARD GAIN HORN ANTENNA	NARDA	638	---	18-26.5GHZ	NOTE 1	
NTA3	BILOG ANTENNA	TESEQ	6112D	32853	25-1000MHz	10/20/2020	10/20/2021
NWQ0	DOUBLE RIDGED WAVEGUIDE ANTENNA	ETS LINDGREN	3117	66657	1GHZ-18GHZ	5/13/2020	5/13/2022
RBG0	EMI ANALYZER	ROHDE & SCHWARZ	ESW44	101533	10HZ-44GHZ	2/19/2020	2/19/2021
RBG2	EMI ANALYZER	ROHDE & SCHWARZ	ESW44	101591	2HZ-44GHZ	3/23/2020	3/23/2021
SAA1	AC POWER SOURCE/ANALYZER	HEWLETT PACKARD	6813A	3524A-00446	0-300VRMS, 1750VA	NOTE 1	
SES0	24VDC POWER SUPPLY	P-TRANS	FS-32024-1M	001	18-27VDC	NOTE 1	
SMAW	DC POWER SUPPLY	VOLTEQ	HY3020EX	02177910	30VDC/20A	NOTE 1	
WKA1	SOFTWARE, UNIVERSAL RCV EMI	ELITE	UNIV_RCV_EMI	1	---	I/O	
XPQ4	HIGH PASS FILTER	K&L MICROWAVE	11SH10-4800/X20000-O/O	1	4.8-20GHZ	9/6/2019	9/6/2021


N/A: Not Applicable

I/O: Initial Only

CNR: Calibration Not Required

NOTE 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.

### 19. Block Diagram of Test Setup



**Radiated Emissions Test Diagram**

20. Antenna Port Conducted Emissions Tests

Test Information	
Manufacturer	Chamberlain Group, Inc.
Product	Automotive Mirror
Model Number	CDMRAA0101E3 (ARQ2-UGDO)
Serial Number	SMP-77482
Mode	Tx

Test Setup Details	
Setup Format	Tabletop
Type of Test Site	EMC Bench
Note	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Occupied Channel Bandwidth	± 224kHz
Power Spectral Density	± 0.372Hz
RF Output Power, Conducted	± 0.349 dB
Unwanted Emissions, Conducted	± 1.39 dB
All Emissions Radiated Below 1GHz	± 2.629 dB
All Emissions Radiated Above 1GHz	± 2.710 dB
Temperature	± 0.165°C
Humidity	± 1.7% RH
DC and Low Frequency Voltages	± 0.115 Volts
Time	± 0.05%

Requirements
<p><u>6dB Bandwidth:</u></p> <p>Per FCC 15.247, Section (a)(2), and ISED RSS-247, Section 5.2(a), the minimum 6dB bandwidth shall be at least 500kHz for all systems using digital modulation techniques.</p>
<p><u>99% Bandwidth:</u></p> <p>RSS-Gen requires the measurement of the 99% bandwidth (Occupied Bandwidth).</p> <p>If measuring the maximum conducted (average) output power for FCC 15.247, the 99% bandwidth is used as the reference for power integration.</p>
<p><u>Peak Conducted Output Power:</u></p> <p>Per FCC 15.247, Section (b)(3) and ISED RSS-247, Section 5.4(d), for systems using digital modulation, the maximum peak conducted output power shall not exceed 1 watt.</p>
<p><u>Peak Power Spectral Density:</u></p> <p>Per FCC 15.247, Section (e), and ISED RSS-247, Section 5.2(b), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. If peak conducted output power was measured, the same method must be used to measure the power spectral density.</p>
<p><u>Low Band Edge:</u></p> <p>Per FCC 15.247, Section (d) and ISED RSS-247, Section 5.5, in any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. Attenuation below the general limits specified in FCC 15.209, Section (a) and ISED RSS-Gen is not required.</p>

Procedures

6dB Bandwidth:

C63.10-2013 Section 11.8 Option 1:

- 1) The following settings were employed on the EMI Test Receiver:
  - Center Frequency = Transmit Frequency of the EUT
  - Frequency Span = 2 x Occupied Channel Bandwidth
  - RBW = 100kHz
  - VBW = 3 x RBW
  - Detector Mode = Max Peak
  - Trace Mode = Max Hold
- 2) Allow the trace to stabilize.
- 3) Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- 4) Determine the 6dB down amplitude.
- 5) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope trace, such that each marker is at or slightly below the 6dB down amplitude determined in step d). If a marker is below this 6dB down amplitude value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers.

99% Bandwidth:

C63.10-2013 section 6.9.3:

- 1) The following settings were employed on the EMI Test Receiver:
  - Center Frequency = Transmit Frequency of the EUT
  - Frequency Span = Between 1.5 and 5 times the OBW
  - RBW = Between 1% to 5% of the OBW
  - VBW = Approximately 3 x RBW
  - Detector Mode = Max Peak
  - Trace Mode = Max Hold
- 2) Allow the trace to stabilize.
- 3) Use the 99% power bandwidth function of the EMI receiver.

Peak Conducted Output Power:

C63.10-2013 section 11.9.1.1:

- 1) The following settings were employed on the EMI Test Receiver:
  - Center Frequency = Transmit Frequency of the EUT
  - RBW =  $\geq$  DTS Bandwidth
  - VBW =  $\geq$  3 x RBW
  - Span =  $\geq$  3 x RBW
  - Sweep Time = Auto couple
  - Detector Mode = Max Peak
  - Trace Mode = Max Hold
- 2) Allow the trace to stabilize.
- 3) Use the peak marker function to determine the peak amplitude level.

Peak Power Spectral Density:

C63.10-20013 section 11.10.2:

- 1) The following settings were employed on the EMI Test Receiver:
  - Center Frequency = Transmit Frequency of the EUT
  - Frequency Span = At least 1.5 times the OBW
  - RBW =  $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$
  - VBW =  $\geq 3 \times \text{RBW}$
  - Detector Mode = Max Peak
  - Sweep Time = Auto Couple
  - Trace Mode = Max Hold
- 2) Allow the trace to stabilize.
- 3) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 4) If measured value exceeds requirement, then reduce RBW (but no less than 3kHz) and repeat.

Low Band Edge:


C63.10-2013 section 11.11:

- 1) Reference Level Measurement
  - Start Frequency = 2400MHz
  - Stop Frequency = 2483.5MHz
  - RBW = 100kHz
  - VBW =  $\geq 3 \times \text{RBW}$
  - Detector Mode = Max Peak
  - Trace Mode = Max Hold
  - Sweep Time = Auto
- 2) Allow the trace to stabilize and use the peak marker function to determine the maximum level.
- 3) Emission Level Measurement
  - Start Frequency = 2310MHz
  - Stop Frequency = 2400MHz
  - RBW = 100kHz
  - VBW =  $\geq 3 \times \text{RBW}$
  - Detector Mode = Max Peak
  - Trace Mode = Max Hold
  - Sweep Time = Auto
- 4) Allow the trace to stabilize and use the peak marker function to determine the maximum level.
- 5) The two sweeps were combined and plotted.
- 6) Ensure that the amplitude of all unwanted emissions is attenuated by at least 20dB.

### Minimum Emission Bandwidth 6dB (2402MHz; Change (10dBm); 5MHz)

#### 6dB Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2402.000000	0.900000	0.500000	---	2401.525000	2402.425000	2.7	PASS



### Occupied Channel Bandwidth 99% (2402MHz; Change (10dBm); 1MHz)

#### 99% Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
2402.000000	1.035000	---	---	2401.462500	2402.497500	PASS



### Peak output power (Sweep) (2402MHz; Change (10dBm); 1MHz)

#### Result

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2402.000000	4.9	30.0	PASS




— Connector 1      × Peak Connector 1

### Peak Power Spectral Density (2402MHz; Change (10dBm); 1MHz)

#### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.882500	-5.834	8.0	PASS



— Limit      — Sum Level      ◆ PSD



### Band Edge low (2402MHz; Change (10dBm); 1MHz)

#### Result


DUT Frequency (MHz)	Result
2402.000000	PASS

#### In Band Peak

Frequency (MHz)	Level (dBm)
2402.225000	4.5

#### Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-48.1	32.5	-15.5	PASS
2399.725000	-48.8	33.2	-15.5	PASS
2399.775000	-48.8	33.3	-15.5	PASS
2399.925000	-49.6	34.0	-15.5	PASS
2399.875000	-50.2	34.7	-15.5	PASS
2399.825000	-50.2	34.7	-15.5	PASS
2399.525000	-50.5	35.0	-15.5	PASS
2399.575000	-50.6	35.1	-15.5	PASS
2399.675000	-50.7	35.2	-15.5	PASS
2399.625000	-50.9	35.3	-15.5	PASS
2399.175000	-50.9	35.4	-15.5	PASS
2399.475000	-50.9	35.4	-15.5	PASS
2399.075000	-51.0	35.5	-15.5	PASS
2399.025000	-51.1	35.6	-15.5	PASS
2399.225000	-51.3	35.8	-15.5	PASS




— Limit    — Sum Level    × Fail

### Minimum Emission Bandwidth 6dB (2440MHz; Change (10dBm); 5MHz)

#### 6dB Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2440.000000	0.850000	0.500000	---	2439.525000	2440.375000	1.9	PASS



### Occupied Channel Bandwidth 99% (2440MHz; Change (10dBm); 1MHz)

#### 99% Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
2440.000000	1.040000	---	---	2439.447500	2440.487500	PASS



### Peak output power (Sweep) (2440MHz; Change (10dBm); 1MHz)

#### Result

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2440.000000	4.1	30.0	PASS




— Connector 1      × Peak Connector 1

### Peak Power Spectral Density (2440MHz; Change (10dBm); 1MHz)

#### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.867500	-6.404	8.0	PASS




— Limit      — Sum Level      ◆ PSD

### Minimum Emission Bandwidth 6dB (2480MHz; Change (10dBm); 5MHz)

#### 6dB Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2480.000000	1.215000	---	---	2479.362500	2480.577500	-6.5	PASS



### Occupied Channel Bandwidth 99% (2480MHz; Change (10dBm); 1MHz)

#### 99% Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
2480.000000	1.035000	---	---	2479.447500	2480.482500	PASS



### Peak output power (Sweep) (2480MHz; Change (10dBm); 1MHz)

#### Result

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2480.000000	3.7	30.0	PASS




— Connector 1      × Peak Connector 1

### Peak Power Spectral Density (2480MHz; Change (10dBm); 1MHz)

#### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.867500	-6.601	8.0	PASS



— Limit      — Sum Level      ◆ PSD

21. Radiated Emissions Tests

Test Information	
Manufacturer	Chamberlain Group, Inc.
Product	Automotive Mirror
Model Number	CDMRAA0101E3 (ARQ2-UGDO)
Serial Number	SMP-77482
Mode	Tx

Test Setup Details	
Setup Format	Tabletop
Type of Test Site	Semi-Anechoic Chamber
Type of Antennas Used	Below 1GHz: Bilog (or equivalent) Above 1GHz: Double-Ridged Waveguide (or equivalent)
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1
Radiated disturbance (electric field strength on an open area test site or alternative test site) (6 GHz – 18 GHz)	3.2
Radiated disturbance (electric field strength on an open area test site or alternative test site) (18 GHz – 26.5 GHz)	3.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (26.5 GHz – 40 GHz)	3.4

Requirements
--------------

Peak EIRP:

Per FCC 15.247, Section (b)(3) and ISED RSS-247, Section 5.4(d), for systems using digital modulation, the maximum peak conducted output power shall not exceed 1 watt.

Per FCC 15.247, Section (b)(4), and ISED RSS-247, Section 5.4(d), the conducted output power limit is based on the use of antennas with directional gains that do not exceed 6dBi. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

---

Radiated Emissions in Non-Restricted Bands:

Per FCC 15.247, Section (d), and ISED RSS-247, Section 5.5, in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated emissions measurement. Attenuation below the general limits specified in §15.209(a) is not required.

Radiated Emissions in Restricted Bands:

Per 15.247, Section (d), radiated emissions which fall in the restricted bands, as defined in FCC 15.205, Section (a), must comply with the radiated emission limits specified in FCC 15.209, Section (a).

Per ISED RSS-247, Section 3.3, radiated emissions which fall in the restricted bands, as defined in ISED RSS-Gen, Section 8.10, must comply with the radiated emission limits specified in RSS-Gen, Section 8.9.

---

High Band Edge:

Per 15.247, Section (d), radiated emissions which fall in the restricted band beginning at 2483.5MHz, as defined in FCC 15.205, Section (a), must comply with the radiated emission limits specified in FCC 15.209, Section (a).

Per ISED RSS-247, Section 3.3, radiated emissions which fall in the restricted band beginning at 2483.5MHz, as defined in ISED RSS-Gen, Section 8.10, must comply with the radiated emission limits specified in RSS-Gen, Section 8.9.

## Procedures

Peak EIRP:

C63.10 Annex G and Section 11.9.1.1:

The EUT was placed on a 1.5 meter high non-conductive stand and set to transmit. A double ridged waveguide antenna was placed at a test distance of 3 meters from the EUT.

- 1) The following settings were employed on the EMI Test Receiver:
  - Center Frequency = Transmit frequency of EUT
  - Span =  $\geq 3 \times \text{RBW}$
  - RBW =  $\geq \text{DTS Bandwidth}$
  - VBW =  $\geq 3 \times \text{RBW}$
  - Number of points in sweep =  $\geq (2 \times \text{span} / \text{RBW})$
  - Sweep time = Auto
  - Detector = Peak
  - Trace = Max hold
- 2) Allow trace to stabilize and use peak marker function to determine the peak amplitude level.
- 3) The equivalent power was determined using equation G.1 in C63.10 to convert field intensity levels measured at 3 meters into EIRP readings.

Radiated Emissions in Non-Restricted Bands:

C63.10-2013 Section 11.11

Radiated measurements were performed in a 32ft. x 20ft. x 14ft. high shielded enclosure. The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

Preliminary radiated emissions tests were performed to determine the emission characteristics of the EUT. For the preliminary test, a broadband measuring antenna was positioned at a 3 meter distance from the EUT. The entire frequency range from 30MHz to 25GHz was investigated using a peak detector function.

The final radiated emission tests were then manually performed over the frequency range of 30MHz to 25GHz.

- 1) The field strength of the fundamental was measured using a double ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand and set to transmit. A peak detector with a resolution bandwidth of 100kHz was used on the spectrum analyzer.
- 2) The field strengths of all of the harmonics not in the restricted band were then measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand and set to transmit. A peak detector with a resolution bandwidth of 100kHz was used on the spectrum analyzer.
- 3) To ensure that maximum or worst case emission levels at the fundamental and harmonics were measured, the following steps were taken when measuring the fundamental emissions and the spurious emissions:
  - a) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
  - b) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
  - c) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.



- d) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead, the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
- 4) All harmonics not in the restricted bands must be at least 20dB below levels measured at the fundamental. However, attenuation below the general limits specified in §15.209(a) is not required.

#### Radiated Emissions in Restricted Bands:

##### C63.10-2013 Section 11.12

- 1) The field strengths of all emissions below 1GHz were measured using a bi-log antenna. The bi-log antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on an 80 cm high non-conductive stand and set to transmit. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- 2) The field strengths of all emissions above 1GHz were measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand and set to transmit. A peak detector with a resolution bandwidth of 1 MHz was used on the spectrum analyzer.
- 3) To ensure that maximum or worst case emission levels were measured, the following steps were taken when taking all measurements:
  - a) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
  - b) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
  - c) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
  - d) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead, the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
- 4) For all radiated emissions measurements below 1GHz, if the peak reading is below the limits listed in 15.209(a), no further measurements are required. If, however, the peak readings exceed the limits listed in 15.209(a), then the emissions are remeasured using a quasi-peak detector.
- 5) For all radiated emissions measurements above 1GHz, the peak readings must comply with the 15.35(b) limits. 15.35(b) states that when average radiated emissions measurements are specified, there also is a limit on the peak level of the radiated emissions. The limit on the peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, all peak readings above 1GHz must be no greater than 20dB above the limits specified in 15.209(a).

---

#### High Band Edge:


##### C63.10-2013 section 6.10.5:

- 1) The EUT was set to transmit continuously at the channel closest to the high band-edge.
- 2) The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand and set to transmit. A peak detector with a resolution bandwidth of 1 MHz was used on the spectrum analyzer.
- 3) To ensure that maximum or worst case emission levels were measured, the following steps were taken when taking all measurements:

- a) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
  - b) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
  - c) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
- 4) The peak readings must comply with the 15.35(b) limits. 15.35(b) states that when average radiated emissions measurements are specified, there also is a limit on the peak level of the radiated emissions. The limit on the peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, all peak readings above 1 GHz must be no greater than 20 dB above the limits specified in 15.209(a).




Test Setup for Spurious Radiated Emissions, 30-1000MHz – Antenna Polarization Horizontal




Test Setup for Spurious Radiated Emissions, 30-1000MHz – Antenna Polarization Vertical




Test Setup for Spurious Radiated Emissions, 1GHz to 18GHz – Antenna Polarization Horizontal



Test Setup for Spurious Radiated Emissions, 1GHz to 18GHz – Antenna Polarization Vertical



Test Setup for Spurious Radiated Emissions, 18GHz to 25GHz – Antenna Polarization Horizontal




Test Setup for Spurious Radiated Emissions, 18GHz to 25GHz – Antenna Polarization Vertical


Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	RF Output Power – Peak EIRP
Mode	Tx
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dBμV)	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dBμV/m at 3m	EIRP (dBm)	Limit (dBm)	Margin (dBm)
2402.00	H	58.64	3.38	32.20	0.00	94.22	-0.78	36.00	-36.78
2402.00	V	58.47	3.38	32.20	0.00	94.05	-0.95	36.00	-36.95
2440.00	H	53.73	3.39	32.52	0.00	89.64	-5.36	36.00	-41.36
2440.00	V	58.50	3.39	32.52	0.00	94.41	-0.59	36.00	-36.59
2480.00	H	53.27	3.40	32.53	0.00	89.20	-5.80	36.00	-41.80
2480.00	V	56.48	3.40	32.53	0.00	92.41	-2.59	36.00	-38.59


Peak Total (dBμV/m) = Meter Reading (dBμV) + CBL Fac (dB) + Ant Fac (dB/m) + Pre Amp (dB)


EIRP (dBm) = Peak Total (dBμV/m) – 95dB












ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNITV RCV EMI RUN 2


UKA1 01/11/20





START = 18000


FREQUENCY MHz


STOP = 26500














ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNITV RCV EMI RUN 4

UKA1 01/11/20



START = 18000

FREQUENCY MHz


STOP = 26500

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIT: RCV EMI RUN 3


UKA1 01/11/20





START = 18000


FREQUENCY MHz

STOP = 26500










ELITE ELECTRONIC ENGINEERING Inc.  
Downers Grove, Ill. 60515

UKA1 01/11/20

UNITV RCV EMI RUN 5



START = 18000

FREQUENCY MHz


STOP = 26500

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIT: RCV EMI RUN 6

UKA1 01/11/20



START = 18000

FREQUENCY MHz

STOP = 26500



Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Peak Measurements in the Restricted Bands
Mode	Tx
Frequency Tested	2402MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dBμV/m at 3m	Peak Total μV/m at 3 m	Peak Limit μV/m at 3 m	Margin (dB)
4804.00	H	50.30		4.82	34.47	-40.22	49.36	293.89	5000.00	-24.62
4804.00	V	51.36		4.82	34.47	-40.22	50.42	332.04	5000.00	-23.56
12010.00	H	50.78	Ambient	6.87	38.62	-39.70	56.57	674.08	5000.00	-17.41
12010.00	V	50.40	Ambient	6.87	38.62	-39.70	56.19	645.22	5000.00	-17.79
19216.00	H	29.84	Ambient	2.21	40.38	-28.22	44.20	162.25	5000.00	-29.78
19216.00	V	29.77	Ambient	2.21	40.38	-28.22	44.13	160.95	5000.00	-29.85

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Average Measurements in the Restricted Bands
Mode	Tx
Frequency Tested	2402MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dB $\mu$ V)	Ambient	CBL Fac. (dB)	Ant Fac. (dB/m)	Pre Amp (dB)	Duty Cycle (dB)	Average Total dB $\mu$ V/m at 3m	Average Total $\mu$ V/m at 3 m	Average Limit $\mu$ V/m at 3 m	Margin (dB)
4804.00	H	38.03		4.82	34.47	-40.22	0.00	37.09	71.56	500.00	-16.89
4804.00	V	35.56		4.82	34.47	-40.22	0.00	34.62	53.85	500.00	-19.36
12010.00	H	35.34	Ambient	6.87	38.62	-39.70	0.00	41.13	113.95	500.00	-12.85
12010.00	V	35.32	Ambient	6.87	38.62	-39.70	0.00	41.11	113.69	500.00	-12.87
19216.00	H	17.08	Ambient	2.21	40.38	-28.22	0.00	31.44	37.34	500.00	-22.54
19216.00	V	17.06	Ambient	2.21	40.38	-28.22	0.00	31.42	37.26	500.00	-22.56

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Peak Measurements in the Non-Restricted Bands
Mode	Tx
Frequency Tested	2402MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dBμV/m at 3m	Peak Total μV/m at 3 m	Peak Limit μV/m at 3 m	Margin (dB)
2402.00	H	58.12		3.38	32.20	0.00	93.70	48413.28		
2402.00	V	57.81		3.38	32.20	0.00	93.39	46715.88		
7206.00	H	39.62	Ambient	5.89	35.67	-40.07	41.11	113.64	5000.00	-32.87
7206.00	V	39.06	Ambient	5.89	35.67	-40.07	40.55	106.55	5000.00	-33.43
9608.00	H	38.62	Ambient	6.27	36.65	-39.59	41.95	125.24	5000.00	-32.02
9608.00	V	38.71	Ambient	6.27	36.65	-39.59	42.04	126.54	5000.00	-31.93
14412.00	H	39.15	Ambient	7.43	39.82	-39.98	46.42	209.32	5000.00	-27.56
14412.00	V	39.20	Ambient	7.43	39.82	-39.98	46.47	210.52	5000.00	-27.51
16814.00	H	38.74	Ambient	7.72	43.44	-38.90	51.00	354.70	5000.00	-22.98
16814.00	V	39.50	Ambient	7.72	43.44	-38.90	51.76	387.14	5000.00	-22.22
21618.00	H	20.43	Ambient	2.25	40.56	-28.49	34.74	54.59	5000.00	-39.24
21618.00	V	21.23	Ambient	2.25	40.56	-28.49	35.54	59.86	5000.00	-38.44
24020.00	H	20.51	Ambient	2.24	40.62	-29.27	34.10	50.72	5000.00	-39.88
24020.00	V	21.49	Ambient	2.24	40.62	-29.27	35.08	56.78	5000.00	-38.90

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Peak Measurements in the Restricted Bands
Mode	Tx
Frequency Tested	2440MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dB $\mu$ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dB $\mu$ V/m at 3m	Peak Total $\mu$ V/m at 3 m	Peak Limit $\mu$ V/m at 3 m	Margin (dB)
4880.00	H	51.02		5.01	34.37	-40.25	50.15	321.63	5000.00	-23.83
4880.00	V	50.87		5.01	34.37	-40.25	50.00	316.12	5000.00	-23.98
7320.00	H	49.33	Ambient	5.84	35.69	-40.06	50.81	347.04	5000.00	-23.17
7320.00	V	49.80	Ambient	5.84	35.69	-40.06	51.28	366.34	5000.00	-22.70
12200.00	H	50.01	Ambient	7.25	38.88	-39.62	56.52	669.78	5000.00	-17.46
12200.00	V	50.50	Ambient	7.25	38.88	-39.62	57.01	708.65	5000.00	-16.97
19520.00	H	31.18	Ambient	2.22	40.39	-27.76	46.03	200.25	5000.00	-27.95
19520.00	V	30.79	Ambient	2.22	40.39	-27.76	45.64	191.46	5000.00	-28.34

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Average Measurements in the Restricted Bands
Mode	Tx
Frequency Tested	2440MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dB $\mu$ V)	Ambient	CBL Fac. (dB)	Ant Fac. (dB/m)	Pre Amp (dB)	Duty Cycle (dB)	Average Total dB $\mu$ V/m at 3m	Average Total $\mu$ V/m at 3 m	Average Limit $\mu$ V/m at 3 m	Margin (dB)
4880.00	H	36.89		5.01	34.37	-40.25	0.00	36.02	63.22	500.00	-17.96
4880.00	V	36.21		5.01	34.37	-40.25	0.00	35.34	58.46	500.00	-18.64
7320.00	H	34.32	Ambient	5.84	35.69	-40.06	0.00	35.80	61.64	500.00	-18.18
7320.00	V	34.36	Ambient	5.84	35.69	-40.06	0.00	35.84	61.93	500.00	-18.14
12200.00	H	35.28	Ambient	7.25	38.88	-39.62	0.00	41.79	122.87	500.00	-12.19
12200.00	V	35.27	Ambient	7.25	38.88	-39.62	0.00	41.78	122.73	500.00	-12.20
19520.00	H	15.87	Ambient	2.22	40.39	-27.76	0.00	30.72	34.36	500.00	-23.26
19520.00	V	15.82	Ambient	2.22	40.39	-27.76	0.00	30.67	34.16	500.00	-23.31

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Peak Measurements in the Non-Restricted Bands
Mode	Tx
Frequency Tested	2440MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dBµV)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dBµV/m at 3m	Peak Total µV/m at 3 m	Peak Limit µV/m at 3 m	Margin (dB)
2440.00	H	52.88		3.39	32.52	0.00	88.79	27512.99		
2440.00	V	58.08		3.39	32.52	0.00	93.99	50065.41		
9760.00	H	38.87	Ambient	6.37	36.87	-39.55	42.55	134.09	5006.54	-31.44
9760.00	V	38.45	Ambient	6.37	36.87	-39.55	42.13	127.76	5006.54	-31.86
14640.00	H	39.99	Ambient	7.32	40.17	-40.18	47.30	231.76	5006.54	-26.69
14640.00	V	39.56	Ambient	7.32	40.17	-40.18	46.87	220.57	5006.54	-27.12
17080.00	H	39.06	Ambient	7.64	42.96	-38.79	50.88	349.90	5006.54	-23.11
17080.00	V	39.39	Ambient	7.64	42.96	-38.79	51.21	363.45	5006.54	-22.78
21960.00	H	20.33	Ambient	2.20	40.58	-28.88	34.23	51.49	5006.54	-39.76
21960.00	V	20.47	Ambient	2.20	40.58	-28.88	34.37	52.33	5006.54	-39.62
24400.00	H	20.69	Ambient	2.22	40.63	-29.29	34.26	51.62	5006.54	-39.73
24400.00	V	20.49	Ambient	2.22	40.63	-29.29	34.06	50.45	5006.54	-39.93

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Peak Measurements in the Restricted Bands
Mode	Tx
Frequency Tested	2480MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dBµV)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dBµV/m at 3m	Peak Total µV/m at 3 m	Peak Limit µV/m at 3 m	Margin (dB)
4960.00	H	50.86		5.21	34.34	-40.28	50.13	320.85	5000.00	-23.85
4960.00	V	51.41		5.21	34.34	-40.28	50.68	341.82	5000.00	-23.30
7440.00	H	49.76	Ambient	5.90	35.64	-40.05	51.25	365.17	5000.00	-22.73
7440.00	V	50.44	Ambient	5.90	35.64	-40.05	51.93	394.91	5000.00	-22.05
12400.00	H	48.53	Ambient	7.29	39.01	-39.54	55.29	581.48	5000.00	-18.69
12400.00	V	48.86	Ambient	7.29	39.01	-39.54	55.62	603.99	5000.00	-18.36
19840.00	H	30.44	Ambient	2.23	40.40	-28.04	45.04	178.56	5000.00	-28.94
19840.00	V	30.84	Ambient	2.23	40.40	-28.04	45.44	186.98	5000.00	-28.54
22320.00	H	31.59	Ambient	2.23	40.59	-28.84	45.56	189.75	5000.00	-28.42
22320.00	V	31.34	Ambient	2.23	40.59	-28.84	45.31	184.36	5000.00	-28.67

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Average Measurements in the Restricted Bands
Mode	Tx
Frequency Tested	2480MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dBµV)	Ambient	CBL Fac. (dB)	Ant Fac. (dB/m)	Pre Amp (dB)	Duty Cycle (dB)	Average Total dBµV/m at 3m	Average Total µV/m at 3 m	Average Limit µV/m at 3 m	Margin (dB)
4960.00	H	36.67		5.21	34.34	-40.28	0.00	35.94	62.63	500.00	-18.04
4960.00	V	38.83		5.21	34.34	-40.28	0.00	38.10	80.32	500.00	-15.88
7440.00	H	34.60	Ambient	5.90	35.64	-40.05	0.00	36.09	63.75	500.00	-17.89
7440.00	V	34.61	Ambient	5.90	35.64	-40.05	0.00	36.10	63.83	500.00	-17.88
12400.00	H	33.95	Ambient	7.29	39.01	-39.54	0.00	40.71	108.53	500.00	-13.27
12400.00	V	33.96	Ambient	7.29	39.01	-39.54	0.00	40.72	108.65	500.00	-13.26
19840.00	H	15.99	Ambient	2.23	40.40	-28.04	0.00	30.59	33.83	500.00	-23.39
19840.00	V	16.02	Ambient	2.23	40.40	-28.04	0.00	30.62	33.95	500.00	-23.36
22320.00	H	16.41	Ambient	2.23	40.59	-28.84	0.00	30.38	33.05	500.00	-23.60
22320.00	V	16.43	Ambient	2.23	40.59	-28.84	0.00	30.40	33.13	500.00	-23.58



Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Radiated Spurious Emissions – Peak Measurements in the Non-Restricted Bands
Mode	Tx
Frequency Tested	2480MHz
Notes	

Freq. (MHz)	Ant Pol	Meter Reading (dB $\mu$ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dB $\mu$ V/m at 3m	Peak Total $\mu$ V/m at 3 m	Peak Limit $\mu$ V/m at 3 m	Margin (dB)
2480.00	H	52.49		3.40	32.53	0.00	88.42	26367.68		
2480.00	V	55.86		3.40	32.53	0.00	91.79	38866.19		
9920.00	H	39.57	Ambient	6.46	37.03	-39.52	43.54	150.39	5000.00	-30.44
9920.00	V	38.96	Ambient	6.46	37.03	-39.52	42.93	140.19	5000.00	-31.05
14880.00	H	38.73	Ambient	7.40	40.39	-40.40	46.12	202.40	5000.00	-27.86
14880.00	V	38.67	Ambient	7.40	40.39	-40.40	46.06	201.01	5000.00	-27.92
17360.00	H	39.64	Ambient	7.65	42.37	-39.10	50.55	336.89	5000.00	-23.43
17360.00	V	40.18	Ambient	7.65	42.37	-39.10	51.09	358.50	5000.00	-22.89
24800.00	H	23.62	Ambient	2.21	40.64	-29.32	37.15	72.01	5000.00	-36.83
24800.00	V	22.71	Ambient	2.21	40.64	-29.32	36.24	64.85	5000.00	-37.74

Test Details	
Manufacturer	Chamberlain Group, Inc.
EUT	Automotive Mirror
Model No.	CDMRAA0101E3 (ARQ2-UGDO)
Serial No.	SMP-77482
Test	Band-Edge
Mode	Tx
Frequency Tested	2480MHz
Notes	

### BAND EDGE – HIGH - PEAK

Freq. (MHz)	Ant Pol	Meter Reading (dB $\mu$ V)	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Peak Total dB $\mu$ V/m at 3m	Peak Total $\mu$ V/m at 3 m	Peak Limit $\mu$ V/m at 3 m	Margin (dB)
2483.50	H	18.45	3.40	32.52	0.00	54.37	523.23	5000.00	-19.61
2483.50	V	20.06	3.40	32.52	0.00	55.98	629.78	5000.00	-18.00

### BAND EDGE – HIGH - AVERAGE

Freq. (MHz)	Ant Pol	Meter Reading (dB $\mu$ V)	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle (dB)	Average Total dB $\mu$ V/m at 3m	Average Total $\mu$ V/m at 3 m	Average Limit $\mu$ V/m at 3 m	Margin (dB)
2483.50	H	7.49	3.40	32.52	0.00	0.00	43.41	148.15	500.00	-10.57
2483.50	V	7.58	3.40	32.52	0.00	0.00	43.50	149.69	500.00	-10.48

## 22. Scope of Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELITE ELECTRONIC ENGINEERING, INC.  
1516 Centre Circle  
Downers Grove, IL 60515  
Robert Bugielski (QA Manager) Phone: 630 495 9770 ext. 168  
Email: [rbugielski@elitetest.com](mailto:rbugielski@elitetest.com)  
Craig Fanning (EMC Lab Manager) Phone: 630 495 9770 ext. 112  
Email: [cfanning@elitetest.com](mailto:cfanning@elitetest.com)  
Stanley Dolecki (Automotive Team Leader) Phone: 630 495 9770 ext. 103  
Email: [sdolecki@elitetest.com](mailto:sdolecki@elitetest.com)  
Website: [www.elitetest.com](http://www.elitetest.com)

## ELECTRICAL

Valid to: June 30, 2021

Certificate Number: 1786.01

In recognition of the successful completion of the A2LA Accreditation Program evaluation process, accreditation is granted to this laboratory to perform the following automotive electromagnetic compatibility and other electrical tests:

**Test Technology:****Test Method(s) <sup>1</sup>:*****Transient Immunity***

ISO 7637-2 (including emissions); ISO 7637-3;  
ISO 16750-2:2012, Sections 4.6.3 and 4.6.4;  
CS-11979, Section 6.4; CS.00054, Section 5.9;  
EMC-CS-2009.1 (CI220); FMC1278 (CI220, CI221, CI222);  
GMW 3097, Section 3.5;  
SAE J1113-11; SAE J1113-12

***Electrostatic Discharge (ESD)***

ISO 10605 (2001, 2008);  
CS-11979 Section 7.0; CS.00054, Section 5.10;  
EMC-CS-2009.1 (CI 280); FMC1278 (CI280); SAE J1113-13;  
GMW 3097 Section 3.6

***Conducted Emissions***

CISPR 25 (2002, 2008), Sections 6.2 and 6.3;  
CISPR 25 (2016), Sections 6.3 and 6.4;  
CS-11979, Section 5.1; CS.00054, Sections 5.6.1 and 5.6.2;  
GMW 3097, Section 3.3.2;  
EMC-CS-2009.1 (CE 420); FMC1278 (CE420, CE421)

***Radiated Emissions Anechoic***

CISPR 25 (2002, 2008), Section 6.4;  
CISPR 25 (2016), Section 6.5;  
CS-11979, Section 5.3; CS.00054, Section 5.6.3;  
GMW 3097, Section 3.3.1;  
EMC-CS-2009.1 (RE 310); FMC1278 (RE310)

***Vehicle Radiated Emissions***

CISPR 12; ICES-002

(A2LA Cert. No. 1786.01) Revised 01/10/2020



Page 1 of 8

5202 Presidents Court, Suite 220 | Frederick, MD 21703-8515 | Phone: 301 644 3248 | Fax: 240 454 9449 | [www.A2LA.org](http://www.A2LA.org)

<b><u>Test Technology:</u></b>	<b><u>Test Method(s) <sup>1</sup>:</u></b>
<i>Bulk Current Injection (BCI)</i>	ISO 11452-4; CS-11979, Section 6.1; CS.00054, Section 5.8.1; GMW 3097, Section 3.4.1; SAE J1113-4; EMC-CS-2009.1 (RI112); FMC1278 (RI112)
<i>Bulk Current Injections (BCI) (Closed Loop Method)</i>	ISO 11452-4; SAE J1113-4
<i>Radiated Immunity Anechoic (Including Radar Pulse)</i>	ISO 11452-2; ISO 11452-5; CS-11979, Section 6.2; CS.00054, Section 5.8.2; GMW 3097, Section 3.4.2; EMC-CS-2009.1 (RI114); FMC1278 (RI114); SAE J1113-21
<i>Radiated Immunity Magnetic Field</i>	ISO 11452-8
<i>Radiated Immunity Reverb</i>	ISO/IEC 61000-4-21; GMW 3097, Section 3.4.3; EMC-CS-2009.1 (RI114); FMC1278 (RI114); ISO 11452-11
<i>Radiated Immunity (Portable Transmitters)</i>	ISO 11452-9; EMC-CS-2009.1 (RI115); FMC1278 (RI115)
<i>Vehicle Radiated Immunity (ALSE)</i>	ISO 11451-2
<i>Electrical Loads</i>	ISO 16750-2, Sections 4.2, 4.3, 4.4, 4.5, 4.6, 4.7, 4.8, 4.9, 4.11, and 4.12
<i>Dielectric Withstand Voltage</i>	MIL-STD-202, Method 301; EIA-364-20D
<i>Insulation Resistance</i>	MIL-STD-202, Method 302; SAE/USCAR-2, Revision 6, Section 5.5.1; EIA-364-21D
<i>Contact Resistance</i>	MIL-STD-202, Method 307; SAE/USCAR-2, Revision 6, Section 5.3.1; EIA/ECA-364-23C; USCAR21-3 Section 4.5.3
<i>DC Resistance</i>	MIL-STD-202, Method 303
<i>Contact Chatter</i>	MIL-STD-202, Method 310; SAE/USCAR-2, Revision 6, Section 5.1.9
<i>Voltage Drop</i>	SAE/USCAR-2, Revision 6, Section 5.3.2; USCAR21-3 Section 4.5.6

**Test Technology:**

**Test Method(s) <sup>1</sup>:**

**Emissions**

Radiated and Conducted  
(3m Semi-anechoic chamber,  
up to 40 GHz)

47 CFR, FCC Part 15 B (using ANSI C63.4:2014);  
47 CFR, FCC Part 18 (using FCC MP-5:1986);  
ICES-001; ICES-003; ICES-005;  
IEC/CISPR 11, Ed. 4.1 (2004-06); AS/NZS CISPR 11 (2004);  
IEC/CISPR 11 Ed 5 (2009-05) + A1 (2010);  
KN 11 (2008-5) with RRL Notice No. 2008-3 (May 20, 2008);  
CISPR 11; EN 55011; KN 11; CNS 13803 (1997, 2003);  
CISPR 14-1; EN 55014-1; AS/NZS CISPR 14.1; KN 14-1;  
IEC/CISPR 22 (1997); EN 55022 (1998) + A1(2000);  
EN 55022 (1998) + A1(2000) + A2(2003); EN 55022 (2006);  
IEC/CISPR 22 (2008-09); AS/NZS CISPR 22 (2004);  
AS/NZS CISPR 22, 3rd Edition (2006); KN 22 (up to 6 GHz);  
CNS 13438 (up to 6 GHz); VCCI V-3 (up to 6 GHz);  
CISPR 32; EN 55032; KN 32

Current Harmonics

IEC 61000-3-2; EN 61000-3-2; KN 61000-3-2

Flicker and Fluctuations

IEC 61000-3-3; EN 61000-3-3; KN 61000-3-3

**Immunity**

Electrostatic Discharge

IEC 61000-4-2, Ed. 1.2 (2001);  
IEC 61000-4-2 (1995) + A1(1998) + A2(2000);  
EN 61000-4-2 (1995); EN 61000-4-2 (2009-05);  
KN 61000-4-2 (2008-5); RRL Notice No. 2008-4 (May 20, 2008);  
IEC 61000-4-2; EN 61000-4-2; KN 61000-4-2;  
IEEE C37.90.3 2001

Radiated Immunity

IEC 61000-4-3 (1995) + A1(1998) + A2(2000);  
IEC 61000-4-3, Ed. 3.0 (2006-02);  
IEC 61000-4-3, Ed. 3.2 (2010);  
KN 61000-4-3 (2008-5); RRL Notice No. 2008-4 (May 20, 2008);  
IEC 61000-4-3; EN 61000-4-3; KN 61000-4-3;  
IEEE C37.90.2 2004

Electrical Fast Transient/Burst

IEC 61000-4-4, Ed. 2.0 (2004-07); IEC 61000-4-4, Ed. 2.1 (2011);  
IEC 61000-4-4 (1995) + A1(2000) + A2(2001);  
KN 61000-4-4 (2008-5); RRL Notice No. 2008-5 (May 20, 2008);  
IEC 61000-4-4; EN 61000-4-4; KN 61000-4-4

Surge

IEC 61000-4-5 (1995) + A1(2000);  
IEC 61000-4-5, Ed 1.1 (2005-11);  
EN 61000-4-5 (1995) + A1(2001);  
KN 61000-4-5 (2008-5); RRL Notice No. 2008-4 (May 20, 2008);  
IEC 61000-4-5; EN 61000-4-5; KN 61000-4-5;  
IEEE C37.90.1 2012

<u>Test Technology:</u>	<u>Test Method(s) <sup>1</sup>:</u>
<b>Immunity (cont'd)</b>	
Conducted Immunity	IEC 61000-4-6 (1996) + A1(2000); IEC 61000-4-6, Ed 2.0 (2006-05); IEC 61000-4-6 Ed. 3.0 (2008); KN 61000-4-6 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); EN 61000-4-6 (1996) + A1(2001); IEC 61000-4-6; EN 61000-4-6; KN 61000-4-6
Power Frequency Magnetic Field Immunity	IEC 61000-4-8 (1993) + A1(2000); IEC 61000-4-8 (2009); EN 61000-4-8 (1994) + A1(2000); KN 61000-4-8 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); IEC 61000-4-8; EN 61000-4-8; KN 61000-4-8
Voltage Dips, Short Interrupts, and Line Voltage Variations	IEC 61000-4-11, Ed. 2 (2004-03); KN 61000-4-11 (2008-5); RRL Notice No. 2008-4 (May 20, 2008); IEC 61000-4-11; EN 61000-4-11; KN 61000-4-11
Ring Wave	IEC 61000-4-12, Ed. 2 (2006-09); EN 61000-4-12:2006; IEC 61000-4-12; EN 61000-4-12; KN 61000-4-12
Generic and Product Specific EMC Standards	IEC/EN 61000-6-1; AS/NZS 61000-6-1; KN 61000-6-1; IEC/EN 61000-6-2; AS/NZS 61000-6-2; KN 61000-6-2; IEC/EN 61000-6-3; AS/NZS 61000-6-3; KN 61000-6-3; IEC/EN 61000-6-4; AS/NZS 61000-6-4; KN 61000-6-4; EN 50130-4; IEC 61326-1; IEC/CISPR 14-2; EN 55014-2; AS/NZS CISPR 14.2; KN 14-2; IEC/CISPR 24; AS/NZS CISPR 24; EN 55024; KN 24; IEC 60601-1-2; JIS T0601-1-2
<i>TxRx EMC Requirements</i>	EN 301 489-1; EN 301 489-3; EN 301 489-9; EN 301 489-17; EN 301 489-19; EN 301 489-52;
<i>European Radio Test Standards</i>	ETSI EN 300 086-1; ETSI EN 300 086-2; ETSI EN 300 113-1; ETSI EN 300 113-2; ETSI EN 300 220-1; ETSI EN 300 220-2; ETSI EN 300 330-1; ETSI EN 300 330-2; ETSI EN 300 440-1; ETSI EN 300 440-2; ETSI EN 300 422-1; ETSI EN 300 422-2; ETSI EN 300 328; ETSI EN 301 893; ETSI EN 301 511; ETSI EN 301 908-1; ETSI EN 908-2; ETSI EN 908-13; ETSI EN 301 413; ETSI EN 302 502

**Test Technology:**

**Test Method(s) <sup>1</sup>:**

*Canadian Radio Tests*

RSS-102 (RF Exposure Evaluation only); RSS-111; RSS-112; RSS-117; RSS-119; RSS-123; RSS-125; RSS-127; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-137; RSS-139; RSS-140; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-191; RSS-192; RSS-194; RSS-195; RSS-196; RSS-197; RSS-199; RSS-210; RSS-211; RSS-213; RSS-215; RSS-216; RSS-220; RSS-222; RSS-236; RSS-238; RSS-243; RSS-244; RSS-246; RSS-247; RSS-251; RSS-252; RSS-287; RSS-288; RSS-310; RSS-GEN

*Mexico Radio Tests*

IFT-008; NOM-208-SCFI

*Japan Radio Tests*

Radio Law No. 131, Ordinance of MPT No. 37, 1981, MIC Notification No. 88:2004, Table No. 22-11; ARIB STD-T66, Regulation 18

*Taiwan Radio Tests*

LP-0002

*Australia/New Zealand Radio Tests*

AS/NZS 4268; Radiocommunications (Short Range Devices) Standard (2014)

*Hong Kong Radio Tests*

HKCA 1039 Issue 6; HKCA 1042; HKCA 1033 Issue 7; HKCA 1061; HKCA 1008; HKCA 1043; HKCA 1057; HKCA 1073

*Korean Radio Test Standards*

KN 301 489-1; KN 301 489-3; KN 301 489-9; KN 301 489-17; KN 301 489-52

*Unlicensed Radio Frequency Devices  
(3 Meter Semi-Anechoic Room)*

47 CFR FCC Part 15C, 15D, 15E, 15F, 15G, 15H (using ANSI C63.10:2013, ANSI C63.17:2013 and FCC KDB 905462 D02 (v02))

*Licensed Radio Service Equipment*

47 CFR FCC Parts 20, 22, 24, 25, 27, 30, 73, 74, 80, 87, 90, 95, 96, 97, 101; ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015;

*OTA (Over the Air) Performance*

GSM, GPRS, EGPRS  
UMTS (W-CDMA)  
LTE including CAT M1  
A-GPS for UMTS/GSM  
LTS A-GPS, A-GLONASS,  
SIB8/SIB16  
Large Device/Laptop/Tablet Testing  
Integrated Device Testing  
WiFi 802.11 a/b/g/n/ac

CTIA Test Plan for Wireless Device Over-the-Air Performance (Method for Measurement for Radiated Power and Receiver Performance) V3.8.2;  
CTIA Test Plan for RF Performance Evaluation of WiFi Mobile Converged Devices V2.1.0

**Test Technology:**

**Test Method(s)<sup>1</sup>:**

***Electrical Measurements and Simulation***

**AC Voltage / Current**

(1mV to 5kV) 60 Hz  
(0.1V to 250V) up to 500 MHz  
(1µA to 150A) 60 Hz

FAA AC 150/5345-10H

FAA AC 150/5345-43J

FAA AC 150/5345-44K

FAA AC 150/5345-46E

**DC Voltage / Current**

(1mV to 15-kV) / (1µA to 10A)

FAA AC 150/5345-47C

FAA EB 67D

**Power Factor / Efficiency / Crest Factor**

(Power to 30kW)

**Resistance**

(1mΩ to 4000MΩ)

**Surge**

(Up to 10 kV / 5 kA) (Combination Wave and Ring Wave)

**On the following products and materials:**

Telecommunications Terminal Equipment (TTE), Radio Equipment, Network Equipment, Information Technology Equipment (ITE), Automotive Electronic Equipment, Automotive Hybrid Electronic Devices, Maritime Navigation and Radio Communication Equipment and Systems, Vehicles, Boats and Internal Combustion Engine Driven Devices, Automotive, Aviation, and General Lighting Products, Medical Electrical Equipment, Motors, Industrial, Scientific and Medical (ISM) Radio-Frequency Equipment, Household Appliances, Electric Tools, Low-voltage Switchgear and Control gear, Programmable Controllers, Electrical Equipment for Measurement, Control and Laboratory Use, Base Materials, Power and Data Transmission Cables and Connectors

<sup>1</sup> When the date, revision or edition of a test method standard is not identified on the scope of accreditation, the laboratory is expected to be using the current version within one year of the date of publication, per part C., Section 1 of A2LA R101 - *General Requirements - Accreditation of ISO-IEC 17025 Laboratories.*

Testing Activities Performed in Support of FCC Declaration of Conformity and Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1<sup>2</sup>

<b>Rule Subpart/Technology</b>	<b>Test Method</b>	<b>Maximum Frequency (MHz)</b>
<b><u>Unintentional Radiators</u></b> Part 15B	ANSI C63.4:2014	40000
<b><u>Industrial, Scientific, and Medical Equipment</u></b> Part 18	FCC MP-5 (February 1986)	40000
<b><u>Intentional Radiators</u></b> Part 15C	ANSI C63.10:2013	40000
<b><u>Unlicensed Personal Communication Systems Devices</u></b> Part 15D	ANSI C63.17:2013	40000





Testing Activities Performed in Support of FCC Declaration of Conformity and Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1<sup>2</sup>

<b>Rule Subpart/Technology</b>	<b>Test Method</b>	<b>Maximum Frequency (MHz)</b>
<u>U-NII without DFS Intentional Radiators</u> Part 15E	ANSI C63.10:2013	40000
<u>U-NII with DFS Intentional Radiators</u> Part 15E	FCC KDB 905462 D02 (v02)	40000
<u>UWB Intentional Radiators</u> Part 15F	ANSI C63.10:2013	40000
<u>BPL Intentional Radiators</u> Part 15G	ANSI C63.10:2013	40000
<u>White Space Device Intentional Radiators</u> Part 15H	ANSI C63.10:2013	40000
<u>Commercial Mobile Services (FCC Licensed Radio Service Equipment)</u> Parts 22 (cellular), 24, 25 (below 3 GHz), and 27	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>General Mobile Radio Services (FCC Licensed Radio Service Equipment)</u> Parts 22 (non-cellular), 90 (below 3 GHz), 95, 97, and 101 (below 3 GHz)	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Citizens Broadband Radio Services (FCC Licensed Radio Service Equipment)</u> Part 96	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Maritime and Aviation Radio Services</u> Parts 80 and 87	ANSI/TIA-603-E; ANSI C63.26:2015	40000
<u>Microwave and Millimeter Bands Radio Services</u> Parts 25, 30, 74, 90 (above 3 GHz), 97 (above 3 GHz), and 101	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Broadcast Radio Services</u> Parts 73 and 74 (below 3 GHz)	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000



Testing Activities Performed in Support of FCC Declaration of Conformity and Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1<sup>2</sup>

<b>Rule Subpart/Technology</b>	<b>Test Method</b>	<b>Maximum Frequency (MHz)</b>
<u>Signal Boosters</u> Part 20 (Wideband Consumer Signal Boosters, Provider-specific signal boosters, and Industrial Signal Boosters) Section 90.219	ANSI C63.26:2015	40000

<sup>2</sup>Accreditation does not imply acceptance to the FCC equipment authorization program. Please see the FCC website (<https://apps.fcc.gov/oetcf/eas/>) for a listing of FCC approved laboratories.





## Accredited Laboratory

A2LA has accredited

### ELITE ELECTRONIC ENGINEERING INC.

Downers Grove, IL

for technical competence in the field of

### Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 8<sup>th</sup> day of August 2019.



Vice President, Accreditation Services  
For the Accreditation Council  
Certificate Number 1786.01  
Valid to June 30, 2021

*For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.*