

Note: This would be a plastic label with a permanent adhesive and affixed on the right side of the device.

LiftMaster VEHICULAR GATE OPENER
UL 325 Usage Class/Clase de Uso: I, II, III

SER:
DATE:
MODEL: SL600UL
CYCLES: CONTINUOUS
INPUTS: 120Vac; 2A; 60Hz
MAX LOAD: 1323bs/26ft

TO OPEN THE GATE MANUALLY:
1) Remove the front cover
2) Insert the key in the lock
3) Turn key 90° clockwise
4) Pull and turn the release lever 90°

PARA ABRIR LA PORTON MANUALMENTE:
1) Retire la cubierta frontal
2) Inserte la llave en la cerradura
3) Gire la llave 90° en el sentido de las agujas del reloj
4) Tire y gire la palanca de liberación 90°

May be patent protected. See www.liftmaster.com/patents
Country of Origin: China

UL LISTED

CHAMBERLAIN GROUP LLC
OAK BROOK, IL, 60523 USA

WARNING / AVERTISSEMENT

To reduce the risk of SERIOUS INJURY or DEATH, disconnect power BEFORE servicing operator. This operator to be serviced ONLY by a Trained Gate System Technician.
Para reducir el riesgo de LESIONES GRAVES o MUERTE, desconecte la energía ANTES de dar servicio al operador. Este operador debe ser atendido ÚNICAMENTE por un Técnico Capacitado en Sistemas des Puertas.

NOTICE: This device complies with Part 15 of the FCC rules and Innovation, Science and Economic Development Canada license-exempt RSSs. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

PART NO.: 041-0521-000
FCC ID: HBWN519

