

# Exposure Evaluation

***hd30*<sup>TM</sup> 900 PS**

**Single-Band Low Power Remote Unit**

FCCID: HCOHD301PSNACI1A

Date: Aug 11, 2017

Model No.: HD30-1-PS-NA-C-I1N



**Dali Wireless, Inc.**  
535 Middlefield Road, Suite 280  
Menlo Park, CA 94025  
<http://www.daliwireless.com>

**CONFIDENTIAL AND PROPRIETARY**

This document contains information proprietary to Dali Wireless. Any disclosure, use or duplication of this document or of any of the information contained herein for other than the specific purpose for which it was disclosed is expressly prohibited, except as Dali Wireless may otherwise agree to in writing.

© Copyright 2016 Dali Wireless. All Rights Reserved

## RF Exposure Evaluation

According to FCC Part 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. More information on evaluating compliance with these limits can be found in the FCC’s OST/OET Bulletin Number 65, “Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation”.

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the occupational/controlled exposures is F/300 for an average time of 6 minutes.

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the general population/uncontrolled exposures is F/1500 for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain antenna as shown in the following example:

The highest expected output power may be 1 dB above the rated 30 dBm. For an output level of 31 dBm with an indoor antenna gain of 5 dB, the EIRP is 36 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 936 MHz is 0.624 mW/cm<sup>2</sup>.

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm <sup>2</sup> )	Safe Distance (cm)
31	5	3981	0.624	23

### RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP / 4\pi S)}$$

Where:

**d** = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

**S** = Allowable Power Density Limit (mW/cm<sup>2</sup>)

**EIRP** = Equivalent isotropically radiated power (mW) = 10<sup>[TX Power (dBm) + Ant Gain (dBi)/10]</sup>

As shown above, the minimum safe distance where the MPE limit is reached is 23 cm from the unit with a 5 dBi antenna and no distribution loss.

If the antenna will be positioned closer to end users than 23 cm, then the installer must calculate the safe distance for a given installation using the formulas provided.