

# Exposure Evaluation

## *hd33*<sup>TM</sup> 150 PS Single-Band Medium Power Remote Unit

FCCID: HCOHD331PSD20A

Date: February 1, 2018

Model No.: hd33-1-PS-D-20-1N-D0-001



**Dali Wireless, Inc.**  
535 Middlefield Road, Suite 280  
Menlo Park, CA 94025  
<http://www.daliwireless.com>

### **CONFIDENTIAL AND PROPRIETARY**

This document contains information proprietary to Dali Wireless. Any disclosure, use or duplication of this document or of any of the information contained herein for other than the specific purpose for which it was disclosed is expressly prohibited, except as Dali Wireless may otherwise agree to in writing.

© Copyright 2018 Dali Wireless. All Rights Reserved

## RF Exposure Evaluation

According to FCC Part 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. More information on evaluating compliance with these limits can be found in the FCC’s OST/OET Bulletin Number 65, “Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation”.

In the Frequency Range of 30 to 300 MHz, the maximum power density limit for the occupational/controlled exposures is 1 mW/cm<sup>2</sup> for an average time of 6 minutes.

In the Frequency Range of 30 to 300 MHz, the maximum power density limit for the general population/uncontrolled exposures is 0.2 mW/cm<sup>2</sup> for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain antenna. However a typical indoor antenna is shown in the following example:

The highest conducted output power is 37 dBm but we need to back off to meet FCC Part 90.219 rules. The ERP can’t exceed 37dBm, so for a set output level of 34 dBm with an indoor antenna gain of 3 dBi, the EIRP is 37 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 152 MHz is 0.2 mW/cm<sup>2</sup>.

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm <sup>2</sup> )	Safe Distance (cm)
34	3	5012	0.2	45

### RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP/4\pi S)}$$

Where:

**d** = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

**S** = Allowable Power Density Limit (mW/cm<sup>2</sup>)

**EIRP** = Equivalent isotropically radiated power (mW) = 10 <sup>[TX Power (dBm) + Ant Gain (dBi)]/10</sup>

As shown above, the minimum safe distance where the MPE limit is reached is 45 cm from with a 3 dBi antenna and no distribution loss.

If the antenna will be positioned closer to end users than 45 cm, then the installer must calculate the safe distance for a given installation using the formulas provided.