

Exposure Evaluation

***hd33*TM 800-900**

Dual-Band Medium Power Remote Unit

FCCID: HCOHD332PSBC10A

Date: March 15, 2018



Dali Wireless, Inc.
535 Middlefield Road, Suite 280
Menlo Park, CA 94025
<http://www.daliwireless.com>

CONFIDENTIAL AND PROPRIETARY

This document contains information proprietary to Dali Wireless. Any disclosure, use or duplication of this document or of any of the information contained herein for other than the specific purpose for which it was disclosed is expressly prohibited, except as Dali Wireless may otherwise agree to in writing.

© Copyright 2017 Dali Wireless. All Rights Reserved

RF Exposure Evaluation

According to FCC Part 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. More information on evaluating compliance with these limits can be found in the FCC’s OST/OET Bulletin Number 65, “Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation”.

Band 1: 800 MHz

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the occupational/controlled exposures is $f/300$ mW/cm² for an average time of 6 minutes.

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the general population/uncontrolled exposures is $f/1500$ mW/cm² for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain outdoor/indoor antenna. However a typical indoor antenna is shown in the following example:

The highest expected output power is 33.6 dBm at 856MHz. For an output level of 33.6 dBm with an indoor antenna gain of 3 dBi, the EIRP is 36.6 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 856 MHz is 0.571 mW/cm².

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm ²)	Safe Distance (cm)
33.6	3	4571	0.571	26

RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP/4\pi S)}$$

Where:

d = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

S = Allowable Power Density Limit (mW/cm²)

EIRP = Equivalent isotropically radiated power (mW) = $10^{[TX\ Power\ (dBm) + Ant\ Gain\ (dBi)]/10}$

As shown above, the minimum safe distance where the MPE limit is reached is 26 cm from the unit with a 3 dBi antenna and no distribution loss.

If the antenna will be positioned closer to end users than 26 cm, then the installer must calculate the safe distance for a given installation using the formulas provided.

Band 2: 900 MHz

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the occupational/controlled exposures is $f/300 \text{ mW/cm}^2$ for an average time of 6 minutes.

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the general population/uncontrolled exposures is $f/1500 \text{ mW/cm}^2$ for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain indoor/outdoor antenna. However a typical indoor antenna is shown in the following example:

The highest expected output power is 33.2 dBm at 937.5MHz. For an output level of 33.2 dBm with an indoor antenna gain of 3 dBi, the EIRP is 36.2 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 937.5 MHz is 0.625 mW/cm^2 .

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm^2)	Safe Distance (cm)
33.2	3	4169	0.625	24

RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP/4\pi S)}$$

Where:

d = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

S = Allowable Power Density Limit (mW/cm^2)

EIRP = Equivalent isotropically radiated power (mW) = $10^{[TX \text{ Power (dBm)} + \text{Ant Gain (dBi)}]/10}$

As shown above, the minimum safe distance where the MPE limit is reached is 24 cm from the unit with a 3 dBi antenna and no distribution loss.

If the antenna will be positioned closer to end users than 24 cm, then the installer must calculate the safe distance for a given installation using the formulas provided.