

Exposure Evaluation

***hd37*TM UHF-800 PS**

Dual-Band Medium Power Remote Unit

FCCID: HCOHD372PSBG21A

Date: April 14, 2021



Dali Wireless, Inc.
535 Middlefield Road, Suite 280
Menlo Park, CA 94025
<http://www.daliwireless.com>

RF Exposure Evaluation

According to FCC Part 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. More information on evaluating compliance with these limits can be found in the FCC’s OST/OET Bulletin Number 65, “Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation”.

In the Frequency Range of 30 to 300 MHz, the maximum power density limit for the occupational/controlled exposures is 1 mW/cm² for an average time of 6 minutes.

In the Frequency Range of 30 to 300 MHz, the maximum power density limit for the general population/uncontrolled exposures is 0.2 mW/cm² for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain outdoor/indoor antenna. However a typical indoor antenna is shown in the following example:

The highest conducted output power is 37 dBm but we might need to back off to meet FCC Part 90.219 rules depending on the cable loss from hd37 remote unit to the antenna. The ERP can’t exceed 37dBm, so for a set output level of 34 dBm with an indoor antenna gain of 3 dBi, the EIRP is 37 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 150 MHz is 0.2 mW/cm².

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm ²)	Safe Distance (cm)
34	3	5012	0.2	45

RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP/4\pi S)}$$

Where:

d = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

S = Allowable Power Density Limit (mW/cm²)

EIRP = Equivalent isotropically radiated power (mW) = 10 ^{[TX Power (dBm) + Ant Gain (dBi)]/10}

As shown above, the minimum safe distance where the MPE limit is reached is 45 cm from a 3 dBi gain antenna for the 150MHz band. Using the same formula, the minimum safe distances are 37cm and 27cm for the 400MHz band and the 800MHz band respectively assuming same antenna gain.

If the antenna will be positioned closer to end users than 45 cm, then the installer must calculate the power back off required for a given installation using the formulas provided.