

Exposure Evaluation

*hd37*TM 700-800-900 PS Tri-Band Medium Power Remote Unit

FCCID: HCOHD373PSABC21A

Date: January 10, 2020



Dali Wireless, Inc.
535 Middlefield Road, Suite 280
Menlo Park, CA 94025
<http://www.daliwireless.com>

CONFIDENTIAL AND PROPRIETARY

This document contains information proprietary to Dali Wireless. Any disclosure, use or duplication of this document or of any of the information contained herein for other than the specific purpose for which it was disclosed is expressly prohibited, except as Dali Wireless may otherwise agree to in writing.

© Copyright 2020 Dali Wireless. All Rights Reserved

RF Exposure Evaluation

According to FCC Part 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. More information on evaluating compliance with these limits can be found in the FCC’s OST/OET Bulletin Number 65, “Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation”.

In the Frequency Range of 300 to 1500 MHz, the maximum power density limit for the occupational / controlled exposures is 0.5 mW/cm² for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain outdoor/indoor antenna. However a typical indoor antenna is shown in the following example:

The highest conducted output power is 37 dBm but we might need to back off to meet FCC Part 90.219 rules depending on the cable loss from hd37 remote unit to the antenna. The ERP can’t exceed 37dBm, so for a set output level of 34 dBm with an indoor antenna gain of 3 dBi, the EIRP is 37 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 700MHz is 0.515 mW/cm².

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm ²)	Safe Distance (cm)
34	3	5012	0.515	28

RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP/4\pi S)}$$

Where:

d = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

S = Allowable Power Density Limit (mW/cm²)

EIRP = Equivalent isotopically radiated power (mW) = 10^[TX Power (dBm) + Ant Gain (dBi)/10]

As shown above, the minimum safe distance where the MPE limit is reached is 28 cm from a 3 dBi gain antenna for the 700MHz band. Using the same formula, the minimum safe distances are 27cm and 26 cm for the 800MHz band and the 900MHz band respectively assuming same antenna gain.

If the antenna will be positioned closer to end users than 28 cm, then the installer must calculate the power back off required for a given installation using the formulas provided.