

Exposure Evaluation

*hd37*TM 150-450-800 PS Tri-Band Medium Power Remote Unit

FCCID: HCOHD373PSFHB21A

Date: November 21, 2019



Dali Wireless, Inc.
535 Middlefield Road, Suite 280
Menlo Park, CA 94025
<http://www.daliwireless.com>

CONFIDENTIAL AND PROPRIETARY

This document contains information proprietary to Dali Wireless. Any disclosure, use or duplication of this document or of any of the information contained herein for other than the specific purpose for which it was disclosed is expressly prohibited, except as Dali Wireless may otherwise agree to in writing.

© Copyright 2019 Dali Wireless. All Rights Reserved

RF Exposure Evaluation

According to FCC Part 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. More information on evaluating compliance with these limits can be found in the FCC’s OST/OET Bulletin Number 65, “Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation”.

In the Frequency Range of 30 to 300 MHz, the maximum power density limit for the occupational/controlled exposures is 1 mW/cm² for an average time of 6 minutes.

In the Frequency Range of 30 to 300 MHz, the maximum power density limit for the general population/uncontrolled exposures is 0.2 mW/cm² for an average time of 30 minutes.

The antenna connected to the product is specific to the deployment. The worst case scenario occurs when using a very high gain outdoor/indoor antenna. However a typical indoor antenna is shown in the following example:

The highest conducted output power is 37 dBm but we might need to back off to meet FCC Part 90.219 rules depending on the cable loss from hd37 remote unit to the antenna. The ERP can’t exceed 37dBm, so for a set output level of 34 dBm with an indoor antenna gain of 3 dBi, the EIRP is 37 dBm.

The maximum power density safe exposure level for general population/uncontrolled exposure of 30 minutes for the frequency of 150 MHz is 0.2 mW/cm².

Conducted Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (mW)	Power Density Limit Allowed (mW/cm ²)	Safe Distance (cm)
34	3	5012	0.2	45

RF Exposure Evaluation Distance Calculation

$$d = \sqrt{(EIRP/4\pi S)}$$

Where:

d = Distance to the center of radiation of the antenna (cm) for the allowable Power Density

S = Allowable Power Density Limit (mW/cm²)

EIRP = Equivalent isotropically radiated power (mW) = 10 ^{[TX Power (dBm) + Ant Gain (dBi)]/10}

As shown above, the minimum safe distance where the MPE limit is reached is 45 cm from a 3 dBi gain antenna for the 150MHz band. Using the same formula, the minimum safe distances are 35cm and 27cm for the 450MHz band and the 800MHz band respectively assuming same antenna gain.

If the antenna will be positioned closer to end users than 45 cm, then the installer must calculate the power back off required for a given installation using the formulas provided.