

RF Exposure Evaluation

FCCID: **HCOT43DSCN2B**

**700, 850 Outdoor Remote Unit, Dual-Band
Dali Wireless Inc.**

Date: November 12, 2012

Report No.: T43-PSC-PAN.1.0

Labs: 8618 Commerce Court, Burnaby, BC, V5A 4N6, Canada



Daryl Meerkerk
Manager



Guihua Sophie Piao
Test Engineer

RF Exposure Evaluation

Test Standard

FCC CFR47, Part 1, 1307 (b), 1310

FCC CFR47, Part 2, Subpart J 1091

FCC 1.1310 states the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Section 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Section 2.1093 of this chapter. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation".

Frequency Range (MHZ)	Electric Field Strength (V/m)	Magnetic Field Strength (A/M)	Power Density (mW/cm²)	Average Time, min
<i>(A) Limits for Occupational/Control Exposures</i>				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
<i>(B) Limits for General Population/Uncontrolled Exposures</i>				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

EUT Operating Condition

The maximum exposure is at 881 MHz.

RF exposure evaluation distance calculation

881 MHz radio with 21 dBi antenna

Freq (MHz)	Output Power to Antenna (dBm)	Antenna Gain (dBi)	r (cm)
871.5	43.4	21	391.3
881.5	43.7	21	401.4
891.5	43.4	21	391.7

As shown above, the minimum distance where the MPE limit is reached is 401.4 cm.