

MPE Evaluation

FCC

Maximum exposure limits from CFR 47, FCC Part 1.1310:

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Occupational/Controlled		
General Population/uncontrolled		1

Transmitter	Frequency	Power EIRP	EIRP +10% for tolerance	Power Density	Limit at specified distance	Result
	MHz	mW	mW	mW/cm ²	mW/cm ²	
1	2402	10.55	11.61	0.002310	1.00	PASS
1	2440	19.49	21.44	0.004267	1.00	PASS
1	2480	16.11	17.72	0.003527	1.00	PASS

Distance	20	cm
----------	----	----

Note: The user's manual will stipulate that a 20cm distance from the user is to be maintained.

EIRP values in mW were multiplied by 1.1 to account for a 10% tolerance in the conducted power

The power density is calculated as shown below:

$$S = (P \times G) / (4 \times \pi \times d^2) - \text{used to calculate exposure at 20 cm}$$

$$d = \sqrt{(S / (P \times G) \times 4 \times \pi)} - \text{used to calculate minimum distance to meet limits}$$

S= power density

P = transmitter conducted power (in mW)

G = antenna numeric gain

D = distance to radiation center (20 cm)

IC / ISED

Using RSS-102, Issue 5, Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{(0.6834)}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance). In these cases, the information contained in the RF exposure

Table 1 - Power Density Calculations, IC/ISED

Transmitter	Frequency	Peak Power EIRP	Peak Power* EIRP	Average Power (conducted) +10% for tolerance	Exemption Limit	Compliant
	MHz	mW	mW	mW	W	
1	2402	10.55	11.61	0.3376	2.676	YES
1	2440	19.49	21.44	0.6237	2.705	YES
1	2480	16.11	17.72	0.0516	2.736	YES

*Duty cycle is 3.2 % as specified in test report