

Inovonics – EN1252 RF Exposure Information

9. RF Exposure Information:

Calculation for compliance with MPE requirements (47CFR2.1091) is done using a worst-case transmitter power of 250mW, assumption of a unity gain antenna, and an exposure limit of 0.6mW/cm² (f/1500mW/cm² at 20cm per 47CFR1.1310) for general applications. This device is not carried or worn by the end user. It has an extremely low duty cycle and a low rate of transmission that dramatically reduces the average power level that could pose an exposure hazard.

The transmitter is typically activated by the opening or closing of a door or window. In addition to these change-of-state transmissions, the transmitter is configured to transmit a supervisory message once every 3 minutes. The averaging interval specified in Table 1(B) of 47CFR1.1310 is 30 minutes. For the purposes of this calculation, it is assumed that ten supervisory and five change-of- state messages will be sent in the 30 minute interval. Each supervisory message consists of 3 redundant packets, and each change of state message contains 21 packets, for a total of 135 packets in the 30 minute interval. A packet is typically 20ms in length.

The worst-case power density at a distance of 20cm is then,

$$250mW \times \frac{135 \text{ packets}}{30 \text{ min}} \times \frac{20ms}{\text{packet}} \times \frac{1 \text{ min}}{60 \times 10^3 \text{ ms}} \times \frac{1}{4\pi (20cm)^2} = 74.6 \frac{nW}{cm^2}$$

This is well below the 0.6mW/cm² limit.

C1212010-001 X1

PROPRIETARY & CONFIDENTIAL DOCUMENTATION © 2013

The information contained in this document is proprietary in nature and is confidential to and the sole property of Inovonics Corporation. This document may not to be reproduced or redistributed without prior written permission from Inovonics Corporation.