

## MPE Evaluation

### FCC

Maximum exposure limits from CFR 47, FCC Part 1.1310:

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Occupational/Controlled						
General Population/uncontrolled		YES				
E1501v3						
Frequency	EIRP	EIRP +10% for tolerance	Power Density	Limit at specified distance	% of limit	Result
MHz	mW	mW	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>		
902.4	111.43	122.57	0.024397	0.601600	4.06%	PASS
914.8	88.31	97.14	0.019335	0.609867	3.17%	PASS
927.6	75.34	82.87	0.016496	0.618400	2.67%	PASS

Distance	20	cm
----------	----	----

Note: The user's manual will stipulate that a 20cm distance from the user is to be maintained.

Power values in mW were multiplied by 1.1 to account for a 10% tolerance

The power density is calculated as shown below:

$$S = (P \times G) / (4 \times \pi \times D^2) - \text{used to calculate exposure at 20 cm}$$

$$EIRP = P \times G, \text{ measured as field strength}$$

$$d = \sqrt{(S / (P \times G) \times 4 \times \pi)} - \text{used to calculate minimum distance to meet limits}$$

S= power density

P = transmitter conducted power (in mW)

D = distance to radiation center (20 cm)

## IC / ISED

### Using RSS-102, Issue 5, Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{(0.6834)}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance). In these cases, the information contained in the RF exposure

Table 1 - Power Density Calculations, IC/ISED

Frequency	Peak EIRP*	Peak EIRP +10% for tolerance	Exemption Limit	Compliant
MHz	mW	mW	mW	
902.4	111.43	122.57	1370.853	YES
915.0	88.31	97.14	1383.689	YES
927.6	75.34	82.87	1396.901	YES

\*Peak power was used to show compliance, as it would be equal to or higher than the source-based, time averaged maximum EIRP. Antenna gain is 0 dBi.