



MEASUREMENT REPORT

FCC PART 15.225 / NFC 13.56MHz

FCC ID: HD5-EDA710

Applicant: Honeywell International Inc
Honeywell Safety and Productivity Solutions

Application Type: Class II Permissive Change

Product: Tablet

Model No.: EDA71-0

Brand Name: Honeywell

FCC Classification: Part 15 Low Power Communication Device Transmitter (DXX)

FCC Rule Part(s): Part 15 Subpart C (Section 15.225)

Test Procedure(s): ANSI C63.10-2013

Test Date: May 11 ~ 19, 2021

Reviewed By:

Jame Yuan

Jame Yuan

Approved By:

Robin Wu

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2105RSU001-U1	Rev. 01	Initial Report	05-19-2021	Valid

This is to request for Class II permissive change for FCC ID: HD5-EDA710 originally granted on 2019-05-29.

This application is based on:

1. Replace NFC chipset model name from NQ310 to PN553, two chipsets are identical, meet pin-for-pin requirement, the unique difference is chipset model different.
2. There is not any change in design, circuitry or construction for this device.
3. We assess all test items of FCC Section 15.225.

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Testing Facility	5
2. PRODUCT INFORMATION	6
2.1. Equipment Description.....	6
2.2. Radio Specification	6
2.3. Test Mode	6
2.4. Test Configuration and Software.....	7
2.5. EMI Suppression Device(s)/Modifications.....	7
2.6. Test Environment Condition.....	7
3. ANTENNA REQUIREMENTS	8
4. TEST EQUIPMENT CALIBRATION DATE	9
5. MEASUREMENT UNCERTAINTY	13
6. TEST RESULT	14
6.1. Summary	14
6.2. In-band Emission.....	15
6.2.1. Test Limit	15
6.2.2. Test Procedure Used	15
6.2.3. Test Setting.....	15
6.2.4. Test Setup.....	16
6.2.5. Test Result.....	17
6.3. Out-band Emission	18
6.3.1. Test Limit	18
6.3.2. Test Procedure Used	18
6.3.3. Test Setting.....	18
6.3.4. Test Setup.....	19
6.3.5. Test Result.....	20
6.4. Occupied Bandwidth.....	21
6.4.1. Test Limit	21
6.4.2. Test Procedure Used	21
6.4.3. Test Setting.....	21
6.4.4. Test Setup.....	21
6.4.5. Test Result.....	22

6.5.	Frequency Tolerance.....	23
6.5.1.	Test Limit	23
6.5.2.	Test Procedure Used	23
6.5.3.	Test Setting.....	23
6.5.4.	Test Setup.....	24
6.5.5.	Test Result.....	25
6.6.	AC Conducted Emissions Measurement.....	26
6.6.1.	Test Limit	26
6.6.2.	Test Setup.....	26
6.6.3.	Test Result.....	27
7.	CONCLUSION.....	29
	Appendix A - Test Setup Photograph	30
	Appendix B - EUT Photograph.....	31

1. General Information

1.1. Applicant

Honeywell International Inc
Honeywell Safety and Productivity Solutions
9680 Old Bailes Road, Fort Mill, SC 29707 United States

1.2. Manufacturer

Honeywell International Inc
Honeywell Safety and Productivity Solutions
9680 Old Bailes Road, Fort Mill, SC 29707 United States

1.3. Testing Facility

<input checked="" type="checkbox"/>	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou – Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou – SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
	A2LA: 3628.01 FCC: CN1166 VCCI: R-20025, G-20034, C-20020, T-20020 CNAS: L10551 ISED: CN0001
<input type="checkbox"/>	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 FCC: CN1284 CNAS: L10551 ISED: CN0105
<input type="checkbox"/>	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2 nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725 FCC: 291082, TW3261 ISED: TW3261

2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	Tablet
Model No.:	EDA71-0
Brand Name:	Honeywell
Wi-Fi Specification:	802.11a/b/g/n/ac
Bluetooth Version:	v4.2 dual mode
NFC:	13.56MHz
Accessories	
USB Adapter:	Model No.: ADS-12B-06 05010E Input Power: 100 - 240V ~ 50/60Hz, Max. 0.3A Output Power: 5VDC 2.0A
USB Charging Cup:	M/N: EDA70-UC
Battery1#:	Model No.: BAT-EDA50US Capacitance: 15.2Wh, 4000mAh Rated Voltage: 3.8V
Battery2#:	Model No.: EDA70-EXT Capacitance: 33.45Wh, 8850mAh Rated Voltage: 3.78V

2.2. Radio Specification

Frequency Range	13.56MHz
Channel Number	1
Type of modulation	ASK
Antenna Type	Loop Antenna

Note 1: For other features of this EUT, test report will be issued separately.


Note 2: All product information is provided by the manufacturer.

2.3. Test Mode

Test Mode
Mode 1: Transmit by NFC

2.4. Test Configuration and Software

The device was tested per the guidance ANSI C63.10-2013 that was used to reference the appropriate EUT setup for radiated spurious emissions and AC line conducted emission testing.



2.5. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.6. Test Environment Condition

Ambient Temperature	15 ~ 35 °C
Relative Humidity	20 ~75 %RH

3. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **Tablet** is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. TEST EQUIPMENT CALIBRATION DATE

Conducted Emission (WZ-SR2)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2022/01/12
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2021/09/09
Thermal Hygrometer	testo	608-H1	MRTSUE06404	1 year	2021/07/26
Shielding Room	MIX-BEP	Chamber-SR2	MRTSUE06215	N/A	N/A

Conducted Emission (SIP-SR2)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06613	1 year	2021/07/02
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2021/09/09
Thermal Hygrometer	testo	608-H1	MRTSUE06621	1 year	2021/12/03

Radiated Emission (WZ-AC1)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2022/01/12
PXA Signal Analyzer	Keysight	N9030B	MRTSUE06395	1 year	2021/08/30
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/10/22
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2021/08/08
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2021/09/27
Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06597	1 year	2021/12/14
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2021/11/14
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
Thermal Hygrometer	testo	608-H1	MRTSUE06403	1 year	2021/07/26

Radiated Emission (WZ-AC2)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
MXE EMI Receiver	Keysight	N9038A	MRTSUE06125	1 year	2021/07/02
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/10/22
Bilog Period Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2021/05/26
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2021/10/25
Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06597	1 year	2021/12/14
Broadband Coaxial Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2021/11/14
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
Thermal Hygrometer	Minggao	ETH529	MRTSUE06170	1 year	2021/12/08

Radiated Emission (SIP-AC1)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06612	1 year	2021/07/02
EXA Signal Analyzer	Keysight	N9010B	MRTSUE06559	1 year	2021/07/23
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/10/22
Bilog Period Antenna	Schwarzbeck	VULB9168	MRTSUE06645	1 year	2021/08/30
Double Ridged Horn Antenna	R&S	HF907	MRTSUE06610	1 year	2021/08/30
Preamplifier	EMCI	EMC051845SE	MRTSUE06600	1 year	2021/11/09
Thermal Hygrometer	testo	608-H1	MRTSUE06620	1 year	2021/12/03
Anechoic Chamber	RIKEN	SIP-AC1	MRTSUE06554	1 year	2021/12/24

Radiated Emission (SIP-AC2)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06613	1 year	2021/07/02
MXA Signal Analyzer	Keysight	N9020B	MRTSUE06604	1 year	2021/09/26
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/10/22
Bilog Period Antenna	Schwarzbeck	VULB9168	MRTSUE06646	1 year	2021/08/30
Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06648	1 year	2021/11/26
Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06599	1 year	2021/11/26
Preamplifier	EMCI	EMC051845SE	MRTSUE06644	1 year	2021/11/09
Preamplifier	EMCI	EMC184045SE	MRTSUE06602	1 year	2021/10/12
Thermal Hygrometer	testo	608-H1	MRTSUE06624	1 year	2021/12/03
Anechoic Chamber	RIKEN	SIP-AC2	MRTSUE06781	1 year	2021/12/24

Radiated Emission (SIP-AC3)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06612	1 year	2021/07/02
EXA Signal Analyzer	Keysight	N9010B	MRTSUE06559	1 year	2021/07/23
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/10/22
Bilog Period Antenna	Schwarzbeck	VULB9168	MRTSUE06647	1 year	2021/08/08
Double Ridged Horn Antenna	R&S	HF907	MRTSUE06611	1 year	2021/09/13
Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06598	1 year	2021/11/26
Preamplifier	EMCI	EMC012645SE	MRTSUE06642	1 year	2022/01/15
Preamplifier	EMCI	EMC184045SE	MRTSUE06641	1 year	2022/01/15
Thermal Hygrometer	testo	608-H1	MRTSUE06622	1 year	2021/12/03
Anechoic Chamber	RIKEN	SIP-AC3	MRTSUE06782	1 year	2021/12/24

Conducted Test Equipment (WZ-TR3)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2022/04/13
EXA Signal Analyzer	Keysight	N9010B	MRTSUE06607	1 year	2022/01/07
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2022/04/13
Power Meter	Agilent	U2021XA	MRTSUE06030	1 year	2021/10/22
USB wideband power sensor	Keysight	U2021XA	MRTSUE06446	1 year	2021/08/30
USB wideband power sensor	Keysight	U2021XA	MRTSUE06447	1 year	2021/08/08
Bluetooth Test Set	Anritsu	MT8852B-042	MRTSUE06389	1 year	2021/06/11
Audio Analyzer	Agilent	U8903B	MRTSUE06143	1 year	2021/06/11
Modulation Analyzer	HP	HP8901A	MRTSUE06098	1 year	2021/09/26
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2021/10/20
DC Power Supply	GWINSTEK	DPS-3303C	MRTSUE06064	N/A	N/A
Temperature & Humidity Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2021/10/22
Thermal Hygrometer	testo	608-H1	MRTSUE06401	1 year	2021/07/26

Conducted Test Equipment (SIP-SR5)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2022/04/13
PXA Signal Analyzer	Keysight	N9030B	MRTSUE06395	1 year	2021/08/30
USB wideband power sensor	Agilent	U2021XA	MRTSUE06595	1 year	2021/09/26
USB wideband power sensor	Agilent	U2021XA	MRTSUE06596	1 year	2021/09/26
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2021/10/20
Bluetooth Test Set	Anritsu	MT8852B-042	MRTSUE06389	1 year	2021/06/11
Temperature Chamber	BAOYT	BYG-408CS	MRTSUE06847	1 year	2022/02/23
Thermal Hygrometer	testo	622	MRTSUE06629	1 year	2021/11/25

Software	Version	Function
EMI Software	V3	EMI Test Software

5. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
Radiated Disturbance
Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): Horizontal: 9kHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 9kHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.78dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 1.13dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.28%

6. TEST RESULT

6.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.225 (a), (b), (c)	In-Band Emission	15.848 μ V/m @ 30m 13.553 ~ 13.567 MHz 334 μ V/m @ 30m 13.410 ~ 13.553 MHz 13.567 ~ 13.710 MHz 106 μ V/m @ 30m 13.110 ~ 13.410 MHz 13.710 ~ 14.010 MHz	Radiated	Pass	Section 6.2
15.225(d)	Out-Band Emission	Emissions outside of the specified band (13.110~14.010 MHz) must meet the radiated limits detailed in 15.209		Pass	Section 6.3
2.1049	20dB Bandwidth 99% Bandwidth	N/A		Pass	Section 6.4
15.225(e)	Frequency Stability Tolerance	$\pm 0.01\%$ of operating frequency		Pass	Section 6.5
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 6.6

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

6.2. In-band Emission

6.2.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.225		
Frequency (MHz)	Distance (m)	Level (μ V/m)
13.553 ~13.567	30	15848
13.410 ~13.553, 13.567 ~13.710	30	334
13.110 ~13.410, 13.710 ~14.010	30	106

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dB μ V/m) = 20 log E field strength (μ V/m)

6.2.2. Test Procedure Used


ANSI C63.10-2013 - Section 6.4.7

6.2.3. Test Setting

1. RBW = 9kHz
2. VBW = 3 * RBW
3. Detector = Peak
4. Trace mode = Max hold
5. Sweep = Auto couple
6. Allow the trace to stabilize

6.2.4. Test Setup

9kHz ~ 30MHz Test Setup:



6.2.5. Test Result

Test Engineer	Tommy Tang	Test Date	2021/05/11
Test Mode	Mode1	Test Site	WZ-AC1

Frequency (MHz)	Reading Level (dB μ V/m)	Factor (dB)	Measure Level (dB μ V/m)	Limit (@3m) (dB μ V/m)	Margin [dB]
Face On					
13.35	25.65	20.56	46.20	80.51	-34.31
13.46	26.16	20.60	46.76	90.47	-43.71
13.56	30.21	20.80	51.01	123.99	-72.98
13.67	25.22	20.65	45.87	90.47	-44.60
13.77	22.63	20.69	43.32	80.51	-37.19
Face Off					
13.35	20.61	20.56	41.16	80.51	-39.35
13.45	22.42	20.60	43.01	90.47	-47.46
13.56	24.49	20.80	45.29	123.99	-78.70
13.67	20.18	20.65	40.83	90.47	-49.64
13.77	17.40	20.69	38.09	80.51	-42.42

Note 1: All measurements were performed using a loop antenna. The antenna was positioned in two orthogonal (face on and face off) and the position with the highest emission level was recorded.

Note 2: Measurements were tested at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear extrapolation factor (40 dB/decade) as specified in &15.31(f)(2).

Extrapolation Factor = $20 \cdot \log(30/3)^2 = 40$ dB

For example, Limit (@3m) = $20 \cdot \log(106) + 40 = 80.51$ dB μ V/m

Note 3: All measurements were recorded using an EMI test receiver employing a peak detector.

6.3. Out-band Emission

6.3.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level ($\mu\text{V}/\text{m}$)
0.009 - 0.490	300	2400/F (kHz)
0.490 - 1.705	30	24000/F (kHz)
1.705 - 30	30	30
30 - 88	3	100
88 - 216	3	150
216 - 960	3	200
Above 960	3	500

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dB $\mu\text{V}/\text{m}$) = 20 log E field strength ($\mu\text{V}/\text{m}$)

6.3.2. Test Procedure Used


ANSI C63.10-2013 - Section 6.5.4

6.3.3. Test Setting


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 9kHz for emission below 30MHz and 100kHz for emission between 30MHz and 1GHz
3. VBW = 3 * RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.3.4. Test Setup

9kHz ~ 30MHz Test Setup:



30MHz ~ 1GHz Test Setup:



6.3.5. Test Result

Test Engineer	Tommy Tang	Test Date	2021/05/11
Test Mode	Mode1	Test Site	WZ-AC1

Out-Band Emission Below 30MHz						
Frequency (MHz)	Reading Level (dB μ V/m)	Factor (dB)	Measure Level (dB μ V/m)	Limit(@3m) (dB μ V/m)	Margin (dB)	Detector
Face On						
2.12	13.79	20.18	33.97	69.54	-35.57	Peak
Face Off						
3.70	15.02	20.31	35.33	69.54	-34.21	Peak

Out-Band Emission Above 30MHz							
Polarization	Frequency (MHz)	Reading Level (dB μ V/m)	Factor (dB)	Measure Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
H	40.67	10.76	17.44	28.20	40.00	-11.80	Peak
H	67.83	5.88	16.29	22.17	40.00	-17.83	Peak
H	94.51	2.99	12.45	15.44	43.50	-28.06	Peak
H	141.07	0.88	17.49	18.37	43.50	-25.13	Peak
H	284.63	5.10	16.96	22.06	46.00	-23.94	Peak
H	774.96	5.84	26.14	31.98	46.00	-14.02	Peak
V	40.67	21.73	17.44	39.17	40.00	-0.83	Peak
V	67.83	14.07	16.29	30.36	40.00	-9.64	Peak
V	94.51	6.05	12.45	18.50	43.50	-25.00	Peak
V	121.67	4.30	15.85	20.15	43.50	-23.35	Peak
V	709.49	5.57	25.06	30.63	46.00	-15.37	Peak
V	905.43	5.22	27.22	32.44	46.00	-13.56	Peak

Note 1: Below 30MHz measurement was performed using a loop antenna. The antenna was positioned in two orthogonal (face on and face off) and the position with the highest emission level was recorded.

Note 2: Measurements were tested at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear extrapolation factor (40 dB/decade) as specified in &15.31(f)(2). Extrapolation Factor = $40 \cdot \log^{(30/3)} = 40$ dB

For example, Limit (@3m) = $20 \cdot \log(30) + 40 = 69.54$ dB μ V/m

Note 3: All measurements were recorded using an EMI test receiver employing a peak detector.

6.4. Occupied Bandwidth

6.4.1. Test Limit

The occupied bandwidth is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequency.


6.4.2. Test Procedure Used

ANSI C63.10-2013 - Section 6.9.3

6.4.3. Test Setting

1. Spectrum analyzer frequency is set to the nominal EUT channel center frequency.
2. Set RBW \geq 1% to 5% of the OBW
3. VBW = Approximately three times RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation
5. Detector = Peak
6. Trace mode = Max hold
7. Sweep = Auto couple
8. Allow the trace to stabilize
9. Using 99% power bandwidth function of the instrument and report the measured bandwidth


6.4.4. Test Setup



6.4.5. Test Result

Test Engineer	Tommy Tang	Test Date	2021/05/19
Test Mode	Mode1	Test Site	WZ-AC1

Frequency (MHz)	20dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
13.56	121.0	174.8



Note: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

6.5. Frequency Tolerance

6.5.1. Test Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.

6.5.2. Test Procedure Used

ANSI C63.10-2013 - Section 6.8

6.5.3. Test Setting

Frequency Stability Under Temperature Variations:


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change. For hand-carried battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

6.5.4. Test Setup



6.5.5. Test Result

Test Engineer	Tommy Tang	Test Date	2021/05/12
Test Mode	Mode1	Test Site	WZ-TR3

Reference Voltage: 3.80Vdc					
Deviation Limit: +/- 0.01% = 1356Hz					
Voltage (%)	Power Battery	Temp (°C)	Freq. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100	3.80	-20	13560930	930	0.69
		-10	13560940	940	0.69
		0	13560930	930	0.69
		+10	13560930	930	0.69
		+20	13560930	930	0.69
		+30	13560940	940	0.69
		+40	13560940	940	0.69
		+50	13560940	940	0.69
Battery Upper	4.35	+ 20	13560940	940	0.69
Battery Endpoint	3.45	+ 20	13560940	940	0.69

Note 1: Frequency Tolerance (ppm) = {[Measured Frequency (MHz) - Declared Frequency (MHz)] / Declared Frequency (MHz)} * 10⁶.

Note 2: Battery upper voltage is 4.35Vdc, battery endpoint voltage is 3.45Vdc, which are declared by the manufacturer.

6.6. AC Conducted Emissions Measurement


6.6.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.6.2. Test Setup



6.6.3. Test Result

Site: WZ-SR2	Time: 2021/05/14 - 14:25
Limit: FCC_Part15.207_CE_AC Power	Engineer: Antony Yang
Probe: ENV216_101683_Filter Off_With Adapter	Polarity: Line
EUT: Tablet	Power: AC 120V/60Hz
Test Mode: NFC Operation	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.198	33.531	23.891	-30.163	63.694	9.639	QP
2			0.198	15.568	5.928	-38.126	53.694	9.639	AV
3		*	0.490	39.210	29.541	-16.958	56.168	9.669	QP
4			0.490	24.930	15.261	-21.238	46.168	9.669	AV
5			1.494	31.772	22.067	-24.228	56.000	9.705	QP
6			1.494	17.182	7.477	-28.818	46.000	9.705	AV
7			2.714	30.456	20.620	-25.544	56.000	9.836	QP
8			2.714	15.683	5.847	-30.317	46.000	9.836	AV
9			3.922	29.660	19.611	-26.340	56.000	10.049	QP
10			3.922	15.745	5.695	-30.255	46.000	10.049	AV
11			16.306	38.336	27.819	-21.664	60.000	10.517	QP
12			16.306	24.979	14.462	-25.021	50.000	10.517	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Site: WZ-SR2	Time: 2021/05/14 - 14:32
Limit: FCC_Part15.207_CE_AC Power	Engineer: Antony Yang
Probe: ENV216_101683_Filter Off_With Adapter	Polarity: Neutral
EUT: Tablet	Power: AC 120V/60Hz
Test Mode: NFC Operation	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.270	35.903	26.254	-25.215	61.118	9.648	QP
2			0.270	22.691	13.042	-28.427	51.118	9.648	AV
3		*	0.490	41.347	31.669	-14.821	56.168	9.678	QP
4			0.490	28.522	18.844	-17.646	46.168	9.678	AV
5			1.010	34.752	25.042	-21.248	56.000	9.710	QP
6			1.010	21.062	11.352	-24.938	46.000	9.710	AV
7			1.910	33.461	23.751	-22.539	56.000	9.710	QP
8			1.910	19.342	9.632	-26.658	46.000	9.710	AV
9			4.418	31.985	21.839	-24.015	56.000	10.146	QP
10			4.418	17.778	7.632	-28.222	46.000	10.146	AV
11			14.606	38.078	27.578	-21.922	60.000	10.500	QP
12			14.606	26.208	15.708	-23.792	50.000	10.500	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

7. CONCLUSION

The data collected relate only the item(s) tested and show that the device is compliance with Part 15C of the FCC Rules.

————— The End —————

Appendix A - Test Setup Photograph

Refer to "2105RSU001-UT" file.

Appendix B - EUT Photograph

Refer to "2105RSU001-UE" file.