

Date: June 28, 2023

Safety and Productivity Solutions 9680 Old Bailes Road Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

Request for Modular/Limited Modular Approval

Sub	oject: Manufacturer's Declaration for $oxtimes$ - Modular Approval $oxdot$ - Spli	t Modular A	Approval		
	□ - Limited Modular Approval □ - Limited Spli	it Modular /	Approval		
FC	C ID: HD5-HONSR28PRT				
	8 Basic Requirements – FCC Part 15.212(a)(1)				
	For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the F	Following Pa	ages		
	Modular Approval Requirement	Requirement Met			
1.	The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)		
	Details: <the a="" all="" and="" antenna="" board="" circuitry.="" components="" connector="" contains="" covers="" is="" located="" metal="" module="" next="" of="" on="" rf="" shield="" the="" to="" top="" which=""></the>				
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	⊠ - YES	□ - NO(*)		
	Details: <data application="" as="" buffered="" circuit="" described="" description="" in="" is="" modulation="" operational="" provided="" the="" to="" with=""></data>				
3.	The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)		
	Details: <the application="" contains="" filed="" its="" module="" own="" please="" power="" refer="" regulation.="" schematic="" supply="" this="" to="" with=""></the>				
4.	The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)		
	Details: <the a="" an="" and="" antenna="" antennas="" application="" approved="" be="" connector="" connector.="" connects="" considered="" device="" found="" in="" ipex="" is="" its="" list="" manual="" may="" module="" non-standard="" of="" provided="" tested="" the="" this="" to="" user="" using="" which="" with=""></the>				
5.	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)		
	Details: <the as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" td="" test="" tested="" v<="" was=""><td>vith this ap</td><td>olication></td></the>	vith this ap	olication>		

Modular Approval Requirement			Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: ZMOFM101GL12" or "Contains FCC ID: ZMOFM101GL12" Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization.	⊠ - YES	□ - NO(*)	
	Details: <there .filed="" a="" application.<="" are="" as="" exhibit="" filed="" in="" installation="" instructions="" is="" label="" labeling="" manual="" module="" on="" shown="" specific="" td="" the="" this="" with=""><td></td><td>Host</td></there>		Host	
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)	
	Details: <the 15c="" application.="" complies="" fcc="" filed="" in="" installation="" instructions="" manual="" module="" oe="" part="" requirements.="" the="" this="" to="" with=""></the>	M installer a	re provided	
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)	
	Details: < The module meets RF exposure in mobile configuration.>			

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations - KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement	Requirement Met		
 For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280. 	⊠ - Provided in Separate Cover Letter	□ - N/A	
Details: See the separate cover letter			
For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate Cover Letter	⊠ - N/A	
Details: <example a="" –n=""></example>			

Split Modular Requirements				
Requirement	Provided in Manual			
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	☐ - Provided in Separate Cover Letter	⊠ - N/A		
Details: <example a="" n="" –=""></example>				

OEM	I Integration Manual Guida	ance – KDB 996369 D03 Section 2				
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures						
for third-parties to use and/or integrate the module into a host device.						
Requirement						
		☐ - No,	an entianally shape to			
Is this module intended for sale to third parties?	If No, and LMA applies, the ap not make the following detailed needs to be basic integration and the information below operational description. If the info confidential, this will requester explaining the module is that integration instruction documents. If No, and LMA applies, the application of the provided integration integration integration in the provided integration and the information below operational description. If the information in the provided integration and the information below operational description. If the information in the provided integration in the provided		o public. However there still ructions for a users manual st still be included in the plicant wishes to keep this a separate statement cover for sale to third parties and re internal confidential tts.			
As of May 1, 2019, the FCC transmitter applicants shoul they are not applicable. For expension of the state o	C requires ALL the following include information in the cample information on trace	ng information to be in the installation neir instructions for all these items inc ce antenna design could indicate "Not	dicating clearly when t Applicable". Also if a			
	and the following items ca	not intended for sale to third parties, n be placed in the operational descrip				
1 List of applicable FCC wiles		etter as cited above.				
List of applicable FCC rules. a. Only list rules.	related to the transmitter.	2.2				
Summarize the specific oper		2 006260 D02 Section 2 2				
		ble loss, reduction of power for point to				
	professional installation info					
Limited Module Procedures.						
		ee uses to verify the host meets the				
necessary limit		•	□ - All Items shown			
	osure evaluation is necessar oliance is ensured, such as 0	ry, state how control will be maintained	to the left are provided in the Modular			
Trace antenna designs. KD		orace in for frew freets, etc.	Integration Guide (or			
		connectors, isolation requirements,	UM) for Full Modular			
tests for design	n verification, and production	n test procedures for ensuring	Approval (MA) or			
		ed to keep confidential must be	LMA.			
	nformation provided in the o					
5. RF exposure considerations			☐ - An LMA applies			
		allow host manufacturers to use the essary: first to the host manufacturer	and is approved			
		cm from body) and second additional	ONLY for use by the			
		in the host product manuals.	grantee in their own			
6. Antennas. KDB 996369 D03		in the neet product manage.	products, and not intended for sale to 3 rd			
		and all applicable professional	parties as provided in			
		antenna list shall also identify the	a separate cover			
		c – note that "omni-directional" is not	letter. Therefore the			
considered a t			information shown to			
7. Label and compliance inform			the left is found in the			
	integrators that they need to ID: " with their finished prod	o provide a physical or e-label stating duct	theory of operation.			
8. Information on test modes a	nd additional testing require	ments. KDB 996369 D03, Section 2.9				
		sideration by host integrators including				
		d simultaneous configurations.				
	ation on how to configure te					
9. Additional testing, Part 15 S	ubpart B disclaimer. KDB 99	96369 D03, Section 2.10				

Sincerely,

Groy Trang

Name: Cindy Jiang Title: Global Regulatory Compliance Manager