

1 RF Exposure Report

1.1 RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS 102, Issue 5, Section 2.5.2 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

1.2 RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b) showed in Table 1. And as per the RSS 102, Issue 5, Section 2.5.2 the MPE limits mentioned in Table 2.

Table 1: Limits for Maximum Permissible Exposure (MPE) as per FCC

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F or *f* = Frequency in MHz

Table 2: Limits for Maximum Permissible Exposure (MPE) as per ISED Canada

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)
Limits for Occupational / controlled Exposures			
100-6000	$15.60f^{0.25}$	$0.04138f^{0.25}$	$0.6455f^{0.5}$
Limits for General population / Uncontrolled Exposure			
300-6000	$3.142 f^{0.3417}$	$0.008335f^{0.3417}$	$0.02619f^{0.6834}$

F or *f* = Frequency in MHz

RF Exposure

Reference test report No:
ULR-TC56882130000073F/74F/75F

Seite 2 von 4
Page 2 of 4

1.2.1 Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

1.2.2 EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

1.2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as fixed device.

RF Exposure	Reference test report No: ULR-TC56882130000073F/74F/75F	Seite 3 von 4 Page 3 of 4
--------------------	--	------------------------------

Test Results

1. Protocol: BT

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
4.27	2.6730	2440	8.49	1	8.8920	0.0047	1	0.5409

2. Protocol: BLE

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
4.27	2.6730	2480	5.08	1	4.0551	0.0022	1	0.5469

3. Protocol: Wi-Fi 2.4GHz

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
4.27	2.6730	2437	18.87	1	97.0510	0.0516	1	0.5404

4. Protocol: Wi-Fi 5GHz (UNII-1)

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
3.10	2.0417	5240	12.97	1	24.9459	0.0101	1	0.9119

5. Protocol: Wi-Fi 5GHz (UNII-2A)

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
3.10	2.0417	5260	13.14	1	25.9418	0.0105	1	0.9142

RF Exposure

Reference test report No:
ULR-TC56882130000073F/74F/75F

Seite 4 von 4
Page 4 of 4

6. Protocol: Wi-Fi 5GHz (UNII-2C)

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
3.10	2.0417	5500	12.86	1	24.3220	0.0099	1	0.9425

7. Protocol: Wi-Fi 5GHz (UNII-3)

Antenna Gain (dBi)	Antenna gain in linear scale	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up Value in (dB)	Maximum output power including Tune-up value (mW)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	ISED Limit (mW/cm ²)
3.10	2.0417	5825	11.93	1	19.6336	0.0080	1	0.9803

Note:

1. Antenna gain details are taken from the antenna data sheet
2. Manufacturer has declared the tune-up value as ± 1 dB is considered in MPE calculation.

***** END OF TEST REPORT*****