

MRT Technology (Suzhou) Co., Ltd Phone: +86-512-66308358 Web: www.mrt-cert.com Report No.: 2212RSU051-U3 Report Version: V01 Issue Date: 2023-02-23

SAR MEASUREMENT REPORT

- FCC ID: HD5-IH45
- Applicant: Honeywell International Inc.

Honeywell Safety and Productivity Solutions

Product: Handheld UHF RFID Reader

- Model No.: IH45
- Brand Name: Honeywell
- FCC Rule Part(s): FCC 47 CFR Part 2.1093
- **Result:** Complies
- **Received Date:** 2023-01-13
- **Test Date:** 2023-02-16

Reviewed By:

Jame Yuan

Approved By:



Robin Wu

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in IEEE1528, KDB 447498 and KDB 865664. Test results reported herein relate only to the item(s) tested. The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.



Revision History

Report No.	Version	Description	Issue Date	Note
2212RSU051-U3	V01	Initial Report	2023-02-23	Valid



CONTENTS

Des	scription		Page
1.	Gene	al Information	5
	1.1.	Applicant	5
	1.2.	Manufacturer	5
	1.3.	Testing Facility	5
	1.4.	Product Information	6
	1.5.	Radio Specification under Test	6
	1.6.	Antennas Details	7
2.	Sumn	nary of Test Result	8
	2.1.	Test Standards	8
	2.2.	Environment Condition	8
	2.3.	RF Exposure Limits	8
	2.4.	Test Result Summary	9
3.	Speci	fic Absorption Rate (SAR)	10
	3.1.	Introduction	
	3.2.	Definition	10
4.	DASY	6 Measurement System	11
	4.1.	Introduction	
	4.2.	DASY6 Measurement System Diagram	11
	4.3.	System Components Details	
5.	The S	AR Measurement Procedure	23
	5.1.	Measurement Process Diagram	23
	5.2.	Test Position Definition	24
	5.3.	Test Procedure	27
6.	Syste	m Verificaiton	30
	6.1.	Tissue Check	
	6.2.	System Check	
7.	Analy	sis and Results	35
	7.1.	Antennna Location	
	7.2.	RFID Antenna Directivity Plot	
	7.3.	Conducted Power	
	7.4.	SAR Exclusion Analysis	
	7.5.	SAR Test Results	
	7.6.	Estimated SAR Calculation	



8.	Simultaneous Transmission Analysis	40
9.	Test Equipment Used	41
10.	Measurement Uncertainty	42
Anne	ex A - System Check Result	44
Anne	ex B - Test Data Plots	45
Anne	ex C - SAR Test Setup Photos	46
Anne	ex D - EUT Photos	47
Anne	ex E - Equipment Calibration Report	48



1. General Information

1.1. Applicant

Honeywell International Inc. Honeywell Safety and Productivity Solutions 9680 Old Bailes Road, Fort Mill, SC 29707 United States

1.2. Manufacturer

Honeywell International Inc. Honeywell Safety and Productivity Solutions 9680 Old Bailes Road, Fort Mill, SC 29707 United States

1.3. Testing Facility

\bowtie	Test Site – MRT Suzhou Laboratory				
Laboratory Location (Suzhou - Wuzhong)					
	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China Laboratory Location (Suzhou - SIP)				
	4b Building, Liand	o U Valley, No.200	Xingpu Rd., Shengp	u Town, Suzhou Indu	ustrial Park, China
	Laboratory Accre	editations			
	A2LA: 3628.01		CNAS	: L10551	
	FCC: CN1166		ISED:	CN0001	
	VCCI:	□R-20025	□G-20034	C-20020	□T-20020
		□R-20141	□G-20134	C-20103	□T-20104
	Test Site – MRT S	Shenzhen Laborat	tory		
	Laboratory Location (Shenzhen)				
	1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS	: L10551	
	FCC: CN1284		ISED:	CN0105	
	Test Site – MRT Taiwan Laboratory				
	Laboratory Location (Taiwan)				
	No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: L3261-19072	25			
	FCC: 291082, TW	/3261	ISED:	TW3261	



1.4. Product Information

Product Name	Handheld UHF RFID Reader	
Model No.	IH45	
EUT Identification No.	20230113Sample#02	
EUT Type	Portable Device	
Exposure Category	General Population/Uncontrolled Exposure	
Accessories 1		
Home Base	Model No.: CT40-HB	
	Input Power: 12V, 3A	
	Output Power: 5V, 2A	
Accessories 2		
Rechargeable Li-ion Battery	Model No.: BAT-EDA50US	
	Capacitance: 15.2Wh, 4000mAh	
	Rated Voltage: 3.8V	
Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be		
the responsibility of the manufacturer.		

1.5. Radio Specification under Test

UHF RFID Specification		
Frequency Range	902~ 928MHz	
Channel Number	50	
Type of Modulation	ASK	
Bluetooth Specification		
Bluetooth Version	BLE Only	
Frequency Range	2402MHz~ 2480MHz	
Channel Number	40	
Channel Spacing	2MHz	
Data Rate	1Mbps & 2Mbps	
Type of Modulation	GFSK	



1.6. Antennas Details

Operating Condition	UHF RFID (1Tx, 1Rx)	
	Bluetooth (1Tx, 1Rx)	
Antenna Type	UHF RFID: Panel	
	Bluetooth: PIFA	
Antenna Gain	UHF RFID: 4.16dBi	
Antenna Gain	Bluetooth: 1.85dBi	
Simultaneously	UHF RFID transmit simultaneously with Bluetooth.	
Transmitting Scenarios		



2. Summary of Test Result

2.1. Test Standards

No.	Identity	Document Title	
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices	
2	IEEE 1528-2013	IEEE Recommended Practice for Determining the Peak Spatial-Average	
		Specific Absorption Rate (SAR) in the Human Head from Wireless	
		Communications Devices: Measurement Techniques	
3	IEEE C95.1-2005	IEEE Standard for Safety Levels with Respect to Human Exposure to	
		Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz	
4	KDB 447498 D01 v06	General RF Exposure Guidance	
5	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz	
6	KDB 865664 D02 v01r02	RF Exposure Reporting	

2.2. Environment Condition

Ambient Temperature	20.5°C~24.0°C
Temperature of Simulant	20.0°C~23.5°C
Relative Humidity	38%RH ~55%RH

2.3. RF Exposure Limits

Human Exposure	Basic restrictions for electric, magnetic and electromagnetic fields. (Unit in mW/g or W/kg)
Spatial Peak SAR ¹	4.00
(Head and Body)	1.60
Spatial Average SAR ²	
(Whole Body)	0.08
Spatial Peak SAR ³	100
(Arms and Legs)	4.00

Notes:

1. The Spatial Peak value of the SAR averaged over any 1gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

2. The Spatial Average value of the SAR averaged over the whole body.

3. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over appropriate averaging time.



2.4. Test Result Summary

Worst SAR List

Highest Reported SAR	Extremity 10g SAR (W/kg)
UHF RFID	0.99

Highest Simultaneous SAR

Highest Simultaneous SAR	Extremity 10g SAR (W/kg)
UHF RFID + BLE	0.993



3. Specific Absorption Rate (SAR)

3.1. Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational /controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2. Definition

The SAR in the tissue-equivalent liquid can be determined by the rate of temperature increase or by E-field measurements, according to Formulas (1) or (2):

$$SAR = \frac{\sigma E^2}{\rho} \tag{1}$$

$$SAR = c_{\rm h} \frac{{\rm d}T}{{\rm d}t} \bigg|_{t=0}$$
⁽²⁾

where

SAR is the specific absorption rate in W/kg;

E is the rms value of the electric field strength in the tissue medium in V/m;

 σ is the electrical conductivity of the tissue medium in S/m;

ho is the mass density of the tissue medium in kg/m³;

 c_h is the specific heat capacity of the tissue medium in J/(kg K);



is the initial time derivative of temperature in the tissue medium in K/s.




4. DASY6 Measurement System

4.1. Introduction

DASY6 is the latest generation of the Dosimetric Assessment System optimized for specific absorption rate (SAR) measurements, SAR compliance. DASY6 builds on the power of our industry - leading dosimetric and near-field evaluation system, DASY52. Running on a significantly more robust platform and a more powerful measurement server, DASY6 offers much faster scanning with no sacrifice of measurement precision. All hardware and software are fully compatible with DASY52. The new system seamlessly integrates two software solutions, the novel cDASY V6.6 - optimized for SAR compliance testing to significantly reduce SAR assessment costs - and the widely used DASY V5.2 for generalized near-field evaluations with maximized flexibility.

4.2. DASY6 Measurement System Diagram



The DASY6 system in cDASY6/DASY5 V5.2 SAR Configuration is shown below:

The System consist of the following components:

DASY6 Measurement Server, Data Acquisition Electronics (DAE), Probes, Light-Beam Unit, Phantoms, Media, Device Holder for SAM-Twin Phantom, Laptop Extension Kit to Mounting Device, Robot System Platform & Pedestal, Verification of the Parameters with the Dielectric Assessment Kit (DAK), Modulation and Interference Analyzer (MAIA), Omni-Directional Ultra-Wideband Antenna (ANT), cDASY6 software, DASY5 NEO software and SEMCAD data evaluation software.




4.3. System Components Details

DASY6 Platforms MP6E-TX60L

MP6E-TX60L platform is a compact cost-effective platform based on TX60L. It consists of:

- a stable non-metalic platform for the TX60L robot
- a frame for two standard-size phantoms (1.0 × 0.5 m)
- a frame for one half-size phantom (0.5 × 0.5 m)

It includes two easily moveable trolleys for the phone and tablet/computer positioner and two platforms for positioning dipoles and other antennas.



Material The beams consist of a composite of wood and epoxy (permittivity of 3.3 and loss tangent of <0.07)

Size The footprint of the platform is 1590 mm x 1060 mm.

Robots -TX60L

The MRT DASY6 system uses the high-precision industrial robots TX60L from Staubli SA (France). The TX robot family - the successor of the well-known RX robot family - continues to offer the features important for DASY6 applications:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance-free as all gears are direct drive, no belt drives)
- Jerk-free straight movements (brushless synchron motors, no stepper motors)

 Low extremely low frequency (ELF) interference (motor control fields are shielded by the closed metallic construction)

The robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is provided on CDs delivered with the robot. Paper manuals are available directly from Staubli upon request.







DASY6 Measurement Server

The DASY6 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board. The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations. Data Acquisition Electronics (DAE)



The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter, and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.





Probes

E-Field Probe(EX3DV4)

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO 17025. Construction:

Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Frequency: 4 MHz ~ 10 GHz Linea

Linearity: ±0.2 dB (30 MHz ~ 10 GHz)

Directivity:

±0.1 dB in TSL (rotation around probe axis)

±0.3 dB in TSL (rotation normal to probe axis)

Dynamic Range: 10 μ W/g to 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)

Dimensions:

Overall length: 337 mm (Tip: 20 mm)

Tip diameter: 2.5 mm (Body: 12 mm)

Typical distance from probe tip to dipole centers: 1 mm

Applications:

High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better than 30%.



MSTV1 (Mother Scan Teaching V1) Electronics & TP6V2 (Teaching Probe 6V2) Probe

MSTV1 (Mother Scan Teaching V1) electronics together with the TP6V2 (Teaching Probe 6V2) probe is used for mother scan of DASY6 system. This probe uses a 3D Renishaw LP2 sensor which ensures accurate detection of any shape and a measurement repeatability of 8 µm.





Light-Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm, as well as the probe length and the horizontal probe offset, are measured. The software then corrects all movements within the measurement jobs, such that the robot coordinates are valid for the probe tip.



The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



Phantoms

SAM-Twin Phantom

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

SAM-Twin V5.0 and higher has the same shell geometry and is manufactured from the same material as SAM-Twin V4.0, but with the top structure reinforced.

Material	Vinyl ester, fiberglass reinforced (VE-GF)		
	The phantom shell is compatible with SPEAG		
	tissue simulating liquids (sugar and oil based).		
Liquid Compatibility	Use of other liquids may render the phantom		
	warranty void (see note or consult SPEAG		
	support).	1	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)		
Dimensions	Length: 1000 mm		
(incl. Wooden	Width: 500 mm		
Support)	Height: adjustable feet		
Filling Volume	approx. 25 liters		
Current	DASY6: standard-size platform slot		
Support	DASY52 stand-alone: SPEAG standard phantom table		




ELI phantom

The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 and higher has the same shell geometry and is manufactured from the same material as ELI V4.0, but has reinforced top structure. ELI V6.0, released in August 2014, has the same shell geometry as ELI V4.0 but offers increased longterm stability.

Material	Vinyl ester, fiberglass reinforced (VE-GF)	
	The phantom shell is compatible with SPEAG	
	tissue simulating liquids (sugar and oil	
Liquid Compatibility	based). Use of other liquids may render the	
	phantom warranty void (see note or consult	
	SPEAG support).	
Shell Thickness	$2.0 \pm 0.2 \text{ mm}$ (bottom plate)	
Dimensions	Major axis: 600 mm	
Dimensions	Minor axis: 400 mm	
Filling Volume	approx. 30 liters	
	DASY6: standard-size platform slot	
Support	DASY52 stand-alone: SPEAG standard	
	phantom table	






SAM Face Down Phantom

The SAM Face Down Phantom V10 allows assessment of the exposure of the face and in particular the eyes for handheld devices operated in front of the face. e.g., video phones, cameras, organizers, etc. It is manufactured from high precision injection molded polypropylene. The Mounting Device for Transmitters including extensions kit can be used to position the device.

Material	Epoxy based		
	The phantom shell is compatible with		
	SPEAG tissue simulating liquids (sugar		
Liquid Compatibility	and oil based). Use of other liquids may		
	render the phantom warranty void (see		
	note or consult SPEAG support).		
Shell Thickness	2 ± 0.2 mm (6 mm at ear point)		
Head Shape	Standard compatible SAM head.		
SAM Head Stand Phar	ntom		



The SAM Head Stand Phantom V10 allows assessment of the exposure of the top-head or around-the-head wireless accessories, e.g., head-belts, etc. It is manufactured from high precision injection molded polypropylene. The Mounting Device for Transmitters including extensions kit can be used to position the device.

Material	Epoxy based
	The phantom shell is compatible with
	SPEAG tissue simulating liquids (sugar
Liquid Compatibility	and oil based). Use of other liquids may
	render the phantom warranty void (see
	note or consult SPEAG support).
Shell Thickness	2 ± 0.2 mm (6 mm at ear point)
Head Shape	Standard compatible SAM head.







Wrist Phantom

The Wrist Phantom V10 is shape-compatible with the CTIA approved OTA GFPC-V1 and optimized for SAR evaluation of watches and other wireless hand accessories.

Material	Epoxy based		
	The phantom shell is compatible		
	with SPEAG tissue simulating		
Liquid Compatibility	liquids (sugar and oil based). Use of		
Liquid Compatibility	other liquids may render the		
	phantom warranty void (see note or		
	consult SPEAG support).		
Shell Thickness	Shell Thickness		
Wrigt Shapp	Design compatible with CTIA		
Wrist Shape	forearm.		







Device Holder for SAM-Twin Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of ± 0.5 mm would produce uncertainty in the SAR of $\pm 20\%$. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions at which the devices must be measured are defined by the standards.

MD4HHTV5 - Mounting Device for Hand-Held Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). **Material:** Polyoxymethylene (POM)



MDA4WTV5 - Mounting Device Adaptor for Ultra Wide Transmitters

An upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.

Material: Polyoxymethylene (POM)

MDA4SPV6 - Mounting Device Adaptor for Smart Phones

The solid low-density MDA4SPV6 adaptor assuring no impact on the DUT radiation performance and is conform with any DUT design and shape.

Material: ROHACELL







Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device (Body-Worn) enables testing of transmitter devices according to IEC 62209-2 specifications. The device holder can be locked for positioning at a flat phantom section. **Material:** Polyoxymethylene (POM), PET-G, Foam

MDA4LAP - Mounting Device Adaptor for Laptops

A simple but effective and easy-to-use extension for the Mounting Device; facilitates testing of larger devices (e.g., laptops, cameras, etc.) according to IEC 62209-2; lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM as well as ELI and other Flat Phantoms.

Material: Polyoxymethylene (POM), PET-G, Foam

Modulation and Interference Analyzer(MAIA)

MAIA is a hardware interface used to evaluate the modulation and audio interference characteristics of RF signals in the frequency range 698 - 6000 MHz. DASY6 evaluates the time-domain and frequency domain properties of the uplink signal transmitted by the DUT during SAR measurement with MAIA. MAIA uses USB powered active electronics to identify the modulation of the DUT. It can be operated over the air interface using the built-in ultra-broadband planar log spiral antenna (698 - 6000 MHz) or in conducted mode using the coaxial SMA 50 Ohm connector (300 - 6000 MHz).

To prevent damage in conducted mode due to high peak power, an external RF attenuator may be mounted. The LED on the MAIA hardware also indicates whether it is connected.











DAK-3.5 (200MHz - 20GHz)

This precision dielectric measurement system is designed to cover the 200MHz – 20GHz frequency range with a single open-ended coaxial dielectric probe. The system uses advanced algorithms and novel hardware to measure the dielectric properties of liquids, solids, and semi-solids over a broad range of parameters. The measurement method is fast and non-destructive to the material under test.



Evaluation of reference liquids over a broad frequency range for specific absorption rate (SAR) measurements, in accordance with IEC 62209, IEEE 1528, and several federal regulations. Evaluating Software: DAK software version 2.0

MRT simulating liquid		
Product	Test Frequency (MHz)	Main Ingredients
HSL450	400 – 500	Water, Sucrose, NaCl
MSL450	400 - 500	Water, Sucrose, NaCl

Speag Broad-Band simulating liquid	t	
Product	Test Frequency (MHz)	Main Ingredients
HBBL600-10000V6	600 – 10000	Water, Oil
MBBL600-6000V6	600 - 6000	Water, Oil





5. The SAR Measurement Procedure

5.1. Measurement Process Diagram

General Procedure

For IEEE1528-2013 Head SAR





Measurement 6.6.4

For Body SAR

SAR scan procedures described in section 2.7 of KDB 865664 D01 v01r04 should be applied to body SAR


test.




5.2. Test Position Definition

Head SAR Test Position

Define two imaginary lines on the handset-the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset-the midpoint of the width wt of the handset at the level of the acoustic output [point A in Fixed case and Clamshell case], and the midpoint of the width w_b at the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output [see Fixed case]. The horizontal line is also tangential to the face of the handset at point A. The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset [see Clamshell case], especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets, the vertical centerline passes through point A but not the tip edge of the phone.








Key

- B Direction of B-M line back endpoint
- F Direction of N-F line front endpoint
- N Direction of N-F line neck endpoint
- M Mouth reference point
- LE Left ear reference point (ERP)




Key

- B Line B-M back endpoint
- M Line B-M front endpoint
- N Line N-F neck endpoint
- F Line N-F front endpoint
- RE Right ear reference point (ERP)

Cheek Position

The cheek position has the following characteristics, based on the geometrical lines described above:

- The N-F line (see above) is in the plane defined by the handset vertical centerline and horizontal line
- Handset touches the pinna
- The handset vertical centerline is aligned with the Reference Plane.



Key

- M Mouth reference point
- LE Left ear reference point
- RE Right ear reference point




Tilt Position

The tilt position is established as follows:

-Repeat the steps to place the device in the cheek position.

-While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°. -Rotate the handset around the horizontal line by 15°.

-While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point on the handset is in contact with the phantom, e.g., the antenna with the back of the head.



Key

M Mouth reference po	int
----------------------	-----

RE Right ear reference point

Body SAR Test Position

For body-worn accessory, hotspot mode and other exposure conditions to human body should be conducted pursuant to the test position requirements of SAR KDBs for certain product.



5.3. Test Procedure

Step 1 Setup a Connection

First, engineer should record the conducted power before the test. Then establish a call in handset at the maximum power level with a base station simulator via air interface, or make the EUT establish transmission by itself in testing band. Place the EUT to certain test position.

Step 2 Power Reference Measurements

To measure the local E-field value at a fixed location which value will be taken as a reference value for calculating a possible power drift.

Step 3 Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.



Area Scan Parameters extracted from KDB 805004 D01V01r04			
	≤ 3 GHz	> 3 GHz	
Maximum distance from closest measurement			
point (geometric center of probe sensors) to	5 mm ± 1 mm	½·δ·ln(2) mm ± 0.5 mm	
phantom surface			
Maximum probe angle from probe axis to			
phantom surface normal at the measurement	30° ± 1°	20° ± 1°	
location			
	≤ 2 GHz: ≤ 15 mm	3 - 4 GHz: ≤ 12 mm	
	2 - 3 GHz: ≤ 12 mm	4 - 6 GHz: ≤ 10 mm	
Maximum area scan spatial resolution:	When the x or y dimension of the test device, in the		
	measurement plane orientation, is smaller than the		
Δ XArea, Δ YArea	above, the measurement resolution must be \leq the		
	corresponding x or y dimension of the test device with at		
	least one measurement point on the test device.		
Note: δ is the penetration depth of a plane-wave a	at normal incidence to the tissu	ue medium; see IEEE Std	
1528-2013 for details.			

Area Scan Parameters extracted from KDB 865664 D01v01r04



Step 4 Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

			≤ 3 GHz	> 3 GHz
Movimum zoom ooor	anatial ray	volution: Ax- Ax-	≤ 2 GHz: ≤ 8 mm	3 - 4 GHz: ≤ 5 mm*
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		2 - 3 GHz: ≤ 5 mm*	4 - 6 GHz: ≤ 4 mm*	
				3 - 4 GHz: ≤ 4 mm
	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	4 - 5 GHz: ≤ 3 mm
Movimum zoom				5 - 6 GHz: ≤ 2 mm
Maximum zoom		$\Delta z_{Zoom}(1)$: between		3 - 4 GHz: ≤ 3 mm
scan spatial		1 st two points closest	≤ 4 mm	4 - 5 GHz: ≤ 2.5 mm
resolution, normal	graded grid	to phantom surface		5 - 6 GHz: ≤ 2 mm
to phantom surface		Δz _{zoom} (n>1):		
		between subsequent	≤ 1.5·Δz _{zoom} (n-1) mm	
		points		
Minimum zoom				3-4 GHz: ≥ 28 mm
scan volume		x, y, z	≥ 30 mm	4-5 GHz: ≥ 25 mm
scan volume				5-6 GHz: ≥ 22 mm
Note: * When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation				
procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may				
be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Zoom Scan Parameters extracted from KDB 865664 D01 v01r04

Step 5 Power Drift Measurements

Repetition of the E-field measurement at the fixed location mentioned in Step 1 to make sure the two results differ by less than \pm 0.2 dB.

Step 6 Test Data

After the test, SAR test data should be exported by SEMCAD.





6. System Verificaiton

6.1. Tissue Check

■ Refer to KDB 865664 D01 v01r04, the depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm with ≤ ± 0.5 cm variation for SAR measurements ≤ 3 GHz and ≥ 10.0 cm with ≤ ± 0.5 cm variation for measurements > 3 GHz.

15cm Depth Head Tissue



Dielectric properties of the head tissue-equivalent liquid

Frequency	Relative Permittivity	Conductivity (σ)
MHz	٤r	S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1 450	40.5	1.20
1 500	40.4	1.23
1 640	40.2	1.31
1 750	40.1	1.37
1 800	40.0	1.40
1 900	40.0	1.40
2 000	40.0	1.40
2 100	39.8	1.49
2 300	39.5	1.67
2 450	39.2	1.80
2 600	39.0	1.96
3 000	38.5	2.40
3 500	37.9	2.91
4 000	37.4	3.43
4 500	36.8	3.94
5 000	36.2	4.45
5 200	36.0	4.66
5 400	35.8	4.86
5 600	35.5	5.07
5 800	35.3	5.27
6 000	35.1	5.48

Note: For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5800MHz are provided (i.e. the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000MHz that were linearly extrapolated from the values at 3000MHz and 5800MHz.



Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY6 Dielectric

Freq.	Perm.	Cond.	Target	Target	Deviation	Deviation	Tissue	Test Date
(MHz)			Perm.	Cond.	Perm. %	Cond. %	Temperature	
850	43.26	0.91	41.50	0.92	4.24	-1.09	22.5°C	2023.02.16

Assessment Kit and keysight PNA-L Network Analyzer N5234B.


Note: The ±5% deviation of tissue parameter is recommended.



6.2. System Check

Purpose

The purpose of the system check is to verify that the system operates within its specifications at the device test frequencies. System check verifies the measurement repeatability of a SAR system before compliance testing and is not a validation of all system specifications. The latter is not required for testing a device but is mandatory before the system is deployed.



System Performance Check Setup Diagram

System Check Procedure

The system check procedure is a complete 1g and 10g peak spatial-average SAR measurement using a source having a previously determined system check target value. The measured 1g and 10g SAR are normalized to the target input power of the specific source and compared to their respective target values. A description of the different measurement tasks to be performed is given below, together with the information that can be deduced from their results:

a. The Power Reference Measurement and Power Drift Measurement are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the amplifier output power. If it is too high (above ± 0.1 dB), the



system check should be repeated; some amplifiers have very high drift during warm-up. A stable amplifier gives drift results in the DASY6 system below ±0.02 dB.

b. The second step is optional. For probes with integrated optical surface detection sensor this step must be conducted, otherwise the step can be skipped. The Surface Check tests the optical surface detection system of the DASY6 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1 mm). In that case it is better to abort the system check and stir the liquid.

c. The Area Scan measures the SAR above the dipole on a plane parallel to the surface. It is used to locate the approximate location of the peak SAR. The proposed scan uses large grid spacing for faster measurement; due to the symmetric field, the peak detection is reliable. If a finer graphic is desired, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result.

d. The Zoom Scan measures the field in a volume around the peak SAR value assessed in the previous Area Scan.

If the system check gives reasonable results, the SAR peak, 1 g and 10 g spatial average SAR values normalized to 1 W dipole input power give reference data for comparisons. The next sections analyze the expected uncertainties of these values, as well as additional checks for further information or troubleshooting.

Freq.	1g SAR	10g SAR	Target	Target	Deviation	Deviation	Tissue	Test Date
(MHz)	(W/kg)	(W/kg)	1g SAR	10g SAR	1g SAR	10g SAR	Temp.	
			(W/kg)	(W/kg)	(%)	(%)		
850	9.88	6.44	10.10	6.52	-2.18	-1.23	22.5°C	2023.02.16

Result of System Performance Check

Note:


1. The $\pm 10\%$ deviation of system check result is required.

2. System check value listed above has been harmonized to 1W.




7. Analysis and Results

7.1. Antennna Location



7.2. RFID Antenna Directivity Plot





7.3. Conducted Power

UHF RFID Band

Band	CH.	Freq. (MHz) Average Power (dBm)		Tune-up Power (dBm)	Duty Cycle %	
	0	902.75	28.89	29.0		
UHF RFID	24	914.75	28.59	29.0	98.86	
	49	927.25	28.46	29.0		

Bluetooth-LE

Band (GHz)	Data Rate (Mbps)	CH.	Freq. (MHz)	Average Power (dBm)	Tune-up Power (dBm)	Duty Cycle %
		0	2402	-1.58	-1.0	61.96
	1	19	2440	-1.70	-1.0	61.96
2.4		39	2480	-1.86	-1.0	61.96
(2.4~2.4835)	2	0	2402	-1.56	-1.0	31.41
		19	2440	-1.70	-1.0	31.41
		39	2480	-1.85	-1.0	31.41



7.4. SAR Exclusion Analysis

Per FCC KDB 447498 D01v06, the SAR exclusion threshold for distances<50mm is defined by the following equation:

 $\frac{Max Power of Channel(mW)}{Test Separation Distance(mm)} \times \sqrt{Frequency(GHz)} \le 3.0$, for head and boy SAR;

 $\frac{Max Power of Channel(mW)}{Test Separation Distance(mm)} \times \sqrt{Frequency(GHz)} \le 7.5, \text{ for Extremity SAR.}$

For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

- {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance 50 mm) * (f(MHz)/150)]} mW, for 100 MHz to 1500 MHz
- 2) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance 50 mm)*10]} mW, for > 1500 MHz and ≤ 6 GHz

Antenna Distance to Phantom/User (mm)
25

Note:

- 1. Antenna to user distance = Antenna to out-surface of EUT distance + Out-surface of EUT to user distance.
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Required test configuration

Handheld UHF RFID Reader						
Exposure Conditions Mode Back Side						
	UHF RFID	Yes				
Extremity	Bluetooth-LE	No				



7.5. SAR Test Results

СН.	Freq. (MHz)	Test Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-10g (W/kg)	Reported SAR-10g (W/kg)	SAR Plot #
0	902.75	Front	25	28.89	29.0	1.03	98.86	1.01	0.83	0.86	
24	914.75	Front	25	28.59	29.0	1.10	98.86	1.01	0.89	0.99	1
49	927.25	Front	25	28.46	29.0	1.13	98.86	1.01	0.84	0.96	

Note: SAR is measured from the front of the RFID antenna at that antenna-to-finger distance and use that SAR value in place of back

side SAR data, from the antenna directivity plot, the result is more conservative.



7.6. Estimated SAR Calculation

Per FCC KDB 447498 D01v06 section 4.3.2 b) 1), when an antenna qualifies for the standalone SAR test exclusion of 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value was estimated according to the following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg for test separation distance ≤ 50 mm to determine the simultaneous transmission SAR test exclusion criteria:

Estimated
$$SAR = \frac{\sqrt{f(GHz)}}{7.5} * \frac{(Max Power of channel, mW)}{Min. Separation, mm}$$
, for 1-g SAR

Estimated $SAR = \frac{\sqrt{f(GHz)}}{18.75} * \frac{(Max Power of channel, mW)}{Min. Separation, mm}$, for 10-g SAR

When the test separation distance is > 50 mm, estimated 1g-SAR 0.4W/kg/10g-SAR 1.0W/kg is used for simultaneous evaluation.

Toot Modo	Freq.	Test	Ant-to-User	Tune-up Power	Tune-up Power	Estimated SAR
Test Mode	(MHz)	Position	Distance	(dBm)	(mW)	(W/kg)
Bluetooth-LE	2480	Back	25	-1.0	0.79	0.003

Note: Antenna to User distance = Antenna to out-surface of EUT distance + Out-surface of EUT to User distance.



8. Simultaneous Transmission Analysis

Transmit	Maximum SA	Maximum SAR(10g) (W/kg)					
Configuration	UHF RFID	BLE	(W/kg)				
UHF RFID + BLE	0.99	0.003	0.993				

The above numerical summed SAR results for all the worst-case simultaneous transmission scenarios are below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and SAR test result is complies.



9. Test Equipment Used

SR3 - SAR					
Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Stäubli Robot TX60L	Stäubli	TX60L	MRTSUE06412	only once	only once
Robot Controller	Stäubli	CS8C	MRTSUE06412	only once	only once
ELI Phantom Shell	Speag	V8	MRTSUE06420	N/A	N/A
DAK	Speag	DAK-3.5	MRTSUE06435	N/A	N/A
Dipole Validation Kits	Speag	D850V2	MRTSUE06427	3 years	2024/06/14
DAE4	Speag	SD 000 D04 BN	MRTSUE06414	1 year	2023/05/16
E-Field Probe	Speag	EX3DV4(SN 7524)	MRTSUE06438	1 year	2023/07/21
Network Analyzer	Keysight	N5234B	MRTSUE06454	1 year	2023/06/04
Directional Coupler	Agilent	778D	MRTSUE06083	1 year	2023/03/17
Directional Coupler	Agilent	87301D OPT 292	MRTSUE06082	1 year	2023/03/07
Signal Generator	Keysight	N5183B	MRTSUE06197	1 year	2023/07/08
Power Sensor	Keysight	U2021XA	MRTSUE06447	1 year	2023/06/04
Thermohygrometer	Testo	622	MRTSUE06361	1 year	2023/05/09

Software	Version	Function
DASY NEO	52.10.4.1527	SAR Test Software



10. Measurement Uncertainty

DASY5 Uncertainty Budget	, according t	o IEEE 15	528 (0.3	- 3 GHz	range)			
E	Uncert.	Prob.	Div.	(ci)	(ci)	Std. Unc.	Std. Unc.	(vi)
Error Description	value	Dist.		1g	10g	(1g)	(10g)	veff
Measurement System		·	•					
Probe Calibration	±6.0 %	N	1	1	1	±6.0 %	±6.0 %	8
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Modulation Response	±2.4 %	R	$\sqrt{3}$	1	1	±1.4 %	±1.4 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.02 %	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Probe Positioning	±0.4 %	R	$\sqrt{3}$	1	1	±0.2 %	±0.2 %	∞
Max. SAR Eval.	±2.0 %	R	$\sqrt{3}$	1	1	±1.2 %	±1.2 %	∞
Test Sample Related		•	1		1			
Device Positioning	±2.9%	Ν	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6%	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	∞
Power Scaling ^p	±0%	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Phantom and Setup								
Phantom Uncertainty	±6.1%	R	$\sqrt{3}$	1	1	±3.5 %	±3.5 %	∞
SAR correction	±1.9%	N	1	1	0.84	±1.9 %	±1.6 %	∞
Liquid Cond. (mea.)DAK	±2.5%	N	1	0.78	0.71	±2.0 %	±1.8 %	∞
Liquid Perm. (mea.)DAK	±2.5%	N	1	0.23	0.26	±0.6 %	±0.7 %	∞
Temp. unc. – Conductivity ^{BB}	±3.4%	R	$\sqrt{3}$	0.78	0.71	±1.5 %	±1.4 %	∞
Temp. unc. – Permittivity ^{BB}	±0.4%	R	$\sqrt{3}$	0.23	0.26	±0.1 %	±0.1 %	∞
Combined Std. Uncertainty		÷	·		·	±11.3%	±11.2%	459
Expanded STD Uncertainty						±22.6%	±22.4%	



DASY5 Uncertainty Budget	, according t	o IEEE 15	28 (3 - 0	6 GHz ra	ange)			
Error Description	Uncert.	Prob.	Div	(ci)	(ci)	Std. Unc.	Std. Unc.	(vi)
Error Description	value	Dist.	Div.	1g	10g	(1g)	(10g)	veff
Measurement System		·	-			·	·	-
Probe Calibration	±6.55 %	N	1	1	1	±6.55 %	±6.55 %	8
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±2.0 %	R	$\sqrt{3}$	1	1	±1.2 %	±1.2 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Modulation Response	±2.4 %	R	$\sqrt{3}$	1	1	±1.4 %	±1.4 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.04 %	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Probe Positioning	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Max. SAR Eval.	±4.0 %	R	$\sqrt{3}$	1	1	±2.3 %	±2.3 %	∞
Test Sample Related		·	-			·		-
Device Positioning	±2.9%	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6%	Ν	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	8
Power Scaling ^p	±0%	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	8
Phantom and Setup								
Phantom Uncertainty	±6.6%	R	$\sqrt{3}$	1	1	±3.8 %	±3.8 %	8
SAR correction	±1.9%	N	1	1	0.84	±1.9 %	±1.6 %	∞
Liquid Cond. (mea.)DAK	±2.5%	N	1	0.78	0.71	±2.0 %	±1.8 %	8
Liquid Perm. (mea.) ^{DAK}	±2.5%	Ν	1	0.23	0.26	±0.6 %	±0.7 %	8
Temp. unc. – Conductivity ^{BB}	±3.4%	R	√3	0.78	0.71	±1.5 %	±1.4 %	8
Temp. unc. – Permittivity ^{BB}	±0.4%	R	√3	0.23	0.26	±0.1 %	±0.1 %	8
Combined Std. Uncertainty						±11.9%	±11.8%	569
Expanded STD Uncertainty						±23.8%	±23.6%	



Annex A - System Check Result

Test Date: 2023/02/16

SystemPerformanceCheck-SAM2-D850HSL

DUT: Dipole 850 MHz D850V2; Type: D850V2

Communication System: CW; Frequency: 850 MHz; Duty Cycle: 1:1 Medium parameters used: f = 850 MHz; σ = 0.91 S/m; ϵ_r = 43.26; ρ = 1000 kg/m³ Phantom section: Flat Section DASY5 Configuration:

- Probe: EX3DV4 SN7524; ConvF(10.05, 10.05, 10.05) @ 850 MHz; Calibrated: 2022/7/22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 2022/5/17
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

configuration/d=15mm, Pin=250mW, dist=1.4mm (EX-Probe)/Area Scan (6x14x1): Measurement grid:

dx=15mm, dy=15mm; Maximum value of SAR (measured) = 3.19 W/kg


configuration/d=15mm, Pin=250mW, dist=1.4mm (EX-Probe)/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm; Reference Value = 59.05 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 3.92 W/kg

SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.61 W/kg

Smallest distance from peaks to all points 3 dB below = 17.6 mm

Ratio of SAR at M2 to SAR at M1 = 63.5%

Maximum value of SAR (measured) = 3.39 W/kg



0 dB = 3.39 W/kg = 5.30 dBW/kg



Annex B - Test Data Plots

Plot 1#

Test Date: 2023/02/16

DUT: Handheld UHF RFID Reader; Type: IH40 Procedure Name: UHF RFID Mid Extremity Front Communication System: UHF RFID; Frequency: 914.75 MHz; Duty Cycle: 1:1 Medium parameters used: f = 914.75 MHz; $\sigma = 0.94$ S/m; $\varepsilon_r = 43.09$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section DASY5 Configuration:

- Probe: EX3DV4 SN7524; ConvF(10.05, 10.05, 10.05) @ 914.75 MHz; Calibrated: 2022/7/22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 2022/5/17
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Configuration/UHF RFID Mid Extremity Front/Area Scan (9x10x1): Measurement grid: dx=15mm,

dy=15mm; Maximum value of SAR (measured) = 1.52 W/kg

Configuration/UHF RFID Mid Extremity Front/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm,

dy=8mm, dz=5mm; Reference Value = 26.39 V/m; Power Drift = 0.00 dB


Peak SAR (extrapolated) = 1.80 W/kg

SAR(1 g) = 1.22 W/kg; SAR(10 g) = 0.890 W/kg

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 20 mm)

Ratio of SAR at M2 to SAR at M1 = 67.4%

Maximum value of SAR (measured) = 1.57 W/kg



0 dB = 1.57 W/kg = 1.96 dBW/kg



Annex C - SAR Test Setup Photos

Please refer to document "2212RSU051-UT".



Annex D - EUT Photos

Please refer to document "2212RSU051-UE".



Annex E - Equipment Calibration Report

Please refer to document "Annex E - Equipment Calibration Report.pdf".

The End