

RF Exposure Lab

802 N. Twin Oaks Valley Road, Suite 105 • San Marcos, CA 92069 • U.S.A.

TEL (760) 471-2100 • FAX (760) 471-2121

<http://www.rfexposurelab.com>

CERTIFICATE OF COMPLIANCE SAR EVALUATION

Vocollect, Inc.
703 Rodi Road
Pittsburgh, PA 15235

Dates of Test:
Test Report Number:

May 23-26, 2022
SAR.20220607
Revision A

FCC ID:	HD5-TAP1000-02
IC Certificate:	1693B-TAP100002
HVIN/Model(s):	A700x Series Family TAP10x0-02
Contains WLAN Module:	Laird Connectivity, LLC Model 60SIPT FCC: SQG-60SIPT IC: 3147A-60SIPT
Test Sample:	Engineering Unit Same as Production
Serial Number:	7418200044, 7518200141, 7618230017
Equipment Type:	Handheld Reader containing Wireless Module
Classification:	Portable Transmitter Next to Body
TX Frequency Range:	2412 – 2462 MHz; 5180 – 5320 MHz; 5500 – 5700 MHz; 5745 – 5825 MHz
Frequency Tolerance:	± 2.5 ppm
Maximum RF Output:	2450 MHz (b) – 18.0 dBm, 2450 MHz (g) – 18.0 dBm, 2450 MHz (n20) – 18.0 dBm, 2450 MHz (n40) – 16.0 dBm, 5250 MHz (a) – 18.0 dBm, 5250 MHz (n/ac20) – 18.0 dBm, 5250 MHz (n/ac40) – 16.0 dBm, 5250 MHz (ac80) – 14.0 dBm, 5600 MHz (a) – 18.0 dBm, 5600 MHz (n/ac20) – 18.0 dBm, 5600 MHz (n/ac40) – 16.0 dBm, 5600 MHz (ac80) – 14.0 dBm, 5800 MHz (a) – 18.0 dBm, 5800 MHz (n/ac20) – 18.0 dBm, 5800 MHz (n/ac40) – 16.0 dBm, 5800 MHz (ac80) – 14.0 dBm Conducted
Signal Modulation:	DSSS, OFDM
Antenna Type:	Internal
Application Type:	Certification
FCC Rule Parts:	Part 2, 15C, 15E
KDB Test Methodology:	KDB 447498 D01 v07, KDB 248227 v02r02, KDB 616217 D04 v01r02
Industry Canada:	RSS-102 Issue 5, Safety Code 6
Maximum SAR Value Body:	1.12 W/kg Reported
Simultaneous SAR Body:	1.24 W/kg Reported
Maximum SAR Value Extremity:	2.16 W/kg Reported
Simultaneous SAR Extremity:	2.29 W/kg Reported
Separation Distance:	0 mm

This wireless mobile and/or portable device has been shown to be compliant for localized specific absorption rate (SAR) for uncontrolled environment/general exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and IEC 62209-1528:2020 (See test report).

I attest to the accuracy of the data. All measurements were performed by myself or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RF Exposure Lab, LLC certifies that no party to this application is subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



Jay M. Moulton
Vice President



Testing Cert. #
2387.01

Table of Contents

1.	Introduction	4
	SAR Definition [5].....	5
2.	SAR Measurement Setup.....	6
	Robotic System.....	6
	System Hardware.....	6
	System Electronics.....	7
	Probe Measurement System.....	7
3.	Probe and Dipole Calibration.....	15
4.	Phantom & Simulating Tissue Specifications.....	16
	Head & Body Simulating Mixture Characterization	16
5.	ANSI/IEEE C95.1 – 1992 RF Exposure Limits [2].....	17
	Uncontrolled Environment	17
	Controlled Environment.....	17
6.	Measurement Uncertainty	18
7.	System Validation.....	19
	Tissue Verification.....	19
	Test System Verification.....	19
8.	SAR Test Data Summary	21
	Procedures Used To Establish Test Signal	21
	Device Test Condition	21
	SAR Data Summary – 2450 MHz Body 802.11b Body	47
	SAR Data Summary – 2450 MHz Body 802.11b Extremity	48
	SAR Data Summary – 5250 MHz Body 802.11a Body	49
	SAR Data Summary – 5250 MHz Body 802.11a Extremity	50
	SAR Data Summary – 5600 MHz Body 802.11a Body	51
	SAR Data Summary – 5600 MHz Body 802.11a Extremity	52
	SAR Data Summary – 5800 MHz Body 802.11a Body	53
	SAR Data Summary – 5800 MHz Body 802.11a Extremity	54
	SAR Data Summary – Simultaneous Evaluation	55
9.	Test Equipment List.....	56
10.	Conclusion	57
11.	References.....	58
	Appendix A – System Validation Plots and Data	59
	Appendix B – SAR Test Data Plots	71
	Appendix C – SAR Test Setup Photos	80
	Appendix D – Probe Calibration Data Sheets.....	91
	Appendix E – Dipole Calibration Data Sheets	102
	Appendix F – Phantom Calibration Data Sheets	117
	Appendix G – Validation Summary.....	119

Comment/Revision	Date
Original Release	June 21, 2022
Revision A – Correct the date on 2450 MHz Verification Test	August 10, 2022

Note: The latest version supersedes all previous versions listed in the above table. The latest version shall be used.

1. Introduction

This measurement report shows compliance of the Vocollect, Inc. HVIN/Model A700x Series Family TAP10x0-02 FCC ID: HD5-TAP1000-02 with FCC Part 2, 1093, ET Docket 93-62 Rules for mobile and portable devices and IC Certificate: 1693B-TAP100002 with RSS102 Issue 5 & Safety Code 6. The FCC/ISED have adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on August 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC/ISED regulated portable devices. [1], [6]

The test results recorded herein are based on a single type test of Vocollect, Inc. HVIN/Model A700x Series Family TAP10x0-02 and therefore apply only to the tested sample.

The test procedures and limits, as described in ANSI C95.1 – 1999 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [2], ANSI C95.3 – 2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields [3], IEEE Std.1528 – 2013 Recommended Practice [4], and Industry Canada Safety Code 6 Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3kHz to 300 GHz were employed.

The following table indicates all the wireless technologies operating in the A700x Series Family TAP10x0-02 Handheld Reader containing Wireless Module. The table also shows the tolerance for the power level for each mode.

Band	Technology	3GPP Nominal Power dBm	Setpoint Nominal Power dBm	Tolerance dBm	Lower Tolerance dBm	Upper Tolerance dBm
WLAN – 2.4 GHz	802.11bgn20	N/A	N/A	N/A	N/A	18.0
WLAN – 2.4 GHz	802.11n40	N/A	N/A	N/A	N/A	16.0
WLAN – 5 GHz Band I, IIA, IIC, III	802.11a/n/ac20	N/A	N/A	N/A	N/A	18.0
WLAN – 5 GHz Band I, IIA, IIC, III	802.11n/ac40	N/A	N/A	N/A	N/A	16.0
WLAN – 5 GHz Band I, IIA, IIC, III	802.11ac80	N/A	N/A	N/A	N/A	14.0
Bluetooth	Bluetooth	N/A	N/A	N/A	N/A	10.1
BLE	Bluetooth	N/A	N/A	N/A	N/A	6.7
NFC	NFC	N/A	N/A	N/A	N/A	< 1.0

SAR Definition [5]

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ).

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

where:

σ = conductivity of the tissue (S/m)

ρ = mass density of the tissue (kg/m³)

E = rms electric field strength (V/m)

2. SAR Measurement Setup

Robotic System

These measurements are performed using the DASY52 automated dosimetric assessment system. The DASY52 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Intel Core2 computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 2.1).

System Hardware

A cell controller system contains the power supply, robot controller teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the HP Intel Core2 computer with Windows XP system and SAR Measurement Software DASY52, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 2.1 SAR Measurement System Setup

System Electronics

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

Probe Measurement System

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration (see Fig. 2.2) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi fiber line ending at the front of the probe tip. (see Fig. 2.3) It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY52 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped at reaching the maximum.



DAE System

Probe Specifications

Calibration: In air from 10 MHz to 6.0 GHz
In brain and muscle simulating tissue at Frequencies of 450 MHz, 835 MHz, 1750 MHz, 1900 MHz, 2450 MHz, 2600 MHz, 3500 MHz, 5200 MHz, 5300 MHz, 5600 MHz, 5800 MHz

Frequency: 10 MHz to 6 GHz

Linearity: ± 0.2 dB (30 MHz to 6 GHz)

Dynamic: 10 mW/kg to 100 W/kg

Range: Linearity: ± 0.2 dB

Dimensions: Overall length: 330 mm

Tip length: 20 mm

Body diameter: 12 mm

Tip diameter: 2.5 mm

Distance from probe tip to sensor center: 1 mm

Application: SAR Dosimetry Testing
Compliance tests of wireless device



Figure 2.2 Triangular Probe Configurations



Figure 2.3 Probe Thick-Film Technique

Probe Calibration Process

Dosimetric Assessment Procedure

Each probe is calibrated according to a dosimetric assessment procedure described in with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in and found to be better than +/-0.25dB. The sensitivity parameters (Norm X, Norm Y, Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe is tested.

Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a waveguide above 1GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm².

Temperature Assessment *

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium, correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor based temperature probe is used in conjunction with the E-field probe

$$SAR = C \frac{\Delta T}{\Delta t}$$

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

where:

Δt = exposure time (30 seconds),

σ = simulated tissue conductivity,

C = heat capacity of tissue (brain or muscle),

ρ = Tissue density (1.25 g/cm³ for brain tissue)

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place.

Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;




Figure 2.4 E-Field and Temperature Measurements at 900MHz




Figure 2.5 E-Field and Temperature Measurements at 1800MHz

Data Extrapolation

The DASY52 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given like below;

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i (i=x,y,z)
 U_i = input signal of channel i (i=x,y,z)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

with V_i = compensated signal of channel i (i = x,y,z)
 $Norm_i$ = sensor sensitivity of channel i (i = x,y,z)
 $\mu V/(V/m)^2$ for E-field probes
 $ConvF$ = sensitivity of enhancement in solution
 E_i = electric field strength of channel i in V/m

The RSS value of the field components gives the total field strength (Hermetian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in W/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm^3

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{free} = \frac{E_{tot}^2}{3770}$$

with P_{pwc} = equivalent power density of a plane wave in W/cm^2
 E_{tot} = total electric field strength in V/m

Scanning procedure

- The DASY installation includes predefined files with recommended procedures for measurements and system check. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.
- The „reference“ and „drift“ measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. +/- 5 %.
- The highest integrated SAR value is the main concern in compliance test applications. These values can mostly be found at the inner surface of the phantom and cannot be measured directly due to the sensor offset in the probe. To extrapolate the surface values, the measurement distances to the surface must be known accurately. A distance error of 0.5mm could produce SAR errors of 6% at 1800 MHz. Using predefined locations for measurements is not accurate enough. Any shift of the phantom (e.g., slight deformations after filling it with liquid) would produce high uncertainties. For an automatic and accurate detection of the phantom surface, the DASY5 system uses the mechanical surface detection. The detection is always at touch, but the probe will move backward from the surface the indicated distance before starting the measurement.
- The „area scan“ measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The scan uses different grid spacings for different frequency measurements. Standard grid spacing for head measurements in frequency ranges ≤ 2 GHz is 15 mm in x - and y- dimension. For higher frequencies a finer resolution is needed, thus for the grid spacing is reduced according the following table:

Area scan grid spacing for different frequency ranges	
Frequency range	Grid spacing
≤ 2 GHz	≤ 15 mm
2 – 4 GHz	≤ 12 mm
4 – 6 GHz	≤ 10 mm

Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation. Results of this coarse scan are shown in annex B.

- A „zoom scan” measures the field in a volume around the 2D peak SAR value acquired in the previous „coarse” scan. It uses a fine meshed grid where the robot moves the probe in steps along all the 3 axis (x,y and z-axis) starting at the bottom of the Phantom. The grid spacing for the cube measurement is varied according to the measured frequency range, the dimensions are given in the following table:

Zoom scan grid spacing and volume for different frequency ranges			
Frequency range	Grid spacing for x, y axis	Grid spacing for z axis	Minimum zoom scan volume
≤ 2 GHz	≤ 8 mm	≤ 5 mm	≥ 30 mm
2 – 3 GHz	≤ 5 mm	≤ 5 mm	≥ 28 mm
3 – 4 GHz	≤ 5 mm	≤ 4 mm	≥ 28 mm
4 – 5 GHz	≤ 4 mm	≤ 3 mm	≥ 25 mm
5 – 6 GHz	≤ 4 mm	≤ 2 mm	≥ 22 mm

DASY is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in annex B. Test results relevant for the specified standard (see section 3) are shown in table form in section 7.

Spatial Peak SAR Evaluation

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of all points in the three directions x, y and z. The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 1 to 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting 'Graph Evaluated'.
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR - values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computermathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff].

Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

Advanced Extrapolation

DASY uses the advanced extrapolation option which is able to compensate boundary effects on E-field probes.

SAM PHANTOM

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 2.6)

Phantom Specification

Phantom: SAM Twin Phantom (V4.0)
Shell Material: Vivac Composite
Thickness: 2.0 ± 0.2 mm




Figure 2.6 SAM Twin Phantom

Device Holder for Transmitters

In combination with the SAM Twin Phantom V4.0 the Mounting Device (see Fig. 2.7), enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC, CENELEC, IEC and IEEE specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



Figure 2.7 Mounting Device

Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produce infinite number of configurations. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

3. Probe and Dipole Calibration

See Appendix D and E.

4. Phantom & Simulating Tissue Specifications

Head & Body Simulating Mixture Characterization

The head and body mixtures consist of the material based on the table listed below. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. Body tissue parameters that have not been specified in IEEE1528-2013 are derived from the issue dielectric parameters computed from the 4-Cole-Cole equations.

Table 4.1 Typical Composition of Ingredients for Tissue

Ingredients	Simulating Tissue				
	2450 MHz Head	5250 MHz Head	5600 MHz Head	5750 MHz Head	
Mixing Percentage					
Water	Proprietary Mixture Procured from Speag				
Sugar					
Salt					
HEC					
Bactericide					
DGBE					
Dielectric Constant	Target	39.20	35.93	35.53	35.36
Conductivity (S/m)	Target	1.80	4.71	5.07	5.22

5. ANSI/IEEE C95.1 – 1992 RF Exposure Limits [2]

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 5.1 Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIROMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Head	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00

¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

6. Measurement Uncertainty

Measurement uncertainty table is not required per KDB 865664 D01 v01 section 2.8.2 page 12. SAR measurement uncertainty analysis is required in the SAR report only when the highest measured SAR in a frequency band is ≥ 1.5 W/kg for 1-g SAR. The equivalent ratio (1.5/1.6) should be applied to extremity and occupational exposure conditions. The highest reported value is less than 1.5 W/kg. Therefore, the measurement uncertainty table is not required.

7. System Validation

Tissue Verification

Table 7.1 Measured Tissue Parameters

		2450 MHz Head		5250 MHz Head	
Date(s)		May 26, 2022		May 23, 2022	
Liquid Temperature (°C)	20.0	Target	Measured	Target	Measured
Dielectric Constant: ϵ		39.20	38.57	35.93	34.94
Conductivity: σ		1.80	1.82	4.71	4.75
		5600 MHz Head		5750 MHz Head	
Date(s)		May 23, 2022		May 23, 2022	
Liquid Temperature (°C)	20.0	Target	Measured	Target	Measured
Dielectric Constant: ϵ		35.53	34.52	35.36	34.35
Conductivity: σ		5.07	5.13	5.22	5.30
		2450 MHz Head			
Date(s)		Jun. 17, 2022			
Liquid Temperature (°C)	20.0	Target	Measured		
Dielectric Constant: ϵ		39.20	38.60		
Conductivity: σ		1.80	1.83		

See Appendix A for data printout.

Test System Verification

Prior to assessment, the system is verified to the $\pm 10\%$ of the specifications at the test frequency by using the system kit. Power is normalized to 1 watt. (Graphic Plots Attached)

Table 7.2 System Dipole Validation Target & Measured

	Test Frequency	Targeted SAR _{1g} (W/kg)	Measure SAR _{1g} (W/kg)	Tissue Used for Verification	Deviation Target and Fast SAR to SAR (%)	Plot Number
26-May-2022	2450 MHz	54.10	52.00	Head	- 3.88	1
23-May-2022	5250 MHz	79.50	81.90	Head	+ 3.02	2
23-May-2022	5600 MHz	83.20	84.50	Head	+ 1.56	3
23-May-2022	5750 MHz	80.50	82.20	Head	+ 2.11	4
17-Jun-2022	2450 MHz	54.10	55.60	Head	+ 2.77	5

	Test Frequency	Targeted SAR _{10g} (W/kg)	Measure SAR _{10g} (W/kg)	Tissue Used for Verification	Deviation (%)	Plot Number
26-May-2022	2450 MHz	25.00	24.00	Head	- 4.00	1
23-May-2022	5250 MHz	22.90	23.40	Head	+ 2.18	2
23-May-2022	5600 MHz	23.80	24.10	Head	+ 1.26	3
23-May-2022	5750 MHz	23.00	23.50	Head	+ 2.17	4
17-Jun-2022	2450 MHz	25.00	25.30	Head	+ 1.20	5

See Appendix A for data plots.




Figure 7.1 Dipole Validation Test Setup

8. SAR Test Data Summary

See Measurement Result Data Pages

See Appendix B for SAR Test Data Plots.
See Appendix C for SAR Test Setup Photos.

Procedures Used To Establish Test Signal

The device was either placed into simulated transmit mode using the manufacturer's test codes or the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Condition

In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power unless otherwise noted. If a conducted power deviation of more than 5% occurred, the test was repeated. The power drift of each test is measured at the start of the test and again at the end of the test. The drift percentage is calculated by the formula $((\text{end}/\text{start})-1)*100$ and rounded to three decimal places. The drift percentage is calculated into the resultant SAR value on the data sheet for each test.

The device was tested on the front, back and left side for body SAR. The device was also tested on the bottom for extremity SAR. The bottom is only next to the hand during operation. The device is carried on the body with a belt clip holster which will allow the device to be next to the body on the four sides not the top or bottom. The belt clip is made of all plastic. Therefore, the measured positions are the most conservative.

The data rates used when evaluating the WiFi transmitter were the lowest data rates for each mode. The device was operating at its maximum output power at the lowest data rate for all measurements.

The NFC transmitter operates at less than 1 mW. The transmitter is excluded from SAR testing if it is less than 1 mW. Therefore, the NFC transmitter is excluded from SAR testing.

The antenna was on a minimum of 10 cm of Styrofoam during each test.

Antenna Location



Band	Mode	Bandwidth (MHz)	Channel	Frequency (MHz)	Data Rate	Antenna	Avg Power (dBm)	Tune-up Pwr (dBm)
2450 MHz	802.11b	20	1	2412	1 Mbps	Chain A	17.21	18.00
			6	2437			17.39	18.00
			11	2462			17.28	18.00
	802.11g	20	1	2412	6 Mbps	Chain A	Not Required	18.00
			6	2437				18.00
			11	2462				18.00
	802.11n	20	1	2412	MCS0	Chain A		18.00
			6	2437				18.00
			11	2462				18.00
	802.11n	40	3	2422	MCS0	Chain A	16.00	
			6	2437			16.00	
			9	2452			16.00	
5.15-5.25 GHz	802.11a	20	36	5180	6 Mbps	Chain A	17.38	18.00
			40	5200			17.49	18.00
			44	5220			17.44	18.00
			48	5240			17.40	18.00
	802.11n/ac	20	36	5180	MCS0	Chain A	Not Required	18.00
			40	5200				18.00
			44	5220				18.00
			48	5240				18.00
	802.11n/ac	40	38	5190	MCS0	Chain A		16.00
			46	5230				16.00
	802.11ac	80	42	5210	MCS0	Chain A	14.00	
	5.25-5.35 GHz	802.11a	20	52	5260	6 Mbps	Chain A	17.51
56				5280	17.54			18.00
60				5300	17.56			18.00
64				5320	17.52			18.00
802.11n		20	52	5260	MCS0	Chain A	Not Required	18.00
			56	5280				18.00
			60	5300				18.00
			64	5320				18.00
802.11n		40	54	5270	MCS0	Chain A		16.00
			62	5310				16.00
802.11ac		80	58	5290	MCS0	Chain A	14.00	

Band	Mode	Bandwidth (MHz)	Channel	Frequency (MHz)	Data Rate	Antenna	Avg Power (dBm)	Tune-up Pwr (dBm)
5600 MHz	802.11a	20	100	5500	6 Mbps	Chain A	17.66	18.00
			104	5520			17.69	18.00
			108	5540			17.72	18.00
			112	5560			17.75	18.00
			116	5580			17.79	18.00
			120	5600			17.78	18.00
			124	5620			17.81	18.00
			128	5640			17.76	18.00
			132	5660			17.70	18.00
			136	5680			17.73	18.00
	140	5700	17.72	18.00				
	802.11n/ac	20	MCS0	Chain A	100	5500	Not Required	18.00
					104	5520		18.00
					108	5540		18.00
					112	5560		18.00
					116	5580		18.00
					120	5600		18.00
					124	5620		18.00
					128	5640		18.00
					132	5660		18.00
					136	5680		18.00
	140	5700	18.00					
	802.11n/ac	40	MCS0	Chain A	102	5510	16.00	
					110	5550	16.00	
					118	5580	16.00	
					126	5610	16.00	
	802.11ac	80	MCS0	Chain A	136	5680	16.00	
					106	5530	14.00	
					122	5610	14.00	
	138	5690	14.00					
5800 MHz	802.11a	20	6 Mbps	Chain A	149	5745	17.79	
					153	5765	17.82	
					157	5785	17.86	
					161	5805	17.83	
					165	5825	17.84	
	802.11n	20	MCS0	Chain A	Not Required	149	5745	18.00
						153	5765	18.00
						157	5785	18.00
						161	5805	18.00
						165	5825	18.00
	802.11n	40	MCS0	Chain A	Not Required	151	5755	16.00
						159	5795	16.00
	802.11ac	80	MCS0	Chain A	Not Required	155	5775	14.00

Band	Mode	Channel	Frequency (MHz)	Data Rate	Antenna	Avg Power (dBm)	Tune-up Pwr (dBm)					
2450 MHz	Bluetooth v4.0	0	2402	Basic Rate GFSK	Chain A	9.26	10.10					
		39	2441			9.38	10.10					
		78	2480			9.21	10.10					
		0	2402	EDR $\pi/4$ DQPSK		Chain A	Not Required	6.70				
		39	2441					6.70				
		78	2480					6.70				
		0	2402	EDR 8-DPSK				Chain A	Not Required	6.70		
		39	2441							6.70		
		78	2480							6.70		
		0	2402	Low Energy GFSK						Chain A	Not Required	6.70
		39	2441									6.70
		78	2480									6.70

Figure 8.1 Test Reduction Table – 2.4 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11b	Front	1 – 2412 MHz	Reduced ⁴
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Tested
	Back	1 – 2412 MHz	Reduced ⁴
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Tested
	Left	1 – 2412 MHz	Reduced ¹
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Reduced ¹
	Bottom	1 – 2412 MHz	Reduced ¹
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Reduced ¹
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	
802.11g	Front	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Back	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Left	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Bottom	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	
802.11n	Front	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Back	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Left	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Bottom	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.2 Test Reduction Table – 5.1 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5150 MHz	Front	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Back	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Left	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Bottom	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Right, Top	48 – 5240 MHz	Reduced ¹
		36 – 5180 MHz	Reduced ²
40 – 5200 MHz		Reduced ²	
44 – 5220 MHz		Reduced ²	
802.11n 5150 MHz	Front	48 – 5240 MHz	Reduced ²
		36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Back	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Left	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Bottom	48 – 5240 MHz	Reduced ¹
		36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
	Right, Top	44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
36 – 5180 MHz		Reduced ²	
40 – 5200 MHz		Reduced ²	
802.11ac 5210 MHz	Right, Top	44 – 5220 MHz	Reduced ²
		48 – 5240 MHz	Reduced ²
		42 – 5210 MHz	Reduced ¹
		42 – 5210 MHz	Reduced ¹
		42 – 5210 MHz	Reduced ¹
802.11ac 5210 MHz	Front	42 – 5210 MHz	Reduced ¹
	Back	42 – 5210 MHz	Reduced ¹
	Left	42 – 5210 MHz	Reduced ¹
	Bottom	42 – 5210 MHz	Reduced ¹

Reduced¹ – When the the adjusted SAR is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity, SAR is not required for the UNII-1 with the same or lower maximum output power in that test configuration per KDB 248227 D01 v02r02 section 5.3.1 1) page 11.

Reduced² – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Figure 8.3 Test Reduction Table – 5.2 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5250 MHz	Front	52 – 5260 MHz	Reduced ⁴
		56 – 5280 MHz	Tested
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ⁴
	Back	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
	Left	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
	Bottom	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
Right, Top	52 – 5260 MHz	Reduced ³	
	56 – 5280 MHz	Reduced ³	
	60 – 5300 MHz	Reduced ³	
	64 – 5320 MHz	Reduced ³	
802.11n 5250 MHz	Front	52 – 5260 MHz	Reduced ⁴
		56 – 5280 MHz	Reduced ⁴
		60 – 5300 MHz	Reduced ⁴
		64 – 5320 MHz	Reduced ⁴
	Back	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
	Left	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
	Bottom	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
Right, Top	52 – 5260 MHz	Reduced ³	
	56 – 5280 MHz	Reduced ³	
	60 – 5300 MHz	Reduced ³	
	64 – 5320 MHz	Reduced ³	
802.11ac 5210 MHz	Front	58 – 5290 MHz	Reduced ⁴
	Back	58 – 5290 MHz	Reduced ¹
	Left	58 – 5290 MHz	Reduced ⁴
	Bottom	58 – 5290 MHz	Reduced ⁴
	Right, Top	58 – 5290 MHz	Reduced ³

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.4 Test Reduction Table – 5.6 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5600 MHz	Front	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
	136 – 5680 MHz	Reduced ⁵	
	140 – 5700 MHz	Reduced ⁵	
	Back	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
	136 – 5680 MHz	Reduced ⁴	
	140 – 5700 MHz	Reduced ⁴	
	Left	100 – 5500 MHz	Reduced ¹
		104 – 5520 MHz	Reduced ¹
		108 – 5540 MHz	Reduced ¹
		112 – 5560 MHz	Reduced ¹
		116 – 5580 MHz	Reduced ¹
		120 – 5600 MHz	Reduced ¹
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ¹
		132 – 5660 MHz	Reduced ¹
	136 – 5680 MHz	Reduced ¹	
	140 – 5700 MHz	Reduced ¹	
	Bottom	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
	136 – 5680 MHz	Reduced ⁴	
	140 – 5700 MHz	Reduced ⁴	
	Right, Top	100 – 5500 MHz	Reduced ³
		104 – 5520 MHz	Reduced ³
		108 – 5540 MHz	Reduced ³
		112 – 5560 MHz	Reduced ³
116 – 5580 MHz		Reduced ³	
120 – 5600 MHz		Reduced ³	
124 – 5620 MHz		Reduced ³	
128 – 5640 MHz		Reduced ³	
132 – 5660 MHz		Reduced ³	
136 – 5680 MHz	Reduced ³		
140 – 5700 MHz	Reduced ³		

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.5 Test Reduction Table – 5.6 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11n 5600 MHz	Front	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Reduced ⁵
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Reduced ⁵
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
		136 – 5680 MHz	Reduced ⁵
	140 – 5700 MHz	Reduced ⁵	
	Back	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Reduced ⁴
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Reduced ⁴
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
		136 – 5680 MHz	Reduced ⁴
	140 – 5700 MHz	Reduced ⁴	
	Left	100 – 5500 MHz	Reduced ¹
		104 – 5520 MHz	Reduced ¹
		108 – 5540 MHz	Reduced ¹
		112 – 5560 MHz	Reduced ¹
		116 – 5580 MHz	Reduced ¹
		120 – 5600 MHz	Reduced ¹
		124 – 5620 MHz	Reduced ¹
		128 – 5640 MHz	Reduced ¹
		132 – 5660 MHz	Reduced ¹
		136 – 5680 MHz	Reduced ¹
	140 – 5700 MHz	Reduced ¹	
	Bottom	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Reduced ⁴
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Reduced ⁴
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
		136 – 5680 MHz	Reduced ⁴
	140 – 5700 MHz	Reduced ⁴	
	Right, Top	100 – 5500 MHz	Reduced ³
		104 – 5520 MHz	Reduced ³
		108 – 5540 MHz	Reduced ³
		112 – 5560 MHz	Reduced ³
116 – 5580 MHz		Reduced ³	
120 – 5600 MHz		Reduced ³	
124 – 5620 MHz		Reduced ³	
128 – 5640 MHz		Reduced ³	
132 – 5660 MHz		Reduced ³	
136 – 5680 MHz		Reduced ³	
140 – 5700 MHz	Reduced ³		

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.6 Test Reduction Table – 5.6 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11ac 5600 MHz	Front	106 – 5530 MHz	Reduced ⁵
		122 – 5610 MHz	Reduced ⁵
		138 – 5690 MHz	Reduced ⁵
	Back	106 – 5530 MHz	Reduced ⁴
		122 – 5610 MHz	Reduced ⁴
		138 – 5690 MHz	Reduced ⁴
	Left	106 – 5530 MHz	Reduced ¹
		122 – 5610 MHz	Reduced ¹
		138 – 5690 MHz	Reduced ¹
	Bottom	106 – 5530 MHz	Reduced ⁴
		122 – 5610 MHz	Reduced ⁴
		138 – 5690 MHz	Reduced ⁴
Right, Top	106 – 5530 MHz	Reduced ³	
	122 – 5610 MHz	Reduced ³	
	138 – 5690 MHz	Reduced ³	

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.7 Test Reduction Table – 5.8 GHz A710x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5800 MHz	Front	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Tested
	Back	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Tested
	Left	149 – 5745 MHz	Reduced ¹
		153 – 5765 MHz	Reduced ¹
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ¹
		165 – 5825 MHz	Reduced ¹
	Bottom	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Tested
Right, Top	149 – 5745 MHz	Reduced ³	
	153 – 5765 MHz	Reduced ³	
	157 – 5785 MHz	Reduced ³	
	161 – 5805 MHz	Reduced ³	
	165 – 5825 MHz	Reduced ³	
802.11n 5800 MHz	Front	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Reduced ⁵
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Reduced ⁵
	Back	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Reduced ⁴
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Reduced ⁴
	Left	149 – 5745 MHz	Reduced ¹
		153 – 5765 MHz	Reduced ¹
		157 – 5785 MHz	Reduced ¹
		161 – 5805 MHz	Reduced ¹
		165 – 5825 MHz	Reduced ¹
	Bottom	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Reduced ⁴
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Reduced ⁴
Right, Top	149 – 5745 MHz	Reduced ³	
	153 – 5765 MHz	Reduced ³	
	157 – 5785 MHz	Reduced ³	
	161 – 5805 MHz	Reduced ³	
	165 – 5825 MHz	Reduced ³	
802.11ac 5800 MHz	Front	155 – 5775 MHz	Reduced ⁵
	Back	155 – 5775 MHz	Reduced ⁴
	Left	155 – 5775 MHz	Reduced ¹
	Bottom	155 – 5775 MHz	Reduced ⁴
	Right, Top	155 – 5775 MHz	Reduced ³

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.8 Test Reduction Table – 2.4 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11b	Front	1 – 2412 MHz	Reduced ⁴
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Tested
	Back	1 – 2412 MHz	Reduced ⁵
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Tested
	Left	1 – 2412 MHz	Reduced ¹
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Reduced ¹
	Bottom	1 – 2412 MHz	Reduced ¹
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Reduced ¹
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	
802.11g	Front	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Back	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Left	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Bottom	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	
802.11n	Front	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Back	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Left	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Bottom	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.9 Test Reduction Table – 5.1 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5150 MHz	Front	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Back	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Left	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Bottom	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Right, Top	48 – 5240 MHz	Reduced ¹
		36 – 5180 MHz	Reduced ²
40 – 5200 MHz		Reduced ²	
44 – 5220 MHz		Reduced ²	
802.11n 5150 MHz	Front	48 – 5240 MHz	Reduced ²
		36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Back	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Left	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Bottom	48 – 5240 MHz	Reduced ¹
		36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
	Right, Top	44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
36 – 5180 MHz		Reduced ²	
40 – 5200 MHz		Reduced ²	
802.11ac 5210 MHz	Right, Top	44 – 5220 MHz	Reduced ²
		48 – 5240 MHz	Reduced ²
		42 – 5210 MHz	Reduced ¹
		42 – 5210 MHz	Reduced ¹
		42 – 5210 MHz	Reduced ¹

Reduced¹ – When the the adjusted SAR is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity, SAR is not required for the UNII-1 with the same or lower maximum output power in that test configuration per KDB 248227 D01 v02r02 section 5.3.1 1) page 11.

Reduced² – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Figure 8.10 Test Reduction Table – 5.2 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5250 MHz	Front	52 – 5260 MHz	Reduced ⁴
		56 – 5280 MHz	Tested
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ⁴
	Back	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
	Left	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
	Bottom	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
Right, Top	52 – 5260 MHz	Reduced ³	
	56 – 5280 MHz	Reduced ³	
	60 – 5300 MHz	Reduced ³	
	64 – 5320 MHz	Reduced ³	
802.11n 5250 MHz	Front	52 – 5260 MHz	Reduced ⁴
		56 – 5280 MHz	Reduced ⁴
		60 – 5300 MHz	Reduced ⁴
		64 – 5320 MHz	Reduced ⁴
	Back	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
	Left	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
	Bottom	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
Right, Top	52 – 5260 MHz	Reduced ³	
	56 – 5280 MHz	Reduced ³	
	60 – 5300 MHz	Reduced ³	
	64 – 5320 MHz	Reduced ³	
802.11ac 5210 MHz	Front	58 – 5290 MHz	Reduced ⁴
	Back	58 – 5290 MHz	Reduced ¹
	Left	58 – 5290 MHz	Reduced ⁴
	Bottom	58 – 5290 MHz	Reduced ⁴
	Right, Top	58 – 5290 MHz	Reduced ³

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.11 Test Reduction Table – 5.6 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5600 MHz	Front	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
		136 – 5680 MHz	Reduced ⁵
	140 – 5700 MHz	Reduced ⁵	
	Back	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
		136 – 5680 MHz	Reduced ⁴
	140 – 5700 MHz	Reduced ⁴	
	Left	100 – 5500 MHz	Reduced ¹
		104 – 5520 MHz	Reduced ¹
		108 – 5540 MHz	Reduced ¹
		112 – 5560 MHz	Reduced ¹
		116 – 5580 MHz	Reduced ¹
		120 – 5600 MHz	Reduced ¹
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ¹
		132 – 5660 MHz	Reduced ¹
		136 – 5680 MHz	Reduced ¹
	140 – 5700 MHz	Reduced ¹	
	Bottom	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Tested
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
		136 – 5680 MHz	Tested
	140 – 5700 MHz	Reduced ⁵	
	Right, Top	100 – 5500 MHz	Reduced ³
		104 – 5520 MHz	Reduced ³
		108 – 5540 MHz	Reduced ³
		112 – 5560 MHz	Reduced ³
		116 – 5580 MHz	Reduced ³
		120 – 5600 MHz	Reduced ³
124 – 5620 MHz		Reduced ³	
128 – 5640 MHz		Reduced ³	
132 – 5660 MHz		Reduced ³	
136 – 5680 MHz		Reduced ³	
140 – 5700 MHz	Reduced ³		

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.12 Test Reduction Table – 5.6 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11n 5600 MHz	Front	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Reduced ⁵
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Reduced ⁵
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
		136 – 5680 MHz	Reduced ⁵
	140 – 5700 MHz	Reduced ⁵	
	Back	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Reduced ⁴
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Reduced ⁴
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
		136 – 5680 MHz	Reduced ⁴
	140 – 5700 MHz	Reduced ⁴	
	Left	100 – 5500 MHz	Reduced ¹
		104 – 5520 MHz	Reduced ¹
		108 – 5540 MHz	Reduced ¹
		112 – 5560 MHz	Reduced ¹
		116 – 5580 MHz	Reduced ¹
		120 – 5600 MHz	Reduced ¹
		124 – 5620 MHz	Reduced ¹
		128 – 5640 MHz	Reduced ¹
		132 – 5660 MHz	Reduced ¹
		136 – 5680 MHz	Reduced ¹
	140 – 5700 MHz	Reduced ¹	
	Bottom	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Reduced ⁵
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Reduced ⁵
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
		136 – 5680 MHz	Reduced ⁵
	140 – 5700 MHz	Reduced ⁵	
	Right, Top	100 – 5500 MHz	Reduced ³
		104 – 5520 MHz	Reduced ³
		108 – 5540 MHz	Reduced ³
		112 – 5560 MHz	Reduced ³
116 – 5580 MHz		Reduced ³	
120 – 5600 MHz		Reduced ³	
124 – 5620 MHz		Reduced ³	
128 – 5640 MHz		Reduced ³	
132 – 5660 MHz		Reduced ³	
136 – 5680 MHz		Reduced ³	
140 – 5700 MHz	Reduced ³		

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.13 Test Reduction Table – 5.6 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11ac 5600 MHz	Front	106 – 5530 MHz	Reduced ⁵
		122 – 5610 MHz	Reduced ⁵
		138 – 5690 MHz	Reduced ⁵
	Back	106 – 5530 MHz	Reduced ⁴
		122 – 5610 MHz	Reduced ⁴
		138 – 5690 MHz	Reduced ⁴
	Left	106 – 5530 MHz	Reduced ¹
		122 – 5610 MHz	Reduced ¹
		138 – 5690 MHz	Reduced ¹
	Bottom	106 – 5530 MHz	Reduced ⁵
		122 – 5610 MHz	Reduced ⁵
		138 – 5690 MHz	Reduced ⁵
Right, Top	106 – 5530 MHz	Reduced ³	
	122 – 5610 MHz	Reduced ³	
	138 – 5690 MHz	Reduced ³	

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.14 Test Reduction Table – 5.8 GHz A720x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5800 MHz	Front	149 – 5745 MHz	Tested
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Tested
	Back	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Tested
	Left	149 – 5745 MHz	Reduced ¹
		153 – 5765 MHz	Reduced ¹
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ¹
		165 – 5825 MHz	Reduced ¹
	Bottom	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Tested
Right, Top	149 – 5745 MHz	Reduced ³	
	153 – 5765 MHz	Reduced ³	
	157 – 5785 MHz	Reduced ³	
	161 – 5805 MHz	Reduced ³	
	165 – 5825 MHz	Reduced ³	
802.11n 5800 MHz	Front	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Reduced ⁵
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Reduced ⁵
	Back	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Reduced ⁵
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Reduced ⁵
	Left	149 – 5745 MHz	Reduced ¹
		153 – 5765 MHz	Reduced ¹
		157 – 5785 MHz	Reduced ¹
		161 – 5805 MHz	Reduced ¹
		165 – 5825 MHz	Reduced ¹
	Bottom	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Reduced ⁴
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Reduced ⁴
Right, Top	149 – 5745 MHz	Reduced ³	
	153 – 5765 MHz	Reduced ³	
	157 – 5785 MHz	Reduced ³	
	161 – 5805 MHz	Reduced ³	
	165 – 5825 MHz	Reduced ³	
802.11ac 5800 MHz	Front	155 – 5775 MHz	Reduced ⁵
	Back	155 – 5775 MHz	Reduced ⁵
	Left	155 – 5775 MHz	Reduced ¹
	Bottom	155 – 5775 MHz	Reduced ⁴
	Right, Top	155 – 5775 MHz	Reduced ³

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.15 Test Reduction Table – 2.4 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11b	Front	1 – 2412 MHz	Reduced ⁴
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Tested
	Back	1 – 2412 MHz	Reduced ⁴
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Tested
	Left	1 – 2412 MHz	Reduced ¹
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Reduced ¹
	Bottom	1 – 2412 MHz	Reduced ¹
		6 – 2437 MHz	Tested
		11 – 2462 MHz	Reduced ¹
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	
802.11g	Front	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Back	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Left	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Bottom	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	
802.11n	Front	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Back	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Left	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
	Bottom	1 – 2412 MHz	Reduced ²
		6 – 2437 MHz	Reduced ²
		11 – 2462 MHz	Reduced ²
Right, Top	1 – 2412 MHz	Reduced ³	
	6 – 2437 MHz	Reduced ³	
	11 – 2462 MHz	Reduced ³	

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.16 Test Reduction Table – 5.1 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5150 MHz	Front	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Back	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Left	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Bottom	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Right, Top	48 – 5240 MHz	Reduced ¹
		36 – 5180 MHz	Reduced ²
40 – 5200 MHz		Reduced ²	
44 – 5220 MHz		Reduced ²	
802.11n 5150 MHz	Front	48 – 5240 MHz	Reduced ²
		36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Back	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
	Left	36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
		44 – 5220 MHz	Reduced ¹
	Bottom	48 – 5240 MHz	Reduced ¹
		36 – 5180 MHz	Reduced ¹
		40 – 5200 MHz	Reduced ¹
	Right, Top	44 – 5220 MHz	Reduced ¹
		48 – 5240 MHz	Reduced ¹
36 – 5180 MHz		Reduced ²	
40 – 5200 MHz		Reduced ²	
802.11ac 5210 MHz	Right, Top	44 – 5220 MHz	Reduced ²
		48 – 5240 MHz	Reduced ²
		42 – 5210 MHz	Reduced ¹
		42 – 5210 MHz	Reduced ¹
		42 – 5210 MHz	Reduced ¹
802.11ac 5210 MHz	Front	42 – 5210 MHz	Reduced ¹
	Back	42 – 5210 MHz	Reduced ¹
	Left	42 – 5210 MHz	Reduced ¹
	Bottom	42 – 5210 MHz	Reduced ¹

Reduced¹ – When the the adjusted SAR is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity, SAR is not required for the UNII-1 with the same or lower maximum output power in that test configuration per KDB 248227 D01 v02r02 section 5.3.1 1) page 11.

Reduced² – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Figure 8.17 Test Reduction Table – 5.2 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5250 MHz	Front	52 – 5260 MHz	Reduced ⁴
		56 – 5280 MHz	Tested
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ⁴
	Back	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
	Left	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
	Bottom	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Tested
		64 – 5320 MHz	Reduced ¹
Right, Top	52 – 5260 MHz	Reduced ³	
	56 – 5280 MHz	Reduced ³	
	60 – 5300 MHz	Reduced ³	
	64 – 5320 MHz	Reduced ³	
802.11n 5250 MHz	Front	52 – 5260 MHz	Reduced ⁴
		56 – 5280 MHz	Reduced ⁴
		60 – 5300 MHz	Reduced ⁴
		64 – 5320 MHz	Reduced ⁴
	Back	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
	Left	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
	Bottom	52 – 5260 MHz	Reduced ¹
		56 – 5280 MHz	Reduced ¹
		60 – 5300 MHz	Reduced ¹
		64 – 5320 MHz	Reduced ¹
Right, Top	52 – 5260 MHz	Reduced ³	
	56 – 5280 MHz	Reduced ³	
	60 – 5300 MHz	Reduced ³	
	64 – 5320 MHz	Reduced ³	
802.11ac 5210 MHz	Front	58 – 5290 MHz	Reduced ⁴
	Back	58 – 5290 MHz	Reduced ¹
	Left	58 – 5290 MHz	Reduced ⁴
	Bottom	58 – 5290 MHz	Reduced ⁴
	Right, Top	58 – 5290 MHz	Reduced ³

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.18 Test Reduction Table – 5.6 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5600 MHz	Front	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
	136 – 5680 MHz	Reduced ⁵	
	140 – 5700 MHz	Reduced ⁵	
	Back	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
	136 – 5680 MHz	Reduced ⁴	
	140 – 5700 MHz	Reduced ⁴	
	Left	100 – 5500 MHz	Reduced ¹
		104 – 5520 MHz	Reduced ¹
		108 – 5540 MHz	Reduced ¹
		112 – 5560 MHz	Reduced ¹
		116 – 5580 MHz	Reduced ¹
		120 – 5600 MHz	Reduced ¹
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ¹
		132 – 5660 MHz	Reduced ¹
	136 – 5680 MHz	Reduced ¹	
	140 – 5700 MHz	Reduced ¹	
	Bottom	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Tested
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Tested
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
	136 – 5680 MHz	Reduced ⁴	
	140 – 5700 MHz	Reduced ⁴	
	Right, Top	100 – 5500 MHz	Reduced ³
		104 – 5520 MHz	Reduced ³
		108 – 5540 MHz	Reduced ³
		112 – 5560 MHz	Reduced ³
116 – 5580 MHz		Reduced ³	
120 – 5600 MHz		Reduced ³	
124 – 5620 MHz		Reduced ³	
128 – 5640 MHz		Reduced ³	
132 – 5660 MHz		Reduced ³	
136 – 5680 MHz	Reduced ³		
140 – 5700 MHz	Reduced ³		

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.19 Test Reduction Table – 5.6 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11n 5600 MHz	Front	100 – 5500 MHz	Reduced ⁵
		104 – 5520 MHz	Reduced ⁵
		108 – 5540 MHz	Reduced ⁵
		112 – 5560 MHz	Reduced ⁵
		116 – 5580 MHz	Reduced ⁵
		120 – 5600 MHz	Reduced ⁵
		124 – 5620 MHz	Reduced ⁵
		128 – 5640 MHz	Reduced ⁵
		132 – 5660 MHz	Reduced ⁵
		136 – 5680 MHz	Reduced ⁵
	140 – 5700 MHz	Reduced ⁵	
	Back	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Reduced ⁴
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Reduced ⁴
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
		136 – 5680 MHz	Reduced ⁴
	140 – 5700 MHz	Reduced ⁴	
	Left	100 – 5500 MHz	Reduced ¹
		104 – 5520 MHz	Reduced ¹
		108 – 5540 MHz	Reduced ¹
		112 – 5560 MHz	Reduced ¹
		116 – 5580 MHz	Reduced ¹
		120 – 5600 MHz	Reduced ¹
		124 – 5620 MHz	Reduced ¹
		128 – 5640 MHz	Reduced ¹
		132 – 5660 MHz	Reduced ¹
		136 – 5680 MHz	Reduced ¹
	140 – 5700 MHz	Reduced ¹	
	Bottom	100 – 5500 MHz	Reduced ⁴
		104 – 5520 MHz	Reduced ⁴
		108 – 5540 MHz	Reduced ⁴
		112 – 5560 MHz	Reduced ⁴
		116 – 5580 MHz	Reduced ⁴
		120 – 5600 MHz	Reduced ⁴
		124 – 5620 MHz	Reduced ⁴
		128 – 5640 MHz	Reduced ⁴
		132 – 5660 MHz	Reduced ⁴
		136 – 5680 MHz	Reduced ⁴
	140 – 5700 MHz	Reduced ⁴	
	Right, Top	100 – 5500 MHz	Reduced ³
		104 – 5520 MHz	Reduced ³
		108 – 5540 MHz	Reduced ³
		112 – 5560 MHz	Reduced ³
116 – 5580 MHz		Reduced ³	
120 – 5600 MHz		Reduced ³	
124 – 5620 MHz		Reduced ³	
128 – 5640 MHz		Reduced ³	
132 – 5660 MHz		Reduced ³	
136 – 5680 MHz		Reduced ³	
140 – 5700 MHz	Reduced ³		

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.20 Test Reduction Table – 5.6 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11ac 5600 MHz	Front	106 – 5530 MHz	Reduced ⁵
		122 – 5610 MHz	Reduced ⁵
		138 – 5690 MHz	Reduced ⁵
	Back	106 – 5530 MHz	Reduced ⁴
		122 – 5610 MHz	Reduced ⁴
		138 – 5690 MHz	Reduced ⁴
	Left	106 – 5530 MHz	Reduced ¹
		122 – 5610 MHz	Reduced ¹
		138 – 5690 MHz	Reduced ¹
	Bottom	106 – 5530 MHz	Reduced ⁴
		122 – 5610 MHz	Reduced ⁴
		138 – 5690 MHz	Reduced ⁴
Right, Top	106 – 5530 MHz	Reduced ³	
	122 – 5610 MHz	Reduced ³	
	138 – 5690 MHz	Reduced ³	

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.

Figure 8.21 Test Reduction Table – 5.8 GHz A730x

Mode	Side	Required Channel	Tested/Reduced
802.11a 5800 MHz	Front	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Tested
	Back	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Tested
	Left	149 – 5745 MHz	Reduced ¹
		153 – 5765 MHz	Reduced ¹
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ¹
		165 – 5825 MHz	Reduced ¹
	Bottom	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Tested
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Tested
Right, Top	149 – 5745 MHz	Reduced ³	
	153 – 5765 MHz	Reduced ³	
	157 – 5785 MHz	Reduced ³	
	161 – 5805 MHz	Reduced ³	
	165 – 5825 MHz	Reduced ³	
802.11n 5800 MHz	Front	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Reduced ⁵
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Reduced ⁵
	Back	149 – 5745 MHz	Reduced ⁵
		153 – 5765 MHz	Reduced ⁵
		157 – 5785 MHz	Reduced ⁵
		161 – 5805 MHz	Reduced ⁵
		165 – 5825 MHz	Reduced ⁵
	Left	149 – 5745 MHz	Reduced ¹
		153 – 5765 MHz	Reduced ¹
		157 – 5785 MHz	Reduced ¹
		161 – 5805 MHz	Reduced ¹
		165 – 5825 MHz	Reduced ¹
	Bottom	149 – 5745 MHz	Reduced ⁴
		153 – 5765 MHz	Reduced ⁴
		157 – 5785 MHz	Reduced ⁴
		161 – 5805 MHz	Reduced ⁴
		165 – 5825 MHz	Reduced ⁴
Right, Top	149 – 5745 MHz	Reduced ³	
	153 – 5765 MHz	Reduced ³	
	157 – 5785 MHz	Reduced ³	
	161 – 5805 MHz	Reduced ³	
	165 – 5825 MHz	Reduced ³	
802.11ac 5800 MHz	Front	155 – 5775 MHz	Reduced ⁵
	Back	155 – 5775 MHz	Reduced ⁵
	Left	155 – 5775 MHz	Reduced ¹
	Bottom	155 – 5775 MHz	Reduced ⁴
	Right, Top	155 – 5775 MHz	Reduced ³

Reduced¹ – When the reported SAR is ≤ 0.4 W/kg for body or 1.0 W/kg for extremity, SAR is not required for the remaining test configuration per KDB 248227 D01 v02r02 section 5.1.1 1) page 9.

Reduced² – When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required per KDB 248227 D01 v02r02 section 5.2.2 2) page 10.

Reduced³ – When the antenna is more than 25 mm from a side, the test can be reduced per 47 CFR 1.1307.

Reduced⁴ – When the reported SAR is >0.4 W/kg for body or 1.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 0.8 W/kg for body or 2.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 2) page 9.

Reduced⁵ – When the reported SAR is >0.8 W/kg for body or 2.0 W/kg for extremity, test the next highest configuration until the SAR value is ≤ 1.2 W/kg for body or 3.0 W/kg for extremity per KDB 248227 D01 v02r02 section 5.1.1 3) page 9.


SAR Data Summary – 2450 MHz Body 802.11b Body

MEASUREMENT RESULTS

Plot	Gap	Model	Frequency		Modulation	Position	End Power (dBm)	Measured SAR (W/kg)	Reported SAR (W/kg)	
			MHz	Ch.						
-----	0 mm	A710x	2437	6	DSSS	Front	17.39	0.430	0.50	
-----			2462	11	DSSS		17.28	0.324	0.38	
-----			2437	6	DSSS	Back	17.39	0.685	0.79	
-----			2462	11	DSSS		17.28	0.561	0.66	
-----			2437	6	DSSS	Left	17.39	0.0799	0.09	
-----			A720x	A710x	2437	6	DSSS	Front	17.39	0.505
-----		2462			11	DSSS	17.28		0.389	0.46
1		2437		6	DSSS	Back	17.39	0.823	0.95	
-----		2462		11	DSSS		17.28	0.752	0.89	
-----		2437		6	DSSS	Left	17.39	0.0778	0.09	
-----		A730x		A710x	2437	6	DSSS	Front	17.39	0.502
-----			2462		11	DSSS	17.28		0.412	0.49
-----			2437	6	DSSS	Back	17.39	0.576	0.66	
-----			2462	11	DSSS		17.28	0.492	0.58	
-----			2437	6	DSSS	Left	17.39	0.145	0.17	
-----			A710x	2441	39	GFSK	Front	9.38	0.0537	0.06
-----		2441		39	GFSK	Back	9.38	0.0856	0.10	
-----		2441		39	GFSK	Left	9.38	0.0102	0.01	
-----		A720x	2441	39	GFSK	Front	9.38	0.0631	0.07	
-----			2441	39	GFSK	Back	9.38	0.103	0.12	
-----			2441	39	GFSK	Left	9.38	0.0101	0.01	
-----		A730x	2441	39	GFSK	Front	9.38	0.0627	0.07	
-----			2441	39	GFSK	Back	9.38	0.0721	0.08	
-----			2441	39	GFSK	Left	9.38	0.0181	0.02	
-----		Repeat	2437	6	DSSS	Back	17.39	0.809	0.93	

Body
1.6 W/kg (mW/g)
 averaged over 1 gram

- Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
- SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
- Test Signal Call Mode Test Code Base Station Simulator
- Test Configuration With Belt Clip Without Belt Clip N/A
- Tissue Depth is at least 15.0 cm



Jay M. Moulton
 Vice President

SAR Data Summary – 2450 MHz Body 802.11b Extremity

MEASUREMENT RESULTS

Plot	Gap	Model	Frequency		Modulation	Position	End Power (dBm)	Measured SAR (W/kg)	Reported SAR (W/kg)
			MHz	Ch.					
2	0 mm	A710x	2437	6	DSSS	Bottom	17.39	0.928	1.07
-----		A720x	2437	6	DSSS	Bottom	17.39	0.825	0.95
-----		A730x	2437	6	DSSS	Bottom	17.39	0.881	1.01
-----		A710x	2441	39	GFSK	Bottom	9.38	0.116	0.13
-----		A720x	2441	39	GFSK	Bottom	9.38	0.103	0.12
-----		A730x	2441	39	GFSK	Bottom	9.38	0.110	0.13

Extremity
4.0 W/kg (mW/g)
 averaged over 10 gram

1. Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
2. SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
3. Test Signal Call Mode Test Code Base Station Simulator
4. Test Configuration With Belt Clip Without Belt Clip N/A
5. Tissue Depth is at least 15.0 cm



Jay M. Moulton
 Vice President

SAR Data Summary – 5250 MHz Body 802.11a Body

MEASUREMENT RESULTS

Plot	Gap	Model	Frequency		Modulation	Position	End Power (dBm)	Measured SAR (W/kg)	Reported SAR (W/kg)	
			MHz	Ch.						
----	0 mm	A710x	5280	56	OFDM	Front	17.56	0.395	0.44	
----			5300	60	OFDM		17.52	0.421	0.47	
----			5300	60	OFDM	Back	17.52	0.288	0.32	
----			5300	60	OFDM	Left	17.52	0.043	0.05	
----		A720x	Front	5280	56	OFDM	Front	17.56	0.420	0.47
3				5300	60	OFDM		17.52	0.460	0.51
----			5300	60	OFDM	Back	17.52	0.287	0.32	
----			5300	60	OFDM	Left	17.52	0.0641	0.07	
----		A730x	Front	5280	56	OFDM	Front	17.56	0.371	0.41
----				5300	60	OFDM		17.52	0.395	0.44
----			5300	60	OFDM	Back	17.52	0.254	0.28	
----			5300	60	OFDM	Left	17.52	0.051	0.06	

Body
1.6 W/kg (mW/g)
 averaged over 1 gram

1. Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
2. SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
3. Test Signal Call Mode Test Code Base Station Simulator
4. Test Configuration With Belt Clip Without Belt Clip N/A
5. Tissue Depth is at least 15.0 cm



Jay M. Moulton
 Vice President


SAR Data Summary – 5250 MHz Body 802.11a Extremity

MEASUREMENT RESULTS

Plot	Gap	Model	Frequency		Modulation	Position	End Power (dBm)	Measured SAR (W/kg)	Reported SAR (W/kg)
			MHz	Ch.					
4	0 mm	A710x	5300	60	OFDM	Bottom	17.52	0.742	0.83
-----		A720x	5300	60	OFDM	Bottom	17.52	0.638	0.71
-----		A730x	5300	60	OFDM	Bottom	17.52	0.617	0.69

Extremity
4.0 W/kg (mW/g)
 averaged over 10 gram

1. Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
2. SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
3. Test Signal Call Mode Test Code Base Station Simulator
4. Test Configuration With Belt Clip Without Belt Clip N/A
5. Tissue Depth is at least 15.0 cm



 Jay M. Moulton
 Vice President

SAR Data Summary – 5600 MHz Body 802.11a Body

MEASUREMENT RESULTS									
Plot	Gap	Model	Frequency		Modulation	Position	End Power	Measured SAR (W/kg)	Reported SAR (W/kg)
			MHz	Ch.			(dBm)		
----	0 mm	A710x	5580	116	OFDM	Front	17.79	0.835	0.88
----			5620	124	OFDM		17.81	0.856	0.89
----			5580	116	OFDM	Back	17.79	0.690	0.72
----			5620	124	OFDM		17.81	0.689	0.72
----			5620	124	OFDM	Left	17.81	0.113	0.12
----		A720x	Front	5580	116	OFDM	17.79	1.04	1.09
5				5620	124	OFDM	17.81	1.05	1.10
----			Back	5580	116	OFDM	17.79	0.746	0.78
----				5620	124	OFDM	17.81	0.794	0.83
----			5620	124	OFDM	Left	17.81	0.152	0.16
----		A730x	Front	5580	116	OFDM	17.79	0.858	0.90
----				5620	124	OFDM	17.81	0.847	0.88
----			Back	5580	116	OFDM	17.79	0.600	0.63
----				5620	124	OFDM	17.81	0.631	0.66
----			5620	124	OFDM	Left	17.81	0.110	0.11
----	Repeat		5620	124	OFDM	Front	17.81	1.03	1.08

Body
1.6 W/kg (mW/g)
 averaged over 1 gram

- Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
- SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
- Test Signal Call Mode Test Code Base Station Simulator
- Test Configuration With Belt Clip Without Belt Clip N/A
- Tissue Depth is at least 15.0 cm




Jay M. Moulton
 Vice President

SAR Data Summary – 5600 MHz Body 802.11a Extremity

MEASUREMENT RESULTS									
Plot	Gap	Model	Frequency		Modulation	Position	End Power	Measured SAR (W/kg)	Reported SAR (W/kg)
			MHz	Ch.			(dBm)		
----	0 mm	A710x	5580	116	OFDM	Bottom	17.79	1.78	1.87
----			5620	124	OFDM		17.81	1.75	1.83
----		A720x	5580	116	OFDM	Bottom	17.79	1.80	1.89
----			5620	124	OFDM		17.81	1.97	2.06
6			5580	116	OFDM		17.79	2.06	2.16
----			5620	124	OFDM		17.81	1.85	1.93
----		A730x	5580	116	OFDM	Bottom	17.79	1.66	1.74
----			5620	124	OFDM		17.81	1.67	1.75
----		Repeat	5580	116	OFDM	Bottom	17.79	2.04	2.14

Extremity
4.0 W/kg (mW/g)
 averaged over 10 gram

1. Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
2. SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
3. Test Signal Call Mode Test Code Base Station Simulator
4. Test Configuration With Belt Clip Without Belt Clip N/A
5. Tissue Depth is at least 15.0 cm



 Jay M. Moulton
 Vice President


SAR Data Summary – 5800 MHz Body 802.11a Body

MEASUREMENT RESULTS

Plot	Gap	Model	Frequency		Modulation	Position	End Power (dBm)	Measured SAR (W/kg)	Reported SAR (W/kg)
			MHz	Ch.					
----	0 mm	A710x	5785	157	OFDM	Front	17.86	0.881	0.91
----			5825	165	OFDM		17.84	0.880	0.91
----			5785	157	OFDM	Back	17.86	0.764	0.79
----			5825	165	OFDM		17.84	0.771	0.80
----			5785	157	OFDM	Left	17.86	0.0966	0.10
----			A720x	5745	149	OFDM	Front	17.79	1.04
7		5785		157	OFDM	17.86		1.08	1.12
----		5825		165	OFDM	17.81		1.07	1.12
----		5785		157	OFDM	Back	17.86	0.802	0.83
----		5825		165	OFDM		17.84	0.816	0.85
----		5785		157	OFDM		Left	17.86	0.127
----		A730x	5785	157	OFDM	Front	17.86	0.944	0.97
----			5825	165	OFDM		17.84	0.930	0.96
----			5785	157	OFDM	Back	17.86	0.943	0.97
----			5825	165	OFDM		17.84	0.817	0.85
----			5785	157	OFDM		Left	17.86	0.106
----		Repeat	5785	157	OFDM	Front	17.86	1.06	1.09

Body
1.6 W/kg (mW/g)
 averaged over 1 gram

- Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
- SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
- Test Signal Call Mode Test Code Base Station Simulator
- Test Configuration With Belt Clip Without Belt Clip N/A
- Tissue Depth is at least 15.0 cm




Jay M. Moulton
 Vice President

SAR Data Summary – 5800 MHz Body 802.11a Extremity

MEASUREMENT RESULTS									
Plot	Gap	Model	Frequency		Modulation	Position	End Power (dBm)	Measured SAR (W/kg)	Reported SAR (W/kg)
			MHz	Ch.					
----	0 mm	A710x	5785	157	OFDM	Bottom	17.86	1.43	1.48
----			5825	165	OFDM		17.84	1.49	1.55
----		A720x	5785	157	OFDM	Front	17.86	1.82	1.88
8			5825	165	OFDM		17.84	1.90	1.97
----		A730x	5785	157	OFDM	Front	17.86	1.77	1.83
----			5825	165	OFDM		17.84	1.60	1.66
----		Repeat	5825	165	OFDM	Front	17.84	1.88	1.95

Extremity
4.0 W/kg (mW/g)
averaged over 10 gram

1. Battery is fully charged for all tests.
 Power Measured Conducted ERP EIRP
2. SAR Measurement
 Phantom Configuration Left Head Eli4 Right Head
 SAR Configuration Head Body
3. Test Signal Call Mode Test Code Base Station Simulator
4. Test Configuration With Belt Clip Without Belt Clip N/A
5. Tissue Depth is at least 15.0 cm



Jay M. Moulton
 Vice President

SAR Data Summary – Simultaneous Evaluation

MEASUREMENT RESULTS – WiFi & BT								
Frequency		Modulation	Frequency		Modulation	SAR ₁	SAR ₂	SAR Total
MHz	Ch.		MHz	Ch.				
5785	157	OFDM	2440	39	GFSK	1.12	0.12	1.24
Body 2.0 W/kg (mW/g) averaged over 10 gram								

The sum of the two transmitters is less than the limit; therefore, the simultaneous transmission meets the requirements.

MEASUREMENT RESULTS – WiFi & BT								
Frequency		Modulation	Frequency		Modulation	SAR ₁	SAR ₂	SAR Total
MHz	Ch.		MHz	Ch.				
5580	116	OFDM	2440	39	GFSK	2.16	0.13	2.29
Extremity 4.0 W/kg (mW/g) averaged over 10 gram								

The sum of the two transmitters is less than the limit; therefore, the simultaneous transmission meets the requirements.

9. Test Equipment List

Table 9.1 Equipment Specifications

Type	Calibration Due Date	Calibration Done Date	Serial Number
Staubli Robot TX60L	N/A	N/A	F07/55M6A1/A/01
Measurement Controller CS8c	N/A	N/A	1012
ELI5 Flat Phantom	N/A	N/A	2037
Device Holder	N/A	N/A	N/A
Data Acquisition Electronics 4	04/12/2023	04/12/2022	1416
SPEAG E-Field Probe EX3DV4	02/16/2023	02/16/2022	3662
Speag Validation Dipole D2450V2	06/03/2023	06/03/2021	881
Speag Validation Dipole D5GHzV2	06/08/2023	06/08/2021	1119
Agilent N1911A Power Meter	03/16/2023	03/16/2022	GB45100254
Agilent N1922A Power Sensor	03/17/2023	03/17/2022	MY45240464
Agilent (HP) 8561E Spectrum Analyzer	03/17/2023	03/17/2022	31720068
Agilent (HP) 83752A Synthesized Sweeper	03/17/2023	03/17/2022	3610A01048
Agilent (HP) 8753C Vector Network Analyzer	03/17/2023	03/17/2022	3135A01724
Agilent (HP) 85047A S-Parameter Test Set	03/16/2023	03/16/2022	2904A00595
Agilent 778D Dual Directional Coupler	N/A	N/A	MY48220184
MiniCircuits BW-N20W5+ Fixed 20 dB Attenuator	N/A	N/A	N/A
MiniCircuits SPL-10.7+ Low Pass Filter	N/A	N/A	R8979513746
Apriel Dielectric Probe Assembly	N/A	N/A	0011
Head Equivalent Matter (2450 MHz)	N/A	N/A	N/A
Head Equivalent Matter (5 GHz)	N/A	N/A	N/A

10. Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC/ISED. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body is a very complex phenomena that depends on the mass, shape, and size of the body; the orientation of the body with respect to the field vectors; and, the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

11. References

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio Frequency Radiation, August 1996
- [2] ANSI/IEEE C95.1 – 1992, American National Standard Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 300kHz to 100GHz, New York: IEEE, 1992.
- [3] ANSI/IEEE C95.3 – 2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave, New York: IEEE, 2002.
- [4] International Electrotechnical Commission, IEC 62209-2 (Edition 1.0), Human Exposure to radio frequency fields from hand-held and body mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), March 2010.
- [5] IEEE Standard 1528 – 2013, IEEE Recommended Practice for Determining the Peak-Spatial Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communication Devices: Measurement Techniques, June 2013.
- [6] Industry Canada, RSS – 102 Issue 5, Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), March 2015.
- [7] Health Canada, Safety Code 6, Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3kHz to 300 GHz, 2009.

Appendix A – System Validation Plots and Data

```
*****
Test Result for UIM Dielectric Parameter
Thu 26/May/2022
Freq  Frequency(GHz)
FCC_eH Limits for Head Epsilon
FCC_sH Limits for Head Sigma
Test_e Epsilon of UIM
Test_s Sigma of UIM
*****
Freq      FCC_eH FCC_sH Test_e Test_s
2.4100    39.26  1.76   38.67  1.77
2.4120    39.258 1.762  38.666 1.772*
2.4200    39.25  1.77   38.65  1.78
2.4300    39.24  1.78   38.63  1.79
2.4370    39.226 1.787  38.623 1.804*
2.4400    39.22  1.79   38.62  1.81
2.4420    39.216 1.792  38.61  1.812*
2.4500    39.20  1.80   38.57  1.82
2.4600    39.19  1.81   38.57  1.83
2.4620    39.186 1.812  38.566 1.832*
2.4700    39.17  1.82   38.55  1.84
2.4720    39.168 1.822  38.546 1.846*
2.4800    39.16  1.83   38.53  1.87
```

* value interpolated

```
*****
Test Result for UIM Dielectric Parameter
Fri 17/Jun/2022
Freq  Frequency(GHz)
FCC_eH Limits for Head Epsilon
FCC_sH Limits for Head Sigma
Test_e Epsilon of UIM
Test_s Sigma of UIM
*****
Freq      FCC_eH FCC_sH Test_e Test_s
2.4100    39.26  1.76   38.70  1.78
2.4120    39.258 1.762  38.696 1.782*
2.4200    39.25  1.77   38.68  1.79
2.4300    39.24  1.78   38.66  1.80
2.4370    39.226 1.787  38.653 1.814*
2.4400    39.22  1.79   38.65  1.82
2.4420    39.216 1.792  38.64  1.822*
2.4500    39.20  1.80   38.60  1.83
2.4600    39.19  1.81   38.60  1.84
2.4620    39.186 1.812  38.596 1.842*
2.4700    39.17  1.82   38.58  1.85
2.4720    39.168 1.822  38.576 1.856*
2.4800    39.16  1.83   38.56  1.88
```

* value interpolated

Test Result for UIM Dielectric Parameter

Mon 23/May/2022

Freq Frequency(GHz)

FCC_eH Limits for Head Epsilon

FCC_sH Limits for Head Sigma

Test_e Epsilon of UIM

Test_s Sigma of UIM

Freq	FCC_eH	FCC_sH	Test_e	Test_s
5.1000	36.10	4.55	35.11	4.58
5.1200	36.08	4.57	35.09	4.60
5.1400	36.05	4.59	35.06	4.62
5.1600	36.03	4.61	35.04	4.65
5.1800	36.01	4.63	35.02	4.67
5.2000	35.99	4.65	34.99	4.69
5.2200	35.96	4.68	34.97	4.71
5.2400	35.94	4.70	34.95	4.73
5.2500	35.93	4.71	34.935	4.745*
5.2600	35.92	4.72	34.92	4.76
5.2800	35.89	4.74	34.89	4.78
5.3000	35.87	4.76	34.86	4.80
5.3200	35.85	4.78	34.84	4.82
5.3400	35.83	4.80	34.82	4.85
5.3600	35.80	4.82	34.80	4.87
5.3800	35.78	4.84	34.77	4.89
5.4000	35.76	4.86	34.75	4.91
5.4200	35.73	4.88	34.73	4.94
5.4400	35.71	4.90	34.72	4.96
5.4600	35.69	4.92	34.69	4.98
5.4800	35.67	4.94	34.66	5.00
5.5000	35.64	4.96	34.63	5.02
5.5200	35.62	4.98	34.61	5.04
5.5400	35.60	5.00	34.59	5.06
5.5600	35.57	5.02	34.57	5.09
5.5800	35.55	5.04	34.54	5.11
5.6000	35.53	5.07	34.52	5.13
5.6200	35.51	5.09	34.49	5.15
5.6400	35.48	5.11	34.47	5.18
5.6600	35.46	5.13	34.45	5.20
5.6800	35.44	5.15	34.43	5.22
5.7000	35.41	5.17	34.40	5.24
5.7200	35.39	5.19	34.38	5.27
5.7400	35.37	5.21	34.36	5.29
5.7450	35.365	5.215	34.355	5.295*
5.7500	35.36	5.22	34.35	5.30*
5.7600	35.35	5.23	34.34	5.31
5.7800	35.32	5.25	34.32	5.33
5.7850	35.315	5.255	34.31	5.335*
5.8000	35.30	5.27	34.28	5.35
5.8200	35.28	5.29	34.26	5.38
5.8250	35.273	5.295	34.255	5.385*
5.8400	35.25	5.31	34.24	5.40
5.8600	35.23	5.33	34.22	5.42

* value interpolated

RF Exposure Lab

Plot 1

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN: 881


Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: HSL2450; Medium parameters used: $f = 2450$ MHz; $\sigma = 1.82$ S/m; $\epsilon_r = 38.57$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 5/26/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C
Probe: EX3DV4 – SN3662; ConvF(7.28, 7.28, 7.28); Calibrated: 2/16/2022;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 2037
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

Head Verification/2450 MHz/Area Scan (61x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 8.68 W/kg

Head Verification/2450 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.751 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 10.7 W/kg
 $P_{in}=100$ mW
SAR(1 g) = 5.2 W/kg; SAR(10 g) = 2.4 W/kg
Maximum value of SAR (measured) = 5.91 W/kg





RF Exposure Lab

Plot 2

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1119

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1
Medium: HSL 3-6 GHz; Medium parameters used (interpolated): $f = 5250$ MHz; $\sigma = 4.745$ S/m; $\epsilon_r = 34.935$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

Test Date: Date: 5/23/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C
Probe: EX3DV4 – SN3662; ConvF(4.95, 4.95, 4.95); Calibrated 2/16/2022;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 2037
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

Head Verification/5250 MHz/Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.51 W/kg

Head Verification/5250 MHz/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 14.357 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 3.41 W/kg


Pin=10 mW

SAR(1 g) = 0.819 W/kg; SAR(10 g) = 0.234 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.89 W/kg





RF Exposure Lab

Plot 3

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1119


Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1
Medium: HSL 3-6 GHz; Medium parameters used: $f = 5600$ MHz; $\sigma = 5.13$ S/m; $\epsilon_r = 34.52$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 5/23/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C
Probe: EX3DV4 – SN3662; ConvF(4.66, 4.66, 4.66); Calibrated: 2/16/2022;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 2037
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

Head Verification/5600 MHz/Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.72 W/kg

Head Verification/5600 MHz/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 15.398 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 3.59 W/kg
Pin=10 mW
SAR(1 g) = 0.845 W/kg; SAR(10 g) = 0.241 W/kg
Maximum value of SAR (measured) = 2.01 W/kg





RF Exposure Lab

Plot 4

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1119

Communication System: CW; Frequency: 5750 MHz; Duty Cycle: 1:1
 Medium: HSL 3-6 GHz; Medium parameters used (interpolated): $f = 5750$ MHz; $\sigma = 5.3$ S/m; $\epsilon_r = 34.35$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

Test Date: Date: 5/23/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C
 Probe: EX3DV4 – SN3662; ConvF(4.8, 4.8, 4.8); Calibrated: 2/16/2022;
 Sensor-Surface: 2mm (Mechanical Surface Detection)
 Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
 Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 2037
 Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

Head Verification/5750 MHz/Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.57 W/kg

Head Verification/5750 MHz/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 13.697 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 2.65 W/kg


Pin=10 mW

SAR(1 g) = 0.822 W/kg; SAR(10 g) = 0.235 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.77 W/kg





RF Exposure Lab

Plot 5

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN: 881


Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: HSL2450; Medium parameters used: $f = 2450$ MHz; $\sigma = 1.83$ S/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 6/17/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C
Probe: EX3DV4 – SN3662; ConvF(7.28, 7.28, 7.28); Calibrated: 2/16/2022;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 2037
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

Head Verification/2450 MHz/Area Scan (61x101x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm
Maximum value of SAR (interpolated) = 8.22 W/kg

Head Verification/2450 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 56.025 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 11.05 W/kg
 $P_{in} = 100$ mW
SAR(1 g) = 5.56 W/kg; SAR(10 g) = 2.53 W/kg
Maximum value of SAR (measured) = 8.96 W/kg





Appendix B – SAR Test Data Plots

RF Exposure Lab

Plot 1

DUT: A720X; Type: Handheld Reader; Serial: 7518200141

Communication System: WiFi 802.11b (DSSS, 1 Mbps); Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: HSL2450; Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.804$ S/m; $\epsilon_r = 38.623$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

Test Date: Date: 5/26/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(7.28, 7.28, 7.28); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A720X 2450 MHz/Back Mid/Area Scan (9x17x1): Measurement grid: dx=10mm, dy=10mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.07 W/kg

A720X 2450 MHz/Back Mid/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 4.320 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.57 W/kg

SAR(1 g) = 0.823 W/kg; SAR(10 g) = 0.422 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.18 W/kg



RF Exposure Lab

Plot 2

DUT: A710X; Type: Handheld Reader; Serial: 7418200044

Communication System: WiFi 802.11b (DSSS, 1 Mbps); Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: HSL2450; Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.804$ S/m; $\epsilon_r = 38.623$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

Test Date: Date: 5/26/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(7.28, 7.28, 7.28); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A710X 2450 MHz/Bottom Mid/Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 3.07 W/kg

A710X 2450 MHz/Bottom Mid/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 35.48 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 4.36 W/kg

SAR(1 g) = 2.11 W/kg; SAR(10 g) = 0.928 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 3.23 W/kg



RF Exposure Lab

Plot 3

DUT: A720X; Type: Handheld Reader; Serial: 7518200141

Communication System: WiFi 802.11a (OFDM, 6 Mbps); Frequency: 5300 MHz; Duty Cycle: 1:1
Medium: HSL3-6GHz; Medium parameters used: $f = 5300$ MHz; $\sigma = 4.8$ S/m; $\epsilon_r = 34.86$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 5/24/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(4.95, 4.95, 4.95); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A720X 5200 MHz/Front 60/Area Scan (9x17x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 0.792 W/kg

A720X 5200 MHz/Front 60/Zoom Scan (9x9x14)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 2.110 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 1.55 W/kg
SAR(1 g) = 0.460 W/kg; SAR(10 g) = 0.188 W/kg
Maximum value of SAR (measured) = 0.831 W/kg



RF Exposure Lab

Plot 4

DUT: A710X; Type: Handheld Reader; Serial: 7418200044

Communication System: WiFi 802.11a (OFDM, 6 Mbps); Frequency: 5300 MHz; Duty Cycle: 1:1
Medium: HSL3-6GHz; Medium parameters used: $f = 5300$ MHz; $\sigma = 4.8$ S/m; $\epsilon_r = 34.86$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 5/23/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(4.95, 4.95, 4.95); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A710X 5200 MHz/Bottom 60/Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 3.86 W/kg

A710X 5200 MHz/Bottom 60/Zoom Scan (9x9x14)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 18.39 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 9.28 W/kg
SAR(1 g) = 2.32 W/kg; SAR(10 g) = 0.742 W/kg
Maximum value of SAR (measured) = 4.75 W/kg



RF Exposure Lab

Plot 5

DUT: A720X; Type: Handheld Reader; Serial: 7518200141

Communication System: WiFi 802.11a (OFDM, 6 Mbps); Frequency: 5620 MHz; Duty Cycle: 1:1
Medium: HSL3-6GHz; Medium parameters used: $f = 5620$ MHz; $\sigma = 5.15$ S/m; $\epsilon_r = 34.49$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 5/24/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(4.66, 4.66, 4.66); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A720X 5600 MHz/Front 124/Area Scan (9x17x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.82 W/kg

A720X 5600 MHz/Front 124/Zoom Scan (9x9x14)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 2.923 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 3.70 W/kg
SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.399 W/kg
Maximum value of SAR (measured) = 1.97 W/kg



RF Exposure Lab

Plot 6

DUT: A720X; Type: Handheld Reader; Serial: 7518200141

Communication System: WiFi 802.11a (OFDM, 6 Mbps); Frequency: 5620 MHz; Duty Cycle: 1:1
Medium: HSL3-6GHz; Medium parameters used: $f = 5620$ MHz; $\sigma = 5.15$ S/m; $\epsilon_r = 34.49$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


Test Date: Date: 5/24/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(4.66, 4.66, 4.66); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A720X 5600 MHz/Bottom 124/Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 13.6 W/kg

A720X 5600 MHz/Bottom 124/Zoom Scan (9x9x14)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 25.64 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 36.9 W/kg
SAR(1 g) = 7.69 W/kg; SAR(10 g) = 2.06 W/kg
Maximum value of SAR (measured) = 16.2 W/kg



RF Exposure Lab

Plot 7

DUT: A720X; Type: Handheld Reader; Serial: 7518200141

Communication System: WiFi 802.11a (OFDM, 6 Mbps); Frequency: 5785 MHz; Duty Cycle: 1:1
Medium: HSL3-6GHz; Medium parameters used (interpolated): $f = 5785 \text{ MHz}$; $\sigma = 5.335 \text{ S/m}$; $\epsilon_r = 34.31$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

Test Date: Date: 5/24/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(4.8, 4.8, 4.8); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A720X 5800 MHz/Front 157/Area Scan (9x17x1): Measurement grid: dx=10mm, dy=10mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.88 W/kg

A720X 5800 MHz/Front 157/Zoom Scan (9x9x14)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm


Reference Value = 2.660 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 4.08 W/kg

SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.409 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 2.07 W/kg



RF Exposure Lab

Plot 8

DUT: A720X; Type: Handheld Reader; Serial: 7518200141

Communication System: WiFi 802.11a (OFDM, 6 Mbps); Frequency: 5825 MHz; Duty Cycle: 1:1
Medium: HSL3-6GHz; Medium parameters used (interpolated): $f = 5825$ MHz; $\sigma = 5.385$ S/m; $\epsilon_r = 34.255$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

Test Date: Date: 5/24/2022; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(4.8, 4.8, 4.8); Calibrated: 2/16/2022
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1416; Calibrated: 4/12/2022
Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1251
Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Procedure Notes:

A720X 5800 MHz/Bottom 165/Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 14.9 W/kg

A720X 5800 MHz/Bottom 165/Zoom Scan (9x9x14)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm


Reference Value = 19.70 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 39.3 W/kg

SAR(1 g) = 7.44 W/kg; SAR(10 g) = 1.9 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 15.7 W/kg



Appendix D – Probe Calibration Data Sheets



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **RF Exposure Lab**

Certificate No: **EX3-3662_Feb22**

CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3662**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v6, QA CAL-23.v5,
QA CAL-25.v7
Calibration procedure for dosimetric E-field probes**

Calibration date: **February 16, 2022**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	09-Apr-21 (No. 217-03291/03292)	Apr-22
Power sensor NRP-Z91	SN: 103244	09-Apr-21 (No. 217-03291)	Apr-22
Power sensor NRP-Z91	SN: 103245	09-Apr-21 (No. 217-03292)	Apr-22
Reference 20 dB Attenuator	SN: CC2552 (20x)	09-Apr-21 (No. 217-03343)	Apr-22
DAE4	SN: 660	13-Oct-21 (No. DAE4-660_Oct21)	Oct-22
Reference Probe ES3DV2	SN: 3013	27-Dec-21 (No. ES3-3013_Dec21)	Dec-22
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-20)	In house check: Jun-22
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-20)	In house check: Oct-22

Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature
Approved by:	Name Sven Kühn	Function Deputy Manager	Signature

Issued: February 18, 2022

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.42	0.49	0.48	$\pm 10.1 \%$
DCP (mV) ^B	99.8	99.6	98.2	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	147.3	$\pm 2.7 \%$	$\pm 4.7 \%$
		Y	0.0	0.0	1.0		161.3		
		Z	0.0	0.0	1.0		168.0		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-94.7
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Note: Measurement distance from surface can be increased to 3-4 mm for an *Area Scan* job.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
150	52.3	0.76	11.58	11.58	11.58	0.00	1.00	± 13.3 %
220	49.0	0.81	11.43	11.43	11.43	0.00	1.00	± 13.3 %
300	45.3	0.87	11.15	11.15	11.15	0.09	1.00	± 13.3 %
450	43.5	0.87	10.72	10.72	10.72	0.16	1.30	± 13.3 %
750	41.9	0.89	9.23	9.23	9.23	0.52	0.80	± 12.0 %
900	41.5	0.97	8.76	8.76	8.76	0.44	0.80	± 12.0 %
1450	40.5	1.20	8.18	8.18	8.18	0.37	0.80	± 12.0 %
1640	40.2	1.31	8.03	8.03	8.03	0.35	0.86	± 12.0 %
1750	40.1	1.37	7.87	7.87	7.87	0.32	0.86	± 12.0 %
1900	40.0	1.40	7.66	7.66	7.66	0.27	0.86	± 12.0 %
2300	39.5	1.67	7.54	7.54	7.54	0.34	0.90	± 12.0 %
2450	39.2	1.80	7.28	7.28	7.28	0.38	0.90	± 12.0 %
2600	39.0	1.96	7.10	7.10	7.10	0.38	0.90	± 12.0 %
3500	37.9	2.91	6.73	6.73	6.73	0.35	1.30	± 13.1 %
3700	37.7	3.12	6.53	6.53	6.53	0.35	1.30	± 13.1 %
5250	35.9	4.71	4.95	4.95	4.95	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.66	4.66	4.66	0.40	1.80	± 13.1 %
5750	35.4	5.22	4.80	4.80	4.80	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

Calibration Parameter Determined in Head Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
6500	34.5	6.07	5.50	5.50	5.50	0.20	2.00	± 18.6 %

^C Frequency validity above 6GHz is ± 700 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies 6-10 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz; below ± 2% for frequencies between 3-6 GHz; and below ± 4% for frequencies between 6-10 GHz at any distance larger than half the probe tip diameter from the boundary.


Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz, TEM





f=1800 MHz, R22





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range $f(SAR_{head})$ (TEM cell , $f_{eval}= 1900$ MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ, ϑ), f = 900 MHz



Appendix E – Dipole Calibration Data Sheets

Jm

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Client **RF Exposure Lab**

Certificate No: **D2450V2-881_Jun21**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN:881**

Calibration procedure(s) **QA CAL-05 v11
Calibration Procedure for SAR Validation Sources between 0.7-3 GHz**

Calibration date: **June 03, 2021**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	09-Apr-21 (No. 217-03291/03292)	Apr-22
Power sensor NRP-Z91	SN: 103244	09-Apr-21 (No. 217-03291)	Apr-22
Power sensor NRP-Z91	SN: 103245	09-Apr-21 (No. 217-03292)	Apr-22
Reference 20 dB Attenuator	SN: BH9394 (20k)	09-Apr-21 (No. 217-03343)	Apr-22
Type-N mismatch combination	SN: 310982 / 06327	09-Apr-21 (No. 217-03344)	Apr-22
Reference Probe EX3DV4	SN: 7349	28-Dec-20 (No. EX3-7349_Dec20)	Dec-21
DAE4	SN: 601	02-Nov-20 (No. DAE4-601_Nov20)	Nov-21

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB39512475	30-Oct-14 (in house check Oct-20)	In house check: Oct-22
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-20)	In house check: Oct-22
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-20)	In house check: Oct-22
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-20)	In house check: Oct-22
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-20)	In house check: Oct-21

	Name	Function	Signature
Calibrated by:	Jeffrey Katzman	Laboratory Technician	

	Name	Function	Signature
Approved by:	Katja Pokovic	Technical Manager	

Issued: June 8, 2021

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.4
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.7 ± 6 %	1.87 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.9 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	54.1 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.34 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	25.0 W/kg ± 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.3 Ω + 4.3 j Ω
Return Loss	- 24.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.156 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

Extended Calibration

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (<-20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB Publication 865664 D01 v01r04.

D2450V2 SN: 829 - Head						
Date of Measurement	Return Loss (dB)	$\Delta\%$	Impedance Real (Ω)	$\Delta\Omega$	Impedance Imaginary (j Ω)	$\Delta\Omega$
6/3/2021	-24.7		54.3		4.3	
6/3/2022	-25.3	2.4	55.2	0.9	4.1	-0.2

DASY5 Validation Report for Head TSL

Date: 03.06.2021

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:881

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.87$ S/m; $\epsilon_r = 37.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.96, 7.96, 7.96) @ 2450 MHz; Calibrated: 28.12.2020
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 02.11.2020
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 119.0 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 28.0 W/kg

SAR(1 g) = 13.9 W/kg; SAR(10 g) = 6.34 W/kg


Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 49.5%

Maximum value of SAR (measured) = 23.1 W/kg



Impedance Measurement Plot for Head TSL



Appendix F – Phantom Calibration Data Sheets

Certificate of Conformity / First Article Inspection

Item	Oval Flat Phantom ELI 4.0
Type No	QD OVA 001 B
Series No	1003 and higher
Manufacturer	Untersee Composites Knebelstrasse 8 CH-8268 Mannenbach, Switzerland

Tests

Complete tests were made on the prototype units QD OVA 001 AA 1001, QD OVA 001 AB 1002, pre-series units QD OVA 001 BA 1003-1005 as well as on the series units QD OVA 001 BB, 1006 ff.

Test	Requirement	Details	Units tested
Material thickness	Compliant with the standard requirements	Bottom plate: 2.0mm +/- 0.2mm	all
Material parameters	Dielectric parameters for required frequencies	< 6 GHz: Rel. permittivity = 4 +/-1, Loss tangent ≤ 0.05	Material sample
Material resistivity	The material has been tested to be compatible with the liquids defined in the standards if handled and cleaned according to the instructions.	DGBE based simulating liquids. Observe Technical Note for material compatibility.	Equivalent phantoms, Material sample
Shape	Thickness of bottom material, Internal dimensions, Sagging compatible with standards from minimum frequency	Bottom elliptical 600 x 400 mm Depth 190 mm, Shape is within tolerance for filling height up to 155 mm, Eventual sagging is reduced or eliminated by support via DUT	Prototypes, Sample testing

Standards

- [1] CENELEC EN 50361-2001, « Basic standard for the measurement of the Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz – 3 GHz) », July 2001
- [2] IEEE 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques, December 2003
- [3] IEC 62209 – 1, "Specific Absorption Rate (SAR) in the frequency range of 300 MHz to 3 GHz – Measurement Procedure, Part 1: Hand-held mobile wireless communication devices", February 2005
- [4] IEC 62209 – 2, Draft, "Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices – Human models, Instrumentation and Procedures – Part 2: Procedure to determine the Specific Absorption Rate (SAR) in the head and body for 30 MHz to 6 GHz Handheld and Body-Mounted Devices used in close proximity to the Body.", February 2005
- [5] OET Bulletin 65, Supplement C, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", Edition January 2001

Based on the tests above, we certify that this item is in compliance with the standards [1] to [5] if operated according to the specific requirements and considering the thickness. The dimensions are fully compliant with [4] from 30 MHz to 6 GHz. For the other standards, the minimum lower frequency limit is limited due to the dimensional requirements ([1]: 450 MHz, [2]: 300 MHz, [3]: 800 MHz, [5]: 375 MHz) and possibly further by the dimensions of the DUT.

Date 28.4.2008 Signature / Stamp

s p e a g
Schmid & Partner Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland
Phone +41 44 245 9700, Fax +41 44 245 9779
info@speag.com; http://www.speag.com

Appendix G – Validation Summary

Per FCC KDB 865664 D02 v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue equivalent media for system validation according to the procedures outlined in FCC KDB 865664 D01 v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point using the system that normally operates with the probe for routine SAR measurements and according to the required tissue equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

**Table G-1
SAR System Validation Summary**

SAR System #	Freq. (MHz)	Date	Probe S/N	Probe Type	Probe Cal. Point	Cond. (σ)	Perm. (ϵ_r)	CW Validation			Modulation Validation			
								Sens-itivity	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR	
3	2450	03/09/2022	3662	EX3DV4	2450	Head	1.82	38.55	Pass	Pass	Pass	OFDM/TDD	Pass	Pass
3	5250	03/09/2022	3662	EX3DV4	5200	Head	4.75	35.03	Pass	Pass	Pass	OFDM	N/A	Pass
3	5600	03/09/2022	3662	EX3DV4	5600	Head	5.12	34.52	Pass	Pass	Pass	OFDM	N/A	Pass
3	5750	03/09/2022	3662	EX3DV4	5800	Head	5.27	34.26	Pass	Pass	Pass	OFDM	N/A	Pass