

## Variant FCC Test Report

### (PART 90S)

**Report No.:** RFBERD-WTW-P22060603-4

**FCC ID:** HD5-CN85L1N

**Test Model:** CN85L1N

**Received Date:** Sep. 04, 2018

**Test Date:** Sep. 13, 2018 ~ Sep. 29, 2018

**Issued Date:** Jul. 04, 2022

**Applicant:** Honeywell International Inc.

**Address:** 9680 Old Bailes Road, Fort Mill, SC 29707 USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                               | <b>3</b>  |
| <b>1 Certificate of Conformity .....</b>                          | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                            | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                                 | 5         |
| 2.2 Test Site and Instruments .....                               | 6         |
| <b>3 General Information .....</b>                                | <b>7</b>  |
| 3.1 General Description of EUT .....                              | 7         |
| 3.2 Configuration of System under Test .....                      | 8         |
| 3.2.1 Description of Support Units .....                          | 8         |
| 3.3 Test Mode Applicability and Tested Channel Detail .....       | 8         |
| 3.4 EUT Operating Conditions .....                                | 10        |
| 3.5 General Description of Applied Standards and references ..... | 10        |
| <b>4 Test Types and Results .....</b>                             | <b>11</b> |
| 4.1 Output Power Measurement .....                                | 11        |
| 4.1.1 Limits of Output Power Measurement .....                    | 11        |
| 4.1.2 Test Procedures .....                                       | 11        |
| 4.1.3 Test Setup .....                                            | 12        |
| 4.1.4 Test Results .....                                          | 13        |
| 4.2 Modulation Characteristics Measurement .....                  | 18        |
| 4.2.1 Limits of Modulation Characteristics .....                  | 18        |
| 4.2.2 Test Setup .....                                            | 18        |
| 4.2.3 Test Procedure .....                                        | 18        |
| 4.2.4 Test Results .....                                          | 19        |
| 4.3 Frequency Stability Measurement .....                         | 20        |
| 4.3.1 Limits of Frequency Stability Measurement .....             | 20        |
| 4.3.2 Test Procedure .....                                        | 20        |
| 4.3.3 Test Setup .....                                            | 20        |
| 4.3.4 Test Results .....                                          | 21        |
| 4.4 Occupied Bandwidth Measurement .....                          | 26        |
| 4.4.1 Limits of Occupied Bandwidth Measurement .....              | 26        |
| 4.4.2 Test Procedure .....                                        | 26        |
| 4.4.3 Test Setup .....                                            | 26        |
| 4.4.4 Test Results .....                                          | 27        |
| 4.5 Emission Mask Measurement .....                               | 30        |
| 4.5.1 Limits of Emission Mask Measurement .....                   | 30        |
| 4.5.2 Test Setup .....                                            | 30        |
| 4.5.3 Test Procedures .....                                       | 30        |
| 4.5.4 Test Results .....                                          | 31        |
| 4.6 Conducted Spurious Emissions .....                            | 36        |
| 4.6.1 Limits of Conducted Spurious Emissions Measurement .....    | 36        |
| 4.6.2 Test Setup .....                                            | 36        |
| 4.6.3 Test Procedure .....                                        | 36        |
| 4.6.4 Test Results .....                                          | 37        |
| 4.7 Radiated Emission Measurement .....                           | 42        |
| 4.7.1 Limits of Radiated Emission Measurement .....               | 42        |
| 4.7.2 Test Procedure .....                                        | 42        |
| 4.7.3 Deviation from Test Standard .....                          | 42        |
| 4.7.4 Test Setup .....                                            | 43        |
| 4.7.5 Test Results .....                                          | 44        |
| <b>5 Pictures of Test Arrangements .....</b>                      | <b>52</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b>   | <b>53</b> |

### Release Control Record

| Issue No.              | Description      | Date Issued   |
|------------------------|------------------|---------------|
| RFBERD-WTW-P22060603-4 | Original Release | Jul. 04, 2022 |

## 1 Certificate of Conformity

**Product:** Mobile computer

**Brand:** Honeywell

**Test Model:** CN85L1N

**Sample Status:** Engineering Sample

**Applicant:** Honeywell International Inc.

**Test Date:** Sep. 13, 2018 ~ Sep. 29, 2018

**Standards:** FCC Part 90, Subpart I, S  
FCC Part 2

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Lena Wang, **Date:** Jul. 04, 2022  
Lena Wang / Specialist

**Approved by :** Jeremy Lin, **Date:** Jul. 04, 2022  
Jeremy Lin / Project Engineer

## 2 Summary of Test Results

| Applied Standard: FCC Part 90 & Part 2 |                              |        |                                                                                       |
|----------------------------------------|------------------------------|--------|---------------------------------------------------------------------------------------|
| FCC Clause                             | Test Item                    | Result | Remarks                                                                               |
| 2.1046<br>90.635 (b)                   | Effective Radiated Power     | Pass   | Meet the requirement of limit.                                                        |
| 2.1047                                 | Modulation Characteristics   | Pass   | Meet the requirement.                                                                 |
| 2.1055<br>90.213                       | Frequency Stability          | Pass   | Meet the requirement of limit.                                                        |
| 2.1049<br>90.209                       | Occupied Bandwidth           | Pass   | Meet the requirement of limit.                                                        |
| 2.1051<br>90.210                       | Emission Masks               | Pass   | Meet the requirement of limit.                                                        |
| 2.1051<br>90.691                       | Conducted Spurious Emissions | Pass   | Meet the requirement of limit.                                                        |
| 2.1053<br>90.691                       | Radiated Spurious Emissions  | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -32.23 dB at 2469.30 MHz. |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency          | Expanded Uncertainty (k=2) (±) |
|--------------------------------|--------------------|--------------------------------|
| Radiated Emissions up to 1 GHz | 30 MHz ~ 200 MHz   | 2.93 dB                        |
|                                | 200 MHz ~ 1000 MHz | 2.95 dB                        |
| Radiated Emissions above 1 GHz | 1 GHz ~ 18 GHz     | 2.26 dB                        |
|                                | 18 GHz ~ 40 GHz    | 1.94 dB                        |

## 2.2 Test Site and Instruments

| Description & Manufacturer                     | Model No.                  | Serial No.                    | Date of Calibration | Due Date of Calibration |
|------------------------------------------------|----------------------------|-------------------------------|---------------------|-------------------------|
| Test Receiver<br>Agilent                       | N9038A                     | MY51210203                    | Mar. 16, 2018       | Mar. 15, 2019           |
| Spectrum Analyzer<br>Agilent                   | N9010A                     | MY52220314                    | Nov. 24, 2017       | Nov. 23, 2018           |
| Spectrum Analyzer<br>ROHDE & SCHWARZ           | FSU43                      | 101261                        | Jan. 11, 2018       | Jan. 10, 2019           |
| HORN Antenna<br>SCHWARZBECK                    | BBHA 9120 D                | 9120D-969                     | Dec. 12, 2017       | Dec. 11, 2018           |
| BILOG Antenna<br>SCHWARZBECK                   | VULB9168                   | 9168-472                      | Dec. 06, 2017       | Dec. 05, 2018           |
| Fixed Attenuator<br>Mini-Circuits              | MDCS18N-10                 | MDCS18N-10-01                 | Apr. 16, 2018       | Apr. 15, 2019           |
| MXG Vector signal<br>generator<br>Agilent      | N5182B                     | MY53050430                    | Oct. 24, 2017       | Oct. 23, 2018           |
| Preamplifier<br>EMCI                           | EMC 012645                 | 980115                        | Oct. 20, 2017       | Oct. 19, 2018           |
| Preamplifier<br>EMCI                           | EMC 330H                   | 980112                        | Oct. 13, 2017       | Oct. 12, 2018           |
| RF Coaxial Cable<br>HUBER+SUHNNER              | EMC104-SM-SM-<br>8000&3000 | 140811+170717                 | Oct. 20, 2017       | Oct. 19, 2018           |
| RF Coaxial Cable<br>HUBER+SUHNNER              | SUCOFLEX 104               | EMC104-SM-SM-<br>1000(140807) | Oct. 20, 2017       | Oct. 19, 2018           |
| RF Coaxial Cable<br>Worken                     | 8D-FB                      | Cable-Ch10-01                 | Oct. 20, 2017       | Oct. 19, 2018           |
| Boresight Antenna Fixture                      | FBA-01                     | FBA-SIP01                     | NA                  | NA                      |
| Software<br>BV ADT                             | E3<br>6.120103             | NA                            | NA                  | NA                      |
| Antenna Tower<br>MF                            | MFA-440H                   | NA                            | NA                  | NA                      |
| Turn Table<br>MF                               | MFT-201SS                  | NA                            | NA                  | NA                      |
| Antenna Tower & Turn<br>Table Controller<br>MF | MF-7802                    | NA                            | NA                  | NA                      |
| Communications Tester-<br>Wireless<br>Agilent  | 8960 Series 10             | MY53201073                    | Jun. 28, 2017       | Jun. 27, 2019           |
| Radio Communication<br>Analyzer<br>Anritsu     | MT8820C                    | 6201300640                    | Aug. 16, 2017       | Aug. 15, 2019           |
| Temperature & Humidity<br>Chamber              | GTH-120-40-CP-AR           | MAA1306-019                   | Sep. 05, 2018       | Sep. 04, 2019           |
| DC Power Supply<br>Topward                     | 33010D                     | 807748                        | Oct. 25, 2016       | Oct. 24, 2018           |

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.

### 3 General Information

#### 3.1 General Description of EUT

|                            |                                                            |                    |
|----------------------------|------------------------------------------------------------|--------------------|
| <b>Product</b>             | Mobile computer                                            |                    |
| <b>Brand</b>               | Honeywell                                                  |                    |
| <b>Test Model</b>          | CN85L1N                                                    |                    |
| <b>Status of EUT</b>       | Engineering Sample                                         |                    |
| <b>Power Supply Rating</b> | 3.85 Vdc (battery)                                         |                    |
| <b>Modulation Type</b>     | CDMA                                                       | QPSK, OQPSK, HPSK  |
|                            | LTE                                                        | QPSK, 16QAM, 64QAM |
| <b>Frequency Range</b>     | CDMA BC10                                                  | 817.9 ~ 823.1 MHz  |
|                            | LTE Band 26 (Channel Bandwidth: 1.4 MHz)                   | 814.7 ~ 823.3 MHz  |
|                            | LTE Band 26 (Channel Bandwidth: 3 MHz)                     | 815.5 ~ 822.5 MHz  |
|                            | LTE Band 26 (Channel Bandwidth: 5 MHz)                     | 816.5 ~ 821.5 MHz  |
|                            | LTE Band 26 (Channel Bandwidth: 10 MHz)                    | 819 MHz            |
| <b>Emission Designator</b> | CDMA BC10                                                  | 1M28F9W            |
|                            | LTE Band 26 (Channel Bandwidth: 1.4 MHz)                   | 1M09W7D            |
|                            | LTE Band 26 (Channel Bandwidth: 3 MHz)                     | 2M71G7D            |
|                            | LTE Band 26 (Channel Bandwidth: 5 MHz)                     | 4M50W7D            |
|                            | LTE Band 26 (Channel Bandwidth: 10 MHz)                    | 8M98W7D            |
| <b>Max. ERP Power</b>      | CDMA BC10                                                  | 256.45 mW          |
|                            | LTE Band 26 (Channel Bandwidth: 1.4 MHz)                   | 212.32 mW          |
|                            | LTE Band 26 (Channel Bandwidth: 3 MHz)                     | 228.03 mW          |
|                            | LTE Band 26 (Channel Bandwidth: 5 MHz)                     | 241.55 mW          |
|                            | LTE Band 26 (Channel Bandwidth: 10 MHz)                    | 238.23 mW          |
| <b>Antenna Type</b>        | PIFA Antenna with 0 dBi gain (Main) / -0.2 dBi gain (Aux.) |                    |
| <b>HW Version</b>          | V1.0                                                       |                    |
| <b>HW P/N</b>              | V2.0 (DVT)                                                 |                    |
| <b>SW Version</b>          | OS.02.001-HON01.102                                        |                    |
| <b>SW P/N</b>              | 86.00.35-(0206)                                            |                    |
| <b>Accessory Device</b>    | Refer to Note as below                                     |                    |
| <b>Data Cable Supplied</b> | Refer to Note as below                                     |                    |

Note:

1. This report is issued as a supplementary report to BV CPS report no. RF180904C09-4. The difference compared with original report is disable radio 2 by software, after the evaluation, it does not affect the original data, so the original test data is quoted.
2. The host devices are list as below table for difference of SKU.

| Brand     | Model   | Product Name    | USI FG P/N     | Description                                               |
|-----------|---------|-----------------|----------------|-----------------------------------------------------------|
| Honeywell | CN85L1N | Mobile computer | 5487-273335-01 | CN85G4/UPS/6703SR/CAM/WAN/GMS/FCC                         |
| Honeywell | CN85L1N | Mobile computer | 5487-275335-01 | CN85G4/UPS/6703SR/CAM/WAN/GMS/FCC/<br>No 2nd BT/No Zigbee |


3. The EUT contains following accessory devices.

| Product | Brand                            | Model  | Description                 |
|---------|----------------------------------|--------|-----------------------------|
| Battery | Inventus Power, Inc. / Honeywell | CW-BAT | 3.85 Vdc, 5800 mAh, 22.3 Wh |

4. The above Antenna information refers to the manufacturer's antenna specifications, the laboratory shall not be held responsible.

5. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

### 3.2 Configuration of System under Test



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

| Band        | ERP     | Radiated Emission |
|-------------|---------|-------------------|
| CDMA        | X-plane | X-axis            |
| LTE Band 26 | X-plane | X-axis            |



## CDMA

| EUT Configure Mode | Test Item                  | Available Channel | Tested Channel | Mode  |
|--------------------|----------------------------|-------------------|----------------|-------|
| -                  | ERP                        | 476 to 684        | 476, 580, 684  | 1xRTT |
| -                  | Modulation Characteristics | 476 to 684        | 580            | 1xRTT |
| -                  | Frequency Stability        | 476 to 684        | 476, 684       | 1xRTT |
| -                  | Occupied Bandwidth         | 476 to 684        | 476, 580, 684  | 1xRTT |
| -                  | Emission Mask              | 476 to 684        | 476, 580, 684  | 1xRTT |
| -                  | Conducted Emission         | 476 to 684        | 476, 580, 684  | 1xRTT |
| -                  | Radiated Emission          | 476 to 684        | 476, 580, 684  | 1xRTT |

## LTE Band 26

| EUT Configure Mode | Test Item                  | Available Channel | Tested Channel      | Channel Bandwidth | Modulation         | Mode                |
|--------------------|----------------------------|-------------------|---------------------|-------------------|--------------------|---------------------|
| -                  | ERP                        | 26697 to 26783    | 26697, 26740, 26783 | 1.4 MHz           | QPSK, 16QAM, 64QAM | 1 RB / 0 RB Offset  |
|                    |                            | 26705 to 26775    | 26705, 26740, 26775 | 3 MHz             | QPSK, 16QAM, 64QAM | 1 RB / 0 RB Offset  |
|                    |                            | 26715 to 26765    | 26715, 26740, 26765 | 5 MHz             | QPSK, 16QAM, 64QAM | 1 RB / 0 RB Offset  |
|                    |                            | 26740             | 26740               | 10 MHz            | QPSK, 16QAM, 64QAM | 1 RB / 0 RB Offset  |
| -                  | Modulation Characteristics | 26705 to 26775    | 26740               | 5 MHz             | QPSK, 16QAM, 64QAM | 1 RB / 0 RB Offset  |
| -                  | Frequency Stability        | 26697 to 26783    | 26697, 26783        | 1.4 MHz           | QPSK               | 1 RB / 0 RB Offset  |
|                    |                            | 26705 to 26775    | 26705, 26775        | 3 MHz             | QPSK               | 1 RB / 0 RB Offset  |
|                    |                            | 26715 to 26765    | 26715, 26765        | 5 MHz             | QPSK               | 1 RB / 0 RB Offset  |
|                    |                            | 26740             | 26740               | 10 MHz            | QPSK               | 1 RB / 0 RB Offset  |
| -                  | Occupied Bandwidth         | 26697 to 26783    | 26697, 26740, 26783 | 1.4 MHz           | QPSK, 16QAM, 64QAM | 6 RB / 0 RB Offset  |
|                    |                            | 26705 to 26775    | 26705, 26740, 26775 | 3 MHz             | QPSK, 16QAM, 64QAM | 15 RB / 0 RB Offset |
|                    |                            | 26715 to 26765    | 26715, 26740, 26765 | 5 MHz             | QPSK, 16QAM, 64QAM | 25 RB / 0 RB Offset |
|                    |                            | 26740             | 26740               | 10 MHz            | QPSK, 16QAM, 64QAM | 50 RB / 0 RB Offset |
| -                  | Emission Mask              | 26697 to 26783    | 26697, 26783        | 1.4 MHz           | QPSK, 16QAM, 64QAM | 6 RB / 0 RB Offset  |
|                    |                            | 26705 to 26775    | 26705, 26775        | 3 MHz             | QPSK, 16QAM, 64QAM | 15 RB / 0 RB Offset |
|                    |                            | 26715 to 26765    | 26715, 26765        | 5 MHz             | QPSK, 16QAM, 64QAM | 25 RB / 0 RB Offset |
|                    |                            | 26740             | 26740               | 10 MHz            | QPSK, 16QAM, 64QAM | 50 RB / 0 RB Offset |
| -                  | Conducted Emission         | 26697 to 26783    | 26697, 26740, 26783 | 1.4 MHz           | QPSK               | 1 RB / 0 RB Offset  |
|                    |                            | 26705 to 26775    | 26705, 26740, 26775 | 3 MHz             | QPSK               | 1 RB / 0 RB Offset  |
|                    |                            | 26715 to 26765    | 26715, 26740, 26765 | 5 MHz             | QPSK               | 1 RB / 0 RB Offset  |
|                    |                            | 26740             | 26740               | 10 MHz            | QPSK               | 1 RB / 0 RB Offset  |
| -                  | Radiated Emission          | 26740             | 26740               | 10 MHz            | QPSK               | 1 RB / 0 RB Offset  |

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

**Test Condition:**

| Test Item             | Environmental Conditions | Input Power    | Tested By  |
|-----------------------|--------------------------|----------------|------------|
| ERP                   | 25 deg. C, 65 % RH       | 3.85 Vdc       | Thomas Wei |
| Frequency Stability   | 25 deg. C, 65 % RH       | 3.85 Vdc       | Gavin Wu   |
| Occupied Bandwidth    | 25 deg. C, 65 % RH       | 3.85 Vdc       | Gavin Wu   |
| Peak to Average Ratio | 25 deg. C, 65 % RH       | 3.85 Vdc       | Gavin Wu   |
| Emission Mask         | 25 deg. C, 65 % RH       | 3.85 Vdc       | Gavin Wu   |
| Band Edge             | 25 deg. C, 65 % RH       | 3.85 Vdc       | Gavin Wu   |
| Conducted Emission    | 25 deg. C, 65 % RH       | 3.85 Vdc       | Gavin Wu   |
| Radiated Emission     | 25 deg. C, 65 % RH       | 120 Vac, 60 Hz | Thomas Wei |

**3.4 EUT Operating Conditions**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

**3.5 General Description of Applied Standards and references**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

**Test Standard:**

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 90**

**ANSI 63.26-2015**

**Note:** All test items have been performed and recorded as per the above standards.

**References Test Guidance:**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**KDB 971168 D02 Misc Rev Approv License Devices v02r01**

**ANSI/TIA/EIA-603-E 2016**

**Note:** All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for CDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dB}$ .


##### **Conducted Power Measurement:**

- a. The EUT was set up for the maximum power with CDMA and LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


#### 4.1.3 Test Setup

##### EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>




<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

##### Conducted Power Measurement:



#### 4.1.4 Test Results

##### Conducted Output Power (dBm)

| Band               | CDMA  |       |       |
|--------------------|-------|-------|-------|
| Channel            | 476   | 580   | 684   |
| Frequency (MHz)    | 817.9 | 820.5 | 823.1 |
| RC1+SO55           | 24.04 | 24.01 | 24.05 |
| RC3+SO55           | 24.09 | 24.06 | 24.10 |
| RC3+SO32 (+ F-SCH) | 24.07 | 24.04 | 24.08 |
| RC3+SO32 (+SCH)    | 24.04 | 24.01 | 24.05 |
| RTAP 153.6         | 24.06 | 24.07 | 24.00 |
| RETAP 4096         | 23.91 | 23.95 | 23.94 |

| LTE Band 26 |           |                 |                 |           |       |       |               |    |               |                 |           |                 |           |       |               |       |               |
|-------------|-----------|-----------------|-----------------|-----------|-------|-------|---------------|----|---------------|-----------------|-----------|-----------------|-----------|-------|---------------|-------|---------------|
| BW          | MCS Index | RB Size         | RB Offset       |           | Mid   |       | 3GPP MPR (dB) | BW | MCS Index     | RB Size         | RB Offset | Low             | Mid       | High  | 3GPP MPR (dB) |       |               |
|             |           | Channel         |                 |           | 26740 |       |               |    |               | Channel         |           | 26715           | 26740     | 26765 |               |       |               |
|             |           | Frequency (MHz) |                 |           | 819.0 |       |               |    |               | Frequency (MHz) |           | 816.5           | 819.0     | 821.5 |               |       |               |
| 10M         | QPSK      | 1               | 0               |           | 23.47 |       | 0             | 5M | QPSK          | 1               | 0         | 23.36           | 23.47     | 23.56 | 0             |       |               |
|             |           | 1               | 24              |           | 23.48 |       | 0             |    |               | 1               | 12        | 23.50           | 23.48     | 23.57 | 0             |       |               |
|             |           | 1               | 49              |           | 23.53 |       | 0             |    |               | 1               | 24        | 23.53           | 23.53     | 23.65 | 0             |       |               |
|             |           | 25              | 0               |           | 22.49 |       | 1             |    |               | 12              | 0         | 22.51           | 22.49     | 22.66 | 1             |       |               |
|             |           | 25              | 12              |           | 22.37 |       | 1             |    |               | 12              | 6         | 22.37           | 22.37     | 22.58 | 1             |       |               |
|             |           | 25              | 25              |           | 22.54 |       | 1             |    |               | 12              | 13        | 22.55           | 22.54     | 22.65 | 1             |       |               |
|             |           | 50              | 0               |           | 22.42 |       | 1             |    |               | 25              | 0         | 22.43           | 22.42     | 22.54 | 1             |       |               |
|             | 16QAM     | 1               | 0               |           | 23.10 |       | 1             |    | 16QAM         | 1               | 0         | 23.06           | 23.10     | 23.28 | 1             |       |               |
|             |           | 1               | 24              |           | 22.92 |       | 1             |    |               | 1               | 12        | 22.89           | 22.92     | 23.09 | 1             |       |               |
|             |           | 1               | 49              |           | 22.95 |       | 1             |    |               | 1               | 24        | 22.80           | 22.95     | 23.00 | 1             |       |               |
|             |           | 25              | 0               |           | 21.53 |       | 2             |    |               | 12              | 0         | 21.65           | 21.53     | 21.70 | 2             |       |               |
|             |           | 25              | 12              |           | 21.60 |       | 2             |    |               | 12              | 6         | 21.64           | 21.60     | 21.66 | 2             |       |               |
|             |           | 25              | 25              |           | 21.64 |       | 2             |    |               | 12              | 13        | 21.54           | 21.64     | 21.68 | 2             |       |               |
|             | 64QAM     | 50              | 0               |           | 21.46 |       | 2             |    | 64QAM         | 25              | 0         | 21.46           | 21.46     | 21.59 | 2             |       |               |
|             |           | 1               | 0               |           | 21.45 |       | 2             |    |               | 1               | 0         | 21.36           | 21.45     | 21.56 | 2             |       |               |
|             |           | 1               | 24              |           | 21.41 |       | 2             |    |               | 1               | 12        | 21.33           | 21.41     | 21.49 | 2             |       |               |
|             |           | 1               | 49              |           | 21.59 |       | 2             |    |               | 1               | 24        | 21.50           | 21.59     | 21.62 | 2             |       |               |
|             |           | 25              | 0               |           | 20.53 |       | 3             |    |               | 12              | 0         | 20.43           | 20.53     | 20.63 | 3             |       |               |
|             |           | 25              | 12              |           | 20.44 |       | 3             |    |               | 12              | 6         | 20.41           | 20.44     | 20.55 | 3             |       |               |
|             |           | 25              | 25              |           | 20.57 |       | 3             |    |               | 12              | 13        | 20.46           | 20.57     | 20.56 | 3             |       |               |
|             | 50        | 0               |                 | 20.43     |       | 3     | 25            |    | 0             | 20.32           | 20.43     | 20.48           | 3         |       |               |       |               |
|             | BW        | MCS Index       | RB Size         | RB Offset | Low   | Mid   | High          |    | 3GPP MPR (dB) | BW              | MCS Index | RB Size         | RB Offset | Low   | Mid           | High  | 3GPP MPR (dB) |
|             |           |                 | Channel         |           | 26705 | 26740 | 26775         |    |               |                 |           | Channel         |           | 26697 | 26740         | 26783 |               |
|             |           |                 | Frequency (MHz) |           | 815.5 | 819.0 | 822.5         |    |               |                 |           | Frequency (MHz) |           | 814.7 | 819.0         | 823.3 |               |
| 5M          | QPSK      | 1               | 0               | 23.40     | 23.33 | 23.46 | 0             | 3M | QPSK          | 1               | 0         | 23.44           | 23.44     | 23.55 | 0             |       |               |
|             |           | 1               | 7               | 23.39     | 23.35 | 23.45 | 0             |    |               | 1               | 2         | 23.37           | 23.37     | 23.53 | 0             |       |               |
|             |           | 1               | 14              | 23.55     | 23.38 | 23.62 | 0             |    |               | 1               | 5         | 23.48           | 23.49     | 23.53 | 0             |       |               |
|             |           | 8               | 0               | 22.59     | 22.35 | 22.57 | 1             |    |               | 3               | 0         | 23.53           | 23.44     | 23.65 | 0             |       |               |
|             |           | 8               | 3               | 22.43     | 22.24 | 22.56 | 1             |    |               | 3               | 1         | 23.38           | 23.24     | 23.49 | 0             |       |               |
|             |           | 8               | 7               | 22.44     | 22.43 | 22.57 | 1             |    |               | 3               | 3         | 23.54           | 23.50     | 23.61 | 0             |       |               |
|             |           | 15              | 0               | 22.36     | 22.34 | 22.46 | 1             |    |               | 6               | 0         | 22.30           | 22.38     | 22.47 | 1             |       |               |
|             | 16QAM     | 1               | 0               | 23.14     | 22.97 | 23.25 | 1             |    | 16QAM         | 1               | 0         | 23.12           | 23.06     | 23.18 | 1             |       |               |
|             |           | 1               | 7               | 22.97     | 22.89 | 23.03 | 1             |    |               | 1               | 2         | 23.00           | 22.89     | 22.96 | 1             |       |               |
|             |           | 1               | 14              | 22.91     | 22.80 | 22.87 | 1             |    |               | 1               | 5         | 22.95           | 22.84     | 22.86 | 1             |       |               |
|             |           | 8               | 0               | 21.56     | 21.53 | 21.69 | 2             |    |               | 3               | 0         | 22.59           | 22.46     | 22.69 | 1             |       |               |
|             |           | 8               | 3               | 21.58     | 21.49 | 21.63 | 2             |    |               | 3               | 1         | 22.50           | 22.60     | 22.59 | 1             |       |               |
|             |           | 8               | 7               | 21.56     | 21.60 | 21.64 | 2             |    |               | 3               | 3         | 22.56           | 22.51     | 22.68 | 1             |       |               |
|             | 64QAM     | 15              | 0               | 21.36     | 21.41 | 21.57 | 2             |    | 64QAM         | 6               | 0         | 21.43           | 21.42     | 21.48 | 2             |       |               |
|             |           | 1               | 0               | 21.46     | 21.32 | 21.51 | 2             |    |               | 1               | 0         | 21.44           | 21.34     | 21.42 | 2             |       |               |
|             |           | 1               | 7               | 21.37     | 21.39 | 21.48 | 2             |    |               | 1               | 2         | 21.35           | 21.30     | 21.39 | 2             |       |               |
|             |           | 1               | 14              | 21.52     | 21.50 | 21.62 | 2             |    |               | 1               | 5         | 21.50           | 21.58     | 21.50 | 2             |       |               |
|             |           | 8               | 0               | 20.50     | 20.48 | 20.50 | 3             |    |               | 3               | 0         | 21.39           | 21.38     | 21.51 | 2             |       |               |
|             |           | 8               | 3               | 20.45     | 20.44 | 20.54 | 3             |    |               | 3               | 1         | 21.33           | 21.33     | 21.49 | 2             |       |               |
|             |           | 8               | 7               | 20.53     | 20.55 | 20.46 | 3             |    |               | 3               | 3         | 21.52           | 21.57     | 21.41 | 2             |       |               |
|             | 15        | 0               | 20.47           | 20.41     | 20.34 | 3     | 6             |    | 0             | 20.42           | 20.37     | 20.41           | 3         |       |               |       |               |

# ERP Power (dBm)

| CDMA  |         |                 |               |                        |           |          |                    |
|-------|---------|-----------------|---------------|------------------------|-----------|----------|--------------------|
| Plane | Channel | Frequency (MHz) | Reading (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (mW) | Polarization (H/V) |
| X     | 476     | 817.9           | -5.00         | 31.208                 | 24.06     | 254.68   | H                  |
|       | 580     | 820.5           | -5.12         | 31.3                   | 24.03     | 252.93   |                    |
|       | 684     | 823.1           | -4.98         | 31.222                 | 24.09     | 256.45   |                    |
|       | 476     | 817.9           | -11.34        | 31.504                 | 18.01     | 63.24    | V                  |
|       | 580     | 820.5           | -11.12        | 31.117                 | 17.85     | 60.95    |                    |
|       | 684     | 823.1           | -11.52        | 31.922                 | 18.25     | 66.83    |                    |

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

| LTE Band 26                        |         |                 |               |                        |           |          |                    |
|------------------------------------|---------|-----------------|---------------|------------------------|-----------|----------|--------------------|
| Channel Bandwidth: 1.4 MHz / QPSK  |         |                 |               |                        |           |          |                    |
| Plane                              | Channel | Frequency (MHz) | Reading (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (mW) | Polarization (H/V) |
| X                                  | 26697   | 814.7           | -7.01         | 32.01                  | 22.85     | 192.75   | H                  |
|                                    | 26740   | 819             | -6.98         | 32.11                  | 22.98     | 198.61   |                    |
|                                    | 26783   | 823.3           | -6.90         | 32.32                  | 23.27     | 212.32   |                    |
|                                    | 26697   | 814.7           | -12.74        | 32.54                  | 17.65     | 58.21    | V                  |
|                                    | 26740   | 819             | -12.63        | 32.51                  | 17.73     | 59.29    |                    |
|                                    | 26783   | 823.3           | -12.49        | 32.51                  | 17.87     | 61.24    |                    |
| Channel Bandwidth: 1.4 MHz / 16QAM |         |                 |               |                        |           |          |                    |
| X                                  | 26697   | 814.7           | -7.99         | 32.01                  | 21.87     | 153.82   | H                  |
|                                    | 26740   | 819             | -7.96         | 32.11                  | 22.00     | 158.49   |                    |
|                                    | 26783   | 823.3           | -7.88         | 32.32                  | 22.29     | 169.43   |                    |
|                                    | 26697   | 814.7           | -13.72        | 32.54                  | 16.67     | 46.45    | V                  |
|                                    | 26740   | 819             | -13.61        | 32.51                  | 16.75     | 47.32    |                    |
|                                    | 26783   | 823.3           | -13.47        | 32.51                  | 16.89     | 48.87    |                    |
| Channel Bandwidth: 1.4 MHz / 64QAM |         |                 |               |                        |           |          |                    |
| X                                  | 26697   | 814.7           | -8.97         | 32.01                  | 20.89     | 122.74   | H                  |
|                                    | 26740   | 819             | -8.94         | 32.11                  | 21.02     | 126.47   |                    |
|                                    | 26783   | 823.3           | -8.86         | 32.32                  | 21.31     | 135.21   |                    |
|                                    | 26697   | 814.7           | -14.70        | 32.54                  | 15.69     | 37.07    | V                  |
|                                    | 26740   | 819             | -14.59        | 32.51                  | 15.77     | 37.76    |                    |
|                                    | 26783   | 823.3           | -14.45        | 32.51                  | 15.91     | 38.99    |                    |

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

| LTE Band 26                      |         |                 |               |                        |           |          |                    |
|----------------------------------|---------|-----------------|---------------|------------------------|-----------|----------|--------------------|
| Channel Bandwidth: 3 MHz / QPSK  |         |                 |               |                        |           |          |                    |
| Plane                            | Channel | Frequency (MHz) | Reading (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (mW) | Polarization (H/V) |
| X                                | 26705   | 815.5           | -6.71         | 32.02                  | 23.16     | 207.01   | H                  |
|                                  | 26740   | 819.0           | -6.67         | 32.11                  | 23.29     | 213.30   |                    |
|                                  | 26775   | 822.5           | -6.45         | 32.18                  | 23.58     | 228.03   |                    |
|                                  | 26705   | 815.5           | -12.39        | 32.5                   | 17.96     | 62.52    | V                  |
|                                  | 26740   | 819.0           | -12.32        | 32.51                  | 18.04     | 63.68    |                    |
|                                  | 26775   | 822.5           | -12.14        | 32.47                  | 18.18     | 65.77    |                    |
| Channel Bandwidth: 3 MHz / 16QAM |         |                 |               |                        |           |          |                    |
| X                                | 26705   | 815.5           | -7.70         | 32.02                  | 22.17     | 164.82   | H                  |
|                                  | 26740   | 819.0           | -7.66         | 32.11                  | 22.30     | 169.82   |                    |
|                                  | 26775   | 822.5           | -7.44         | 32.18                  | 22.59     | 181.55   |                    |
|                                  | 26705   | 815.5           | -13.38        | 32.5                   | 16.97     | 49.77    | V                  |
|                                  | 26740   | 819.0           | -13.31        | 32.51                  | 17.05     | 50.70    |                    |
|                                  | 26775   | 822.5           | -13.13        | 32.47                  | 17.19     | 52.36    |                    |
| Channel Bandwidth: 3 MHz / 64QAM |         |                 |               |                        |           |          |                    |
| X                                | 26705   | 815.5           | -8.67         | 32.02                  | 21.20     | 131.83   | H                  |
|                                  | 26740   | 819.0           | -8.63         | 32.11                  | 21.33     | 135.83   |                    |
|                                  | 26775   | 822.5           | -8.41         | 32.18                  | 21.62     | 145.21   |                    |
|                                  | 26705   | 815.5           | -14.35        | 32.5                   | 16.00     | 39.81    | V                  |
|                                  | 26740   | 819.0           | -14.28        | 32.51                  | 16.08     | 40.55    |                    |
|                                  | 26775   | 822.5           | -14.10        | 32.47                  | 16.22     | 41.88    |                    |

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

| LTE Band 26                      |         |                 |               |                        |           |          |                    |
|----------------------------------|---------|-----------------|---------------|------------------------|-----------|----------|--------------------|
| Channel Bandwidth: 5 MHz / QPSK  |         |                 |               |                        |           |          |                    |
| Plane                            | Channel | Frequency (MHz) | Reading (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (mW) | Polarization (H/V) |
| X                                | 26715   | 816.5           | -6.48         | 32.04                  | 23.41     | 219.28   | H                  |
|                                  | 26740   | 819.0           | -6.42         | 32.11                  | 23.54     | 225.94   |                    |
|                                  | 26765   | 821.5           | -5.81         | 31.79                  | 23.83     | 241.55   |                    |
|                                  | 26715   | 816.5           | -12.16        | 32.52                  | 18.21     | 66.22    | V                  |
|                                  | 26740   | 819.0           | -12.07        | 32.51                  | 18.29     | 67.45    |                    |
|                                  | 26765   | 821.5           | -11.59        | 32.17                  | 18.43     | 69.66    |                    |
| Channel Bandwidth: 5 MHz / 16QAM |         |                 |               |                        |           |          |                    |
| X                                | 26715   | 816.5           | -7.50         | 32.04                  | 22.39     | 173.38   | H                  |
|                                  | 26740   | 819.0           | -7.44         | 32.11                  | 22.52     | 178.65   |                    |
|                                  | 26765   | 821.5           | -6.83         | 31.79                  | 22.81     | 190.99   |                    |
|                                  | 26715   | 816.5           | -13.18        | 32.52                  | 17.19     | 52.36    | V                  |
|                                  | 26740   | 819.0           | -13.09        | 32.51                  | 17.27     | 53.33    |                    |
|                                  | 26765   | 821.5           | -12.61        | 32.17                  | 17.41     | 55.08    |                    |
| Channel Bandwidth: 5 MHz / 64QAM |         |                 |               |                        |           |          |                    |
| X                                | 26715   | 816.5           | -8.53         | 32.04                  | 21.36     | 136.77   | H                  |
|                                  | 26740   | 819.0           | -8.47         | 32.11                  | 21.49     | 140.93   |                    |
|                                  | 26765   | 821.5           | -7.86         | 31.79                  | 21.78     | 150.66   |                    |
|                                  | 26715   | 816.5           | -14.21        | 32.52                  | 16.16     | 41.30    | V                  |
|                                  | 26740   | 819.0           | -14.12        | 32.51                  | 16.24     | 42.07    |                    |
|                                  | 26765   | 821.5           | -13.64        | 32.17                  | 16.38     | 43.45    |                    |

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15



| LTE Band 26                       |         |                 |               |                        |           |          |                    |
|-----------------------------------|---------|-----------------|---------------|------------------------|-----------|----------|--------------------|
| Channel Bandwidth: 10 MHz / QPSK  |         |                 |               |                        |           |          |                    |
| Plane                             | Channel | Frequency (MHz) | Reading (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (mW) | Polarization (H/V) |
| X                                 | 26740   | 819.0           | -6.19         | 32.11                  | 23.77     | 238.23   | H                  |
|                                   | 26740   | 819.0           | -11.84        | 32.51                  | 18.52     | 71.12    | V                  |
| Channel Bandwidth: 10 MHz / 16QAM |         |                 |               |                        |           |          |                    |
| X                                 | 26740   | 819.0           | -7.20         | 32.11                  | 22.76     | 188.80   | H                  |
|                                   | 26740   | 819.0           | -12.85        | 32.51                  | 17.51     | 56.36    | V                  |
| Channel Bandwidth: 10 MHz / 64QAM |         |                 |               |                        |           |          |                    |
| X                                 | 26740   | 819.0           | -8.22         | 32.11                  | 21.74     | 149.28   | H                  |
|                                   | 26740   | 819.0           | -13.87        | 32.51                  | 16.49     | 44.57    | V                  |

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

## 4.2 Modulation Characteristics Measurement

### 4.2.1 Limits of Modulation Characteristics

N/A



### 4.2.2 Test Setup



### 4.2.3 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector. The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

#### 4.2.4 Test Results



### 4.3 Frequency Stability Measurement

#### 4.3.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

#### 4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5$  °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

#### 4.3.3 Test Setup



#### 4.3.4 Test Results

##### Frequency Error vs. Voltage

| Voltage<br>(Volts) | CDMA            |                       |                 |                       | Limit (ppm) |
|--------------------|-----------------|-----------------------|-----------------|-----------------------|-------------|
|                    | Low Channel     |                       | High Channel    |                       |             |
|                    | Frequency (MHz) | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| 3.85               | 817.900001      | 0.001                 | 822.750003      | 0.004                 | 2.5         |
| 3.27               | 817.900003      | 0.003                 | 822.750004      | 0.004                 | 2.5         |
| 4.43               | 817.900001      | 0.002                 | 822.750002      | 0.003                 | 2.5         |

**Note:** The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

##### Frequency Error vs. Temperature

| Temp. (°C) | CDMA            |                       |                 |                       | Limit (ppm) |
|------------|-----------------|-----------------------|-----------------|-----------------------|-------------|
|            | Low Channel     |                       | High Channel    |                       |             |
|            | Frequency (MHz) | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| -30        | 817.900001      | 0.001                 | 822.750001      | 0.002                 | 2.5         |
| -20        | 817.900001      | 0.002                 | 822.750002      | 0.002                 | 2.5         |
| -10        | 817.900003      | 0.003                 | 822.750002      | 0.003                 | 2.5         |
| 0          | 817.900002      | 0.002                 | 822.750004      | 0.005                 | 2.5         |
| 10         | 817.900003      | 0.003                 | 822.750003      | 0.004                 | 2.5         |
| 20         | 817.899998      | -0.002                | 822.749997      | -0.003                | 2.5         |
| 30         | 817.899997      | -0.004                | 822.749997      | -0.004                | 2.5         |
| 40         | 817.899998      | -0.003                | 822.749998      | -0.002                | 2.5         |
| 50         | 817.899999      | -0.001                | 822.749997      | -0.003                | 2.5         |

### Frequency Error vs. Voltage

| Voltage<br>(Volts) | LTE Band 26                |                       |                 |                       | Limit (ppm) |
|--------------------|----------------------------|-----------------------|-----------------|-----------------------|-------------|
|                    | Channel Bandwidth: 1.4 MHz |                       |                 |                       |             |
|                    | Low Channel                |                       | High Channel    |                       |             |
|                    | Frequency (MHz)            | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| 3.85               | 814.700003                 | 0.004                 | 823.300000      | 0.002                 | 2.5         |
| 3.27               | 814.700003                 | 0.004                 | 823.300000      | 0.002                 | 2.5         |
| 4.43               | 814.700003                 | 0.003                 | 823.300000      | 0.005                 | 2.5         |

**Note:** The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 26                |                       |                 |                       | Limit (ppm) |
|------------|----------------------------|-----------------------|-----------------|-----------------------|-------------|
|            | Channel Bandwidth: 1.4 MHz |                       |                 |                       |             |
|            | Low Channel                |                       | High Channel    |                       |             |
|            | Frequency (MHz)            | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| -30        | 814.700002                 | 0.002                 | 823.300000      | 0.002                 | 2.5         |
| -20        | 814.700001                 | 0.001                 | 823.300000      | 0.004                 | 2.5         |
| -10        | 814.700003                 | 0.004                 | 823.300000      | 0.003                 | 2.5         |
| 0          | 814.700003                 | 0.003                 | 823.300000      | 0.005                 | 2.5         |
| 10         | 814.700001                 | 0.002                 | 823.300000      | 0.003                 | 2.5         |
| 20         | 814.699998                 | -0.002                | 823.300000      | 0.004                 | 2.5         |
| 30         | 814.699999                 | -0.001                | 823.300000      | 0.005                 | 2.5         |
| 40         | 814.699997                 | -0.004                | 823.300000      | 0.004                 | 2.5         |
| 50         | 814.699997                 | -0.004                | 823.300000      | 0.003                 | 2.5         |

### Frequency Error vs. Voltage

| Voltage<br>(Volts) | LTE Band 26              |                       |                 |                       | Limit (ppm) |
|--------------------|--------------------------|-----------------------|-----------------|-----------------------|-------------|
|                    | Channel Bandwidth: 3 MHz |                       |                 |                       |             |
|                    | Low Channel              |                       | High Channel    |                       |             |
|                    | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| 3.85               | 815.500004               | 0.005                 | 822.500000      | 0.002                 | 2.5         |
| 3.27               | 815.500002               | 0.002                 | 822.500000      | 0.002                 | 2.5         |
| 4.43               | 815.500001               | 0.001                 | 822.500000      | 0.003                 | 2.5         |

**Note:** The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 26              |                       |                 |                       | Limit (ppm) |
|------------|--------------------------|-----------------------|-----------------|-----------------------|-------------|
|            | Channel Bandwidth: 3 MHz |                       |                 |                       |             |
|            | Low Channel              |                       | High Channel    |                       |             |
|            | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| -30        | 815.500003               | 0.003                 | 822.500000      | 0.005                 | 2.5         |
| -20        | 815.500002               | 0.002                 | 822.500000      | 0.003                 | 2.5         |
| -10        | 815.500003               | 0.004                 | 822.500000      | 0.003                 | 2.5         |
| 0          | 815.500004               | 0.005                 | 822.500000      | 0.001                 | 2.5         |
| 10         | 815.500004               | 0.004                 | 822.500000      | 0.003                 | 2.5         |
| 20         | 815.499999               | -0.001                | 822.500000      | 0.005                 | 2.5         |
| 30         | 815.499998               | -0.002                | 822.500000      | 0.005                 | 2.5         |
| 40         | 815.499997               | -0.004                | 822.500000      | 0.002                 | 2.5         |
| 50         | 815.499997               | -0.004                | 822.500000      | 0.004                 | 2.5         |

### Frequency Error vs. Voltage

| Voltage<br>(Volts) | LTE Band 26              |                       |                 |                       | Limit (ppm) |
|--------------------|--------------------------|-----------------------|-----------------|-----------------------|-------------|
|                    | Channel Bandwidth: 5 MHz |                       |                 |                       |             |
|                    | Low Channel              |                       | High Channel    |                       |             |
|                    | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| 3.85               | 816.500003               | 0.003                 | 821.500000      | 0.004                 | 2.5         |
| 3.27               | 816.500004               | 0.005                 | 821.500000      | 0.002                 | 2.5         |
| 4.43               | 816.500004               | 0.005                 | 821.500000      | 0.003                 | 2.5         |

**Note:** The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 26              |                       |                 |                       | Limit (ppm) |
|------------|--------------------------|-----------------------|-----------------|-----------------------|-------------|
|            | Channel Bandwidth: 5 MHz |                       |                 |                       |             |
|            | Low Channel              |                       | High Channel    |                       |             |
|            | Frequency (MHz)          | Frequency Error (ppm) | Frequency (MHz) | Frequency Error (ppm) |             |
| -30        | 816.500003               | 0.003                 | 821.500000      | 0.002                 | 2.5         |
| -20        | 816.500001               | 0.002                 | 821.500000      | 0.003                 | 2.5         |
| -10        | 816.500001               | 0.001                 | 821.500000      | 0.004                 | 2.5         |
| 0          | 816.500003               | 0.003                 | 821.500000      | 0.002                 | 2.5         |
| 10         | 816.500003               | 0.004                 | 821.500000      | 0.005                 | 2.5         |
| 20         | 816.499997               | -0.003                | 821.500000      | 0.003                 | 2.5         |
| 30         | 816.499997               | -0.004                | 821.500000      | 0.003                 | 2.5         |
| 40         | 816.499996               | -0.005                | 821.500000      | 0.004                 | 2.5         |
| 50         | 816.499998               | -0.003                | 821.500000      | 0.002                 | 2.5         |



#### Frequency Error vs. Voltage

| Voltage<br>(Volts) | LTE Band 26               |                       | Limit (ppm) |
|--------------------|---------------------------|-----------------------|-------------|
|                    | Channel Bandwidth: 10 MHz |                       |             |
|                    | Frequency (MHz)           | Frequency Error (ppm) |             |
| 3.85               | 819.000001                | 0.001                 | 2.5         |
| 3.27               | 819.000004                | 0.004                 | 2.5         |
| 4.43               | 819.000001                | 0.002                 | 2.5         |

**Note:** The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

#### Frequency Error vs. Temperature

| Temp. (°C) | LTE Band 26               |                       | Limit (ppm) |
|------------|---------------------------|-----------------------|-------------|
|            | Channel Bandwidth: 10 MHz |                       |             |
|            | Frequency (MHz)           | Frequency Error (ppm) |             |
| -30        | 819.000001                | 0.001                 | 2.5         |
| -20        | 819.000003                | 0.004                 | 2.5         |
| -10        | 819.000003                | 0.004                 | 2.5         |
| 0          | 819.000001                | 0.001                 | 2.5         |
| 10         | 819.000002                | 0.002                 | 2.5         |
| 20         | 818.999999                | -0.002                | 2.5         |
| 30         | 818.999998                | -0.002                | 2.5         |
| 40         | 818.999997                | -0.004                | 2.5         |
| 50         | 818.999998                | -0.002                | 2.5         |

## 4.4 Occupied Bandwidth Measurement


### 4.4.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

### 4.4.2 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

### 4.4.3 Test Setup




#### 4.4.4 Test Results


| CDMA    |                 |                               |
|---------|-----------------|-------------------------------|
| Channel | Frequency (MHz) | 99 % Occupied Bandwidth (MHz) |
| 476     | 817.9           | 1.2762                        |
| 580     | 820.5           | 1.2758                        |
| 684     | 823.1           | 1.2778                        |



| LTE Band 26                |                 |                               |        |        |                          |                 |                               |        |        |
|----------------------------|-----------------|-------------------------------|--------|--------|--------------------------|-----------------|-------------------------------|--------|--------|
| Channel Bandwidth: 1.4 MHz |                 |                               |        |        | Channel Bandwidth: 3 MHz |                 |                               |        |        |
| Channel                    | Frequency (MHz) | 99 % Occupied Bandwidth (MHz) |        |        | Channel                  | Frequency (MHz) | 99 % Occupied Bandwidth (MHz) |        |        |
|                            |                 | QPSK                          | 16QAM  | 64QAM  |                          |                 | QPSK                          | 16QAM  | 64QAM  |
| 26697                      | 814.7           | 1.0881                        | 1.0897 | 1.0878 | 26705                    | 815.5           | 2.7052                        | 2.7003 | 2.6999 |
| 26740                      | 819.0           | 1.0877                        | 1.0905 | 1.0920 | 26740                    | 819.0           | 2.7024                        | 2.7008 | 2.7015 |
| 26783                      | 823.3           | 1.0875                        | 1.0897 | 1.0893 | 26775                    | 822.5           | 2.7020                        | 2.6993 | 2.7002 |



| LTE Band 26              |                 |                               |        |        |                           |                 |                               |        |        |
|--------------------------|-----------------|-------------------------------|--------|--------|---------------------------|-----------------|-------------------------------|--------|--------|
| Channel Bandwidth: 5 MHz |                 |                               |        |        | Channel Bandwidth: 10 MHz |                 |                               |        |        |
| Channel                  | Frequency (MHz) | 99 % Occupied Bandwidth (MHz) |        |        | Channel                   | Frequency (MHz) | 99 % Occupied Bandwidth (MHz) |        |        |
|                          |                 | QPSK                          | 16QAM  | 64QAM  |                           |                 | QPSK                          | 16QAM  | 64QAM  |
| 26715                    | 816.5           | 4.4987                        | 4.4983 | 4.4971 | 26740                     | 819.0           | 8.9830                        | 8.9785 | 8.9846 |
| 26740                    | 819.0           | 4.4963                        | 4.4999 | 4.4995 |                           |                 |                               |        |        |
| 26765                    | 821.5           | 4.4926                        | 4.4960 | 4.4983 |                           |                 |                               |        |        |




## 4.5 Emission Mask Measurement

### 4.5.1 Limits of Emission Mask Measurement

According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \log_{10}(f/6.1)$  decibels or  $50+10\log(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43+10\log(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


### 4.5.2 Test Setup




### 4.5.3 Test Procedures


- The measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Record the test plot.


#### 4.5.4 Test Results















## 4.6 Conducted Spurious Emissions

### 4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB. The limit of emission is equal to -13 dBm.

### 4.6.2 Test Setup




### 4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 1 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 100 kHz and VBW = 300 kHz are used for conducted emission measurement.
- Measuring frequency range is from 1 GHz to 10 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz are used for conducted emission measurement.


#### 4.6.4 Test Results




Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.





Note: The signal over the limit in 9 kHz is from spectrum analyzer.

## 4.7 Radiated Emission Measurement

### 4.7.1 Limits of Radiated Emission Measurement

- (1) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB. The limit of emission is equal to -13 dBm.

### 4.7.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15 dB.


**Note:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.7.3 Deviation from Test Standard


No deviation.

#### 4.7.4 Test Setup

##### <Radiated Emission below or equal 1 GHz>



##### <Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.7.5 Test Results

CDMA:


Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5

Condition: PART 90 HORIZONTAL

Remark : CDMA BC10 Link\_L-CH

Tested by: Jisyong Wang


|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm    | dBm        | dBm        | dB         | dB     |        |
| 1    | 1635.80 | -60.85 | -46.06     | -13.00     | -47.85     | -14.79 | Peak   |
| 2 pp | 2453.70 | -46.85 | -36.41     | -13.00     | -33.85     | -10.44 | Peak   |



# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5

Condition: PART 90 VERTICAL

Remark : CDMA BC10 Link\_L-CH

Tested by: Jisyong Wang

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm    | dBm        | dBm        | dB         | dB     |        |
| 1    | 1635.80 | -60.64 | -45.85     | -13.00     | -47.64     | -14.79 | Peak   |
| 2 pp | 2453.70 | -47.95 | -37.51     | -13.00     | -34.95     | -10.44 | Peak   |


# Middle Channel



Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART 90 HORIZONTAL  
Remark : CDMA BC10 Link\_M-CH  
Tested by: Jisyong Wang


|      |         |        | Read   | Limit  | Over   |        |        |
|------|---------|--------|--------|--------|--------|--------|--------|
|      | Freq    | Level  | Level  | Line   | Limit  | Factor | Remark |
|      | MHz     | dBm    | dBm    | dBm    | dB     | dB     |        |
| 1    | 1641.00 | -61.75 | -47.02 | -13.00 | -48.75 | -14.73 | Peak   |
| 2 pp | 2461.50 | -49.85 | -39.41 | -13.00 | -36.85 | -10.44 | Peak   |



# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5

Condition: PART 90 VERTICAL

Remark : CDMA BC10 Link\_M-CH

Tested by: Jisyong Wang

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm    | dBm        | dBm        | dB         | dB     |        |
| 1    | 1641.00 | -61.23 | -46.50     | -13.00     | -48.23     | -14.73 | Peak   |
| 2 pp | 2461.50 | -46.95 | -36.51     | -13.00     | -33.95     | -10.44 | Peak   |


## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
 Condition: PART 90 HORIZONTAL  
 Remark : CDMA BC10 Link\_H-CH  
 Tested by: Jisyoung Wang

|      |         |        | Read   | Limit  | Over   |        |        |
|------|---------|--------|--------|--------|--------|--------|--------|
|      | Freq    | Level  | Level  | Line   | Limit  | Factor | Remark |
|      | MHz     | dBm    | dBm    | dBm    | dB     | dB     |        |
| 1    | 43.58   | -50.93 | -49.46 | -13.00 | -37.93 | -1.47  | Peak   |
| 2    | 116.33  | -66.88 | -56.86 | -13.00 | -53.88 | -10.02 | Peak   |
| 3    | 241.46  | -70.15 | -63.81 | -13.00 | -57.15 | -6.34  | Peak   |
| 4    | 388.90  | -70.47 | -64.46 | -13.00 | -57.47 | -6.01  | Peak   |
| 5    | 556.71  | -66.62 | -64.05 | -13.00 | -53.62 | -2.57  | Peak   |
| 6    | 791.45  | -63.60 | -64.36 | -13.00 | -50.60 | 0.76   | Peak   |
| 7    | 1646.20 | -61.78 | -47.05 | -13.00 | -48.78 | -14.73 | Peak   |
| 8 pp | 2469.30 | -45.23 | -34.79 | -13.00 | -32.23 | -10.44 | Peak   |






# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5  
Condition: PART 90 VERTICAL  
Remark : CDMA BC10 Link\_H-CH  
Tested by: Jisyong Wang

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm    | dBm        | dBm        | dB         | dB     |        |
| 1    | 43.58   | -51.73 | -50.26     | -13.00     | -38.73     | -1.47  | Peak   |
| 2    | 52.31   | -61.29 | -55.75     | -13.00     | -48.29     | -5.54  | Peak   |
| 3    | 114.39  | -62.11 | -52.00     | -13.00     | -49.11     | -10.11 | Peak   |
| 4    | 463.59  | -69.72 | -64.42     | -13.00     | -56.72     | -5.30  | Peak   |
| 5    | 820.55  | -62.82 | -63.37     | -13.00     | -49.82     | 0.55   | Peak   |
| 6    | 972.84  | -61.81 | -64.43     | -13.00     | -48.81     | 2.62   | Peak   |
| 7    | 1646.20 | -61.85 | -47.12     | -13.00     | -48.85     | -14.73 | Peak   |
| 8 pp | 2469.30 | -47.85 | -37.41     | -13.00     | -34.85     | -10.44 | Peak   |


LTE Band 26  
Channel Bandwidth: 10 MHz / QPSK  
Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
Condition: PART 90 HORIZONTAL  
Remak : LTE Band 26 QPSK\_10M Link\_M-CH  
Tested by: Thomas Wei


|      |         | Read   | Limit  | Over   |        |        |        |
|------|---------|--------|--------|--------|--------|--------|--------|
|      | Freq    | Level  | Level  | Line   | Limit  | Factor | Remark |
|      | MHz     | dBm    | dBm    | dBm    | dB     | dB     |        |
| 1 pp | 43.58   | -50.93 | -49.46 | -13.00 | -37.93 | -1.47  | Peak   |
| 2    | 61.04   | -67.95 | -60.21 | -13.00 | -54.95 | -7.74  | Peak   |
| 3    | 173.56  | -70.68 | -64.47 | -13.00 | -57.68 | -6.21  | Peak   |
| 4    | 482.02  | -68.75 | -63.80 | -13.00 | -55.75 | -4.95  | Peak   |
| 5    | 728.40  | -64.37 | -64.83 | -13.00 | -51.37 | 0.46   | Peak   |
| 6    | 903.97  | -63.10 | -63.77 | -13.00 | -50.10 | 0.67   | Peak   |
| 7    | 1638.00 | -61.89 | -47.10 | -13.00 | -48.89 | -14.79 | Peak   |



# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5  
Condition: PART 90 VERTICAL  
Remak : LTE Band 26 QPSK\_10M Link\_M-CH  
Tested by: Thomas Wei

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark |
|------|---------|--------|------------|------------|------------|--------|--------|
|      | MHz     | dBm    | dBm        | dBm        | dB         | dB     |        |
| 1 pp | 43.58   | -51.73 | -50.26     | -13.00     | -38.73     | -1.47  | Peak   |
| 2    | 114.39  | -62.11 | -52.00     | -13.00     | -49.11     | -10.11 | Peak   |
| 3    | 250.19  | -70.49 | -64.50     | -13.00     | -57.49     | -5.99  | Peak   |
| 4    | 418.97  | -70.21 | -64.42     | -13.00     | -57.21     | -5.79  | Peak   |
| 5    | 696.39  | -64.80 | -64.64     | -13.00     | -51.80     | -0.16  | Peak   |
| 6    | 822.49  | -62.76 | -63.30     | -13.00     | -49.76     | 0.54   | Peak   |
| 7    | 1638.00 | -56.20 | -41.41     | -13.00     | -43.20     | -14.79 | Peak   |

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---