

Radio Exposure Evaluation Report

FCC ID : HDC-17600030F1
Contains FCC ID : HDC-649B
Equipment : WiFi 6 Mesh AP
Brand Name : 
Model Name : 841-t6YYYYYY(Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#")
Part Number : 17600030YYYYYYYY(Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#")
Applicant : Adtran
901 Explorer Blvd., Huntsville, AL 35806, USA
Manufacturer : XAVi Technologies Corporation
22F., No.69, Sec. 2, Guangfu Rd., Sanchong Dist.,
New Taipei City 241, Taiwan (R.O.C.)
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Sep. 16, 2021, and testing was started from Sep. 16, 2021 and completed on Sep. 24, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Testing Location	7
2 MAXIMUM PERMISSIBLE EXPOSURE	8
2.1 Limit of Maximum Permissible Exposure	8
2.2 MPE Calculation Method	8
2.3 Calculated Result and Limit.....	9
Photographs of EUT V01	



TEL : 886-3-327-3456
FAX : 886-3-327-0973
Report Template No.: HE1-A1 Ver4.0
FCC ID: HDC-17600030F1



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ben Tseng

Report Producer: Jenny Yang

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Support
1	Galtronics	02036142-07357-1	PIFA	N/A	5G DFS RX
2	Galtronics	02036073-07357-3	PIFA	N/A	BT
3	Galtronics	60-2962-03-4	PCB	U.FL	2.4G+5G
4	Galtronics	60-2962-03-3	PCB	U.FL	2.4G+5G
5	Galtronics	60-2888-03-1	PCB	U.FL	5G
6	Galtronics	60-2791-03	PCB	U.FL	5G
7	Galtronics	60-2791-03	PCB	U.FL	5G
8	Galtronics	60-2888-03-1	PCB	U.FL	5G

**Non-Beamforming**

Ant.	Port	Gain (dBi)		
		2.4G	5G	BT
1	1	-	4.7	-
2	1	-	-	5.3
3	1	2.7	3.7	-
4	2	2.7	3.7	-
5	1	-	3.9	-
6	2	-	2.1	-
7	3	-	2.1	-
8	4	-	3.9	-

Note 1: The EUT has eight antennas.

For 2.4GHz function:

For IEEE 802.11 b/g/n/VHT/ax mode (2TX/2RX)

Ant. 3 (port 1) and Ant. 4 (port 2) could transmit/receive simultaneously.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Only Ant. 2 (port 1) can be used as transmitting/receiving.

For 5GHz function (Low Band):

For IEEE 802.11 a/n/ac/ax mode (2TX/2RX)

Ant. 3 (port 1) and Ant. 4 (port 2) could transmit/receive simultaneously.

For 5GHz function (High Band):

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)

Ant. 5 (port 1), Ant. 6 (port 2), Ant. 7 (port 3) and Ant. 8 (port 4) could transmit/receive simultaneously.

1.1.3 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
841-t6YYYYYY(Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#")	All the models are identical, the difference model served as marketing strategy.

1.1.4 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA182051

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Frequency bands U-NII-2A and U-NII-2C were added	N/A

1.1.5 Accessories

Accessories				
AC Adapter	Brand Name	MASS POWER	Model Name	S030-1A120250VU
	Power Rating	I/P: 100 - 240 Vac, 0.8 A, O/P: 12.0 Vdc, 2.5 A		
	Power Cord	1.45 meter, non-shielded cable, w/o ferrite core		

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory			
☒	Hsinhua	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	
	(TAF: 3785)	TEL: 886-3-327-3456	FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.			
☐	Wen 33rd.St.	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	
	(TAF: 3785)	TEL: 886-3-318-0787	FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.			

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode: Bluetooth+WLAN 2.4GHz+WLAN 5GHz (Low Band)+WLAN 5GHz (High Band)

2.2 MPE Calculation Method

The MPE was calculated at 22 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Ratio (S/Limit)
2.4G;D1D	5.71	22.89	28.60	0.50	29.10	0.81283	22	0.13364	1.00000	0.13364
5.2G;D1D	6.71	23.09	29.80	0.50	30.30	1.07152	22	0.17618	1.00000	0.17618
5.8G;D1D	9.07	26.29	35.36	0.50	35.86	3.85478	22	0.63379	1.00000	0.63379
2.4G;BT-LE	5.3	7.15	12.45	0.50	12.95	0.01972	22	0.00324	1.00000	0.00324
									Sum Ratio	0.95567
									Ratio Limit	1

—————THE END—————