

INTERTEK TESTING SERVICES

RF Exposure

The Equipment Under Test (EUT) is a WiFi 5 Gigabit Router which has Bluetooth and WiFi function, and WiFi operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing; 2422-2452MHz for 802.11n-HT40, 9 channels with 5MHz channel spacing; 5180 MHz - 5240 MHz & 5260MHz – 5320MHz & 5500 – 5580MHz & 5660 – 5700MHz & 5745MHz – 5825MHz for 802.11a/n/ac-HT20 with 21 channels; 5190 MHz ~ 5230 MHz & 5270MHz – 5310MHz & 5510MHz – 5550MHz & 5670MHz & 5755MHz – 5795MHz for 802.11n/ac-HT40 with 9 channels and 5210 MHz & 5290MHz & 5530MHz & 5775MHz for 802.11ac-HT80 with 4 channel. The EUT was powered by 12Vdc via adapter (Input: AC100~240V, 50/60Hz, 1.0A, Output 12Vdc, 3.0A). The Device will automatically discontinue transmission in case of either absence of information to transmit or operational failure. There provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. For more detailed features description, please refer to the user's manual.

Bluetooth Version: 5.0 EDR mode.

Antenna Type: Integral antenna.

Antenna Gain: 4.0dBi.

Modulation Type: GFSK, $\pi/4$ DQPSK, 8DPSK.

The nominal conducted output power specified: 4.0dBm (± 3 dB)

Bluetooth Version: 5.0 BLE mode.

Antenna Type: Integral antenna.

Antenna Gain: 4.0dBi.

Modulation Type: GFSK.

The nominal conducted output power specified: 5.0dBm (± 3 dB)

2.4GHz WiFi:

Antenna Type: Integral Antenna.

Antenna Gain (Chain 1): 3.7dBi

Antenna Gain (Chain 2): 4.7dBi

Antenna Gain (Chain 3): 4.9dBi

Antenna Gain (Chain 4): 4.7dBi

Beamforming Gain: 2.1dBi

Modulation Type: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK and DSSS.

The nominal conducted output power specified: 23dBm (Tolerance: ± 5 dB).

5GHz WiFi:

Antenna Type: Integral Antenna.

Antenna Gain (Chain 1): 4.8dBi

Antenna Gain (Chain 2): 5.0dBi

Antenna Gain (Chain 3): 4.2dBi

Antenna Gain (Chain 4): 4.6dBi

Beamforming Gain: 2.8dBi

Modulation Type: BPSK, QPSK, 16QAM, 64QAM and OFDM.

The nominal conducted output power specified: 22dBm (Tolerance: ± 8 dB).

FCC ID: HDC17600021F1

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

For 5.0 DER mode

The source-based time averaged maximum radiated power = $4+3+4= 11\text{dBm} = 12.59\text{mW}$

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 5.0 BLE mode can be calculated according to OET 65 as follow:

$$= 12.59 / 4\pi R^2$$
$$= 0.003 \text{ mW/cm}^2$$

For 5.0 BLE mode

The source-based time averaged maximum radiated power = $5+3+4= 12\text{dBm} = 15.85\text{mW}$

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 5.0 BLE mode can be calculated according to OET 65 as follow:

$$= 15.85 / 4\pi R^2$$
$$= 0.003 \text{ mW/cm}^2$$

For 2.4GHz Band

The source-based time averaged maximum radiated power in ANT 4 mode = $23+5+4.7= 32.7\text{dBm} = 1862.1\text{mW}$

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$= 1862.1 / 4\pi R^2$$
$$= 0.37 \text{ mW/cm}^2$$

For 5GHz Band

The source-based time averaged maximum radiated power in ANT 3 mode = $22+8+4.2= 34.2\text{dBm} = 2630.3\text{mW}$

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 5GHz band can be calculated according to OET 65 as follow:

$$= 2630.3\text{mW} / 4\pi R^2$$
$$= 0.52 \text{ mW/cm}^2$$

The MPE limit is 1.0 mW/cm^2 for general population and uncontrolled exposure in the Bluetooth frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

For Simultaneous transmitting of 2.4GHz WiFi and 5GHz WiFi, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.37/1 + 0.52/1 = 0.89 < 1$

For Simultaneous transmitting of 2.4GHz WiFi and Bluetooth, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.37/1 + 0.003/1 = 0.373 < 1$

For Simultaneous transmitting of 5GHz WiFi and Bluetooth, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.52/1 + 0.003/1 = 0.523 < 1$

For Simultaneous transmitting of 2.4GHz WiFi, Bluetooth and 5GHz WiFi, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.37/1 + 0.003/1 + 0.52/1 = 0.893 < 1$

Since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in the device is ≤ 1.0 , the EUT is considered to satisfy MPE compliance for simultaneous transmission operations.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”