

※ Red color for reference and will be printed by factory.

Specification	<ul style="list-style-type: none"> - Dimension : 61.4 *51.4 mm - Ink : 單色黑 - Tolerance : - 0.1 mm - Coating: Printable Matt Polyester 打字霧P - Material : 50番白色特多龍 (UL certified) <p>Adhesive : Δ Peel Adhesion: 1.2 kgf/25mm \uparrow Δ Service Temperature: -40~120°C</p>	<ul style="list-style-type: none"> - 公差部分不符合左列標準 - 印刷內容與尺寸以網版data為準 - 沒有指示位置的部分公差為± 0.2mm - 沒有指示的部分傾斜公差為± 0.2度 - 印刷如有不清、斷字或滲墨現象 - 印刷位置與圖比例印刷不符合 <p>※廠商須無條件重新製作!</p>
---------------	--	---

部門	外觀設計課		料號	6710A6873500			
日期	2022/09/14	比例	1/1	單位	mm	工業設計工程師	Dona
該專案經理人或業務之內容核准			檢圖	Angela	Rennier		

6.1. 機下標籤 (貼於下蓋對準框位) ↓

6710A6873500 LABEL PRODUCT 61.4*51.4mm (BSA6020) ←

Adtran Model: BSAP 6020
P/N: 1700971F1
DC Input: 12V  1.5A
PoE Input: 54V  0.6A

901 EXPLORER BLVD.
HUNTSVILLE, AL 35806
www.adtran.com


This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: HDCBSAP6020
Product of Taiwan

SN: 6020wwyy05xxxx

Eth MAC: XXXXXXXXXXXX

Revision: A


  LISTED L.T.E. E502341

